

From the above given tables write a SQL query to find the salesperson(s) and the customer(s) represented here. Return the Customer Name, City, Salesman, commission.

- ➔ Customer table attributes are customer id, customer name, city, grade and salesman id .

1) CREATE DATABASE 1_ASSESSMENT.

```
mysql> create database 1_assessment;  
Query OK, 1 row affected (0.105 sec)
```

2) USE THE DATABASE.

```
mysql> use 1_assessment;  
Database changed
```

3) CREATE TABLE CUSTOMER AND ALSO USING THIS ATTRIBUTE(COLUMN NAME) CUSTOMER_ID , CUSTOMER_NAME , CITY , GRADE , SALESMAN_ID .

```
CREATE TABLE customer(  
customer_id INT PRIMARY KEY,  
customer_name VARCHAR(30)NOT NULL ,  
city VARCHAR(30),  
grade INT ,  
salesman_id INT  
);
```

```
mysql> CREATE TABLE customer(  
-> customer_id int primary key ,  
-> customer_name varchar(30) not null,  
-> city varchar(30),  
-> grade int ,  
-> salesman_id int  
-> );  
Query OK, 0 rows affected (0.373 sec)
```

4) DESCRIBE THE TABLE .

DESC CUSTOMER;

Field	Type	Null	Key	Default	Extra
customer_id	int	NO	PRI	NULL	
customer_name	varchar(30)	NO		NULL	
city	varchar(30)	YES		NULL	
grade	int	YES		NULL	
salesman_id	int	YES		NULL	

```
mysql> DESC CUSTOMER;
```

Field	Type	Null	Key	Default	Extra
customer_id	int	NO	PRI	NULL	
customer_name	varchar(30)	NO		NULL	
city	varchar(30)	YES		NULL	
grade	int	YES		NULL	
salesman_id	int	YES		NULL	

5 rows in set (0.196 sec)

5) INSERT DATA INTO CUSTOMER TABLE ?

INSERT INTO

customer(customer_id,customer_name,city,grade,salesman_id)

VALUES

(3002,"NICK RIMANDO","NEW YORK",100,5001),

(3007,"BRAD DAVIS","NEW YORK",200,5001),

(3005,"GRAHAM ZUSI","CALIFORNIA",200,5002),

(3008,"JUALIAN GREEN","LONDON",300,5002),

(3004,"FABIAN JOHNSON","PARIS",300,5006),

(3009,"GEOFF CAMERORI","BARLIN",100,5003),

(3003,"JOZY ALTIDOR","MOSCOW",200,5007),

(3001,"BRAD GUZAN","LONDON",NULL,5005);

```
mysql> insert into customer(customer_id,customer_name,city,grade,salesman_id)
-> values
-> (3002,"NICK RIMANDO","NEW YORK",100,5001),
-> (3007,"BRAD DAVIS","NEW YORK",200,5001),
-> (3005,"GRAHAM ZUSI","CALIFORNIA",200,5002),
-> (3008,"JUALIAN GREEN","LONDON",300,5002),
-> (3004,"FABIAN JOHNSON","PARIS",300,5006),
-> (3009,"GEOFF CAMERORI","BARLIN",100,5003),
-> (3003,"JOZY ALTIDOR","MOSCOW",200,5007),
-> (3001,"BRAD GUZAN","LONDON",NULL,5005);
Query OK, 8 rows affected (0.278 sec)
Records: 8 Duplicates: 0 Warnings: 0
```

6) FETCH THE RECORD OF CUSTOMER ?

```
SELECT * FROM customer;
```

customer_id	customer_name	city	grade	salesman_id
3001	BRAD GUZAN	LONDON	NULL	5005
3002	NICK RIMANDO	NEW YORK	100	5001
3003	JOZY ALTIDOR	MOSCOW	200	5007
3004	FABIAN JOHNSON	PARIS	300	5006
3005	GRAHAM ZUSI	CALIFORNIA	200	5002
3007	BRAD DAVIS	NEW YORK	200	5001
3008	JUALIAN GREEN	LONDON	300	5002
3009	GEOFF CAMEROR	BARLIN	100	5003

```
mysql> select * from customer;
```

customer_id	customer_name	city	grade	salesman_id
3001	BRAD GUZAN	LONDON	NULL	5005
3002	NICK RIMANDO	NEW YORK	100	5001
3003	JOZY ALTIDOR	MOSCOW	200	5007
3004	FABIAN JOHNSON	PARIS	300	5006
3005	GRAHAM ZUSI	CALIFORNIA	200	5002
3007	BRAD DAVIS	NEW YORK	200	5001
3008	JUALIAN GREEN	LONDON	300	5002
3009	GEOFF CAMERORI	BARLIN	100	5003

```
8 rows in set (0.016 sec)
```

7) CREATE TABLE SALESMAN?

ATTRIBUTE : SALESMAN_ID , NAME , CITY , COMMISSION

```
create table salesman(
salesman_Id INT PRIMARY KEY ,
name VARCHAR (30),
city VARCHAR (30),
commission VARCHAR (10)
);
```

```
mysql> create table salesman(
-> salesman_id int primary key,
-> name varchar(30),
-> city varchar(30),
-> commission varchar(10)
-> );
Query OK, 0 rows affected (0.439 sec)
```

8) INSERT DATA INTO SALESMAN TABLE ?

```
INSERT INTO salesman (salesman_id , name , city , commission)
values
(5001,"JAMES HOOG","NEW YORK","0.15"),
(5002,"NAIL KNITE","PARIS","0.13"),
(5005,"PIT ALEX","LONDON","0.11"),
```

```
(5006,"MC LYON","PARIS","0.14"),
(5007,"PAUL ADAM","ROME","0.13"),
(5003,"LAUSON HEN","SAN JOSE","0.12");
```

```
mysql> insert into salesman (salesman_id,name,city,commission)
-> values
-> (5001,"JAMES HOOG","NEW YORK","0.15"),
-> (5002,"NAIL KNITE","PARIS","0.13"),
-> (5005,"PIT ALEX","LONDON","0.11"),
-> (5006,"MC LYON","PARIS","0.14"),
-> (5007,"PAUL ADAM","ROME","0.13"),
-> (5003,"LAUSON HEN","SAN JOSE","0.12");
Query OK, 6 rows affected (0.111 sec)
Records: 6  Duplicates: 0  Warnings: 0
```

9) DESCRIBE THE TABLE ?

```
DESC SALESMAN;
```

Field	Type	Null	Key	Default	Extra
salesman_id	int	NO	PRI	NULL	
name	varchar(30)	YES		NULL	
city	varchar(30)	YES		NULL	
commission	varchar(10)	YES		NULL	

```
mysql> DESC SALESMAN;
```

Field	Type	Null	Key	Default	Extra
salesman_id	int	NO	PRI	NULL	
name	varchar(30)	YES		NULL	
city	varchar(30)	YES		NULL	
commission	varchar(10)	YES		NULL	

4 rows in set (0.076 sec)

10) FETCH THE RECORDS FROM THE SALESMAN TABLE ?

SELECT * FROM SALESMAN;

salesman_id	name	city	commission
5001	JAMES HOOG	NEW YORK	0.15
5002	NAIL KNITE	PARIS	0.13
5003	LAUSON HEN	SAN JOSE	0.12
5005	PIT ALEX	LONDON	0.11
5006	MC LYON	PARIS	0.14
5007	PAUL ADAM	ROME	0.13

```
mysql> select * from salesman;
```

salesman_id	name	city	commission
5001	JAMES HOOG	NEW YORK	0.15
5002	NAIL KNITE	PARIS	0.13
5003	LAUSON HEN	SAN JOSE	0.12
5005	PIT ALEX	LONDON	0.11
5006	MC LYON	PARIS	0.14
5007	PAUL ADAM	ROME	0.13

6 rows in set (0.012 sec)

11) From the above given tables write a SQL query to find the salesperson(s) and the customer(s) represented here. Return the Customer Name, City, Salesman, commission.

```
mysql> select customer_name , customer.city as customer_city , salesman.salesman_id , commission
-> from customer
-> inner join salesman on
-> customer.salesman_id=salesman.salesman_id;
```

customer_name	customer_city	salesman_id	commission
BRAD GUZAN	LONDON	5005	0.11
NICK RIMANDO	NEW YORK	5001	0.15
JOZY ALTIDOR	MOSCOW	5007	0.13
FABIAN JOHNSON	PARIS	5006	0.14
GRAHAM ZUSI	CALIFORNIA	5002	0.13
BRAD DAVIS	NEW YORK	5001	0.15
JUALIAN GREEN	LONDON	5002	0.13
GEOFF CAMERORI	BARLIN	5003	0.12

8 rows in set (0.020 sec)