

# Semantic Role Labeling


CS-585

Natural Language Processing

Derrick Higgins

# Semantic Role Labeling

---



# Can we figure out that these have the same meaning?

---

XYZ corporation **bought** the stock.

They **sold** the stock to XYZ corporation.

The stock was **bought** by XYZ corporation.

The **purchase** of the stock by XYZ corporation...

The stock **purchase** by XYZ corporation...

# A Shallow Semantic Representation: Semantic Roles

---

Predicates (bought, sold, purchase) represent an **event**

**Semantic roles** express the abstract role that arguments of a predicate can take in the event



# Semantic Role Labeling

---

## Semantic Roles

# Getting to semantic roles

Neo-Davidsonian event representation:

Sasha broke the window

Pat opened the door

$$\begin{aligned} \exists e, x, y \text{ } \textit{Breaking}(e) \wedge \textit{Breaker}(e, \textit{Sasha}) \\ \wedge \textit{BrokenThing}(e, y) \wedge \textit{Window}(y) \\ \exists e, x, y \text{ } \textit{Opening}(e) \wedge \textit{Opener}(e, \textit{Pat}) \\ \wedge \textit{OpenedThing}(e, y) \wedge \textit{Door}(y) \end{aligned}$$

Subjects of break and open: **Breaker** and **Opener**

**Deep roles** specific to each event (breaking, opening)

# Thematic roles

---

- **Breaker** and **Opener** have something in common!
  - Volitional actors
  - Often animate
  - Direct causal responsibility for their events
- Thematic roles are a way to capture this semantic commonality between *Breakers* and *Eaters*.
- They are both AGENTS.
- The *BrokenThing* and *OpenedThing*, are THEMES.
  - prototypically inanimate objects affected in some way by the action

# Thematic roles

---

- One of the oldest linguistic models
  - Indian grammarian Panini between the 7th and 4th centuries BCE
- Modern formulation from Fillmore (1966,1968), Gruber (1965)
  - Fillmore influenced by Lucien Tesnière's (1959) *Éléments de Syntaxe Structurale*, the book that introduced dependency grammar
  - Fillmore first referred to roles as *actants* (Fillmore, 1966) but switched to the term *case*



# Thematic roles

## A typical set:

Thematic Role	Definition	Example
AGENT	The volitional causer of an event	<i>The waiter</i> spilled the soup.
EXPERIENCER	The experiencer of an event	<i>John</i> has a headache.
FORCE	The non-volitional causer of the event	<i>The wind</i> blows debris from the mall into our yards.
THEME	The participant most directly affected by an event	Only after Benjamin Franklin broke <i>the ice</i> ...
RESULT	The end product of an event	The city built a <i>regulation-size baseball diamond</i> ...
CONTENT	The proposition or content of a propositional event	Mona asked “ <i>You met Mary Ann at a supermarket?</i> ”
INSTRUMENT	An instrument used in an event	He poached catfish, stunning them <i>with a shocking device</i> ...
BENEFICIARY	The beneficiary of an event	Whenever Ann Callahan makes hotel reservations <i>for her boss</i> ...
SOURCE	The origin of the object of a transfer event	I flew in <i>from Boston</i> .
GOAL	The destination of an object of a transfer event	I drove <i>to Portland</i> .

# Thematic grid, case frame, $\theta$ -grid

Example usages of “break”

*John broke the window.*

AGENT            THEME

*John broke the window with a rock.*

AGENT            THEME            INSTRUMENT

*The rock broke the window.*

INSTRUMENT            THEME

*The window broke.*

THEME

*The window was broken by John.*

THEME                            AGENT

**thematic grid, case frame,  $\theta$ -grid**

Break:

AGENT, THEME, INSTRUMENT.

Some realizations:

AGENT/Subject, THEME/Object

AGENT/Subject, THEME/Object, INSTRUMENT/PP<sub>with</sub>

INSTRUMENT/Subject, THEME/Object

THEME/Subject

# Problems with Thematic Roles

---

- Hard to create standard set of roles or formally define them
- Often roles need to be fragmented to be defined.

Levin and Rappaport Hovav (2015): two kinds of INSTRUMENTS  
intermediary instruments that can appear as subjects

The cook opened the jar with the new gadget.

The new gadget opened the jar.

enabling instruments that cannot

Shelly ate the sliced banana with a fork.

\*The fork ate the sliced banana.

# Alternatives to thematic roles

---

1. **Fewer roles:** generalized semantic roles, defined as prototypes (Dowty 1991)

PROTO-AGENT

PROTO-PATIENT

**PropBank**

2. **More roles:** Define roles specific to a group of predicates

**FrameNet**

# Semantic Role Labeling

---

## The Proposition Bank (PropBank)

# PropBank

---

- Palmer, Martha, Daniel Gildea, and Paul Kingsbury. 2005. The Proposition Bank: An Annotated Corpus of Semantic Roles. *Computational Linguistics*, 31(1):71–106

# PropBank Roles

---

## Proto-Agent

Following Dowty 1991

- Volitional involvement in event or state
- Sentience (and/or perception)
- Causes an event or change of state in another participant
- Movement (relative to position of another participant)

## Proto-Patient

- Undergoes change of state
- Causally affected by another participant
- Stationary relative to movement of another participant

# PropBank Roles

---

- Following Dowty 1991
  - Role definitions determined verb by verb, with respect to the other roles
  - Semantic roles in PropBank are thus verb-sense specific.
- Each verb sense has numbered argument: Arg0, Arg1, Arg2,...

Arg0: PROTO-AGENT

Arg1: PROTO-PATIENT

Arg2: usually: benefactive, instrument, attribute, or end state

Arg3: usually: start point, benefactive, instrument, or attribute

Arg4 the end point

*(Arg2-Arg5 are not really that consistent, causes a problem for labeling)*



# PropBank Frame Files

## **agree.01**

Arg0: Agreeer

Arg1: Proposition

Arg2: Other entity agreeing

Ex1: [Arg0 The group] *agreed* [Arg1 it wouldn't make an offer].

Ex2: [ArgM-TMP Usually] [Arg0 John] *agrees* [Arg2 with Mary]  
[Arg1 on everything].

## **fall.01**

Arg1: Logical subject, patient, thing falling

Arg2: Extent, amount fallen

Arg3: start point

Arg4: end point, end state of arg1

Ex1: [Arg1 Sales] *fell* [Arg4 to \$25 million] [Arg3 from \$27 million].

Ex2: [Arg1 The average junk bond] *fell* [Arg2 by 4.2%].

# Advantage of a PropBank Labeling

---

**increase.01** “go up incrementally”

Arg0: causer of increase

Arg1: thing increasing

Arg2: amount increased by, EXT, or MNR

Arg3: start point

Arg4: end point

This would allow us to see the commonalities in these 3 sentences:

[Arg0 Big Fruit Co. ] increased [Arg1 the price of bananas].

[Arg1 The price of bananas] was increased again [Arg0 by Big Fruit Co. ]

[Arg1 The price of bananas] increased [Arg2 5%].

# Modifiers or adjuncts of the predicate: Arg-M


---

<b>ArgM-TMP</b>	when?	yesterday evening, now
<b>LOC</b>	where?	at the museum, in San Francisco
<b>DIR</b>	where to/from?	down, to Bangkok
<b>MNR</b>	how?	clearly, with much enthusiasm
<b>PRP/CAU</b>	why?	because ... , in response to the ruling
<b>REC</b>		themselves, each other
<b>ADV</b>	miscellaneous	
<b>PRD</b>	secondary predication	...ate the meat raw

# PropBanking a Sentence


Martha Palmer 2013

A sample  
parse tree



# The same parse tree PropBanked

Martha Palmer 2013



# Annotated PropBank Data

- Penn English TreeBank, OntoNotes 5.0.
  - Total ~2 million words
- Penn Chinese TreeBank
- Hindi/Urdu PropBank
- Arabic PropBank

2013 Verb Frames Coverage  
Count of word sense (lexical units)

<i><b>Language</b></i>	<i><b>Final Count</b></i>
<b>English</b>	<b>10,615*</b>
<b>Chinese</b>	<b>24,642</b>
<b>Arabic</b>	<b>7,015</b>

From Martha Palmer 2013 Tutorial

# Plus nouns and light verbs

---

## Example Noun: *Decision*

- ▶ Roleset: **Arg0: decider**, **Arg1: decision...**
- ▶ “...[**your**<sub>ARG0</sub>] [decision<sub>REL</sub>]  
[to say look I don't want to go through this anymore<sub>ARG1</sub>]”

## Example within an LVC: *Make a decision*

- ▶ “...[**the President**<sub>ARG0</sub>] [made<sub>REL-LVB</sub>]  
the [fundamentally correct<sub>ARGM-ADJ</sub>]  
[decision<sub>REL</sub>] [**to get on offense**<sub>ARG1</sub>]”

Slide from Palmer 2013

# Semantic Role Labeling

---

FrameNet



# Capturing descriptions of the same event by different nouns/verbs

---

[Arg1 The price of bananas] increased [Arg2 5%].

[Arg1 The price of bananas] rose [Arg2 5%].

There has been a [Arg2 5%] rise [Arg1 in the price of bananas].

# FrameNet

---

- Baker et al. 1998, Fillmore et al. 2003, Fillmore and Baker 2009, Ruppenhofer et al. 2006
- Roles in PropBank are specific to a verb
- Role in FrameNet are specific to a **frame**: a background knowledge structure that defines a set of frame-specific semantic roles, called **frame elements**,
  - includes a set of predicates that use these roles

# The “Change position on a scale” Frame

---

This frame consists of words that indicate the change of an ITEM's position on a scale (the ATTRIBUTE) from a starting point (INITIAL VALUE) to an end point (FINAL VALUE)

[ITEM Oil] *rose* [ATTRIBUTE in price] [DIFFERENCE by 2%].

[ITEM It] has *increased* [FINAL\_STATE to having them 1 day a month].

[ITEM Microsoft shares] *fell* [FINAL\_VALUE to 7 5/8].

[ITEM Colon cancer incidence] *fell* [DIFFERENCE by 50%] [GROUP among men].

a steady *increase* [INITIAL\_VALUE from 9.5] [FINAL\_VALUE to 14.3] [ITEM in dividends]

a [DIFFERENCE 5%] [ITEM dividend] *increase...*

# The “Change position on a scale” Frame

<b>VERBS:</b>	dwindle	move	soar	escalation	shift
advance	edge	mushroom	swell	explosion	tumble
climb	explode	plummet	swing	fall	
decline	fall	reach	triple	fluctuation	<b>ADVERBS:</b>
decrease	fluctuate	rise	tumble	gain	increasingly
diminish	gain	rocket		growth	
dip	grow	shift	<b>NOUNS:</b>	hike	
double	increase	skyrocket	decline	increase	
drop	jump	slide	decrease	rise	

# The “Change position on a scale” Frame

Core Roles	
ATTRIBUTE	The ATTRIBUTE is a scalar property that the ITEM possesses.
DIFFERENCE	The distance by which an ITEM changes its position on the scale.
FINAL_STATE	A description that presents the ITEM’s state after the change in the ATTRIBUTE’s value as an independent predication.
FINAL_VALUE	The position on the scale where the ITEM ends up.
INITIAL_STATE	A description that presents the ITEM’s state before the change in the ATTRIBUTE’s value as an independent predication.
INITIAL_VALUE	The initial position on the scale from which the ITEM moves away.
ITEM	The entity that has a position on the scale.
VALUE_RANGE	A portion of the scale, typically identified by its end points, along which the values of the ATTRIBUTE fluctuate.
Some Non-Core Roles	
DURATION	The length of time over which the change takes place.
SPEED	The rate of change of the VALUE.
GROUP	The GROUP in which an ITEM changes the value of an ATTRIBUTE in a specified way.

# Relation between frames

---

Inherits from:

Is Inherited by:

Perspective on:

Is Perspectivized in:

Uses:

Is Used by:

Subframe of:

Has Subframe(s):

Precedes:

Is Preceded by:

Is Inchoative of:

Is Causative of:

# Relation between frames

“cause change position on a scale”

Is Causative of: Change position on a scale

Adds an agent Role

[AGENT They] *raised* [ITEM the price of their soda] [DIFFERENCE by 2%].

- *add.v, crank.v, curtail.v, cut.n, cut.v, decrease.v, development.n, diminish.v, double.v, drop.v, enhance.v, growth.n, increase.v, knock down.v, lower.v, move.v, promote.v, push.n, push.v, raise.v, reduce.v, reduction.n, slash.v, step up.v, swell.v*

# Relations between frames




Figure from Das et al 2010



# Schematic of Frame Semantics






Figure from Das et al (2014)

# FrameNet and PropBank representations



# Semantic Role Labeling

---

## Semantic Role Labeling Algorithm

# Semantic role labeling (SRL)

- The task of finding the semantic roles of each argument of each predicate in a sentence.
- FrameNet versus PropBank:

[You]	can't	[blame]	[the program]	[for being unable to identify it]
COGNIZER		TARGET	EVALUEE	REASON

[The San Francisco Examiner]	issued	[a special edition]	[yesterday]
ARG0	TARGET	ARG1	ARGM-TMP

# Why Semantic Role Labeling

---

- A useful shallow semantic representation
- Improves NLP tasks like:
  - question answering  
Shen and Lapata 2007, Surdeanu et al. 2011
  - machine translation  
Liu and Gildea 2010, Lo et al. 2013

# A simple modern algorithm

---

```
function SEMANTICROLELABEL(words) returns labeled tree


  parse  $\leftarrow$  PARSE(words)
  for each predicate in parse do
    for each node in parse do
      featurevector  $\leftarrow$  EXTRACTFEATURES(node, predicate, parse)
      CLASSIFYNODE(node, featurevector, parse)
```

# How do we decide what is a predicate

---


- If we're just doing PropBank verbs
  - Choose all verbs
  - Possibly removing light verbs (from a list)
- If we're doing FrameNet (verbs, nouns, adjectives)
  - Choose every word that was labeled as a target in training data

# Semantic Role Labeling





# Features



Headword of constituent

Examiner

Headword POS

NNP

Voice of the clause

Active

Subcategorization of pred

VP -> VBD NP PP

Named Entity type of constituent

ORGANIZATION

First and last words of constituent

The, Examiner


Linear position, clause re: predicate

before

# Path Features

Path in the parse tree from the constituent to the predicate

$NP \uparrow S \downarrow VP \downarrow VBD$



# Frequent path features

Frequency	Path	Description
14.2%	VB↑VP↓PP	PP argument/adjunct
11.8	VB↑VP↑S↓NP	subject
10.1	VB↑VP↓NP	object
7.9	VB↑VP↑VP↑S↓NP	subject (embedded VP)
4.1	VB↑VP↓ADVP	adverbial adjunct
3.0	NN↑NP↑NP↓PP	prepositional complement of noun
1.7	VB↑VP↓PRT	adverbial particle
1.6	VB↑VP↑VP↑VP↑S↓NP	subject (embedded VP)
14.2		no matching parse constituent
31.4	Other	

From Palmer, Gildea, Xue 2010

# Final feature vector

---

- For “The San Francisco Examiner”,
- Arg0, [issued, NP, Examiner, NNP, active, before, VP→VBD NP PP, ORG, The, Examiner, NP↑S↓VP↓VBD ]
- Other features could be used as well
  - sets of n-grams inside the constituent
  - other path features
    - the upward or downward halves
    - whether particular nodes occur in the path

# 3-step version of SRL algorithm

---

1. **Pruning:** use simple heuristics to prune unlikely constituents.
2. **Identification:** a binary classification of each node as an argument to be labeled or a NONE.
3. **Classification:** a 1-of- $N$  classification of all the constituents that were labeled as arguments by the previous stage


# Why add Pruning and Identification steps?

---

- Algorithm is looking at one predicate at a time
- Very few of the nodes in the tree could possibly be arguments of that one predicate
- Imbalance between
  - positive samples (constituents that are arguments of predicate)
  - negative samples (constituents that are not arguments of predicate)
- Imbalanced data can be hard for many classifiers
- <sup>49</sup>• So we prune the **very** unlikely constituents first, and then use a classifier to get rid of the rest.

# Pruning heuristics – Xue and Palmer (2004)

- Add sisters of the predicate, then aunts, then great-aunts, etc
  - But ignoring anything in a coordination structure



# A common final stage: joint inference

---

- The algorithm so far classifies everything **locally** – each decision about a constituent is made independently of all others
- But this can't be right: Lots of **global** or **joint** interactions between arguments
  - Constituents in FrameNet and PropBank must be non-overlapping.
    - A local system may incorrectly label two overlapping constituents as arguments
    - PropBank does not allow multiple identical arguments
      - labeling one constituent ARG0
      - Thus should increase the probability of another being ARG1



# How to do joint inference

---

- Reranking
  - The first stage SRL system produces multiple possible labels for each constituent
  - The second stage classifier the best **global** label for all constituents
  - Often a classifier that takes all the inputs along with other features (sequences of labels)

# More complications: FrameNet

We need an extra step to find the frame

```
function SEMANTICROLELABEL(words) returns labeled tree  
function SEMANTICROLELABEL(words) returns labeled tree  
  parse ← PARSE(words)  
  for each predicate in parse do  
  for each predicate in parse do ExtractFrameFeatures(predicate, parse)  
  for each node in parse do  
  for each node in parse do ClassifyFrame(predicate, predicatevector)  
  for each node in parse do featurevector ← EXTRACTFEATURES(node, predicate, parse)  
  for each node in parse do CLASSIFYNODE(node, featurevector, parse)  
  for each node in parse do featurevector ← EXTRACTFEATURES(node, predicate, parse)  
  CLASSIFYNODE(node, featurevector, parse, Frame)
```

# Features for Frame Identification

---

Das et al (2014)

the POS of the parent of the head word of  $t_i$

the set of syntactic dependencies of the head word<sup>21</sup> of  $t_i$

if the head word of  $t_i$  is a verb, then the set of dependency labels of its children

the dependency label on the edge connecting the head of  $t_i$  and its parent

the sequence of words in the prototype,  $w_\ell$

the lemmatized sequence of words in the prototype


the lemmatized sequence of words in the prototype and their part-of-speech tags  $\pi_\ell$

WordNet relation<sup>22</sup>  $\rho$  holds between  $\ell$  and  $t_i$

WordNet relation<sup>22</sup>  $\rho$  holds between  $\ell$  and  $t_i$ , and the prototype is  $\ell$

WordNet relation<sup>22</sup>  $\rho$  holds between  $\ell$  and  $t_i$ , the POS tag sequence of  $\ell$  is  $\pi_\ell$ , and the POS tag sequence of  $t_i$  is  $\pi_t$

# Not just English



“The police are thoroughly investigating the cause of the accident.”

# Not just verbs: NomBank




Figure from Jiang and Ng 2006

# Additional Issues for nouns

---

- Features:
  - Nominalization lexicon (employment → employ)
  - Morphological stem
    - Healthcare, Medicate → care
- Different positions
  - Most arguments of nominal predicates occur inside the NP
  - Others are introduced by support verbs
  - Especially light verbs “X made an argument”, “Y took a nap”

# Semantic Role Labeling

---

- A level of shallow semantics for representing events and their participants
  - Intermediate between parses and full semantics
- Two common architectures, for various languages
  - FrameNet: Frame-specific roles
  - PropBank: Proto-roles
- Current systems extract by
  - parsing sentence
  - Finding predicates in the sentence
    - For each one, classify each parse tree constituent