

Hidden Markov models and the Viterbi algorithm

CS-585

Natural Language Processing


Derrick Higgins

Hidden Markov Model (HMM)


- A *generative* framework for sequence labeling
 - Expresses a joint probability distribution $P(t_{1..n}, w_{1..n})$ over the observed word sequence and unobserved tag/label sequence
 - A “generative story” according to which each word is generated according to a distribution dependent on a fixed-length tag history

Hidden Markov Model (HMM)


- **Assumption:** POS generated as random process, and each POS randomly generates a word




Hidden Markov Model (HMM)



Hidden Markov Model (HMM)




Hidden Markov Model (HMM)




Hidden Markov Model (HMM)

the large
AT0 AJ0




Hidden Markov Model (HMM)

the large
AT0 AJ0 AJ0




Hidden Markov Model (HMM)

the large red
AT0 AJ0 AJ0



Hidden Markov Model (HMM)

the large red cats
AT0 AJ0 AJ0 NN2



HMM – POS generation

- First-order (bigram) Markov assumptions:
 - **Limited Horizon:** Tag depends only on previous tag

$$P(t_{i+1} = t^k | t_1 = t^{j_1}, \dots, t_i = t^{j_i}) = P(t_{i+1} = t^k | t_i = t^{j_i})$$

- **Time invariance:** No change over time

$$P(t_{i+1} = t^k | t_i = t^j) = P(t_2 = t^k | t_1 = t^j) = P(t^j \rightarrow t^k)$$

HMM – Word generation

- Output probabilities:
 - Probability of getting word w^k for tag t^j :

$$P(w^k | t^j)$$

Assumption:

Not dependent on other tags or words!

Combining Probabilities

Probability of a tag sequence:

$$P(t_1, t_2, \dots, t_N) = P(t_1)P(t_1 \rightarrow t_2) \dots P(t_{N-1} \rightarrow t_N)$$

Assume t_0 = “universal” start tag:

$$= P(t_0 \rightarrow t_1)P(t_1 \rightarrow t_2) \dots P(t_{N-1} \rightarrow t_N)$$

$$= \prod_i P(t_{i-1} \rightarrow t_i)$$

Prob. of word sequence *and* tag sequence:

$$P(W, T) = \prod_i P(t_{i-1} \rightarrow t_i) P(w_i | t_i)$$

Training from labeled data

- Labeled training = each word has a POS tag
- Thus:

$$P_{MLE}(t^j) = \frac{C(t^j)}{N}$$

$$P_{MLE}(t^j \rightarrow t^k) = \frac{C(t^j, t^k)}{C(t^j)}$$

$$P_{MLE}(w^k | t^j) = \frac{C(t^j: w^k)}{C(t^j)}$$

$$P_{MLE}(t^j | w^k) = \frac{C(t^j: w^k)}{C(w^k)}$$

Three Basic POS Computations

Model m contains transition and output probabilities

- Compute the probability of a text:

$$P_m(W_{1,N})$$

- Compute maximum probability tag sequence:

$$\operatorname{argmax}_{T_{1,N}} P_m(T_{1,N} | W_{1,N})$$

- Compute maximum likelihood model

$$\operatorname{argmax}_m P_m(W_{1,N})$$

Inference and search for sequence modeling

- We can make the search tractable in a few ways
 - Greedy search: commit to tag assignments one by one, and use them as context for the remaining assignments
 - Beam search: consider only a limited number of hypotheses for partial tag assignments, and discard the rest
 - Dynamic programming: store intermediate results in a data structure to reduce backtracking and transform the exponential search into a quadratic one

Inference and search for sequence modeling

- We can make the search tractable in a few ways
 - Greedy search: commit to tag assignments one by one, and use them as context for the remaining assignments
 - Beam search: consider only a limited number of hypotheses for partial tag assignments, and discard the rest
 - Dynamic programming: store intermediate results in a data structure to reduce backtracking and transform the exponential search into a quadratic one

$P_m(W_{1,N})$: Forward Algorithm

Define $a_k(i) = P(w_{1,k}, t_k = t^i)$

for i in $[1, \dots, N_t]$:

$$a_1(i) \leftarrow P_m(t_0 \rightarrow t^i) P_m(w_1 | t^i)$$

for k in $[2, \dots, N]$

for j in $[1, \dots, N_t]$:

$$a_k(j) \leftarrow \left(\sum_i a_{k-1}(i) P_m(t^i \rightarrow t^j) \right) P_m(w_k | t^j)$$

$$P_m(W_{1,N}) = \sum_i a_N(i)$$

$$\text{Complexity} = O(N_t^2 N)$$

$P_m(W_{1,N})$: Forward Algorithm

Define $a_k(i) = P(w_{1,k}, t_k = t^i)$

for i in $[1, \dots, N_t]$:

$$a_1(i) \leftarrow P_m(t_0 \rightarrow t^i) P_m(w_1 | t^i)$$

for k in $[2, \dots, N]$

for j in $[1, \dots, N_t]$:

$$a_k(j) \leftarrow \left(\sum_i a_{k-1}(i) P_m(t^i \rightarrow t^j) \right) P_m(w_k | t^j)$$

Initialize:
probability of
generating the first
word and tag

$$P_m(W_{1,N}) = \sum_i a_N(i)$$

$$\text{Complexity} = O(N_t^2 N)$$

$P_m(W_{1,N})$: Forward Algorithm

Define $a_k(i) = P(w_{1,k}, t_k = t^i)$

for i in $[1, \dots, N_t]$:

$$a_1(i) \leftarrow P_m(t_0 \rightarrow t^i) P_m(w_1 | t^i)$$

for k in $[2, \dots, N]$

for j in $[1, \dots, N_t]$:

$$a_k(j) \leftarrow \left(\sum_i a_{k-1}(i) P_m(t^i \rightarrow t^j) \right) P_m(w_k | t^j)$$

For each index k ,
For each tag j ,
Sum probabilities
across prior tags
that could be
transitioned from

$$P_m(W_{1,N}) = \sum_i a_N(i)$$

$$\text{Complexity} = O(N_t^2 N)$$

$P_m(W_{1,N})$: Forward Algorithm

Define $a_k(i) = P(w_{1,k}, t_k = t^i)$

for i in $[1, \dots, N_t]$:

$$a_1(i) \leftarrow P_m(t_0 \rightarrow t^i) P_m(w_1 | t^i)$$

for k in $[2, \dots, N]$

for j in $[1, \dots, N_t]$:


$$a_k(j) \leftarrow \left(\sum_i a_{k-1}(i) P_m(t^i \rightarrow t^j) \right) P_m(w_k | t^j)$$

$$P_m(W_{1,N}) = \sum_i a_N(i)$$

$$\text{Complexity} = O(N_t^2 N)$$

To get forward probability of whole sequence, loop over indices, loop over tags, and sum over tags

Forward algorithm



$P_m(W_{1,N})$: Backward Algorithm

Define $b_k(i) = P(w_{k+1,N} | t_k = t^i)$

for i in $[1, \dots, N_t]$:

$b_N(i) \leftarrow 1$

for k in $[N - 1, \dots, 1]$

for j in $[1, \dots, N_t]$:

$b_k(j) \leftarrow \sum_i P_m(t^j \rightarrow t^i) P_m(w_{k+1} | t^i) b_{k+1}(i)$

$P_m(W_{1,N}) = \sum_i P_m(t_0 \rightarrow t^i) P_m(w_1 | t^i) b_1(i)$

Complexity = $O(N_t^2 N)$

$P_m(W_{1,N})$: Backward Algorithm

Define $b_k(i) = P(w_{k+1,N} | t_k = t^i)$

for i in $[1, \dots, N_t]$:

$b_N(i) \leftarrow 1$

Initialize: probability of
ending up at the end
of the sequence

for k in $[N - 1, \dots, 1]$

for j in $[1, \dots, N_t]$:

$b_k(j) \leftarrow \sum_i P_m(t^j \rightarrow t^i) P_m(w_{k+1} | t^i) b_{k+1}(i)$

$P_m(W_{1,N}) = \sum_i P_m(t_0 \rightarrow t^i) P_m(w_1 | t^i) b_1(i)$

Complexity = $O(N_t^2 N)$

$P_m(W_{1,N})$: Backward Algorithm

Define $b_k(i) = P(w_{k+1,N} | t_k = t^i)$

For each index k ,
For each tag j ,
Sum probabilities
across following
tags that could be
transitioned to

for i in $[1, \dots, N_t]$:

$b_N(i) \leftarrow 1$

for k in $[N-1, \dots, 1]$

for j in $[1, \dots, N_t]$:

$b_k(j) \leftarrow \sum_i P_m(t^j \rightarrow t^i) P_m(w_{k+1} | t^i) b_{k+1}(i)$

$P_m(W_{1,N}) = \sum_i P_m(t_0 \rightarrow t^i) P_m(w_1 | t^i) b_1(i)$

Complexity = $O(N_t^2 N)$

$P_m(W_{1,N})$: Backward Algorithm

Define $b_k(i) = P(w_{k+1,N} | t_k = t^i)$

for i in $[1, \dots, N_t]$:

$b_N(i) \leftarrow 1$

for k in $[N - 1, \dots, 1]$

for j in $[1, \dots, N_t]$:

$$b_k(j) \leftarrow \sum_i P_m(t^j \rightarrow t^i) P_m(w_{k+1} | t^i) b_{k+1}(i)$$


$$P_m(W_{1,N}) = \sum_i P_m(t_0 \rightarrow t^i) P_m(w_1 | t^i) b_1(i)$$

Complexity = $O(N_t^2 N)$

To get backward probability of whole sequence, loop over indices, loop over tags, and sum over tags

Backward algorithm

$P_m(W_{1,3})$



P(W)

- So, using forward probabilities:

$$P_m(W_{1,N}) = \sum_i a_N(i)$$

- Using backward probabilities:

$$P_m(W_{1,N}) = \sum_i P_m(t_0 \rightarrow t^i) P_m(w_1 | t^i) b_1(i)$$

- Using both:

$$P_m(W_{1,N}) = \sum_i a_r(i) b_r(i)$$

(for any $1 \leq r \leq N$)

Three Basic POS Computations

Model m contains transition and output probabilities

- Compute the probability of a text:

$$P_m(W_{1,N})$$

- Compute maximum probability tag sequence:

$$\operatorname{argmax}_{T_{1,N}} P_m(T_{1,N} | W_{1,N})$$

- Compute maximum likelihood model

$$\operatorname{argmax}_m P_m(W_{1,N})$$

Viterbi Tagging

Most probable tag sequence given text:

$$\begin{aligned} T^* &= \operatorname{argmax}_T P_m(T|W) \\ &= \operatorname{argmax}_T \frac{P_m(T)P_m(W|T)}{P_m(W)} \end{aligned}$$

(Bayes' Theorem)

$$= \operatorname{argmax}_T P_m(T)P_m(W|T)$$


(W is constant for all T)

$$= \operatorname{argmax}_T \prod_i (m(t_{i-1} \rightarrow t_i)m(w_i|t_i))$$

(First-order Markov assumption)

$$= \operatorname{argmax}_T \sum_i \log(m(t_{i-1} \rightarrow t_i)m(w_i|t_i))$$


Viterbi algorithm



$-\log(m)$	t^1	t^2	t^3
$t_0 \rightarrow$	2.3	1.7	1.0
$t^1 \rightarrow$	1.7	1.0	2.3
$t^2 \rightarrow$	0.3	3.3	3.3
$t^3 \rightarrow$	1.3	1.3	2.3

$-\log(m)$	w^1	w^2	w^3
t^1	0.7	2.3	2.3
t^2	1.7	0.7	3.3
t^3	1.7	1.7	1.3


Viterbi algorithm



$-\log(m)$	t^1	t^2	t^3
$t_0 \rightarrow$	2.3	1.7	1.0
$t^1 \rightarrow$	1.7	1.0	2.3
$t^2 \rightarrow$	0.3	3.3	3.3
$t^3 \rightarrow$	1.3	1.3	2.3

$-\log(m)$	w^1	w^2	w^3
t^1	0.7	2.3	2.3
t^2	1.7	0.7	3.3
t^3	1.7	1.7	1.3

Viterbi algorithm



$-\log(m)$	t^1	t^2	t^3
$t_0 \rightarrow$	2.3	1.7	1.0
$t^1 \rightarrow$	1.7	1.0	2.3
$t^2 \rightarrow$	0.3	3.3	3.3
$t^3 \rightarrow$	1.3	1.3	2.3

$-\log(m)$	w^1	w^2	w^3
t^1	0.7	2.3	2.3
t^2	1.7	0.7	3.3
t^3	1.7	1.7	1.3

Viterbi Algorithm

$D(0, \text{START}) = 0$

for each tag $t \neq \text{START}$ **do:**

$D(0, t) = -\infty$

for $i \leftarrow 1$ **to** N **do:**

for each tag t^j **do:**

$$D(i, t^j) \leftarrow \max_k (D(i-1, t^k) + \text{lm}(w_i | t^j) + \text{lm}(t^k \rightarrow t^j))$$

$\log P(W, T) = \max_j D(N, t^j)$

where $\text{lm}(w_i | t^j) \stackrel{\text{def}}{=} \log P_m(w_i | t^j)$ and so forth

Viterbi Algorithm

$D(0, \text{START}) = 0$

for each tag $t \neq \text{START}$ **do:**

$D(0, t) = -\infty$



Score for each index, tag
combination

for $i \leftarrow 1$ **to** N **do:**

for each tag t^j **do:**

$$D(i, t^j) \leftarrow \max_k (D(i-1, t^k) + \text{lm}(w_i | t^j) + \text{lm}(t^k \rightarrow t^j))$$

$\log P(W, T) = \max_j D(N, t^j)$

where $\text{lm}(w_i | t^j) \stackrel{\text{def}}{=} \log P_m(w_i | t^j)$ and so forth