

BIG DATS PROGRAMING

ASSIGNMENT-2

1 To implement the PageRank algorithm using map reduce in hadoop, given adjacency list and initial page rank values in two different text files. The primary step here is to read the two text files and split them, then following the map reduce process for page rank algorithm implementation. But this process contains of reading two text files lead to more number of mappers and its very computationally expensive. To overcome this in this assignment Distributed cache of hadoop is used so that one of the files is cached and the other is used as input in here. The Intial Page rank values file is cached and Adjacency list file is used as input file.

The overall design flow of map reduce for Page Rank is shown in below:

The Page rank algorithm is a iterative algorithm and In each iteration rank values are computes and updated with previous values until the change in values from present and previous iteration is around 10^{-6} , i.e. the values are very similar with minute error.

Based on the given graph the rank values are computed using the standard page rank formula. And the generalized version for computing ranks is shown below.

$$\mathbf{r} = c\mathbf{P}\mathbf{Tr} + (1 - c)/n$$

In each iteration we take the updated page rank value file and upload it into the cache and also the rank values are outputted into new file. This type of iteration is also called as power iteration

$$\mathbf{r}^t = c \cdot \mathbf{P}^T \cdot \mathbf{r}^{t-1} + (1 - c)\mathbf{1}/n$$

r_i^t : PageRank value of node i at iteration t

$$r_1^t = c \cdot r_4^{t-1} \cdot p_{4,1} + (1 - c)/5$$

$$r_2^t = c \cdot r_1^{t-1} \cdot p_{1,2} + (1 - c)/5$$

$$r_3^t = c \cdot r_2^{t-1} \cdot p_{2,3} + c \cdot r_5^{t-1} \cdot p_{5,3} + (1 - c)/5$$

$$r_4^t = c \cdot r_2^{t-1} \cdot p_{2,4} + c \cdot r_3^{t-1} \cdot p_{3,4} + (1 - c)/5$$

$$r_5^t = c \cdot r_4^{t-1} \cdot p_{4,5} + (1 - c)/5$$

1.1 Design of Mapper, This takes the input adjacency list row and also the Page Rank values, But as mentioned above, The page rank values are stored in Distributed cache and not given as input file path like adjacency list.

Let's see how the Page rank rank values are used in Mapper from Distributed cache, The pagerank.txt file is stored in distributed cache, This file is used in mapper class in such a way the values of PageRank are stored in a Hash Map.

Distributed cache, The hdfs file system sends small text files to each datanodes while running map reduce job through distributed cache. And these files are deleted after the job is completed from data nodes. This usage will decrease the time taken by reading file each and every time from hdfs.




Fig: Showing the working of Distributed cache

Before Mapper design, the data from distributed cache is loaded and stored in a Hash Map, The Hashmap consists of key as nth node index and values as the rank of that node. This can be achieved by overriding the setup method, And this process follow as shown below.

As a initial step read the cached files into URI array and check whether there are any files, If there are any files create File system object and pass configuration object into it, File system is a abstract class of fairly generic file system, After this open the file using File system object and convert the byte stream into character with input stream reader and store it as buffer reader. As next step check this buffered for not empty and read line by line until its empty, Using string tokenize each line is tokenized and the first token is used as key i.e nth node index and the value as PageRank until all the buffer reader is empty. The output here is the Hash Map with key as nth node index and PageRank value of it.

The Hash table created above is used for fetching page rank values based on the adjacent list node index values. As shown below.

Hash Map:		Adjacency List:	
<u>Key</u>	<u>value</u>	<u>i</u>	<u>j</u>
1	0.2	1	[2]
2	0.2	2	[3, 4]
3	0.2	3	[4]
4	0.2	4	[1, 5]
5	0.2	5	[3]

As show above the Mapper would read each line of adjacency list file and in this line is in <Text value> and the key be object, From the Object the value is converted into string and string tokenize it. After this the first value of tokenizer is used as key to hash map for getting the page rank value (from above I is the key for hashmap). Once we got the key next all tokens are taken into loop and compute $\text{rank} \times \text{transition probability}$ of the nodes and output it with <token, $\text{rank} \times \text{transition probability}$ > the transition probability is calculates using $\text{len}(\text{tokens})-1$

Output of mapper for line 2 of adjacency list is shown below

<3, $\text{hashmap}[2] \times 1 / \text{len}(\text{tokenizers}-1)$ >

<4, $\text{hashmap}[2] \times 1 / \text{len}(\text{tokenizers}-1)$ >

In above 3, 4 represents nodes and in a similar for all nodes its calculated.

1.2 Reducer:

After Shuffling and sorting the input for reducer is <node number, list of values>. For example

<1,[0.25]>

<3, [0.2, 0.1]> etc.....

In the reducer For each of this input we compute the final using formula mentioned above and the output is written as <node number, rank>

And this process is continued until 30 iterations in the main/driver class of map reduce process.

1.3 I haven't used a combiner in this process, as the data and graph is small it doesn't have that great effect on the network congestion. And if we use combiner in this problem it will be after mapper output and before shuffle and sorting so it does not have any effect. And also the combiner is nothing but the reducer and one can use same reducer as combiner in many cases but it fails if the reducer that is implemented here for a single mapper in this case doesn't act as combiner. May be one can write separate class for reducer that act as combiner and further more customized class for reducer. This Combiner system may not work for multiple mapper if the same reducer is used.

2. The Experimentation results are shown below.

1	0.15555492363830498
2	0.16223821815273626
3	0.23119216214996707
4	0.29545977242068655
5	0.15555492363830498

2.1




Fig: Showing output files created after 30 iterations

VMAILAPATH1 [SSH: JAGUAR.CS.GSU.EDU]		data > pr_test > Iteration29 > ≡ part-r-00000	
> Iteration17		1	1 0.15555492363830498
> Iteration18		2	2 0.16223821815273626
> Iteration19		3	3 0.23119216214996707
> Iteration20		4	4 0.29545977242068655
> Iteration21		5	5 0.15555492363830498
> Iteration22		6	
> Iteration23			
> Iteration24			
> Iteration25			
> Iteration26			
> Iteration27			
> Iteration28			
✓ Iteration29			
≡ _SUCCESS			
≡ part-r-00000			

Fig: showing result after 30 iterations

The results are as shown above and these results are from the 30th iteration. The error in results from 29th iteration to 30th iteration is nearly 10^{-4} . Since there is very minute change in results we stopped iterations at this point.

The results are as equal to the results that are given in the class.

VMAILAPATH1 [SSH: JAGUAR.CS.GSU.EDU]

main / java

hadoop

HadoopExamples

PageRank.java

prtest.java

WordCount.java

test

target

.classpath

OUTLINE

HadoopExamples

prtest

PowerIterationMapper

map(Object, Text, Context) : void

setup(Context) : void

JAVA DEPENDENCIES

HadoopExamples

src/main/java

HadoopExamples

PageRank.java

WordCount.java

prtest.java

MAVEN PROJECTS

HadoopExamples

workspacejava > HadoopExamples > src > main > java > HadoopExamples > prtest.java > prtest > PowerIterationMapper >

68

}

69

70

public void map(Object key, Text value, Context context

71

throws IOException, InterruptedException {

72

// You need to complete this function.

73

// tokenizing the value i.e first line in adjacency list by converting

74

//the value into string

75

StringTokenizer itr = new StringTokenizer(value.toString());

76

// Degree of the node is found by using the below line

77

nThisNodeOutDegree = itr.countTokens() - 1;

78

// getting first element in a line as index for hash map

79

nThisNodeIndex = Integer.parseInt(itr.nextToken());

80

// With the key got above use it for hashmap and access the rank of the nodes

81

dThisNodePRValue = vPRValues.get(nThisNodeIndex);

82

// Loop for accessing remaining token in itr or elements in line

83

// and each of these elements are consider as node j and also output of mapper

84

// after getting the rank and transition probability from nThisNodeOutDegree

85

// we compute and result as rank*transition probability and output the result with

86

// nNeighborNodeIndex as key

87

while (itr.hasMoreTokens()) {

88

nNeighborNodeIndex.set(Integer.parseInt(itr.nextToken()));

89

Double resultValue = dThisNodePRValue * 1 / nThisNodeOutDegree;

90

dThisNodePassingValue.set(resultValue);

91

context.write(nNeighborNodeIndex, dThisNodePassingValue);

92

}

93

}

94

}

95

Fig: Showing the mapper code

```

198 private DoubleWritable dNewPRValue = new DoubleWritable();
199
200
201
202 public void reduce(IntWritable key, Iterable<DoubleWritable> values,
203                   Context context
204                   ) throws IOException, InterruptedException {
205     // You need to complete this function.
206     // Initialixing a variable for sum of computed rank*transistion probabilities
207     // and also the decay factor c = 0.85
208     Double sum = 0.0;
209     Double decay = 0.85;
210
211     // A for loop is used to sum the values in a list that get after sorting and shuffling stage
212     for (DoubleWritable val : values) {
213         sum += val.get();
214     }
215     // the sum got above is used to compute new rank
216     // writing this values and key as output
217     sum = sum * decay + (1-decay) / a;
218     dNewPRValue.set(sum);
219     context.write(key, dNewPRValue);
220 }
221
222
223 Run | Debug
224 public static void main(String[] args) throws Exception {
225     // args[0] the initial PageRank values
226     String sInputPathForOneIteration = args[0];

```

Fig: Showing reducer code

```

227 CONNECTION=0
228 IO_ERROR=0
229 WRONG_LENGTH=0
230 WRONG_MAP=0
231 WRONG_REDUCE=0
232 File Input Format Counters
233   Bytes Read=24
234 File Output Format Counters
235   Bytes Written=109
236
237 Iteration: 26
238 2020-02-27 16:55:14,458 WARN impl.MetricsSystemImpl: JobTracker metrics system already initialized!
239 2020-02-27 16:55:14,460 WARN mapreduce.JobResourceUploader: Hadoop command-line option parsing not performed. Implement the Tool
240 1 interface and execute your application with ToolRunner to remedy this.
241 2020-02-27 16:55:14,626 INFO input.FileInputFormat: Total input files to process : 1
242 2020-02-27 16:55:14,629 INFO mapreduce.JobSubmitter: number of splits:1
243 2020-02-27 16:55:14,646 INFO mapreduce.JobSubmitter: Submitting tokens for job: job_local1322535501_0027
244 2020-02-27 16:55:14,646 INFO mapreduce.JobSubmitter: Executing with tokens: []
245 2020-02-27 16:55:14,702 INFO mapred.LocalDistributedCacheManager: Creating symlink: /home/vmalapatii/hadoop/tmp/mapred/local/job
246 _local1322535501_0027_2aea3206-78ff-45eb-9a17-b7ef9125e823/part-r-000000 <- /home/vmalapatii/part-r-000000
247 2020-02-27 16:55:14,704 INFO mapred.LocalDistributedCacheManager: Localized hdfs://localhost:9000/user/vmalapatii/data/output_p
248 r/Iteration25/part-r-000000 as file:/home/vmalapatii/hadoop/tmp/mapred/local/job_local1322535501_0027_2aea3206-78ff-45eb-9a17-b7
249 ef9125e823/part-r-000000
250 2020-02-27 16:55:14,752 INFO mapreduce.Job: The url to track the job: http://localhost:8080/
251 2020-02-27 16:55:14,753 INFO mapreduce.Job: Running job: job_local1322535501_0027
252 2020-02-27 16:55:14,753 INFO mapred.LocalJobRunner: OutputCommitter set in config null
253 2020-02-27 16:55:14,754 INFO output.FileOutputCommitter: File Output Committer Algorithm version is 2
254 2020-02-27 16:55:14,754 INFO output.FileOutputCommitter: FileOutputCommitter skip cleanup _temporary folders under output direc
255 tory:false, ignore cleanup failures: false
256 2020-02-27 16:55:14,754 INFO mapred.LocalJobRunner: OutputCommitter is org.apache.hadoop.mapreduce.lib.output.FileOutputCommitt
257 er
258 2020-02-27 16:55:14,776 INFO mapred.LocalJobRunner: Waiting for map tasks
259 2020-02-27 16:55:14,777 INFO mapred.LocalJobRunner: Starting task: attempt_local1322535501_0027_m_000000_0
260 2020-02-27 16:55:14,779 INFO output.FileOutputCommitter: File Output Committer Algorithm version is 2
261 2020-02-27 16:55:14,779 INFO output.FileOutputCommitter: FileOutputCommitter skip cleanup _temporary folders under output direc
262 tory:false, ignore cleanup failures: false
263 2020-02-27 16:55:14,779 INFO mapred.Task: Using ResourceCalculatorProcessTree : [ ]
264 2020-02-27 16:55:14,780 INFO mapred.MapTask: Processing split: hdfs://localhost:9000/user/vmalapatii/data/02AdjacencyList.txt:0

```

Fig: Showing the printed screen at 26th iteration during execution of the code


```
VMALAPATI1 [SSH: JAGUAR.CS.GSU.EDU]
  > Iteration27
  > Iteration28
  > Iteration29
  ▣ _SUCCESS
  ▣ part-r-00000
  > pr_test
    > Iteration0
    > Iteration1
    > Iteration2
  > OUTLINE
    The active editor cannot provide outline
    information.
  > JAVA DEPENDENCIES
    > src/main/java
      > HadoopExamples
        > PageRank.java
        > WordCount.java
        > prtest.java
  > MAVEN PROJECTS
    > HadoopExamples

HDFS: Number of read operations=1727
HDFS: Number of large read operations=0
HDFS: Number of write operations=294
HDFS: Number of bytes read erasure-coded=0
Map-Reduce Framework
  Map input records=5
  Map output records=7
  Map output bytes=84
  Map output materialized bytes=104
  Input split bytes=127
  Combine input records=0
  Combine output records=0
  Reduce input groups=5
  Reduce shuffle bytes=104
  Reduce input records=7
  Reduce output records=5
  Spilled Records=14
  Shuffled Maps =1
  Failed Shuffles=0
  Merged Map outputs=1
  GC time elapsed (ms)=31
  Total committed heap usage (bytes)=436953888
Shuffle Errors
  BAD_ID=0
  CONNECTION=0
  IO_ERROR=0
  WRONG_LENGTH=0
  WRONG_MAP=0
  WRONG_REDUCE=0
File Input Format Counters
  Bytes Read=24
File Output Format Counters
  Bytes Written=110
vmalapati1@kvm_vmalapati1:~$ hdfs dfs -get /user/vmalapati1/data/output_pr/* /home/vmalapati1/data/pr_test/
2020-02-27 16:55:37,677 INFO sasl.SaslDataTransferClient: SASL encryption trust check: localhostTrusted = false, remoteHostTrus
ted = false
vmalapati1@kvm_vmalapati1:~$ []
```

Fig: showing the get usage for getting files in hdfs into local system