



5 Not to be reproduced without written permission.

COPY RIGHT & CONFIDENTIAL

This document is the exclusive property of SHRIDHAN SENSORTEK and contains confidential information. This document or its contents shall not be used, reproduced or disclosed in whole or in part, without prior written permission of SHRIDHAN SENSORTEK.

This document and all its copies shall be
returned to SHRIDHAN SENSORTEK on demand.

FLOAT SWITCH

MODEL: SDN 102 | SS 316

ELECTRICAL SPECIFICATION:

CONTACT FORM	: SPST
⁴ VOLTAGE	: 200V DC
SWITCHING CURRENT MAX.	: 0.5A
CONTACT VA MAXIMUM	: 15VA
MATERIAL	: SS 316

DIMENSIONS & INFO:

L = 850 mm (Total Length)
D2 = 100 mm (Switch Point 1 - Falling)
D3 = 200 mm (Switch Point 2)
D4 = 300 mm (Switch Point 3)
STEM DIA = 12.7 mm
FLOAT DIA = 52 mm SS316L
STOPPER = 41 x 15 mm
ENCLOSURE = 85 dia x 80 mm
CONE HT = 35 mm

GLAND = M20 x 30 mm

ADAPTER DETAILS:

- 2 BSP (M)
- Outer Dia: 69 mm
- HEX: 36 A/F
- O-Ring groove @ 10mm
- 1/4 BSP(M) side port

CABLE GLAND:

- M-20, Side mounted
- Dia: 20 mm
- Protrusion: 30 mm

NOTES:

1. Switch changes form on FALLING level at D2.
2. Reference from Collar bottom.
3. Switch tolerance: +/- 2 mm
4. Qty: 01 No.



SHRIDHAN®
Automate Your Field

All Dimensions in mm

DRG NO: SDN-204-001 | REV: A | UNITS: mm

Ro

Rev

Description

EUROPE

Scale :NTS

Customer Name :

End User :

Cust Ref :

SO No. :

Projection :

Project:

