

Bharath Raj P's Software Skills & Projects Guide

A beginner-friendly handbook for rebuilding the core skills behind your résumé

Python · JavaScript · React · FastAPI · Node.js · SQL · Git · APIs · Security · AI systems

Created for Bharath Raj P · Start small, build often, explain clearly.

Contents

1	How to use this guide	1
1.1	A simple mental model of software	1
2	Foundations before frameworks	1
2.1	Programming is instructions plus data	1
2.1.1	The minimum concepts to rebuild	2
2.1.2	JavaScript is the browser language	2
2.2	C, Java, and the value of fundamentals	2
3	Web fundamentals: what happens after a click	2
3.1	HTML, CSS, and JavaScript have different jobs	2
3.2	HTTP, JSON, and REST APIs	3
3.2.1	Status codes you should recognize	3
4	React: build interfaces from small pieces	3
4.0.1	A practical form pattern	4
5	Backend development: turn rules into reliable endpoints	4
5.1	FastAPI and Express solve a similar problem	4
5.1.1	Keep routes thin	4
6	Databases: remember the right information	5
6.1	Relational databases and SQL	5
6.2	MongoDB and document thinking	5
6.2.1	The CRUD habit	5
7	Authentication and security basics	5
7.1	Authentication answers “who are you?”	5
7.1.1	Safe habits to use in every project	6
8	Tools that make you faster	6
8.1	Git and GitHub	6
8.2	Postman, logs, and debugging	6
9	Selected project walkthroughs	7
9.1	NEXORA: a secure data workspace	7
9.2	BR JARVIS: route a task to a suitable AI provider	7
9.3	Farmaa: farmer and buyer marketplace flows	7
9.4	JobBoard Pro: turn job searching into a system	8
10	A 12-week rebuild roadmap	8
10.0.1	Weekly study routine	8
11	Interview practice: explain, do not recite	8
11.1	Questions to answer in your own words	8
11.2	A good project answer structure	9
12	Build checklists	9
12.1	Before calling a project complete	9
12.2	Your next three portfolio upgrades	9
13	Glossary	9
14	Evidence and starting points	10

1 How to use this guide

This is not a textbook to memorize in one week. It is a rebuild plan. Read a short section, type the example yourself, change one value, deliberately make one mistake, and then repair it. That loop is how concepts become working knowledge.

The learning loop: understand one idea → write a tiny example → inspect the output → change it → explain it in your own words → commit the result to GitHub.

Your current résumé already points to a useful direction: [backend \(backend\)](#) systems, [frontend \(frontend\)](#) interfaces, secure workflows, and AI-enabled applications. The purpose of this guide is to make each resume line understandable enough that you can discuss it in an interview and rebuild a smaller version from scratch.

1.1 A simple mental model of software

Most applications have five moving parts:

- **Input:** a person clicks, types, uploads, or sends a request.
- **Interface:** the browser or mobile app shows controls and feedback.
- **Rules:** the backend checks permissions, validates data, and decides what may happen.
- **Storage:** a database remembers users, records, and history.
- **Feedback:** the system returns a result, error, or updated screen.



图 1 The basic path behind a modern web request.

When you feel lost, ask four questions: **What is the input?** **Where is it validated?** **Where is it stored?** **What does the user see next?** These questions work for React forms, FastAPI routes, SQL tables, and your own projects.

2 Foundations before frameworks

2.1 Programming is instructions plus data

Every language has the same foundation: variables store values, conditions choose a path, loops repeat work, functions package a reusable action, and data structures organize information.

```

# Python: a tiny function with input, rule, and output.
def price_after_discount(price, percent):
    if percent < 0 or percent > 100:
        raise ValueError("Discount must be between 0 and 100")
    return price * (1 - percent / 100)

print(price_after_discount(500, 10)) # 450.0
  
```

Read the example line by line. `price` and `percent` are inputs. The `if` protects the rule. `return` sends the result back to the caller. This exact structure appears later in API validation, database updates, and business logic.

2.1.1 The minimum concepts to rebuild

| Concept | Plain meaning | Small practice | | — | — | — | | Variables | Names for values | Store a name, score, and boolean value. | | Conditions | Choose based on true or false | Print “eligible” only if age is 18 or more. | | Loops | Repeat over a list | Sum all numbers in a list. | | Functions | Reusable named steps | Write a function that validates a phone number. | | Lists and dictionaries | Groups of ordered or named values | Store three jobs and their status. | | Errors | A signal that an expected rule failed | Handle a missing key without crashing. |

2.1.2 JavaScript is the browser language

JavaScript controls behavior in the browser and can also run on servers through Node.js. It shares the same building blocks as Python, but browser code often reacts to user events.

```
const jobs = ["NEXORA", "BR JARVIS", "Farmaa"];

function projectLabel(name) {
  return `Project: ${name}`;
}

console.log(jobs.map(projectLabel));
```

Practice: replace the list with your own projects, add a fourth item, and use filter to keep names with more than six characters.

2.2 C, Java, and the value of fundamentals

You do not need to become an expert in every language at once. Use C to understand memory, types, and control flow. Use Java to understand classes, interfaces, and larger application structure. Use Python for quick backend, automation, and data tasks. Use JavaScript for web interaction.

Rule of thumb: learn the problem first, then choose the language. A “find duplicate values” problem is still the same problem in C, Java, Python, and JavaScript.

3 Web fundamentals: what happens after a click

3.1 HTML, CSS, and JavaScript have different jobs

HTML provides structure. **CSS** controls presentation. **JavaScript** controls behavior. Keep this separation clear: do not put business rules inside CSS, and do not use JavaScript when semantic HTML can solve the problem.

```
<button id="save-button">Save profile</button>
```

```
#save-button { background: #146c43; color: white; padding: 10px 14px; }
```

```
document.querySelector("#save-button").addEventListener("click", () => {
  console.log("Save action requested");
});
```

3.2 HTTP, JSON, and REST APIs

[Hypertext Transfer Protocol \(HTTP\)](#) is the language of browser-to-server requests. A request has a method, URL, headers, and sometimes a body. A response has a status code and usually data. [JavaScript Object Notation \(JSON\)](#) is the common text format for the data.

Method	Use it for	Example
GET	Read data	Get one project or a list of jobs.
POST	Create data	Create a user or upload a file.
PATCH	Change part of data	Change an application stage.
DELETE	Remove data	Delete an old job record.

A [Representational State Transfer \(REST\)](#) API often organizes URLs around resources:

GET	/projects	→ list projects
POST	/projects	→ create a project
GET	/projects/42	→ read project 42
PATCH	/projects/42	→ update project 42
DELETE	/projects/42	→ delete project 42

3.2.1 Status codes you should recognize

200 means success. 201 means something was created. 400 means the request is malformed. 401 means sign-in is needed. 403 means signed in but not allowed. 404 means the item does not exist. 500 means the server failed unexpectedly. You do not memorize every code; you learn to use them as clues while debugging.

4 React: build interfaces from small pieces

React helps you divide a page into components. A component receives inputs called **props**, keeps changing values in **state**, and returns what the browser should display.

```
import { useState } from "react";

export default function Counter() {
  const [count, setCount] = useState(0);
  return (
    <button onClick={() => setCount(count + 1)}>
      Clicked {count} times
    </button>
  );
}
```

In this example, count is state and setCount changes it. React re-renders the component when state changes. Start with these skills before advanced React topics:

1. Build a component and pass props.
2. Use state for form fields, menus, and filters.
3. Render a list with map and a stable key.
4. Fetch data with `useEffect` only when needed.
5. Show loading, success, and error states.

4.0.1 A practical form pattern

```
async function submitProfile(event) {
  event.preventDefault();
  const response = await fetch("/api/profile", {
    method: "POST",
    headers: { "Content-Type": "application/json" },
    body: JSON.stringify({ name, phone }),
  });
  if (!response.ok) setError("Could not save profile");
}
```

Before calling an API, validate obvious inputs in the interface. The backend must validate again, because a browser check can be bypassed. This “validate twice” habit is one of the most useful security basics.

5 Backend development: turn rules into reliable endpoints

5.1 FastAPI and Express solve a similar problem

FastAPI is a Python framework; Express is a Node.js framework. Both receive requests, validate input, apply rules, call storage, and return responses. The syntax differs, but the engineering questions are identical.

```
# FastAPI example
from fastapi import FastAPI, HTTPException
from pydantic import BaseModel

app = FastAPI()

class NoteInput(BaseModel):
    text: str

@app.post("/notes", status_code=201)
def create_note(note: NoteInput):
    if len(note.text.strip()) < 3:
        raise HTTPException(status_code=400, detail="Write at least 3 characters")
    return {"id": 1, "text": note.text.strip()}
```

The important idea is not the decorator syntax. It is the sequence: **accept input** → **validate** → **apply a rule** → **return a clear result**.

5.1.1 Keep routes thin

Avoid putting every rule in one route function. A cleaner shape is:

```
route → request schema → service function → database → response schema
```

Routes describe HTTP. Services describe business rules. Database code stores data. This separation makes a project easier to test and explain.

6 Databases: remember the right information

6.1 Relational databases and SQL

A relational database stores data in tables. A table has columns; each row is one record. A primary key identifies a row. A foreign key connects one table to another.

```
CREATE TABLE tasks (
  id INTEGER PRIMARY KEY,
  title TEXT NOT NULL,
  status TEXT NOT NULL DEFAULT 'pending',
  user_id INTEGER NOT NULL
);

SELECT title, status
FROM tasks
WHERE user_id = 7 AND status != 'done';
```

Learn SELECT, INSERT, UPDATE, DELETE, WHERE, JOIN, and indexes. That is enough to build many useful systems. [Object-Relational Mapper \(ORM\)](#) libraries such as SQLAlchemy make database rows easier to work with from code, but understanding the SQL beneath them keeps you in control.

6.2 MongoDB and document thinking

MongoDB stores document-shaped data. It can be useful when fields vary often or when a record naturally looks like nested JSON. A user profile with preferences is an easy example. Do not choose MongoDB only because it feels easier; choose based on how your data relates and how you need to query it.

6.2.1 The CRUD habit

[Create, Read, Update, Delete \(CRUD\)](#) is the core of most business applications. For every new feature, write a tiny table:

User need	Operation	API idea	Database action
Add a job application	Create	POST /applications	Insert one row.
See active applications	Read	GET /applications	Select filtered rows.
Move to interview stage	Update	PATCH /applications/:id	Update one row.
Remove a test record	Delete	DELETE /applications/:id	Delete one row.

7 Authentication and security basics

7.1 Authentication answers “who are you?”

Authorization answers “what may you do?” Keep them separate. Logging in proves an identity. Role checks decide whether that identity can access a route or record.

Your projects use useful real-world patterns: [One-Time Password \(OTP\)](#) for phone verification, [Open Authorization \(OAuth\)](#) for Google sign-in, refresh-token rotation for sessions, [JSON Web Token \(JWT\)](#) access tokens, and [rate limit \(rate limit\)](#) controls for repeated requests.

1. User enters phone number.
2. Server validates the phone format and rate limit.
3. Server sends or verifies the one-time password.
4. Server creates a session or signed token.
5. Protected routes check identity and role before returning data.

7.1.1 Safe habits to use in every project

- Never commit real passwords, API keys, or tokens to GitHub.
- Validate input on the server, even if the frontend also validates it.
- Hash passwords; do not store plain text passwords.
- Return helpful but not sensitive error messages.
- Give each user access only to their own records unless a role explicitly allows more.
- Add tests around login, permissions, and important business rules.

8 Tools that make you faster

8.1 Git and GitHub

Git records history. GitHub hosts that history and makes collaboration visible. A small, clear commit is more valuable than a large unclear one.




图 2 A practical Git loop for personal and team work.

```

git status
git add src/profile.ts
git commit -m "feat: validate phone input"
git push origin main
  
```

Before committing, read `git diff`. Ask: **Does this change do one understandable thing?** Use messages such as `fix: handle empty file upload` or `docs: clarify setup steps`.

8.2 Postman, logs, and debugging

Use Postman to send API requests before your frontend is complete. Test a happy path, an invalid input, a missing token, and an unauthorized user. When something fails, read the error from bottom to top:

1. What was the request URL and method?
2. What status code returned?
3. What data did I send?
4. What did the server log say?
5. Which layer owns the failure: UI, API, rule, or database?

Debugging sentence starter: “The request reaches the route, but validation rejects the payload because the field name does not match the schema.” A specific sentence leads to a specific fix.

9 Selected project walkthroughs

This section explains your four main projects in plain language. Use it to prepare for interviews. For each project, be ready to answer: **What problem does it solve? What is the input? What is the main workflow? What did you build? What would you improve next?**

9.1 NEXORA: a secure data workspace

Simple explanation: NEXORA helps a signed-in user bring CSV or Excel data into a personal workspace. The system previews the data first, saves it in batches, and records what happened.




图 3 NEXORA's sign-in, import, storage, and audit trail workflow.

Why the architecture matters: importing a large file directly in one operation can make a server slow or unreliable. NEXORA previews the schema, splits work into batches, and logs the import. Authentication protects who can see a collection. This is a strong example of **backend** rules plus a **frontend** workflow.

Small rebuild exercise: create a page that accepts a CSV file, shows the first five rows, and sends the file metadata to a FastAPI route. Do not start with 1,000 rows; make five rows work first.

9.2 BR JARVIS: route a task to a suitable AI provider

Simple explanation: BR JARVIS is an AI gateway. It chooses a model provider based on a policy, checks whether that provider has the required capability, and uses a limited fallback when a provider fails.




图 4 BR JARVIS keeps AI routing observable and recoverable.

Key lesson: an AI feature is not only “send a prompt.” A dependable system must decide which model is suitable, record failures, avoid repeatedly calling a failing provider, and test its routing rules. The same discipline applies to payment gateways, notification services, and any third-party integration.

Small rebuild exercise: create a Python dictionary of three “providers” with a name, cost, and capabilities. Write a function that selects the first provider supporting a requested capability. Add a test that proves an unsupported provider is skipped.

9.3 Farmaa: farmer and buyer marketplace flows

Simple explanation: Farmaa connects farmers and buyers through mobile and backend workflows. It identifies the user, confirms their role, issues tokens, and lets the appropriate person use marketplace features.




图 5 Farmaa's role-aware authentication and marketplace workflow.

Key lesson: roles change what a user may do. A farmer and buyer may both sign in, but they should not automatically see the same controls or data. This is authorization. The phone OTP expiry and request limits are examples of rules designed to reduce misuse.

Small rebuild exercise: build a two-role app with a dropdown for farmer or buyer. After login, show a different dashboard heading for each role. Then move the role check to a FastAPI route.

9.4 JobBoard Pro: turn job searching into a system

Simple explanation: JobBoard Pro helps a user capture applications, assign a stage, import/export spreadsheet data, and inspect a funnel. AI helpers assist with interview preparation and cover-letter workflows.




图 6 JobBoard Pro turns scattered job-search activity into an inspectable workflow.

Key lesson: dashboards are not just charts. A useful dashboard begins with reliable data: an application has a company, role, date, stage, and notes. Once those records are consistent, filters and charts become meaningful.

Small rebuild exercise: create a React list of five applications. Add a stage selector with Saved, Applied, Interview, and Offer. Count how many records belong to each stage.

10 A 12-week rebuild roadmap

You do not need to study everything every day. Use focused blocks and keep one small repository for each week's output.

| Weeks | Focus | Deliverable | | - | - | - | | 1-2 | Python, JavaScript, Git, terminal basics | Ten tiny scripts and a clean GitHub repository. | | 3-4 | HTML, CSS, React components and forms | A responsive profile or task-tracker interface. | | 5-6 | APIs, FastAPI or Express, Postman | A CRUD API with validation and useful errors. | | 7-8 | SQL, schema design, authentication | A user-scoped notes or tasks application. | | 9-10 | Testing, logging, security basics | Tests for routes, roles, and edge cases. | | 11-12 | Rebuild one selected project feature | A documented mini-version of NEXORA, Farmaa, BR JARVIS, or JobBoard Pro. |

10.0.1 Weekly study routine

- **Day 1:** learn one concept and type a 20-line example.
- **Day 2:** repeat it without looking at notes.
- **Day 3:** connect it to an API or database.
- **Day 4:** break it on purpose and debug it.
- **Day 5:** write a short README explaining what you built.
- **Day 6:** review, clean variable names, and commit.
- **Day 7:** rest or watch one focused tutorial only after you know the questions you need answered.

11 Interview practice: explain, do not recite

11.1 Questions to answer in your own words

1. What is the difference between authentication and authorization?
2. Why does an API validate input even when a React form validates it?
3. What happens from a button click to a database update in your project?
4. When would you use a SQL table instead of a document database?
5. How do you investigate a 401 or 500 error?
6. What is the reason for a Git commit instead of saving files only on your laptop?
7. How does NEXORA reduce risk when importing user files?
8. Why does BR JARVIS need fallback and cooldown behavior?
9. How does Farmaa separate farmer and buyer actions?

10. What data must JobBoard Pro store before it can show a useful funnel chart?

11.2 A good project answer structure

Use this simple format: **problem** → **user** → **workflow** → **technical decision** → **evidence** → **next improvement**.

Example: “NEXORA helps a user organize imported spreadsheet data. I built a React and FastAPI workflow that previews a file schema, stores records in batches, and creates an activity log. I used authenticated user-scoped collections so one user’s data is separated from another’s. Next, I would add stronger import error reporting and a resumable job status view.”

12 Build checklists

12.1 Before calling a project complete

- The README explains setup, purpose, features, and the main workflow.
- Environment variables are documented without exposing secrets.
- Invalid inputs produce a clear response.
- A new user cannot access another user’s data.
- Important rules have at least one `test (test)`.
- The app has loading, empty, and error states.
- The project has a small demo dataset or safe example request.
- You can explain the architecture in one minute.

12.2 Your next three portfolio upgrades

1. Write one detailed case study for NEXORA with a screenshot of the import flow and a short architecture diagram.
2. Add a short BR JARVIS test demonstration that shows a failed provider, fallback, and logged cooldown.
3. Record a one-minute screen walkthrough for Farmaa or JobBoard Pro and link it from the project README.

13 Glossary

API – Application Programming Interface: A contract that lets one software component request data or work from another component.

backend – backend: The server-side part of an application: business rules, authentication, persistence, and integrations.

CRUD – Create, Read, Update, Delete: The four basic operations used to manage stored data.

frontend – frontend: The browser-visible part of an application: screens, interactions, and client-side state.

HTTP – Hypertext Transfer Protocol: The request-and-response protocol commonly used by web browsers and web servers.

JSON – JavaScript Object Notation: A lightweight text format used to exchange structured data.

JWT – JSON Web Token: A signed token that can carry claims about an authenticated user.

LLM – Large Language Model: A model that generates or transforms language and code from prompts.

OAuth – Open Authorization: A protocol family commonly used to let an app use an identity provider such as Google without handling the user’s password.

ORM – Object-Relational Mapper: A library that maps application objects to rows in a relational database.

OTP – One-Time Password: A short code used once to help verify that a person controls a phone number or email address.

rate limit – rate limit: A control that restricts how often a caller can make an action in a time window.

REST – Representational State Transfer: A practical convention for organizing API resources with URLs and HTTP methods.

test – test: A repeatable check that compares actual program behavior with expected behavior.

14 Evidence and starting points

The project explanations in this guide are based on the implementation evidence reviewed for your résumé.

Use the repositories below as the source of truth when rebuilding or extending a feature.

1. [NEXORA repository](<https://github.com/bharathraj14/nexora>)
2. [BR JARVIS repository](<https://github.com/bharathraj14/BrJarvis>)
3. [Farmaa repository](<https://github.com/bharathraj14/farmaa>)
4. [JobBoard Pro repository](https://github.com/bharathraj14/job_manager)
5. [Bharath Raj P's portfolio](<https://www.bharathrajdev.me/>)

Keep this guide beside your editor. Build one small thing today.