

Status	Finished
Started	Tuesday, 4 November 2025, 6:18 PM
Completed	Tuesday, 4 November 2025, 6:42 PM
Duration	24 mins 16 secs

Question **1**

Correct

The k-digit number N is an Armstrong number if and only if the k-th power of each digit sums to N.

Given a positive integer N, return true if and only if it is an Armstrong number.

Example 1:

Input:

153

Output:

true

Explanation:

153 is a 3-digit number, and $153 = 1^3 + 5^3 + 3^3$.

Example 2:

Input:

123

Output:

false

Explanation:

123 is a 3-digit number, and $123 \neq 1^3 + 2^3 + 3^3 = 36$.

Example 3:

Input:

1634

Output:

true

Note:

$1 \leq N \leq 10^8$

Answer: (penalty regime: 0 %)

```

1  #include<stdio.h>
2  #include<math.h>
3  int main()
4  {
5      int n;
6      scanf("%d",&n);
7      int x=0,n2=n;
8      while(n2!=0)
9      {
10         x++;
11         n2=n2/10;
12     }
13     int sum=0;
14     int n3=n,n4;
15     while(n3!=0)
16     {
17         n4=n3%10;
18         sum=sum+pow(n4,x);
19         n3=n3/10;
20     }
21     if(n==sum)
22         printf("true");
23     else
24         printf("false");
25 }
```



	Input	Expected	Got	
✓	153	true	true	✓
✓	123	false	false	✓

Passed all tests! ✓

Question **2**

Correct

Take a number, reverse it and add it to the original number until the obtained number is a palindrome.

Constraints $1 \leq \text{num} \leq 999999999$ **Sample Input 1**

32

Sample Output 1

55

For example:

Input	Result
32	55
1234	5555

Answer: (penalty regime: 0 %)

```
1  #include<stdio.h>
2  int main()
3  {
4      int rn,n,nt=0,i=0;
5      scanf("%d",&n);
6      do{
7          nt=n;rn=0;
8          while(n!=0)
9          {
10             rn=rn*10+n%10;
11             n=n/10;
12         }
13         n=nt+rn;
14         i++;
15     }
16     while(rn!=nt || i==1);
17     printf("%d",rn);
18 }
```



	Input	Expected	Got	
✓	32	55	55	✓
✓	1234	5555	5555	✓

Passed all tests! ✓



Question **3**

Correct

Maya, a student in an arts and crafts class, wants to create a pattern using stars (*) in a specific format. She plans to use a program to help her construct the pattern.

Write a program that takes an integer as input and constructs the following pattern using nested for loops.

Input: 5

Output:

```
*
* *
* * *
* * * *
* * * * *
* * * *
* * *
* *
*
```

Answer: (penalty regime: 0 %)

```
1  #include<stdio.h>
2  int main()
3  {
4      int n,i,j;
5      scanf("%d",&n);
6      for(i=1;i<=n;i++)
7      {
8          for(j=1;j<=i;j++)
9          {
10             printf("* ");
11         }
12         printf("\n");
13         for(i=n-1;i>=1;i--)
14         {
15             for(j=1;j<=i;j++)
16             {
17                 printf("* ");
18             }
19             printf("\n");
20         }
21 }
```



	Input	Expected	Got	
✓	5	<pre>* *</pre>	<pre>* *</pre>	✓

Passed all tests! ✓