

## Q.1 Create Database

Ans. create database shopping;

```
bharat@bharat:~$ sudo mysql
[sudo] password for bharat:
Welcome to the MySQL monitor.  Commands end with ; or \g.
Your MySQL connection id is 4
Server version: 5.7.29-0ubuntu0.18.04.1 (Ubuntu)

Copyright (c) 2000, 2020, Oracle and/or its affiliates. All rights reserved.


Oracle is a registered trademark of Oracle Corporation and/or its
affiliates. Other names may be trademarks of their respective
owners.

Type 'help;' or '\h' for help. Type '\c' to clear the current input statement.

mysql> create database shopping
-> ;
Query OK, 1 row affected (0.00 sec)

mysql> show database;
ERROR 1064 (42000): You have an error in your SQL syntax; check the manual that corresponds to your MySQL server version for the right syntax
to use near 'database' at line 1
mysql> use shopping;
Database changed
mysql>
```

## Q.2 Design Schema




### Q.3 Create tables

//for creating sales-person table

```
create table sales_person(s_id int primary key auto_increment,s_name varchar(100));
```

//for creating customer table

```
mysql> create table customer(cus_id int primary key auto_increment,cus_name varchar(40),s_id  
int,FOREIGN KEY (s_id) REFERENCES sales_person(s_id));
```



```
Activities Terminal Thu 14:54 bharat@Bharat: ~
File Edit View Search Terminal Help
mysql> desc tables sales_person;
ERROR 1146 (42S02): Table 'shopping.tables' doesn't exist
mysql> desc sales_person;
+-----+-----+-----+-----+-----+-----+
| Field | Type          | Null | Key | Default | Extra          |
+-----+-----+-----+-----+-----+-----+
| s_id  | int(11)       | NO   | PRI | NULL    | auto_increment |
| s_name | varchar(100)  | YES  |     | NULL    |                |
+-----+-----+-----+-----+-----+-----+
2 rows in set (0.00 sec)

mysql> create table customer(cus_id int primary key auto_increment,cus_name varchar(40),s_id
-> int,FOREIGN KEY (s_id) REFERENCES sales_person(s_id));
ERROR 1064 (42000): You have an error in your SQL syntax; check the manual that corresponds to your MySQL server version for the right syntax
to use near 'id)' at line 2
mysql> create table customer(cus_id int primary key auto_increment,cus_name varchar(40),s_id int,FOREIGN KEY (s_id) REFERENCES sales_person(s
id));
ERROR 1064 (42000): You have an error in your SQL syntax; check the manual that corresponds to your MySQL server version for the right syntax
to use near 'id)' at line 1
mysql> create table customer(cus_id int primary key auto_increment,cus_name varchar(40),s_id int,FOREIGN KEY (s_id) REFERENCES sales_person(s
id));
Query OK, 0 rows affected (0.03 sec)

mysql> desc customer;
+-----+-----+-----+-----+-----+-----+
| Field | Type          | Null | Key | Default | Extra          |
+-----+-----+-----+-----+-----+-----+
| cus_id | int(11)       | NO   | PRI | NULL    | auto_increment |
| cus_name | varchar(40)  | YES  |     | NULL    |                |
| s_id  | int(11)       | YES  | MUL | NULL    |                |
+-----+-----+-----+-----+-----+-----+
3 rows in set (0.01 sec)

mysql>
```

//for creating order table

```
create table orders(odr_id int primary key auto_increment,order_detail varchar(100),cus_id int,s_id  
int, foreign key(cus_id) references customer(cus_id),foreign key(s_id) references  
sales_person(s_id));
```

```
Activities Terminal Thu 15:05
bharat@Bharat: ~

File Edit View Search Terminal Help

mysql> create table orders(odr_id int primary key auto_increment,order_detail varchar(100),cus_id int,s_id int foreign key(cus_id) reference
s customer(cus_id),foreign key(s_id) references sales_person(s_id));
ERROR 1064 (42000): You have an error in your SQL syntax; check the manual that corresponds to your MySQL server version for the right syntax
to use near 'foreign key(cus_id) references customer(cus_id),foreign key(s_id) references sal' at line 1
mysql> create table orders(odr_id int primary key auto_increment,order_detail varchar(100),cus_id int,s_id int foreign key(cus_id) reference
s customer(cus_id),foreign key(s_id) references sales_person(s_id));
ERROR 1064 (42000): You have an error in your SQL syntax; check the manual that corresponds to your MySQL server version for the right syntax
to use near 'foreign key(cus_id) references customer(cus_id),foreign key(s_id) references sal' at line 1
mysql> create table orders(odr_id int primary key auto_increment,order_detail varchar(100),cus_id int,s_id int foreign key(cus_id) references
customer(cus_id),foreign key(s_id) references sales_person(s_id));
ERROR 1064 (42000): You have an error in your SQL syntax; check the manual that corresponds to your MySQL server version for the right syntax
to use near 'foreign key(cus_id) references customer(cus_id),foreign key(s_id) references sal' at line 1
mysql> create table orders(odr_id int primary key auto_increment,order_detail varchar(100),cus_id int,s_id int foreign key(cus_id) references
custome
^C
mysql> create table orders(odr_id int primary key auto_increment,order_detail varchar(100),cus_id int,s_id int, foreign key(cus_id) references
customer(cus_id),foreign key(s_id) references sales_person(s_id));
Query OK, 0 rows affected (0.04 sec)

mysql> desc orders;
+-----+-----+-----+-----+-----+-----+
| Field | Type | Null | Key | Default | Extra |
+-----+-----+-----+-----+-----+-----+
| odr_id | int(11) | NO | PRI | NULL | auto_increment |
| order_detail | varchar(100) | YES | | NULL | |
| cus_id | int(11) | YES | MUL | NULL | |
| s_id | int(11) | YES | MUL | NULL | |
+-----+-----+-----+-----+-----+-----+
4 rows in set (0.00 sec)

mysql>
```

```
Activities Terminal Thu 15:08
bharat@Bharat: ~

File Edit View Search Terminal Help

mysql> create table orders(odr_id int primary key auto_increment,order_detail varchar(100),cus_id int,s_id int foreign key(cus_id) reference
s customer(cus_id),foreign key(s_id) references sales_person(s_id));
ERROR 1064 (42000): You have an error in your SQL syntax; check the manual that corresponds to your MySQL server version for the right syntax
to use near 'foreign key(cus_id) references customer(cus_id),foreign key(s_id) references sal' at line 1
mysql> create table orders(odr_id int primary key auto_increment,order_detail varchar(100),cus_id int,s_id int foreign key(cus_id) references
customer(cus_id),foreign key(s_id) references sales_person(s_id));
ERROR 1064 (42000): You have an error in your SQL syntax; check the manual that corresponds to your MySQL server version for the right syntax
to use near 'foreign key(cus_id) references customer(cus_id),foreign key(s_id) references sal' at line 1
mysql> create table orders(odr_id int primary key auto_increment,order_detail varchar(100),cus_id int,s_id int foreign key(cus_id) references
customer(cus_id),foreign key(s_id) references sales_person(s_id));
ERROR 1064 (42000): You have an error in your SQL syntax; check the manual that corresponds to your MySQL server version for the right syntax
to use near 'foreign key(cus_id) references customer(cus_id),foreign key(s_id) references sal' at line 1
mysql> create table orders(odr_id int primary key auto_increment,order_detail varchar(100),cus_id int,s_id int foreign key(cus_id) references
custome
^C
mysql> create table orders(odr_id int primary key auto_increment,order_detail varchar(100),cus_id int,s_id int, foreign key(cus_id) references
customer(cus_id),foreign key(s_id) references sales_person(s_id));
Query OK, 0 rows affected (0.04 sec)

mysql> desc orders;
+-----+-----+-----+-----+-----+-----+
| Field | Type | Null | Key | Default | Extra |
+-----+-----+-----+-----+-----+-----+
| odr_id | int(11) | NO | PRI | NULL | auto_increment |
| order_detail | varchar(100) | YES | | NULL | |
| cus_id | int(11) | YES | MUL | NULL | |
| s_id | int(11) | YES | MUL | NULL | |
+-----+-----+-----+-----+-----+-----+
4 rows in set (0.00 sec)

mysql> show tables;
^C
mysql>
```

Q.4 Insert sample data

Ans.

```
mysql> insert into sales_person(s_id,s_name) values(100,'sales');
insert into customer(cus_id,cus_name,s_id) values (1,'abc',100);
insert into orders(odr_id,order_detail,cus_id,s_id) values(1000,'order is places',1,100);
```

```
Activities Terminal Thu 15:18
bharat@Bharat: ~

File Edit View Search Terminal Help

+-----+
| cus_id | int(11) | YES | MUL | NULL |
| s_id   | int(11) | YES | MUL | NULL |
+-----+
4 rows in set (0.00 sec)

mysql> insert into orders(odr_id,order_detail,cus_id,s_id) values(1000,'order is places',1,100);
Query OK, 1 row affected (0.01 sec)

mysql> ^C;
^C

mysql> insert into sales_person(s_id,s_name) values(101,'sales1');
Query OK, 1 row affected (0.01 sec)

mysql> insert into sales_person(s_id,s_name) values(102,'sales2');
Query OK, 1 row affected (0.01 sec)

mysql> insert into sales_person(s_id,s_name) values(103,'sales3');
Query OK, 1 row affected (0.01 sec)

mysql> insert into customer(cus_id,cus_name,s_id) values (2,'ram',100);
Query OK, 1 row affected (0.01 sec)

mysql> insert into customer(cus_id,cus_name,s_id) values (3,'john',101);
Query OK, 1 row affected (0.01 sec)

mysql> insert into orders(odr_id,order_detail,cus_id,s_id) values(1001,'order is placed 1',1,100);
Query OK, 1 row affected (0.01 sec)

mysql> insert into orders(odr_id,order_detail,cus_id,s_id) values(1001,'order is placed 2',2,101);
ERROR 1062 (23000): Duplicate entry '1001' for key 'PRIMARY'
mysql> insert into orders(odr_id,order_detail,cus_id,s_id) values(1002,'order is placed 2',2,101);
Query OK, 1 row affected (0.01 sec)

mysql> insert into orders(odr_id,order_detail,cus_id,s_id) values(1003,'order is placed 3',2,102);
Query OK, 1 row affected (0.01 sec)

mysql>
```

```
Activities Terminal Thu 15:18
bharat@Bharat: ~

File Edit View Search Terminal Help

Query OK, 1 row affected (0.01 sec)

mysql> select * from sales_person;
+-----+
| s_id | s_name |
+-----+
| 100  | sales  |
| 101  | sales1 |
| 102  | sales2 |
| 103  | sales3 |
+-----+
4 rows in set (0.00 sec)

mysql> select * from customer;
ERROR 1064 (42000): You have an error in your SQL syntax; check the manual that corresponds to your MySQL server version for the right syntax
to use near 'sselect * from customer' at line 1
mysql> select * from customer;
+-----+
| cus_id | cus_name | s_id |
+-----+
| 1      | abc      | 100  |
| 2      | ram      | 100  |
| 3      | john     | 101  |
+-----+
3 rows in set (0.00 sec)

mysql> select * from orders;
+-----+
| odr_id | order_detail | cus_id | s_id |
+-----+
| 1000   | order is places | 1      | 100  |
| 1001   | order is placed 1 | 1      | 100  |
| 1002   | order is placed 2 | 2      | 101  |
| 1003   | order is placed 3 | 2      | 102  |
+-----+
4 rows in set (0.00 sec)

mysql>
```



Q.5 Find the sales person have multiple orders.

Ans. Select \* from sales\_person where s\_id in(select distinct s\_id from orders o where exists(select \* from orders o1 where o1.s\_id=o.s\_id and o1.odr\_id<>o.odr\_id));

```
Activities Terminal Thu 15:27 bharat@Bharat: ~
mysql> select * from sales_person where s_id in(select distinct s_id from orders o where exists(select * from orders o1 where o1.s_id=o.s_id and o1.odr_id<>o.odr_id));
ERROR 1146 (42S02): Table 'shopping.orderso' doesn't exist
mysql> select * from sales_person where s_id in(select distinct s_id from orders o where exists(select * from orders o1 where o1.s_id=o.s_id and o1.odr_id<>o.odr_id));
+-----+-----+
| s_id | s_name |
+-----+-----+
| 100 | sales |
+-----+-----+
1 row in set (0.01 sec)

mysql> select * from orders;
+-----+-----+-----+-----+
| odr_id | order_detail | cus_id | s_id |
+-----+-----+-----+-----+
| 1000 | order is places | 1 | 100 |
| 1001 | order is placed 1 | 1 | 100 |
| 1002 | order is placed 2 | 2 | 101 |
| 1003 | order is placed 3 | 2 | 102 |
+-----+-----+-----+-----+
4 rows in set (0.00 sec)
```

Q.6 Find the all sales person details along with order details

Ans select s\_name,odr\_id,order\_detail from sales\_person inner join orders on sales\_person.s\_id=orders.s\_id;

```
Activities Terminal Thu 15:31 bharat@Bharat: ~
mysql> select * from orders;
+-----+-----+-----+-----+
| odr_id | order_detail | cus_id | s_id |
+-----+-----+-----+-----+
| 1000 | order is places | 1 | 100 |
| 1001 | order is placed 1 | 1 | 100 |
| 1002 | order is placed 2 | 2 | 101 |
| 1003 | order is placed 3 | 2 | 102 |
+-----+-----+-----+-----+
4 rows in set (0.00 sec)

mysql> select odr_id,order_detail,cus_id,s_id from orders where s_id IN(1,2) group by s_id having count(s_id)=2;
ERROR 1055 (42000): Expression #1 of SELECT list is not in GROUP BY clause and contains nonaggregated column 'shopping.orders.odr_id' which is not functionally dependent on columns in GROUP BY clause; this is incompatible with sql_mode=only_full_group_by
mysql> select odr_id,sales_person where s_id in(select distinct s_id from orders o where exists(select * from orders o1 where o1.s_id=o.s_id and o1.odr_id<>o.odr_id));
+-----+-----+
| s_id | s_name |
+-----+-----+
| 100 | sales |
+-----+-----+
1 row in set (0.00 sec)

mysql> select s_name,odr_id,odr_desc from sales_person inner join orders on sales_person.s_id=orders.s_id;
ERROR 1054 (42S22): Unknown column 'odr_desc' in 'field list'
mysql> select s_name,odr_id,odr_detail from sales_person inner join orders on sales_person.s_id=orders.s_id;
ERROR 1054 (42S22): Unknown column 'odr_detail' in 'field list'
mysql> select s_name,odr_id,order_detail from sales_person inner join orders on sales_person.s_id=orders.s_id;
+-----+-----+-----+
| s_name | odr_id | order_detail |
+-----+-----+-----+
| sales | 1000 | order is places |
| sales | 1001 | order is placed 1 |
| sales1 | 1002 | order is placed 2 |
| sales2 | 1003 | order is placed 3 |
+-----+-----+-----+
4 rows in set (0.00 sec)

mysql>
```

### Q.7 Create index

Ans. create index detail on orders(order\_detail);

```

Thu 15:33
bharat@Bharat: ~
File Edit View Search Terminal Help
+-----+
4 rows in set (0.00 sec)

mysql> select odr_id,order_detail,cus_id,s_id from orders where s_id IN(1,2) group by s_id having count(s_id)=2;
ERROR 1055 (42000): Expression #1 of SELECT list is not in GROUP BY clause and contains nonaggregated column 'shopping.orders.odr_id' which is
not functionally dependent on columns in GROUP BY clause; this is incompatible with sql_mode=only_full_group_by
mysql> select odr_id,sales_person where s_id in(select distinct s_id from orders o where exists(select * from orders o1 where o1.s_id=o.s_id a
nd o1.odr_id<>o.odr_id));
+-----+
| s_id | s_name |
+-----+
| 100 | sales |
+-----+
1 row in set (0.00 sec)

mysql> select s_name,odr_id,odr_desc from sales_person inner join orders on sales_person.s_id=orders.s_id;
ERROR 1054 (42S22): Unknown column 'odr_desc' in 'field list'
mysql> select s_name,odr_id,odr_detail from sales_person inner join orders on sales_person.s_id=orders.s_id;
ERROR 1054 (42S22): Unknown column 'odr_detail' in 'field list'
mysql> select s_name,odr_id,order_detail from sales_person inner join orders on sales_person.s_id=orders.s_id;
+-----+
| s_name | odr_id | order_detail |
+-----+
| sales | 1000 | order is places |
| sales | 1001 | order is placed 1 |
| sales1 | 1002 | order is placed 2 |
| sales2 | 1003 | order is placed 3 |
+-----+
4 rows in set (0.00 sec)

mysql> create index detail on order(order_detail);
create index detail on order(order_detail);
^C
mysql> create index detail on orders(order_detail);
Query OK, 0 rows affected (0.04 sec)
Records: 0 Duplicates: 0 Warnings: 0

mysql>

```

### Q.8 How to show index on a table

Ans. show indexes from orders;

Activities Terminal Thu 15:35  
bharat@Bharat: ~

File Edit View Search Terminal Help

```
+-----+
| sales | 1000 | order is places |
| sales | 1001 | order is placed 1 |
| sales1 | 1002 | order is placed 2 |
| sales2 | 1003 | order is placed 3 |
+-----+
4 rows in set (0.00 sec)
```

```
mysql> create index detail on order(order_detail);
create index detail on order(order_detail);
^C
mysql> create index detail on orders(order_detail);
Query OK, 0 rows affected (0.04 sec)
Records: 0 Duplicates: 0 Warnings: 0
```

```
mysql> show indexes from orders;
show indexes from orders;
^C
mysql> show indexes from orders;
```

```
+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+
| Table | Non_unique | Key_name | Seq_in_index | Column_name | Collation | Cardinality | Sub_part | Packed | Null | Index_type | Comment | Index_comment |
+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+
| orders | 0 | PRIMARY | 1 | odr_id | A | 4 | NULL | NULL | YES | BTREE | | |
| orders | 1 | cus_id | 1 | cus_id | A | 2 | NULL | NULL | YES | BTREE | | |
| orders | 1 | s_id | 1 | s_id | A | 3 | NULL | NULL | YES | BTREE | | |
| orders | 1 | detail | 1 | order_detail | A | 4 | NULL | NULL | YES | BTREE | | |
+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+
4 rows in set (0.00 sec)
```

```
mysql>
```

Q.9 Find the order number, sale person name, along with the customer to whom that order belongs to.

Ans. `select c.cus_id,c.cus_name,s.s_id,odr_id,s_name from customer c inner join sales_person s on c.s_id=s.s_id inner join orders o on o.s_id=s.s_id;`

```
Activities Terminal Thu 15:39
bharat@Bharat: ~
File Edit View Search Terminal Help
show indexes from orders;
^C
mysql> show indexes from orders;
+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+
| Table | Non_unique | Key_name | Seq_in_index | Column_name | Collation | Cardinality | Sub_part | Packed | Null | Index_type | Comment | Index_comment |
+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+
| orders |            |          |              | odr_id      | A         |            4 | NULL    | NULL   |      | BTREE      |          |                |
| orders |            |          |              | cus_id      | A         |            2 | NULL    | NULL   | YES  | BTREE      |          |                |
| orders |            |          |              | s_id        | A         |            3 | NULL    | NULL   | YES  | BTREE      |          |                |
| orders |            |          |              | order_detail | A         |            4 | NULL    | NULL   | YES  | BTREE      |          |                |
+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+
4 rows in set (0.00 sec)

mysql> select c.cus_id,c.cus_name,s.s_id,odr_id,s_name from customer c inner join sales_person s on c.s_id=s.s_id inner join orders o on o.s_id=s.s_id;
ERROR 1054 (42S22): Unknown column 'c.cus_id' in 'field list'
mysql> select c.cus_id,c.cus_name,s.s_id,odr_id,s_name from customer c inner join sales_person s on c.s_id=s.s_id inner join orders o on o.s_id=s.s_id;
+-----+-----+-----+-----+-----+
| cus_id | cus_name | s_id | odr_id | s_name |
+-----+-----+-----+-----+-----+
| 1      | abc      | 100  | 1000   | sales  |
| 1      | abc      | 100  | 1001   | sales  |
| 2      | ram      | 100  | 1000   | sales  |
| 2      | ram      | 100  | 1001   | sales  |
| 3      | john     | 101  | 1002   | sales1 |
+-----+-----+-----+-----+-----+
5 rows in set (0.00 sec)

mysql>
```