

Convert `std::any` to `std::variant`

Asked 2 years, 10 months ago Modified 2 years, 10 months ago Viewed 542 times



1



There's not much to be done with a `std::any` (except store it) until its contained type is known or suspected. Then it can be queried (`type()`) or cast (`any_cast`). But what about when instead of one type there is a need to deal with multiple types? In this case a solution can be to convert it to `std::variant`.

E.g. An API provides `std::any` objects, but only a finite set of types is required and the objects need to be stored in a container (vector, tree etc.).

How can `std::any` be converted to `std::variant`?

Disclaimer: `std::any` is mainly intended to be used in library code where its purpose is to replace `void *` in some clever templates and type erasures. As with any new thing `std::any` can be overused and misused. Please think twice if `std::any` is the right solution for your code.

`c++` `c++17` `variant`

Share Improve this question Follow

asked Apr 13, 2020 at 7:02



bolov

70.6k

15

139

217

1 Answer

Sorted by:

Highest score (default)



4



This code takes a `std::any` object along with a list of types and converts the object to `std::variant` or throws `std::bad_any_cast` if the stored type is not one of the given types.

```
#include <any>
#include <variant>
#include <optional>
#include <typeinfo>
```

Your privacy

By clicking "Accept all cookies", you agree Stack Exchange can store cookies on your device and disclose information in accordance with our [Cookie Policy](#).

Accept all cookies

Customize settings

```
bool found = ((a.type() == typeid(Args)) && (v = std::any_cast<Args>(std::move(a)),
```

```

true)) || ...);

    if (!found)
        throw std::bad_any_cast{};

    return std::move(*v);
}

```

Example usage:

```

auto test(const std::any& a)
{
    auto v = any_to_variant_cast<int, std::string>(a);

    std::visit([](auto val) { std::cout << val << std::endl; }, v);
}

```

[Code on godbolt](#)

Some explanations:

`std::optional<std::variant<Args...>>` is used because `std::variant<Args...>` [default constructor](#) constructs the variant holding the value-initialized value of the first alternative and requires the first alternative to be default constructible.

```

((a.type() == typeid(Args) && (v = std::any_cast<Args>(std::move(a)), true)) || ...)
// -----
//          type_check                      any_cast

```

This is a [fold expression](#). I've renamed some of the subexpression to be easier to explain. With the renaming the expression becomes:

```
// ((type_check && (any_cast, true)) || ...)
```

- if `type_check` is `false` then:
 - `(any_cast, true)` is not evaluated due to the short circuit of `&&`
 - `(type_check && (any_cast, true))` evaluates to `false`
 - the next op in the fold expression is evaluated

Your privacy

By clicking "Accept all cookies", you agree Stack Exchange can store cookies on your device and disclose information in accordance with our [Cookie Policy](#).

- `(any_cast, true)` evaluates to `true`
- `(type_check && (any_cast, true))` evaluates to `true`
- the rest of the fold is not evaluated due to the short circuit of `||`
- the whole expression (the fold) evaluates to `true`
- if no `type_check` evaluates to `true` then the whole expression (the fold) evaluates to `false`

[Share](#) [Improve this answer](#) [Follow](#)[edited Apr 13, 2020 at 8:32](#)[answered Apr 13, 2020 at 7:02](#)[bolov](#)**70.6k**

15

139

217

Your privacy

By clicking "Accept all cookies", you agree Stack Exchange can store cookies on your device and disclose information in accordance with our [Cookie Policy](#).