

## Complicated declarations in C

Most of the times declarations are simple to read, but it is hard to read some declarations which involve pointer to functions. For example, consider the following declaration from “signal.h”.

```
void (*bsd_signal(int, void (*)(int)))(int);
```

[Run on IDE](#)

Let us see the steps to read complicated declarations.

- 1) Convert C declaration to postfix format and read from left to right.
- 2) To convert expression to postfix, start from innermost parenthesis, If innermost parenthesis is not present then start from declarations name and go right first. When first ending parenthesis encounters then go left. Once whole parenthesis is parsed then come out from parenthesis.
- 3) Continue until complete declaration has been parsed.

Let us start with simple example. Below examples are from “K & R” book.

```
1) int (*fp) ();
```

[Run on IDE](#)

Let us convert above expression to postfix format. For the above example, there is no innermost parenthesis, that's why, we will print declaration name i.e. “fp”. Next step is, go to right side of expression, but there is nothing on right side of “fp” to parse, that's why go to left side. On left side we found “\*”, now print “\*” and come out of parenthesis. We will get postfix expression as below.

```
fp * () int
```

Now read postfix expression from left to right. e.g. fp is pointer to function returning int

Let us see some more examples.

```
2) int (*daytab)[13]
```

[Run on IDE](#)

Postfix : daytab \* [13] int

Meaning : daytab is pointer to array of 13 integers.

```
3) void (*f[10]) (int, int)
```

[Run on IDE](#)

Postfix : `f[10] * (int, int) void`

Meaning : `f` is an array of 10 of pointer to function(which takes 2 arguments of type `int`) returning `void`

4) `char ((*x())[ ]) ()`

[Run on IDE](#)

Postfix : `x () * [] * () char`

Meaning : `x` is a function returning pointer to array of pointers to function returning `char`

5) `char ((*x[3])())[5]`

[Run on IDE](#)

Postfix : `x[3] * () * [5] char`

Meaning : `x` is an array of 3 pointers to function returning pointer to array of 5 `char`'s

6) `int ((*(*arr[5]))()) ()`

[Run on IDE](#)

Postfix : `arr[5] * () * () * int`

Meaning : `arr` is an array of 5 pointers to functions returning pointer to function returning pointer to integer

7) `void (*bsd_signal(int sig, void (*func)(int)))(int);`

[Run on IDE](#)

Postfix : `bsd_signal(int sig, void(*func)(int)) * (int) void`

Meaning : `bsd_signal` is a function that takes integer & a pointer to a function(that takes integer as argument and returns `void`) and returns pointer to a function(that take integer as argument and returns `void`)


This article is compiled by "Narendra Kangralkar" and reviewed by GeeksforGeeks team. Please write comments if you find anything incorrect, or you want to share more information about the topic discussed above.



**DON'T OVERSTRESS IT**

GATEWAY OF INDIA  
20 MINS  
VIA THE FREEWAY

FLATS START 42 LACS | CONCEPT BY ARCHITECT HAFEEZ CONTRACTOR



**WOO**COMMERCE

The Most Customizable  
eCommerce Platform  
For Building Your  
Online Business.

Get Started >

## GATE CS Corner Company Wise Coding Practice

C/C++ pointer

### Recommended Posts:

Redeclaration of global variable in C

Use of bool in C

How Linkers Resolve Global Symbols Defined at Multiple Places?

Understanding "extern" keyword in C

Scope rules in C

(Login to Rate and Mark)

3.7

Average Difficulty : 3.7/5.0  
Based on 89 vote(s)

☐

Add to TODO List

☐

Mark as DONE

Writing code in comment? Please use [ide.geeksforgeeks.org](http://ide.geeksforgeeks.org), generate link and share the link here.

Load Comments

Share this post!

@geeksforgeeks, Some rights reserved

Contact Us!

About Us!

Advertise with us!

Privacy Policy

