

## React performance and Rendering

- React Perf
  - Code splitting
  - dynamic imports
  - Lazy Loading
  - React.Lazy and
  - react suspense
- Memoization
  - React.memo
  - useMemo
  - useCallback

### title: Code Splitting and Lazy Loading

#### Scenario Without Code Splitting and Lazy Loading

In a standard setup, all of your JavaScript code, including all the components, gets bundled into one large file during the build process.

When a user accesses your application, this entire bundle is loaded and executed in the browser.

Suppose we have this app with three components  
HomePage,AboutPage,ContactPage and a Navbar component to  
navigate between them

Below is an example of how you can create HomePage, AboutPage,  
and ContactPage components and implement routing for these  
components using react-router-dom.

First, you need to install react-router-dom if you haven't already:

**npm install react-router-dom**

Then, you can create your components and implement the routing as  
follows:

### Create the HomePage Component:

```
const HomePage = () => {  
  return (  
    <div>  
      <h1>Home Page</h1>  
      <p>Welcome to the Home Page!</p>  
    </div>  
  );  
};  
  
export default HomePage;
```

### Create the AboutPage Component:

```
// AboutPage.jsx  
import React from 'react';
```

```
const AboutPage = () => {  
  return (  
    <div>  
      <h1>About Page</h1>  
      <p>Learn more about us on this page.</p>  
    </div>  
  );  
};  
  
export default AboutPage;
```

## Create the ContactPage Component:

```
// ContactPage.jsx  
import React from 'react';  
  
const ContactPage = () => {  
  return (  
    <div>  
      <h1>Contact Page</h1>  
      <p>Get in touch with us through this page.</p>  
    </div>  
  );  
};  
  
export default ContactPage;
```

## Create the Navbar Component:

```
// Navbar.jsx  
import React from 'react';  
import { Link } from 'react-router-dom';  
  
const Navbar = () => {  
  return (  
    <nav>  
      <ul>  
        <li>  
          <Link to="/">Home</Link>  
        </li>  
      </ul>  
    </nav>  
  );  
};
```

```

        </li>
        <li>
          <Link to="/about">About</Link>
        </li>
        <li>
          <Link to="/contact">Contact</Link>
        </li>
      </ul>
    </nav>
  );
};

export default Navbar;

```

## Set Up Routing in the App Component:

```

// App.jsx
import React from 'react';
import { BrowserRouter as Router, Route, Routes } from 'react-router-dom';
import HomePage from './components/HomePage';
import AboutPage from './components/About';
import ContactPage from './components/Contact';
import Navbar from './components/Navbar';

const App = () => {
  return (
    <Router>
      <div>
        <Navbar />
        <Routes>
          <Route path="/" element={<HomePage />} />
          <Route path="/about" element={<AboutPage />} />
          <Route path="/contact" element={<ContactPage />} />
        </Routes>
      </div>
    </Router>
  );
};

export default App;

```

This setup creates a simple React application with three pages: Home, About, and Contact, and a navbar to navigate between them using react-router-dom. When you click on the links in the navbar, the corresponding page component will be rendered.

In this example, all the components (HomePage, AboutPage, and ContactPage) are loaded at once, regardless of whether the user needs them immediately or not.

typically we do not need to create a build if we are running our application in development mode when using Vite.

In development mode, Vite uses a different approach for serving modules compared to a production build. Vite serves each module separately, which means you might not see a single large bundle like in a production build.

To simulate how it looks in production, we create a build first


**npm run build**

Then we serve this build ( which serves the static bundled files )

serve is a static file server that you can use to serve your production build locally. It helps you see how your application will perform in a production environment without deploying it to a remote server.

**sudo npm install -g serve**

**serve -s dist** - Here, -s stands for "single-page application" mode, which ensures that all routes are served correctly.



Here the complete bundle has been loaded which has loaded all the components regardless of if need them or not

Problems That Can Arise in this scenario

1. Long Initial Load Time: The initial load time can be significantly high as the browser needs to download a large JavaScript bundle before rendering any content.
2. Poor Performance: Large bundle sizes can lead to performance issues, especially on slower networks or less powerful devices.
3. Unnecessary Resource Usage: Users might download code for components and features they never interact with, leading to wasted resources.

## title: Dynamic Imports

Dynamic import is a powerful feature in JavaScript that allows you to load modules asynchronously. This means that instead of loading all your JavaScript code upfront, you can load parts of it on demand. This can be particularly useful in large applications where you want to optimize performance and reduce initial load times.

In React, dynamic import can be used to load components only when they are needed. This helps in splitting your code and loading it in smaller chunks, which is often referred to as "code splitting".

Let's take a same example and implement dynamic import using functional components and hooks.

## What is Dynamic Import?

Dynamic import is a feature that allows you to import JavaScript modules (including React components) dynamically and asynchronously. Instead of loading all components at once, you can load them on demand, which can significantly reduce the initial load time of your application. This process is known as code splitting.

## How to do it

1. Instead of importing the components at the top of the file, we use the `import()` function to load them dynamically within the routes.
2. Modify App Component to Use Dynamic Imports:

```
// App.jsx
import React, { useState, useEffect } from "react";
import { BrowserRouter as Router, Route, Routes } from "react-router-dom";
import Navbar from "../components/Navbar";

const App = () => {
  const [HomePage, setHomePage] = useState(null);
  const [AboutPage, setAboutPage] = useState(null);
  const [ContactPage, setContactPage] = useState(null);

  useEffect(() => {
    // Preload HomePage component
    import("../components/HomePage").then((module) => setHomePage(() =>
module.default));
  }, []);

  const loadHomePage = () => {
    import("../components/HomePage").then((module) => setHomePage(() =>
module.default));
  };

  const loadAboutPage = () => {
```



```

    import("./components/About").then((module) => setAboutPage(() =>
module.default));
  };

const loadContactPage = () => {
  import("./components/Contact").then((module) =>
    setContactPage(() => module.default)
  );
};

return (
  <Router>
    <div>
      <nav>
        <ul>
          <li>
            <Link to="/" onClick={loadHomePage}>
              Home
            </Link>
          </li>
          <li>
            <Link to="/about" onClick={loadAboutPage}>
              About
            </Link>
          </li>
          <li>
            <Link to="/contact" onClick={loadContactPage}>
              Contact
            </Link>
          </li>
        </ul>
      </nav>{" "}
    <Routes>
      <Route
        path="/"
        element={HomePage ? <HomePage /> : <div>Loading...</div>}
      />
      <Route
        path="/about"
        element={AboutPage ? <AboutPage /> : <div>Loading...</div>}
      />
    </Routes>
  </div>
</Router>
);

```

```
    <Route
      path="/contact"
      element={ContactPage ? <ContactPage /> : <div>Loading...</div>}
    />
  </Routes>
</div>
</Router>
);
};

export default App;
```

Notice the different chunks that gets created when we build this again

✓ dist

✓ assets

**JS** About-DS4PPFy8.js

**JS** Contact-CmNzC72K.js

**JS** HomePage-BxMNYzwR.js

🌊 index-BPvgi06w.css

**JS** index-CgP6LxbC.js

## How Dynamic Import Optimizes the Code

### Code Splitting:

Dynamic imports create separate chunks for each component. When you run `npm run build`, Vite will create separate files for `HomePage`, `AboutPage`, and `ContactPage`. These files are only loaded when needed.

### On-Demand Loading:

Instead of loading all components at once, components are loaded only when a user navigates to the respective route. This reduces the initial load time, making the app faster to start.

### Improved Performance:

By splitting the code and loading components on-demand, you reduce the size of the initial JavaScript bundle. This can lead to faster page loads and improved performance, especially for users with slower network connections.

## Approach Analysis

### In this implementation:

We maintain state using the `useState` hook to keep track of whether each component has been loaded.

We use the `import()` function to dynamically load the components when a button is clicked.

The `import()` function returns a promise that resolves to the module object, from which we can access the default export (the component itself).

Once the component is loaded, we update the state to render the component.

Now you will see whenever you click on a button only the component associated with that button will get loaded and chunks will be created for each respective component separately

While dynamic import as shown in the example above can be a powerful tool, there are a few reasons why it might not be the best approach for every situation.

1. **Manual State Management:** In the given example, we manually manage the state for each dynamically imported component. This can become cumbersome and error-prone as the number of components grows, leading to more boilerplate code and potential bugs.
2. **Lack of Built-in Fallback UI:** The example does not provide a built-in way to show a fallback UI while the component is

loading. While we can add this manually, it requires additional code and effort. `React.Suspense` offers a straightforward way to handle this. We will see this next

3. Complexity: The code for manually importing and managing state can become complex, especially in larger applications. This complexity can make the code harder to maintain and understand.
4. Best Practices: Using `React.lazy` and `Suspense` is a React-recommended approach for code splitting and lazy loading. It leverages React's built-in mechanisms, ensuring better integration and reliability.

## title: Lazy and Suspense

### Implementing Code Splitting with lazy and suspense

`React.lazy()` allows you to define a component that is loaded dynamically. `React.Suspense` provides a way to handle the loading state while the component is being loaded.

1. Setup the Project:
  - a. Get basic project setup with `react-router-dom` installed.
2. Update Component Imports to Use `React.lazy()`:

- a. Modify the imports in App.jsx to use React.lazy() for dynamic imports.
3. Wrap Components with React.Suspense:
  - a. Use React.Suspense to handle the loading state with a fallback component.

```
// App.jsx
// import React, { useState, useEffect } from "react";
import React, { Suspense, lazy } from "react";
import { BrowserRouter as Router, Route, Routes, Link } from "react-router-dom";
// import HomePage from './components/HomePage';
// import AboutPage from './components/About';
// import ContactPage from './components/Contact';
// import Navbar from './components/Navbar';
// Lazy load the components
const HomePage = lazy(() => import("./HomePage"));
const AboutPage = lazy(() => import("./AboutPage"));
const ContactPage = lazy(() => import("./ContactPage"));

const App = () => {
  // const [HomePage, setHomePage] = useState(null);
  // const [AboutPage, setAboutPage] = useState(null);
  // const [ContactPage, setContactPage] = useState(null);

  // useEffect(() => {
  //   // Preload HomePage component
  //   import("./components/HomePage").then((module) =>
  //     setHomePage(() => module.default)
  //   );
  // }, []);

  // const loadHomePage = () => {
  //   import("./components/HomePage").then((module) =>
  //     setHomePage(() => module.default)
  //   );
  // };
  // };
```

```

// const loadAboutPage = () => {
//   import("./components/About").then((module) =>
//     setAboutPage(() => module.default)
//   );
// };

// const loadContactPage = () => {
//   import("./components/Contact").then((module) =>
//     setContactPage(() => module.default)
//   );
// };

return (
  <Router>
    <div>
      <nav>
        <ul>
          <li>
            <Link to="/">Home</Link>
          </li>
          <li>
            <Link to="/about">About</Link>
          </li>
          <li>
            <Link to="/contact">Contact</Link>
          </li>
        </ul>
      </nav>{" "}
      <Suspense fallback={<div>Loading...</div>}>
        <Routes>
          <Route path="/" element={<HomePage />} />
          <Route path="/about" element={<AboutPage />} />
          <Route path="/contact" element={<ContactPage />} />
        </Routes>
      </Suspense>
    </div>
  </Router>
);
};

export default App;

```



## **React.lazy()**

React.lazy() allows you to dynamically import components, which means the component will only be loaded when it is needed. This helps in reducing the initial load time of the application by splitting the code into smaller chunks.

## **React.Suspense**

It is a component that can wrap lazy-loaded components and handle the loading state. It takes a fallback prop, which is a React element that will be displayed while the component is being loaded.

The fallback prop is used to display a loading indicator while the lazy-loaded component is being fetched. This provides a better user experience as the user is informed that something is happening in the background.