

# JavaScript Operators Mastery Guide (Extended + Interview Tips)

## What is an Operator?

An **operator** in JavaScript is a special symbol that performs an operation on operands (variables or values) to produce a result.

Example:

```
let result = 10 + 5; // '+' adds two numbers → 15
```

Here `+` is the operator, and `10` and `5` are operands.

## 1. Arithmetic Operators

Used for basic math operations.

Operator	Description	Example	Result
<code>+</code>	Addition	<code>10 + 5</code>	15
<code>-</code>	Subtraction	<code>10 - 5</code>	5
<code>*</code>	Multiplication	<code>10 * 5</code>	50
<code>/</code>	Division	<code>10 / 5</code>	2
<code>%</code>	Modulus	<code>10 % 4</code>	2
<code>**</code>	Exponentiation	<code>2 ** 3</code>	8

### Examples:

```
console.log(10 + 3); // 13
console.log(10 - 3); // 7
console.log(10 * 3); // 30
console.log(10 / 3); // 3.333
console.log(10 % 3); // 1
```

**Interview Tip:** Arithmetic operators are often combined with increment/decrement in puzzles. Watch operator precedence carefully.

### Practice:

```
let a = 10, b = 5;
let result = (a * 2 + b) / 3;
console.log(result); // Predict the output
```

## 😴 2. Increment and Decrement Operators

Used to increase or decrease variable values by 1.

Operator	Description	Example
<code>++</code>	Increment	<code>++a</code> or <code>a++</code>
<code>--</code>	Decrement	<code>--a</code> or <code>a--</code>

### Pre vs Post

- **Pre-increment** (`++a`) → increments before use.
- **Post-increment** (`a++`) → increments after use.

### Examples:

```
let a = 5;
console.log(++a); // 6 → pre-increment
console.log(a++); // 6 → post-increment
console.log(a);   // 7
console.log(--a); // 6 → pre-decrement
console.log(a--); // 6 → post-decrement
console.log(a);   // 5
```

**Interview Tip:** Increment/decrement are frequently tested for order of evaluation. Trace line-by-line.

### Practice:

```
let x = 5;
console.log(x++ + ++x); // Predict and explain the output
```

**Answer:** `x++` uses 5, then x becomes 6; `++x` increments x to 7; →  $5 + 7 = 12$ .

## 😬 3. Comparison Operators

Used to compare two values.

Operator	Description	Example	Result
<code>==</code>	Equal (type conversion allowed)	<code>'5' == 5</code>	true
<code>===</code>	Strict equal (no conversion)	<code>'5' === 5</code>	false
<code>!=</code>	Not equal (type conversion allowed)	<code>'5' != 5</code>	false
<code>!==</code>	Strict not equal	<code>'5' !== 5</code>	true
<code>&gt;</code>	Greater than	<code>10 &gt; 5</code>	true
<code>&lt;</code>	Less than	<code>10 &lt; 5</code>	false
<code>&gt;=</code>	Greater or equal	<code>10 &gt;= 10</code>	true
<code>&lt;=</code>	Less or equal	<code>5 &lt;= 10</code>	true

### Examples:

```
console.log(10 == '10'); // true
console.log(10 === '10'); // false
console.log(5 != 10); // true
console.log(5 !== '5'); // true
console.log(15 > 10); // true
```

**Interview Tip:** Always prefer `===` and `!==` to avoid bugs due to implicit type conversion.

### Practice:

```
console.log(0 == false); // ?
console.log(0 === false); // ?
```

**Answer:** `true` and `false` respectively, because `==` converts types while `===` doesn't.

## 👉 4. Not Equal, Null, and NaN

### Not Equal (`!=` and `!==`)

```
console.log(5 != '5'); // false
console.log(5 !== '5'); // true
```

### Null and Undefined

```
let user = null;
let data;
```

```
console.log(user === null); // true
console.log(data === undefined); // true
```

## NaN (Not-a-Number)

Represents invalid numeric results.

```
console.log(0 / 0); // NaN
console.log(parseInt('abc')); // NaN
console.log(isNaN('abc')); // true
console.log(NaN === NaN); // false
console.log(Number.isNaN(NaN)); // true
```

**Interview Tip:** NaN is the only value in JS that is not equal to itself.

### Practice:

```
let n = parseInt('hello');
if (isNaN(n)) console.log('Invalid number');
```

**Answer:** Output → Invalid number because 'hello' cannot convert to a number.

## 5. Logical Operators

Used to combine multiple conditions.

Operator	Description	Example	Result
&&	AND	true && false	false
	OR	true    false	true
!	NOT	!true	false

### Examples:

```
let x = 10, y = 20;
console.log(x > 5 && y > 15); // true
console.log(x > 15 || y > 10); // true
console.log(!(x > y)); // true
```

**Interview Tip:** Logical operators short-circuit — the second condition may not be evaluated if the first already determines the result.

### Practice:

```
let a = 0;
let result = a || 'Default';
console.log(result); // ?
```

**Answer:** 'Default' because `a` is falsy.

---

## 👉 6. Nullish Coalescing (??)

Used for default values when variable is null/undefined (not false or 0).

```
let name = null;
let displayName = name ?? 'Guest';
console.log(displayName); // Guest
```

**Interview Tip:** Use `??` instead of `||` when `0` or `''` are valid values.

**Practice:**

```
let count = 0;
console.log(count ?? 10); // ?
console.log(count || 10); // ?
```

**Answer:** `0` and `10` respectively. `||` treats 0 as falsy, `??` does not.

---

## 👉 7. Optional Chaining (?.)

Safely access nested properties.

```
let user = { profile: { name: 'Alice' } };
console.log(user?.profile?.name); // Alice
console.log(user?.address?.city); // undefined
```

**Interview Tip:** Prevents runtime errors when accessing deep object properties.

**Practice:**

```
let car = { model: 'Tesla' };
console.log(car?.owner?.name ?? 'Owner unknown');
```

**Answer:** 'Owner unknown' because `owner` is undefined.

---

## 8. Combined Practice Programs

### Increment Challenge

```
let a = 5, b = 3;  
let result = ((a++ + ++b) * 2) / (--a);  
console.log(result);
```

**Answer:** Step through to practice operator order.

### Type Coercion Challenge

```
console.log('5' + 2); // '52'  
console.log('5' - 2); // 3  
console.log(true + 1); // 2  
console.log(false + 1); // 1
```

### NaN Handling

```
let invalid = 'abc' / 2;  
console.log(isNaN(invalid)); // true
```

### Logical Short-Circuit

```
let user = null;  
let username = user && user.name;  
console.log(username); // undefined
```

### Complex Mixed Scenario

```
let val = null;  
let res = (val ?? 10) * 2 + (5 > 3 ? 1 : 0);  
console.log(res); // 21
```

## FINAL INTERVIEW TIPS & ANSWERS

- ✓ Always prefer strict equality ( `===` ) to avoid unexpected type coercion.
- ✓ `NaN` is not equal to itself → use `Number.isNaN()` to check.
- ✓ Short-circuiting ( `&&` , `||` ) is key for default values and safe checks.
- ✓ `++a` and `a++` are common trick questions — remember order of evaluation.
- ✓ Use `??` instead of `||` when `0` or `''` are valid values.
- ✓ Know `typeof null` → `'object'` (historical bug but consistent).

- ✓ `parseInt('08')` behaves differently in some cases → prefer `Number()` for conversions.
  - ✓ Understand operator precedence for nested expressions.
- 

This enhanced guide now includes **interview-focused explanations and practice problems with answers**, helping you become fluent and confident in JavaScript operator behavior for both interviews and real-world scenarios.