

4.1.1. Pandas - series creation and manipulation

Write a Python program that takes a list of numbers from the user, creates a Pandas series from it, and then calculates the mean of even and odd numbers separately using the `groupby` and `mean()` operations.

Hint: You can group the Series based on whether each number is even or odd.

Input Format:

- The user should enter a list of numbers separated by space when prompted.

Output Format:

- The program should display the mean of even and odd numbers separately.
- Each mean value should be displayed with a label indicating whether it corresponds to even or odd numbers.

Refer to the sample test cases for better understanding regarding input and output format.

Sample Test Cases

seriesMa...

1import pandas as pd

2

3# Take inputs from the user to create a list of numbers

4numbers = list(map(int, input().split()))

5

6# Create a Pandas series from the list of numbers

7s=pd.Series(numbers)

8# Grouping by even and odd numbers and calculating the mean

9grouped = s.groupby(s%2==0).mean()

10

11# Display the mean of even and odd numbers with labels

Average time

0.010 s

10.00 ms

Maximum time

0.018 s

18.00 ms

3 out of 3 shown test case(s) passed

3 out of 3 hidden test case(s) passed

Test case 118 msDebug

Expected output

1 2 3 4 5 6 7 8 9 10

Mean of even and odd numbers:

Odd ---- 5.0

Even ---- 6.0

dtype: float64

Actual output

1 2 3 4 5 6 7 8 9 10

Mean of even and odd numbers:

Odd ---- 5.0

Even ---- 6.0

dtype: float64

Terminal

Test cases

CODETANTRA

HomeLearn Anywhere

202501090007@mitaoe.ac.inSupportLogout

4.1.2. Dictionary to dataframe

06:12

A dictionary of lists has been provided to you in the editor. Create a DataFrame from the dictionary of lists and perform the listed operations, then display the DataFrame before and after each manipulation.

Create the DataFrame:

- Convert the dictionary to a Pandas DataFrame.

Add a new row:

- Take inputs from the user for the new row data (name, age).
- Add the new row to the DataFrame.
- Display the DataFrame after adding the new row.

Modify a row:

- Modify a specific row by changing the age. Take the row index and new age value from the user.
- Display the DataFrame after modifying the row.

Delete a row:

- Take the row index to be deleted from the user.
- Remove the specified row.
- Display the DataFrame after deleting the row.

Add a new column:

- Add a column **Gender** with values taken from the user.
- Display the DataFrame after adding the new column.

Modify a column:

- Convert names to uppercase.

datafram...

Submit

1import pandas as pd

2

3# Provided dictionary of lists

4data = {

5 'Name': ['Alice', 'Bob', 'Charlie'],

6 'Age': [25, 30, 35],

7}

8

9# Convert the dictionary to a DataFrame

10df = pd.DataFrame(data)

11

Average time0.087 s87.00 ms

Maximum time0.110 s110.00 ms

1 out of 1 shown test case(s) passed

1 out of 1 hidden test case(s) passed

Test case 1110 msDebug

Expected output

Original DataFrame:

.....Name..Age

0...Alice...25

1...Bob...30

2...Charlie...35

New name: Susan

Actual output

Original DataFrame:

.....Name..Age

0...Alice...25

1...Bob...30

2...Charlie...35

New name: Susan

Terminal

Test cases

< Prev

Reset

Submit

Next >

CODETANTRA

HomeLearn Anywhere

202501090007@mitaoe.ac.inSupportLogout

4.1.3. Student Information19:45

Write a program to read a text file containing student information (name, age, and grade) using Pandas. Perform the following tasks:

- Display the first five rows of the data frame.
- Calculate the average age of the students (limit the average age up to 2 decimal places).
- Filter out the students who have a grade above a certain threshold (consider the threshold grade is 'B').

Note:
Refer to the displayed test cases for better understanding.

Sample Test Cases

studentin...

1import pandas as pd

2

3# Read the text file into a DataFrame

4file = input()

5data = pd.read_csv(file, sep="\s+", header=None, names=["Name", "Age", "Grade"])

6print("First five rows:")

7print(data.head())

8

9av=round(data["Age"].mean(),2)

10print("Average age:",av)

Average time0.051 s60.60 ms

Maximum time0.080 s80.00 ms

1 out of 1 shown test case(s) passed

1 out of 1 hidden test case(s) passed

Test case 180 msDebug

Expected output

studentdata.txt

First five rows:

--Name--Age--Grade--

0--John--25----A--

1--Alin--22----B--

2--Emma--24----A--

Actual output

studentdata.txt

First five rows:

--Name--Age--Grade--

0--John--25----A--

1--Alin--22----B--

2--Emma--24----A--

TerminalTest cases

< Prev

Reset

Submit

Next >

4.2.1. Month with the Highest Total Sales01:49

Write a Python program that takes the file name of a CSV file as input, reads the data, and performs the following operations:

- The CSV file contains the columns: Date, Product, Quantity, Price, and City.
- Group the data by Month and calculate the total sales for each month.
- Find the month with the highest total sales and display it.
- Also, display the total sales for the best month.

Sample Data:

Date	Product	Quantity	Price	City
2025-01-01	Product A	5	20	New York
2025-01-01	Product B	3	15	Los Angeles
2025-01-02	Product A	7	20	New York
2025-01-02	Product C	4	30	Chicago
2025-01-03	Product B	2	15	Chicago
2025-01-03	Product A	8	20	Los Angeles
2025-01-04	Product C	6	30	New York
2025-01-04	Product B	5	15	Los Angeles
2025-01-05	Product A	3	20	Chicago
2025-01-05	Product C	10	30	Los Angeles

Note:

The data cannot be displayed in the file. You can refer to the sample data provided for insights.

Sample Test Cases

monthFor...Submit

```
1 import pandas as pd
2
3 # Prompt the user for the file name
4 file_name = input()
5
6 # Load the data
7 df = pd.read_csv(file_name)
8 df["Date"] = pd.to_datetime(df["Date"])
9 df["Sales"] = df["Quantity"] * df["Price"]
10 df["Month"] = df["Date"].dt.to_period("M").astype(str)
11
```

Average time0.023 s23.00 ms

Maximum time0.046 s46.00 ms

1 out of 1 shown test case(s) passed

2 out of 2 hidden test case(s) passed

Test case 146 msDebug

Expected output	Actual output
sales_data.csv	sales_data.csv
Best month: 2025-01	Best month: 2025-01
Total sales: \$1210.00	Total sales: \$1210.00

TerminalTest cases

4.2.2. Best Selling Product

10:54

Write a Python program that takes the file name of a CSV file as input, reads the data, and performs the following operations:

- The CSV file contains the columns: Date, Product, Quantity, Price, and City.
- Find the product that sold the most in terms of quantity sold.
- Display the product that sold the most and the total quantity sold for that product.

Sample Data:

Date	Product	Quantity	Price	City
2025-01-01	Product A	5	20	New York
2025-01-01	Product B	3	15	Los Angeles
2025-01-02	Product A	7	20	New York
2025-01-02	Product C	4	30	Chicago
2025-01-03	Product B	2	15	Chicago
2025-01-03	Product A	8	20	Los Angeles
2025-01-04	Product C	6	30	New York
2025-01-04	Product B	5	15	Los Angeles
2025-01-05	Product A	3	20	Chicago
2025-01-05	Product C	10	30	Los Angeles

Note:

The data cannot be displayed in the file. You can refer to the sample data provided for insights.

Sample Test Cases

monthFor...

Submit

```
1 import pandas as pd
2
3 # Prompt the user for the file name
4 file_name = input()
5
6 # Load the data
7 df = pd.read_csv(file_name)
8
9 # Find the product with the highest total quantity sold
10 product_sales=df.groupby('Product')['Quantity'].sum()
11 best product =product sales.idxmax()
```

Average time

0.019 s

18.67 ms

Maximum time

0.034 s

34.00 ms

1 out of 1 shown test case(s) passed

2 out of 2 hidden test case(s) passed

Test case 1 34 ms

Debug

Expected output

Actual output

sales_data.csv

sales_data.csv

Best-selling product: Product A

Best-selling product: Product A

Total quantity sold: 23

Total quantity sold: 23

Terminal

Test cases

< Prev

Reset

Submit

Next >

4.2.3. City that Sold the Most Products00:32

Write a Python program that takes the file name of a CSV file as input, reads the data, and performs the following operations:

- The CSV file contains the columns: Date, Product, Quantity, Price, and City.
- Group the data by City and calculate the total quantity of products sold for each city.
- Find the city that sold the most products (based on the total quantity sold).

Sample Data:

Date	Product	Quantity	Price	City
2025-01-01	Product A	5	20	New York
2025-01-01	Product B	3	15	Los Angeles
2025-01-02	Product A	7	20	New York
2025-01-02	Product C	4	30	Chicago
2025-01-03	Product B	2	15	Chicago
2025-01-03	Product A	8	20	Los Angeles
2025-01-04	Product C	6	30	New York
2025-01-04	Product B	5	15	Los Angeles
2025-01-05	Product A	3	20	Chicago
2025-01-05	Product C	10	30	Los Angeles

Note:

The data cannot be displayed in the file. You can refer to the sample data provided for insights.

Sample Test Cases

monthFor...Submit

```
1 import pandas as pd
2
3 # Prompt the user for the file name
4 file_name = input()
5
6 # Load the data
7 df = pd.read_csv(file_name)
8
9 city_sales = df.groupby('City')['Quantity'].sum()
10 best_city = city_sales.idxmax()
11
```

Average time0.017 s17.00 ms

Maximum time0.031 s31.00 ms

1 out of 1 shown test case(s) passed

2 out of 2 hidden test case(s) passed

Test case 131 msDebug

Expected output

sales_data.csv

City sold the most products: Los Angeles

Actual output

sales_data.csv

City sold the most products: Los Angeles

Terminal

Test cases

< Prev

Reset

Submit

Next >

4.2.4. Most Frequently Sold Product Pairs

Write a Python program that takes the file name of a CSV file as input, reads the data, and performs the following operations:

- The CSV file contains the following columns: Date, Product, Quantity, Price, and City.
- For each date, find all pairs of products that were sold together (i.e., two products sold on the same date).
- Output the product pair/s that was sold most frequently.

Sample Data:

Date	Product	Quantity	Price	City
2025-01-01	Product A	5	20	New York
2025-01-01	Product B	3	15	Los Angeles
2025-01-02	Product A	7	20	New York
2025-01-02	Product C	4	30	Chicago
2025-01-03	Product B	2	15	Chicago
2025-01-03	Product A	8	20	Los Angeles
2025-01-04	Product C	6	30	New York
2025-01-04	Product B	5	15	Los Angeles
2025-01-05	Product A	3	20	Chicago
2025-01-05	Product C	10	30	Los Angeles

Explanation:

Transactions:

- 2025-01-01: Product A, Product B
- 2025-01-02: Product A, Product C
- 2025-01-03: Product B, Product A
- 2025-01-04: Product C, Product B
- 2025-01-05: Product A, Product C

frequentl...

Submit

1import pandas as pd

2from itertools import combinations

3from collections import Counter

4

5# Prompt user to input the file name

6file_name = input()

7

8# Read data from the specified CSV file

9df = pd.read_csv(file_name)

10date_products = {}

11

Average time

0.021 s

20.67 ms

Maximum time

0.043 s

43.00 ms

1 out of 1 shown test case(s) passed

2 out of 2 hidden test case(s) passed

Test case 1 43 ms

Debug

Expected output

sales_data.csv

Product A and Product B: 2 times

Product A and Product C: 2 times

Actual output

sales_data.csv

Product A and Product B: 2 times

Product A and Product C: 2 times

Terminal

Test cases

4.2.5. Titanic Dataset Analysis and Data Cleaning

You are provided with the Titanic dataset containing information about passengers on the Titanic. Your task is to write Python code to answer the following questions based on the dataset. For each question, perform necessary data cleaning, transformations, and calculations as required.

1. Display the first 5 rows of the dataset.
2. Display the last 5 rows of the dataset.
3. Get the shape of the dataset (number of rows and columns).
4. Get a summary of the dataset (using `.info()`).
5. Get basic statistics (mean, standard deviation, etc.) of the dataset using `.describe()`.
6. Check for missing values and display the count of missing values for each column.
7. Fill missing values in the 'Age' column with the median age.
8. Fill missing values in the 'Embarked' column with the most frequent value (`mode()`).
9. Drop the 'Cabin' column due to many missing values.
10. Create a new column, 'FamilySize' by adding the 'SibSp' and 'Parch' columns.

The Titanic dataset contains columns as shown below,

PassengerId	Survived	Pclass	Name	Sex	Age	SibSp	Parch	Ticket	Fare	Cabin	Embarked

Sample Data:

titanicDat...

Submit

```
1 import pandas as pd
2 import numpy as np
3
4 # Load the Titanic dataset
5 data = pd.read_csv('Titanic-Dataset.csv')
6
7 # 1. Display the first 5 rows of the dataset
8 print(data.head())
9
10 # 2. Display the last 5 rows of the dataset
11 print(data.tail())
```

Average time0.162 s162.00 ms

Maximum time0.162 s162.00 ms

1 out of 1 shown test case(s) passed

Test case 1162 msDebug

Expected output

Actual output

TerminalTest cases

4.2.6. Titanic Dataset Analysis and Data Cleaning - 2

You are provided with the Titanic dataset containing information about passengers on the Titanic. Your task is to write Python code to answer the following questions based on the dataset.

1. Create a new column 'IsAlone' which is 1 if the passenger is alone (FamilySize = 0), otherwise 0.
2. Convert the 'Sex' column to numeric values (male: 0, female: 1).
3. One-hot encode the 'Embarked' column, dropping the first category.
4. Get the mean age of passengers.
5. Get the median fare of passengers.
6. Get the number of passengers by class.
7. Get the number of passengers by gender.
8. Get the number of passengers by survival status.
9. Calculate the survival rate of passengers.
10. Calculate the survival rate by gender.

The Titanic dataset contains columns as shown below,

PassengerId	Survived	Pclass	Name	Sex	Age	SibSp	Parch	Ticket	Fare	Cabin	Embarked

Sample Data:

Explorer

titanicDat...

Submit

```
1 import pandas as pd
2 import numpy as np
3
4 # Load the Titanic dataset
5 data = pd.read_csv('Titanic-Dataset.csv')
6 data['FamilySize'] = data['SibSp'] + data['Parch']
7
8 # 1. Create a new column 'IsAlone' (1 if alone, 0 otherwise)
9 data['IsAlone'] = np.where(data['FamilySize'] == 0, 1, 0)
10
11 # 2. Convert 'Sex' to numeric (male: 0, female: 1)
```

Average time
0.066 s
66.00 ms

Maximum time
0.066 s
66.00 ms

1 out of 1 shown test case(s) passed

Test case 1 66 ms Debug

Expected output
29.69911764795882
14.4542
3... 491
1... 216
2... 184
Name: Pclass, dtype: int64

Actual output
29.69911764795882
14.4542
3... 491
1... 216
2... 184
Name: Pclass, dtype: int64

Terminal

Test cases

4.2.7. Titanic Dataset Analysis and Data Explorer View Meetings Learn anywhere 60.44

You are provided with the Titanic dataset containing information about passengers on the Titanic. Your task is to write Python code to answer the following questions based on the dataset.

1. Calculate the survival rate by class.
2. Calculate the survival rate by embarkation location (Embarked_S).
3. Calculate the survival rate by family size (FamilySize).
4. Calculate the survival rate by being alone (IsAlone).
5. Get the average fare by passenger class (Pclass).
6. Get the average age by passenger class (Pclass).
7. Get the average age by survival status (Survived).
8. Get the average fare by survival status (Survived).
9. Get the number of survivors by class (Pclass).
10. Get the number of non-survivors by class (Pclass).

The Titanic dataset contains columns as shown below,

PassengerId	Survived	Pclass	Name	Sex	Age	SibSp	ParCh	Ticket	Fare	Cabin	Embarked

Sample Data:

titanicDat... Submit

```
1 import pandas as pd
2 import numpy as np
3
4 # Load the Titanic dataset
5 data = pd.read_csv('Titanic-Dataset.csv')
6 data['FamilySize'] = data['SibSp'] + data['ParCh']
7 data['IsAlone'] = np.where(data['FamilySize'] > 0, 0, 1)
8 data = pd.get_dummies(data, columns=['Embarked'], drop_first=True)
9
10 print(data.groupby('Pclass')['Survived'].mean())
11
```

Average time: 0.073 s 73.00 ms

Maximum time: 0.073 s 73.00 ms

1 out of 1 shown test case(s) passed

Test case 1 73 ms Debug

Expected output

Actual output

Pclass

1... 0.629630

2... 0.472826

3... 0.242363

Name: Survived, dtype: float64

Embarked_S

0 0.500000

Terminal Test cases

4.2.8. Titanic Dataset Analysis and Data Cleaning - 400:37

You are provided with the Titanic dataset containing information about passengers on the Titanic. Your task is to write Python code to answer the following questions based on the dataset.

1. Get the number of survivors by gender (Sex).
2. Get the number of non-survivors by gender (Sex).
3. Get the number of survivors by embarkation location (Embarked_S).
4. Get the number of non-survivors by embarkation location (Embarked_S).
5. Calculate the percentage of children (Age < 18) who survived.
6. Calculate the percentage of adults (Age >= 18) who survived.
7. Get the median age of survivors.
8. Get the median age of non-survivors.
9. Get the median fare of survivors.
10. Get the median fare of non-survivors.

The Titanic dataset contains columns as shown below,

PassengerId	Survived	Pclass	Name	Sex	Age	SibSp	ParCh	Ticket	Fare	Cabin	Embarked

Sample Data:

titanicDat...Submit

```
1 import pandas as pd
2 import numpy as np
3
4 # Load the Titanic dataset
5 data = pd.read_csv('Titanic-Dataset.csv')
6 data = pd.get_dummies(data, columns=['Embarked'], drop_first=True)
7
8
9 # 1. Get the number of survivors by gender
10 survivors_by_gender = data[data['Survived'] == 1]['Sex'].value_counts()
11 print(survivors_by_gender)
```

Average time: 0.202 s202.00 ms

Maximum time: 0.202 s202.00 ms

1 out of 1 shown test case(s) passed

Test case 1202 msDebug

Expected output

Actual output

female ... 233

female ... 233

male ... 109

male ... 109

Name: Sex, dtype: int64

Name: Sex, dtype: int64

male ... 468

male ... 468

female ... 81

female ... 81

Name: Sex, dtype: int64

Name: Sex, dtype: int64

TerminalTest cases