cp_6a

1.

Day Name | 20/20

Easy

Write a program that reads a day number and prints the corresponding day name.

Day Number	Day Name
1	Monday
2	Tuesday
3	Wednesday
4	Thursday
5	Friday
6	Saturday
7	Sunday

For example,

If the given day number is **1**, the day name is **Monday**,

If the given day number is **2**, the day name is **Tuesday**, etc.

Input

The input will be a single line containing an integer representing the day number.

Output

The output should be a single line containing a string that is the day name.

Constraints

The day number is always greater than or equal to **1** and less than or equal to **7**.

Explanation

For example, if the given day number is **3**, the output should be **Wednesday** as the day number of **Wednesday** is **3**.

Sample Input 1

```
3
```

Sample Output 1

```
Wednesday
```

Sample Input 2

```
2
```

code

```
day=int(input())
if day==1:
    print("Monday")
```

```
elif day==2:
    print("Tuesday")
elif day==3:
    print("Wednesday")
elif day==4:
    print("Thursday")
elif day==5:
    print("Friday")
elif day==6:
    print("Saturday")
else:
    print("Sunday")
```

2.

Permission to attempt Exam | 30/30

Write a program that reads the attendance percentage `A` and status of having medical report `M` of a student and checks if any of the below conditions is satisfied.

- `A` is greater than or equal to **75**.
- `M` is equal to **"Y"**.

Print **Allowed to write exam** if any of the given conditions is satisfied. Otherwise, print **Cannot write exam**.

Note

- The last character of the attendance percentage `A` contains `%` .
- The remaining characters contain a Number.

Example: `40%` , `60%`

Input

The first line of input contains a string representing `A` .
The second line of input contains a string representing `M` .

Output

The output should be a single line containing a string. **Allowed to write exam** should be printed if `A` is greater than or equal to **75** or `M` is equal to **"Y"**. Otherwise, **Cannot write exam** should be printed.

Explanation

For example, if the given attendance percentage `A = "80%"` and the status of having a medical report is `M = "Y"` ,
✓ `A` is greater than or equal to **75**. (`80 >= 75`)
✕ `M` is equal to **"Y"**.
The output should be **Allowed to write exam** as the attendance percentage is greater than or equal to **75**.

For example, if the given attendance percentage is `A = "70%"` and the status of having a medical report is `M = "Y"` ,
✕ `A` is greater than or equal to **75**. (`70 < 75`)
✓ `M` is equal to **"Y"**.
The output should be **Allowed to write exam** as the attendance percentage is not greater than or equal to **75** but the medical report status is equal to **"Y"**.

For example, if the given attendance percentage is `A = "72%"` and the status of having a medical report is `M = "N"` ,
✕ `A` is greater than or equal to **75**. (`72 < 75`)
✕ `M` is equal to **"Y"**.
The output should be **Cannot write exam** as the attendance percentage is not greater than or equal to **75** and the medical report status is not equal to **"Y"**.

Sample Input 1

```
80%
Y
```

Sample Output 1

```
Allowed to write exam
```

Sample Input 2

```
70%
Y
```

Sample Output 2

```
Allowed to write exam
```

Sample Input 3

```
72%
N
```

Sample Output 3

```
Cannot write exam
```

code:

```python
a=input()
a=a[0:-1]
m=input()
if int(a)>=75 or m=="Y":
    print("Allowed to write exam")
```

```
else:
    print("Cannot write exam")
```

3.

Sum of The Digits - 2 | 30/30

Given an integer between 0 and 10000, write a program to print the sum of its digits.

Input

The first line of input will contain an integer.

Output

The first line of output should be the sum of the digits.

Explanation

For example, if the given number is 25, your code should print the sum of the digits (2 + 5), which is 7.

Similarly, if the given number is 692, your code should print the sum of the digits (6 + 9 + 2), which is 17.

Similarly, if the given number is 9999, your code should print the sum of the digits (9 + 9 + 9 + 9), which is 36.

Sample Input 1

```
25
```

Sample Output 1

```
7
```

Sample Input 2

```
692
```

Sample Output 2

```
17
```

Sample Input 3

```
9999
```

Sample Output 3

```
36
```

code

```
num=int(input())
str_num=str(num)
num_len=len(str_num)
```

```
sum_digits=0
if num_len==1:
    sum_digits=num
    print(sum_digits)
elif num_len==2:
    sum_digits=int(str_num[0])+int(str_num[1])
    print(sum_digits)
elif num_len==3:
    sum_digits=int(str_num[0])+int(str_num[1])+int(str_num
[2])
    print(sum_digits)
elif num_len==4:
    sum_digits=int(str_num[0])+int(str_num[1])+int(str_num
[2])+int(str_num[3])
    print(sum_digits)
```

4.

Simple Calculator | 30/30

Solved

Write a program that reads an operator `O` , and two numbers `A` and `B` .
Print the result by doing arithmetic operations on `A` and `B` based on the operator `O`

Operator	Arithmetic Operation	Represents
+	A + B	Addition of A and B
-	A - B	Subtraction of B from A
*	A * B	Multiplication of A and B
/	A / B	Division of A and B
%	A % B	Remainder when A is divided by B

Input

The first line of input contains a string representing `O` . (`+` , `-` , `*` , `/` , or `%`).
The second line of input contains an integer representing `A` .
The third line of input contains an integer representing `B` .

Output

The output should be a single line containing an integer, that is the result obtained by doing arithmetic operations on `A` and `B` if an operator `O` is equal to `+` , `-` , `*` or `%` .
The output should be a single line containing a float, that is the result obtained by doing arithmetic operations on `A` and `B` if an operator `O` is equal to `/` .

Constraints

The operator (`O`) is always equal to one of `+` , `-` , `*` , `/` or `%` .

Explanation

For example, if the given operator is `O = "+"` and the two numbers are `A = 3` and `B = 5` .

- As `O` is equal to `+` , `A` should be added to `B` .
- The Addition of `A` and `B` is equal to **8**. (`3 + 5 = 8`)

The output should be **8**.

For example, if the given operator is `O = "*"` and the two numbers are `A = 2` and `B = 5` .

- As `O` is equal to `*` , `A` should be multiplied by `B` .
- The Multiplication of `A` and `B` is equal to **10**. (`2 * 5 = 10`)

The output should be **10**.

For example, if the given operator is `O = "-"` and the two numbers are `A = 10` and `B = 9` .

- As `O` is equal to `-` , `B` should be subtracted from `A` .
- The Subtraction of `B` from `A` is equal to **1**. (`10 - 9 = 1`)

The output should be **1**.

code:

```
operator=input()
a=int(input())
b=int(input())
if operator=="+":
    print(a+b)
if operator=="-":
```

```
    print(a-b)
if operator=="*":
    print(a*b)
if operator=="%":
    print(a%b)
if operator=="/":
    print(float(a/b))
```

5.

Print the Value | 30/30

Solved

Easy

Write a program that reads a string `S` . The string `S` contains a number except the last character. The last character of the string contains **T** or **H** or **K**.

Print the Value by multiplying the number in `S` with **10** or **100** or **1000** based on the last character.

Last Character	Represents	Value
T	Tens	Multiply the number in string with **10**
H	Hundreds	Multiply the number in string with **100**
K	Thousands	Multiply the number in string with **1000**

Quick Tip

Make sure the number is converted to an integer before doing any operations like Multiplication (`*`), etc.

Example: `S = 34T`

- The number in **34T** is **34**.
- **34** should be converted to an integer before doing any operations.

Input

The input will be a single line containing a string representing `S` .

Output

The output should be a single line containing an integer that is the value obtained by multiplying the number in `S` with **10** or **100** or **1000** based on the last character.

Explanation

For example, if the given string is `S = 34T` ,

- The number in `S` is **34**.
- The last character of `S` is **T**
- As **T** represents **Tens**, multiply the number in `S` with **10**. So, the value is **340** (`34 * 10 = 340`).

The output should be **340**.

For example, if the given string is `S = 6H` ,

- The number in `S` is **6**.
- The last character of `S` is **H**
- As **H** represents **Hundreds**, multiply the number in `S` with **100**. So, the value is **600** (`6 * 100 = 600`).

The output should be **600**.

code

```
num=input()
if num[-1]=="T":
    print(num[:-1]+"0")
if num[-1]=="H":
    print(num[:-1]+"00")
```

```
if num[-1]=="K":
    print(num[:-1]+"000")
```

6.

Print the Score - 2 | 25/25

Easy

Write a program that reads a distance `D` in km and calculates the total score.

- For the first **50** km (`0 - 50 km`), the score for each km is **3**.
- For the distance above **50** km, the score for each km is **5**.

Input

The input will be a single line containing an integer representing `D` .

Output

The output should be a single line containing an integer that is the score.

Explanation

For example, if the given distance in km is `D = 75` ,
As `D` is greater than **50** km, the total score is the sum of the score of first **50** km and the score of the remaining distance after **50** km.

Score is **3** for each km for 0 to 50 km ⇒ 50 × 3 = 150
Score is **5** for each km for above 50 km ⇒ 25 × 5 = 125

Total ⇒ 275

▶ Detailed Explanation to calculate the score

The output should be **275**.

For example, if the given distance in km is `D = 30` ,
As `D` is less than or equal to **50**, the total score is score for **30** km.

- The score for each km for the first **50** km is **3**.

Score is **3** for each km for 0 to 50 km ⇒ 30 × 3 = 90
Score is **5** for each km for above 50 km ⇒ 0 x 5 = 0

Total ⇒ 90

The output should be **90**.

Sample Input 1

```
75
```

Sample Output 1

```
275
```

code:

```
km=int(input())
total_score=0
first_50=0
next_50=0
if km<=50:
    first_50=(km*3)
elif km>50:
   first_50=50*3
   next_50=(km-50)*5
total_score=first_50+next_50
print(total_score)
```

7.

Print the Score - 3 | 30/30

Easy

Write a program that reads a distance `D` in km and calculates the total score.

- For the first **20** km (`0 - 20 km`), the score for each km is **2**.
- For the next **40** km (`21 - 60 km`), the score for each km is **4**.
- For the distance above **60** km, the score for each km is **6**.
- Apart from the above scores, there is a bonus score of **30**.

Input

The input will be a single line containing an integer representing `D` .

Output

The output should be a single line containing an integer that is the score.

Explanation

For example, if the given distance in km is `D = 125` ,

As `D` is greater than **60** km, the total score is the sum of the score of first **20** km, score of the next **40** km, score of the remaining distance after **60** k the bonus score.

Score is **2** for each km for 0 to 20 km ⇒ 20 × 2 = 40
Score is **4** for each km for 21 to 60 km ⇒ 40 × 4 = 160
Score is **6** for each km for above 60 km ⇒ 65 × 6 = 390

Total	⇒	590
Bonus Score	⇒	30
Total Score	⇒	620

▶ Detailed Explanation to calculate the score

The output should be **620**.

For example, if the given distance in km is `D = 15` ,

As `D` is less than or equal to **20** km, the total score is the sum of the score for **15** km and the bonus score.

- The score for each km for the first **20** km is **2**. Then the score for **15** km is **30**. (`15 * 2 = 30`)
- The **total score** is the sum of the score for **15** km and the bonus score that is **60**. (`30 + 30 = 60`)

Score is **2** for each km for 0 to 20 km ⇒ 15 × 2 = 30
Score is **4** for each km for 21 to 60 km ⇒ 0 x 4 = 0
Score is **6** for each km for above 60 km ⇒ 0 x 6 = 0

Total	⇒	30
Bonus Score	⇒	30
Total Score	⇒	60

code

```
kil=int(input())
total_score=0
bonus_score=30
first_20=0
```

```
first_60=0
after_60=0
if kil<=20:
    first_20=kil*2
elif kil>20 and kil<=60:
    first_20=20*2
    first_60=(kil-20)*4
elif kil>60:
    first_20=20*2
    first_60=40*4
    after_60=(kil-60)*6
total_score=first_60+first_20+after_60+bonus_score
print(total_score)
```

9

Print the Score - 4 | 40/40

Solved

Easy

Write a program that reads a distance `D` in km and calculates the total score.

- For the first **40** km (`0 - 40 km`), the score for each km is **2**.
- For the next **20** km (`41 - 60 km`), the score for each km is **4**.
- For the next **60** km (`61 - 120 km`), the score for each km is **6**.
- For the distance above **120** km, the score for each km is **8**.
- Apart from the above scores, there is a bonus score of **50**.

Input

The input will be a single line containing an integer representing `D` .

Output

The output should be a single line containing an integer that is the score.

Explanation

For example, if the given distance in km is `D = 70` ,

As `D` is greater than **60** km, the total score is the sum of the score of first **40** km, score of the next **20** km, score of the remaining distance after **60** km and the bonus score.

Score is **2** for each km for 0 to 40 km ⇒ 40 × 2 = 80
Score is **4** for each km for 41 to 60 km ⇒ 20 × 4 = 80
Score is **6** for each km for 61 to 120 km ⇒ 10 × 6 = 60
Score is **8** for each km for above 120 km ⇒ 0 x 8 = 0

Total	⇒	220
Bonus Score	⇒	50
Total Score	⇒	270

▶ Detailed Explanation to calculate the score

The output should be **270**.

Sample Input 1

```
70
```

Sample Output 1

```
270
```

code:

```
kilo_mtr=int(input())
total_score=0
bonus_score=50
first_40=0
first_60=0
first_120=0
after_120=0
if kilo_mtr<=40:
```

```
    first_40=kilo_mtr*2
elif kilo_mtr>40 and kilo_mtr<=60:
    first_40=40*2
    first_60=(kilo_mtr-40)*4
elif kilo_mtr >60 and kilo_mtr<=120:
    first_40=40*2
    first_60=20*4
    first_120=(kilo_mtr-60)*6
elif kilo_mtr>120:
    first_40=40*2
    first_60=20*4
    first_120=60*6
    after_120=(kilo_mtr-120)*8
total_score=first_120+first_60+first_40+after_120+bonus_sco
re
print(total_score)
```