L.D. College of Engineering, Ahmedabad

Department of Artificial Intelligence and Machine Learning

Machine Learning (BE05000211)

Project Report

REPORT ON LIBRASCAN

AI-Powered Book Cover Cataloging System using Azure OCR and Large Language Models

Submitted By:

Sr. No.	Name of Student	Enrollment No.
1	Darshil Savaliya	240280152068
2	Harshil Patel	240280152052
3	Aranav Mandani	240280152037

Branch: Artificial Intelligence and Machine Learning

Semester: 5th

Academic Year: 2026-27

Subject: Machine Learning (BE05000211)

Live Application: https://libra-scan.onrender.com

Source Code: https://github.com/darshil2032007/Libra-Scan

Faculty Name & Sign: _____

Date: _____

CONTENTS

Sr. No.	Content	Page No.
1	Introduction	3
2	Objectives	5
3	Technologies and Tools	6
4	System Requirements and Setup	8
5	System Design	11
6	Implementation and Working of the System	17
	Prompt Injection and Guard Rails (6.4.1)	20
7	Results and Output Screens	27
8	Advantages, Limitations and Future Scope	33
9	Conclusion	35
10	References	36

1. Introduction

1.1 Background

A library catalog is the backbone of every library, bookshop and personal collection. Each book needs a record that states its title, author names, publisher, year of publication, edition, language and, above all, its International Standard Book Number (ISBN), the unique identifier that links a physical copy to catalog databases around the world. Most of this information is printed on the book itself: the title, author names and series appear on the front cover, while the ISBN, barcode and publisher appear on the back cover.

Today this information is usually typed in by a person, one book at a time. Recent progress in machine-learning-based optical character recognition (OCR) and in large language models (LLMs) makes it possible to automate the work: a photograph of a cover can be converted into text, and the text can be converted into a structured record. LibraScan, the system described in this report, combines both technologies in a single web application with the tagline “Scan a cover. Catalog a book.”

1.2 Problem Statement

Cataloging books by hand, and building a reliable automatic alternative, both raise several problems:

- **Manual entry is slow.** A librarian has to read every cover and type up to ten fields for each title.
- **Manual entry is error-prone.** A typing mistake in a name or in the 13 digits of an ISBN makes a book hard to find later.
- **Information is split across two covers.** The title and author are on the front, while the ISBN and publisher are usually on the back, so a single photograph is often not enough.
- **OCR alone is not a catalog record.** An OCR engine returns lines of text; it does not know which line is the title and which is a review quotation or a price.
- **LLMs can be wrong or misled.** A language model may invent a value that is not on the cover, and text printed on a cover (or on a deliberately crafted image) may contain instructions aimed at the model.
- **A human must stay in control.** Librarians need to see where on the cover each value came from and how confident the system is, so that they can verify records quickly.

1.3 Motivation and Relevance to Machine Learning

The project is motivated by the practical need to digitise the catalog of small and medium libraries without expensive scanning equipment: a phone camera is enough. It also serves as a complete example of how machine-learning models are used inside a real application.

In LibraScan two pretrained models do the heavy lifting: a deep-learning-based text recognition model (Azure Document Intelligence, Read model) and a transformer-based large language model (Google Gemini 2.5 Flash by default, or an OpenAI model). The engineering work of this project lies around the models: preparing their input, constraining their output, validating the result and measuring confidence, so that machine output can be trusted in practice.

1.4 Scope of the Project

The following are included in the scope of the project:

- Upload of a front cover, or of front and back covers, for a single book or for a batch of up to 50 books.
- Image validation and enhancement, OCR, and LLM-based extraction of ten metadata fields.
- Validation of every value against the OCR text and verification of ISBN check digits.
- Confidence scores, bounding boxes and a review queue for doubtful records.
- A searchable catalog stored in SQLite, with CSV export and an analytics dashboard.
- Deployment of the application as a web service on Render.

No machine-learning model is trained in this project; OCR and extraction are obtained from external services. The system also does not look books up in external bibliographic databases, and it does not include user login or integration with a library management system. These points are discussed as future scope in Chapter 9.

1.5 Organisation of the Report

Chapter 2 states the objectives. Chapter 3 introduces the technologies and Chapter 4 lists the requirements and the setup procedure. Chapter 5 presents the system design: workflow, architecture, database and API. Chapter 6 explains in detail how the system works, stage by stage. Chapter 7 shows the output screens, Chapter 8 describes testing and deployment, Chapter 9 discusses advantages, limitations and future scope, and Chapter 10 concludes the report.

2. Objectives

2.1 Aim

The aim of the project is to build a web-based system that automatically produces a verified catalog record for a book from photographs of its front and back covers, reducing manual typing while keeping the librarian in control of the final record.

2.2 Specific Objectives

1. To accept cover photographs, singly or in bulk, and validate them (JPEG, PNG or WEBP, up to 10 MB).
2. To enhance the photographs with image processing so that the printed text is read reliably.
3. To read the printed text with Azure Document Intelligence while keeping the position and confidence of every line.
4. To extract title, subtitle, authors, publisher, ISBN-10, ISBN-13, edition, year, language and series with a large language model.
5. To protect the pipeline against prompt injection, invented values and invalid ISBNs.
6. To assign a confidence score to every field and automatically flag records that need human review.
7. To process large uploads in the background with a job queue, duplicate detection and automatic retries.
8. To give librarians a verification studio, a catalog with CSV export and an analytics dashboard, and to deploy the whole system online.

2.3 Expected Outcomes

On completion, a librarian should be able to photograph the covers of a stack of books, upload them in one batch and receive a catalog of structured records in which only doubtful entries need attention. Every value shown by the system can be traced back to the exact place on the cover where it was read, which makes verification quick and keeps the final responsibility with the human reviewer.

3. Technologies and Tools

3.1 Optical Character Recognition and Azure Document Intelligence

Optical character recognition converts text in an image into machine-readable text. Modern OCR engines use deep neural networks for text detection and recognition. Azure Document Intelligence (formerly Form Recognizer) provides a prebuilt Read model that returns, for every page, the recognised lines of text, a polygon around each line and a confidence value for every word.

LibraScan uses this model (`prebuilt-read`) because it works on printed text in many styles and returns the geometry that is needed to highlight each extracted value on the cover image.

3.2 Large Language Models for Information Extraction

A large language model is a neural network, based on the transformer architecture, that has been trained on very large text collections. Given instructions and some text, it can produce a structured answer. In LibraScan the model receives the OCR lines together with their position on the cover (for example “top, center, large”) and returns a JSON object with ten fields. The default model is Google Gemini 2.5 Flash; OpenAI models can be selected through configuration. The model is called with temperature 0 so that its answers are as repeatable as possible.

3.3 Image Processing with OpenCV and Pillow

Photographs taken with a phone are often tilted, unevenly lit or noisy. OpenCV, Pillow and NumPy are used to correct the orientation stored in the EXIF data, to resize large images, to improve local contrast with CLAHE (Contrast Limited Adaptive Histogram Equalization), to reduce noise with a bilateral filter and to sharpen the text with an unsharp mask.

3.4 Backend: FastAPI, SQLAlchemy and SQLite

The backend is written in Python with FastAPI, a modern web framework that validates requests with Pydantic models and generates a REST API. It runs on the Uvicorn ASGI server. SQLAlchemy provides the object-relational mapping to an SQLite database, which stores books, batches and jobs. Long-running work is moved to background workers built on Python’s asyncio.

3.5 Frontend

The user interface is built with plain HTML, CSS and JavaScript modules, without a frontend framework. A small hash-based router switches between the Overview, New Scan,

Library, Review Queue and Insights pages. A light and a dark theme are available, and the chosen theme is remembered in the browser.

3.6 Summary of the Technology Stack

Table 3.1 lists the main components with the versions pinned in the project's requirements file.

Table 3.1: Technology stack of LibraScan

Component	Technology	Purpose
Web framework	FastAPI 0.115.8	REST API and static hosting of the frontend
Application server	Uvicorn 0.34.0	Runs the ASGI application
Validation and settings	Pydantic 2.10.6, pydantic-settings 2.7.1	Schemas for requests and results; configuration from environment variables
File upload	python-multipart 0.0.20	Multipart form uploads of cover images
Image processing	opencv-python-headless 4.11.0.86, Pillow 11.1.0, NumPy 2.2.3	Validation, orientation, resize, contrast, denoise, sharpen
OCR	azure-ai-documentintelligence 1.0.0b4, httpx 0.28.1	Azure Read model and REST fallback
LLM	google-genai 1.3.0, openai 1.63.2	Gemini (default) or OpenAI for field extraction
Database	SQLAlchemy 2.0.38 with SQLite	Books, batches and jobs
Testing	pytest 8.3.4 and Node.js test runner	Backend tests and frontend pairing test
Hosting	Render (Python web service)	Public deployment

4. System Requirements and Setup

4.1 Hardware Requirements

The expensive computation (OCR and language-model inference) is carried out by cloud services, so the local hardware requirements are modest. The following are recommended:

- A computer or server that can run Python 3.11, for example with a dual-core processor and 4 GB of RAM.
- Free disk space for the application and for the uploaded cover images.
- A stable internet connection, because every scan calls the OCR and LLM services.
- A phone camera or scanner that can produce sharp photographs of the covers.

4.2 Software Requirements

Table 4.1: Software requirements

Item	Requirement
Operating system	Windows, Linux or macOS
Language runtime	Python 3.11 or newer (3.11.9 is used on Render), pip and venv
Web browser	A current version of Chrome, Edge, Firefox or Safari
Version control	Git, to clone the repository
Node.js	Needed only to run the JavaScript pairing test
Azure account	An Azure Document Intelligence resource (endpoint and key)
LLM account	A Google Gemini API key, or an OpenAI API key

4.3 Configuration Parameters

All settings are read from environment variables or from a `.env` file (see `.env.example`). Table 4.2 lists them with their default values.

Table 4.2: Configuration parameters

Variable	Default	Meaning
APP_ENV	development	Run mode of the application
LOG_LEVEL	INFO	Logging level
BULK_WORKERS	2	Number of background workers for bulk jobs
MAX_UPLOAD_MB	10	Largest accepted image file
UPLOAD_DIR	data/uploads	Folder where cover images are stored
DATABASE_URL	sqlite:///data/books.db	Database connection string
MAX_IMAGE_SIDE	2000	Longest image side in pixels after resizing
OCR_MIN_CONFIDENCE	0.5	OCR lines below this confidence are dropped
AZURE_DI_ENDPOINT, AZURE_DI_KEY	(empty)	Azure Document Intelligence credentials
LLM_PROVIDER	gemini	LLM provider: gemini or openai
LLM_MODEL	gemini-2.5-flash	Model name sent to the provider
GEMINI_API_KEY, OPENAI_API_KEY	(empty)	API key of the chosen provider

4.4 Installation and Execution

The application is installed and started with the following steps:

1. Clone the repository and open the project folder.
2. Create and activate a virtual environment.
3. Install the dependencies with `pip install -r requirements.txt`.
4. Copy `.env.example` to `.env` and enter the Azure and LLM credentials.
5. Start the server and open `http://127.0.0.1:8000` in a browser.

```
git clone https://github.com/darshil2032007/Libra-Scan
cd Libra-Scan
python -m venv .venv
.venv\Scripts\activate          (Windows)
source .venv/bin/activate        (Linux / macOS)
pip install -r requirements.txt
cp .env.example .env
uvicorn app.main:app --reload
```

The deployed version of the application is available at https://libra-scan.onrender.com.

5. System Design

5.1 Overall Workflow

Figure 5.1 shows the complete journey of a book from the uploaded photographs to a verified catalog record. The same sequence is used for a single scan and for every book of a bulk upload.




Figure 5.1: Overall workflow of LibraScan

Stage	What happens	Module
1. Upload covers	Front and optional back image are received and validated	routes/books.py, routes/batches.py
2. Preprocess	Orientation, resize, contrast, denoise, sharpen	services/preprocess.py
3. Azure OCR	Text lines with polygons and confidence	services/ocr.py
4. LLM extract	OCR lines become ten structured fields	services/llm.py, prompts/extract_book.txt
5. Guard and verify	Filtering, grounding and ISBN validation	services/guard.py, services/isbn.py
6. Score and flag	Confidence, warnings, bounding boxes	services/pipeline.py, services/geometry.py
7. Save record	Book stored in SQLite, duplicates detected by hash	db/repository.py, db/models.py
8. Review and export	Verification, correction, CSV export	frontend/js/views/viewer.js, routes/books.py

Table 5.1 maps each stage of the workflow to the part of the code that performs it.**Table 5.1:** Workflow stages and the modules that implement them

5.2 System Architecture

LibraScan follows a layered architecture, shown in Figure 5.2. The browser talks to a FastAPI application over HTTP and JSON. The route handlers are thin: they validate input and call the service layer, where the real work happens. The service layer uses two external services (Azure Document Intelligence and the LLM provider) and local storage (an SQLite database and an uploads folder).




Figure 5.2: Layered architecture of LibraScan

The module `pipeline.py` is the heart of the system. Its function `process_book_images()` chains preprocessing, OCR, filtering, LLM extraction and validation. The module `queue.py` runs two background workers that call this function for bulk uploads, while `batch_service.py` creates batches and controls jobs.

5.3 Project Structure

Table 5.2: Folder and file structure of the repository

Path	Contents
app/main.py	FastAPI application, start-up and shutdown handling, static frontend mount
app/api/routes/	books.py, batches.py, stats.py and health.py: the REST endpoints
app/services/	pipeline, preprocess, ocr, llm, guard, isbn, geometry, queue and batch_service
app/schemas/	Pydantic models for books (book.py) and OCR output (ocr.py)
app/db/	models.py (tables), repository.py (queries) and session.py (connection)
app/core/	config.py (settings) and logging.py
app/prompts/	extract_book.txt, the instruction prompt for the LLM
frontend/	index.html, css/ and js/ (router, api client, queue, pairing and the five views)
scripts/	run_preprocess.py, run_ocr.py, run_llm.py, debug_boxes.py, fetch_openlibrary_dataset.py
tests/	pytest test modules and a Node.js test for the pairing logic
Root files	app.py, render.yaml, requirements.txt, .env.example, README.md, pytest.ini

5.4 Database Design

The database has three tables, shown in Figure 5.3. A **Batch** groups the jobs created by one bulk upload. A **Job** represents one book waiting to be processed or already processed, and records its status, current step, number of attempts and timing. A **Book** is the catalog record produced by a successful job.




Figure 5.3: Entity relationship diagram

Several design decisions are visible in the diagram. The `image_hash` column of a book is unique: it is the SHA-256 hash of the front and back images, and it is how duplicates are detected. The columns `field_boxes`, `ocr_lines` and `warnings` are stored as JSON, so the exact evidence behind every value (bounding boxes, recognised lines and warnings) is kept with the record. The `status` column starts as `pending` and becomes `confirmed` when a librarian verifies the record.

5.5 REST API Design

Table 5.3: REST endpoints of LibraScan

Method	Endpoint	Description
GET	/health	Returns the health status of the application
POST	/books/upload	Uploads a front cover and an optional back cover and returns the extracted record
GET	/books	Lists books, with optional status filter, skip and limit (at most 100)
GET	/books/{id}	Returns one book
PATCH	/books/{id}	Saves a librarian's corrections; the status becomes confirmed
DELETE	/books/{id}	Deletes a book
GET	/books/{id}/image	Returns the front or back cover image (parameter side)
GET	/books/export.csv	Exports the catalog as a CSV file
GET	/stats	Returns the analytics shown on the dashboard
POST	/batches	Creates a bulk batch from uploaded files and queues one job per book
GET	/batches/active	Returns the batches that still have queued or running jobs
GET	/batches/{id}	Returns counts and the list of jobs of a batch
POST	/jobs/{id}/retry	Re-queues a failed or canceled job
POST	/jobs/{id}/cancel	Cancels a job that is still queued
POST	/batches/{id}/retry-failed	Re-queues all failed jobs of a batch
DELETE	/batches/{id}/finished	Removes finished jobs from the batch view
GET	/batches/jobs/{id}/image	Returns the thumbnail of a job before its book exists

5.6 User Interface Design

The interface has five pages and a verification view for a single book, listed in Table 5.4. A sidebar gives access to the pages, and a badge shows the number of books waiting for review.

Table 5.4: Pages of the user interface

Page	Purpose	Main elements
Overview	Health of the library at a glance	Cards: Books Cataloged, Needs Review, Avg Confidence, ISBN Coverage; charts: Books cataloged over time, Review status, Recent scans, Field confidence
New Scan	Add books	Single book or Bulk upload; Front Cover and Back Cover upload areas; Front only or Front + Back mode; Review Book Pairs; live batch queue
Library	Browse the catalog	Searchable list of books, status filter, CSV export
Review Queue	Verify doubtful records	Only books flagged for review, lowest confidence first
Insights	Analytics	Catalog size, 30-day activity, verification breakdown, field confidence, top authors, publishers, languages and years
Verification Studio	Check one record	Opened from the Library, Review Queue, recent scans or a finished job: covers with bounding boxes, OCR line toggle, confidence badges, editable fields, Save and Confirm

6. Implementation and Working of the System

This chapter explains how LibraScan actually works. The core is the function `process_book_images()` in `app/services/pipeline.py`. It is called directly for a single upload and by the background workers for bulk uploads, so both paths behave in exactly the same way. The sections below follow the order in which a book travels through the pipeline.

6.1 Image Upload and Validation

A single book is uploaded with `POST /books/upload`, which requires a front cover and accepts an optional back cover. A bulk upload is sent to `POST /batches`. Every file is validated by the function `validate_and_decode()` before any paid service is called:

- The file must not be larger than `MAX_UPLOAD_MB` (10 MB by default).
- The format must be JPEG, PNG or WEBP.
- The file must decode as a real image; corrupt files are rejected with a clear error message (HTTP 400).

The SHA-256 hash of the front image and the hash of the back image are then combined into one key. If a book with this key already exists in the catalog, the stored record is returned and no OCR or LLM call is made.

6.2 Image Preprocessing

Photographs from a phone are often rotated, uneven in lighting and noisy. The function `preprocess()` therefore applies six steps, listed in Table 6.1, before the image is sent to OCR. Each step can be switched on or off in the code.

Table 6.1: Image preprocessing steps

No.	Step	Operation and parameters	Purpose
1	Validate	Pillow decode; JPEG, PNG or WEBP; at most 10 MB	Reject unusable files early
2	Fix orientation	Apply EXIF rotation; convert to OpenCV BGR array	Phones store rotation as metadata
3	Resize	Downscale with area interpolation so the longest side is at most 2000 px	Limit upload size and OCR time
4	Enhance contrast	CLAHE on the lightness channel of LAB colour space; clip limit 2.0, 8 by 8 tiles	Even out lighting and glare
5	Denoise	Bilateral filter; d = 7, sigmaColor = 50, sigmaSpace = 50	Smooth noise but keep letter edges
6	Sharpen	Unsharp mask; Gaussian sigma 1.0, weights 1.6 and −0.6	Make thin letters stand out

6.3 Text Recognition with Azure OCR

The processed image is encoded as JPEG (quality 95) and sent to the `prebuilt-read` model of Azure Document Intelligence. If the preview API version returns a 404 error, the code falls back to the generally available 2023-07-31 REST API and polls for the result for up to 30 seconds. A failed call is retried once. The front and back covers are sent at the same time using a pool of two threads, so that a two-cover book needs about the same waiting time as a one-cover book.

For every line of text Azure returns, the system keeps the following data:

- the text of the line;
- its polygon and bounding box, converted to relative coordinates between 0 and 1, so that they are independent of image size;
- its confidence, calculated as the mean of the confidence values of its words.

Lines whose confidence is below `OCR_MIN_CONFIDENCE` (0.5) are discarded. The remaining lines are sorted from top to bottom and given global numbers: the front cover receives 0 to N−1 and the back cover continues from N. These numbers are what the language model later uses to say where each value was found.




Figure 6.2: Recognised text lines drawn on a cover image

6.4 Text Filtering and Injection Guard

Text read from a photograph is untrusted input. A cover could, by accident or on purpose, carry text such as “ignore previous instructions”. Before the text reaches the language model, the module `guard.py` filters the OCR lines with the rules in Table 6.2.

Table 6.2: Rules applied before the LLM call

Rule	Limit	Outcome
Tiny or hidden text	Line height below 0.5% of the image height	Line removed; warning “Hidden or tiny text ignored”
Text clean-up	Unicode NFKC normalisation; zero-width, bidirectional and control characters, HTML-like tags, code fences and role markers such as “system:” removed	Cleaned text is used
Instruction-like text	Patterns such as “ignore previous instructions”, “system prompt”, “act as”, “jailbreak”, “developer mode”, “api key”, “reveal”, “new instructions”	Line removed; warning “Suspicious instruction-like text removed”
Book check	At least 3 words in total and at most 400 words per image	Otherwise the error “This does not look like a book cover” is raised
Prompt size	At most 3000 characters of OCR text	Remaining lines are not sent

If any line was removed, the record is later marked for review, so a human always sees books that contained suspicious text.

6.5 Structured Extraction with the LLM

The remaining lines are written into a compact prompt in the form `id | text | position`. The position is derived from the centre and height of each line: the vertical part is top, middle or bottom (boundaries at 0.33 and 0.66), the horizontal part is left, center or right, and the size is small, medium or large (boundaries at 0.04 and 0.08 of the image height). Front and back covers are placed in separate labelled sections, as the following illustration shows.


```
=== FRONT COVER ===
0 | <title text>        | top, center, large
1 | <author name>        | bottom, center, medium
=== BACK COVER ===
2 | <blurb line>         | middle, left, small
3 | ISBN <digits>        | bottom, right, small
```


The instruction prompt (`app/prompts/extract_book.txt`) casts the model as an expert librarian and gives it strict rules: extract only values that appear in the text, use null

6.4.1 Prompt Injection and Guard Rails

Prompt injection occurs when text inside an uploaded image attempts to influence the language model instead of providing book metadata. For example, a cover may contain phrases such as “ignore previous instructions” or “reveal the system prompt”. OCR can read these phrases as ordinary text, so LibraScan treats all text extracted from cover images as untrusted input.

The uploaded example shows a cover carrying instruction-like text and the application rejecting it with the message “This does not look like a book cover”. This demonstrates why image text must be screened before it reaches the extraction model.





Guard rails used by LibraScan

- Filter tiny or hidden text and remove instruction-like phrases.
- Normalize OCR text and remove control characters, tags and role markers.
- Limit the OCR text included in the model prompt.
- Tell the model that cover text is untrusted data.
- Use a random delimiter and canary token to detect prompt interference.
- Require structured JSON and validate the response schema.
- Ground extracted values in OCR text; validate ISBN check digits.
- Flag suspicious records for human review.

when unsure, ignore blurbs, reviews, prices and unrelated numbers, take the title and authors from the front cover and the ISBN and publisher from the back cover, never put author names in the title, and cite the line numbers that support each value. The model must return one JSON object with this structure:

```
{
  "is_book_cover": true,
  "title":   { "value": "...",   "confidence": 0.0-1.0,
"source_line_ids": [0] },
  "authors": { "value": ["..."], "confidence": 0.0-1.0,
"source_line_ids": [1] },
  "subtitle", "publisher", "isbn10", "isbn13",
  "edition", "year", "language", "series"   (same value / confidence /
source_line_ids form)
}
```

The call is made with temperature 0, a limit of 800 output tokens and a JSON response type, to Gemini (default model `gemini-2.5-flash`) or to OpenAI, as configured. Several measures protect the call against prompt injection:

- the OCR text is wrapped in a delimiter tag with a random name, generated for each request, and any tag-like text inside the OCR is removed;
- after the text, the prompt states that the text above is untrusted data;
- a random canary token is added to the instructions with the order never to print it; if it appears in the answer, the answer is rejected;
- the answer must start with an opening brace and end with a closing brace, and it must match the expected schema (checked with Pydantic);
- a failed attempt is repeated once before an error is reported.

6.6 Grounding and Validation of Extracted Fields

Field	Rules
title, subtitle, publisher, edition, series	Must be grounded in the OCR text; at most 300, 300, 150, 100 and 200 characters respectively; no web addresses, markdown links, angle brackets, code fences or control characters
authors	At most 10 names; each at most 100 characters; each name must be grounded in the OCR text
year	A whole number from 1400 up to the current year
language	At most 35 characters, without digits or brackets
isbn10, isbn13	Valid check digit (Section 6.7) and present in the OCR text

A language model can sound confident even when it is wrong. Therefore every value it returns is checked against the OCR text by the function `ground_and_validate()`. A

value is “grounded” if its letters and digits appear in the cited lines or in the whole OCR text, or if at least half of its words match OCR words with a similarity of 0.8 or more.

A value that fails a rule is replaced by null with confidence 0, and a warning such as “Field title removed: not found in OCR text” is recorded. If the model did not cite line numbers for a valid value, the system finds the matching lines itself, so that a bounding box can still be drawn. If the model reports that the image is not a book cover and returns no fields, the upload is rejected.

6.7 ISBN Extraction and Verification

The ISBN is the most valuable field, so it is handled with mathematics as well as with the language model. Regular expressions find ISBN-13 and ISBN-10 patterns in the OCR text, allowing hyphens, spaces and dots between the digits. A candidate is accepted only if its check digit is correct:

```
ISBN-13 :  d1*1 + d2*3 + d3*1 + d4*3 + … + d13*1   must be divisible by
10
ISBN-10 :  10*d1 + 9*d2 + 8*d3 + … + 1*d10         must be divisible by
11   (X counts as 10)
```

A valid ISBN found by the regular expressions is passed to the model as a hint. If the model still returns no ISBN, the system fills it in directly from the OCR text with confidence 0.95. An ISBN returned by the model with a wrong check digit is removed with a warning. When only an ISBN-10 is available, the equivalent ISBN-13 is calculated by adding the prefix 978 and recomputing the check digit.

6.8 Confidence Scoring and Review Decision

Every field has a confidence between 0 and 1. The overall confidence of a book is the mean of the confidences of all fields that have a value, rounded to three decimals. A book is marked `needs_review` when any condition in Table 6.4 is true.

Table 6.4: Conditions that send a book to the review queue

Condition	Example
Guard removed or flagged something	Tiny text or instruction-like text was found on the cover
A value failed validation	An ISBN with a wrong check digit, or a title not found in the OCR text
Title or authors missing	The warning "Title could not be extracted."
Low confidence	title, authors, isbn13, isbn10, publisher or year below 0.60
Suspiciously large box	A field's bounding box covers more than 35% of the cover
No details extracted	Every field is empty
Identical covers	Front and back photographs are the same image

6.9 Bounding Box Generation

Each field cites the OCR lines it came from. The module `geometry.py` turns these lines into a few tight boxes. For each cover side the cited lines are sorted from top to bottom; a line joins the current group when the vertical gap to the group is at most 1.5 times the average line height (with a minimum of 0.02) and the lines overlap horizontally. Each group becomes one rectangle, stored in relative coordinates. The Verification Studio draws these rectangles over the cover images.

6.10 Saving Results and Duplicate Detection

The final result is stored as a `Book` row. It contains the ten fields, the overall confidence, the review flag, the warnings, the paths of the stored images, the OCR lines and the bounding boxes of every field. The status is `pending` until a librarian confirms the record. Because `image_hash` is unique, the same pair of images can never be atalogued twice. The pipeline additionally keeps an in-memory cache of results for the lifetime of the server process, so that repeated requests for the same images do not call the paid services again.

6.11 Bulk Upload and Background Queue

In bulk mode the user drops many photographs at once and chooses between **Front only** and **Front + Back**. In Front + Back mode the browser pairs the files automatically, using the naming rules in Table 6.5. If no front/back names are recognised, files are paired in the

order of upload (first with second, third with fourth, and so on). The user checks the pairs in the Review Book Pairs panel before sending them.

Table 6.5: File name rules for automatic pairing

Side	Recognised endings	Example
Front	front, cover, or a separator followed by f or 1	dune_front.jpg, dune-cover.png, dune_1.jpg
Back	back, rear, or a separator followed by b or 2	dune_back.jpg, dune-rear.png, dune_2.jpg

A batch can contain at most 50 books. The server saves every file to disk immediately, creates one job per book and places the job numbers on an in-process asyncio queue. Two background workers (`BULK_WORKERS`) take jobs from the queue. While a job runs, its current step (Preprocessing, Reading text, Extracting details, Saving) is stored in the database, and the browser polls the batch summary (`GET /batches/{id}`) to show live progress, counts and the average time per book. Figure 6.3 shows the life cycle of a job and Table 6.6 explains the statuses.




Figure 6.3: Life cycle of a processing job

Table 6.6: Job statuses

Status	Meaning
queued	Waiting for a worker
processing	A worker is running the pipeline; the step is shown in the interface
done	A book record was created
duplicate	The same images are already in the catalog; the existing book is linked and no OCR or LLM call is made
failed	The image was invalid, or all attempts failed; the error message is stored
canceled	The user canceled the job while it was still queued

The queue is designed to survive problems. If the OCR or LLM service answers with a rate-limit, connection or timeout error, the worker retries up to three times, waiting 1, 2 and 4 seconds. Invalid images fail immediately without retries. When the server starts, jobs left in the processing state by an earlier crash are reset to queued, and all queued jobs are placed on the queue again. In the interface the user can retry or cancel a job, retry all failed jobs of a batch, and clear finished jobs from the view.

6.12 Verification, Correction and Export

A finished book can be opened in the Verification Studio. The front and back covers are shown with the bounding boxes of the selected field, every field carries a confidence badge, and the OCR lines can be shown or hidden. The librarian corrects any value and presses **Save and Confirm** (shortcut Ctrl+Enter). This sends a `PATCH` request, and the status of the book changes to `confirmed`. The Library page lists all books with search and a status filter, the Review Queue shows only flagged books with the lowest confidence first, and the whole catalog can be downloaded as a CSV file with the columns id, title, authors, publisher, isbn10, isbn13, year, confidence and status.

6.13 Analytics Dashboard

The endpoint `GET /stats` computes the numbers for the Overview and Insights pages with SQL aggregate queries. It returns the number of books, books needing review, confirmed and pending books, books scanned today, books without ISBN-13, the average confidence and the average confidence of six fields (title, authors, publisher, isbn13, year, language). It also returns the number of books added on each of the last 30 days, the six most recent scans, and the top five authors, publishers and languages, together with the distribution of publication years.

6.14 Helper Scripts and Test Dataset

The `scripts` folder contains small command-line tools used during development. `Run_preprocess.py`, `run_ocr.py` and `run_llm.py` run the individual stages on an image, and `debug_boxes.py` runs the whole pipeline and saves images annotated with the field boxes and OCR line numbers. `Fetch_openlibrary_dataset.py` builds a test dataset of cover images and metadata from Open Library for five categories: romance, dystopian, steampunk, psychological thriller and mythology, with up to 20 books per category by default and publication years from 2016 to 2026.

7. Results and Output Screens

This chapter presents the output screens of the deployed LibraScan application (https://libra-scan.onrender.com). The screens follow the order in which a librarian uses the system.

7.1 Input Data

Figure 7.1 shows examples of the front and back cover photographs used to test the system.




Figure 7.1: Sample front and back cover photographs used as input

7.2 Overview Dashboard

The Overview page is the landing page. It shows the number of books cataloged, the books that need review, the average confidence and the ISBN coverage, followed by charts of the books over time, the review status, the recent scans and the confidence of each field




Figure 7.2: Overview page of LibraScan

7.3 Scanning a Single Book

On the New Scan page the user chooses Single book, adds a front cover and optionally a back cover, and starts the scan. Figure 7.3 shows the upload area and Figure 7.4 shows the progress while the pipeline runs.




Figure 7.3: New Scan page with front




Figure 7.4: Processing progress of a scan

7.4 Bulk Upload and Queue

In Bulk upload mode many photographs can be added at once. The system pairs them and shows the pairs for checking (Figure 7.5). After the batch is sent, the queue shows the status of every job (Figure 7.6).




Figure 7.5: Bulk upload: Review Book Pairs




Figure 7.6: Bulk upload: batch queue with live progress

7.5 Verification Studio

The Verification Studio shows the extracted fields next to the cover images. Each field has a confidence badge, and selecting a field highlights the part of the cover where the value was read (Figure 7.7). The librarian can correct a value and confirm the record (Figure 7.8).




Figure 7.7: Verification Studio with bounding boxes on the covers




Figure 7.8: Editing a field and confirming the record

7.6 Library and Review Queue

The Library page lists every cataloged book and can be searched and filtered by status. The Review Queue lists only the books flagged for review, starting with the lowest confidence.




Figure 7.11: Insights page with catalog analytics

7.8 CSV Export

The Export CSV button downloads the catalog as a file that can be opened in any spreadsheet program (Figure 7.12).




Figure 7.12: Exported books.csv opened in a spreadsheet

7.9 Dark Mode




Figure 7.13: LibraScan in dark mode

7.10 Discussion

The output screens show the main benefits of the design. The user types nothing for a book whose cover is read correctly, and the whole catalog can be built from photographs. Because every value is linked to bounding boxes, a reviewer can check a field by looking at one highlighted area instead of reading the entire cover. The review queue focuses attention on the books that the pipeline itself considers uncertain, which are the ones with low confidence, failed validation or suspicious text. The duplicate check and the retry policy keep the number of paid API calls low and make bulk processing robust.

8. Advantages, Limitations and Future Scope

8.1 Advantages

- **Saves time.** A book is cataloged from two photographs instead of typing ten fields, and a whole stack can be uploaded in one batch.
- **Trustworthy output.** Values are grounded in the OCR text, ISBNs are verified mathematically and doubtful records are flagged.
- **Transparent.** Every value is linked to bounding boxes and a confidence score, so a reviewer can check it quickly.
- **Secure by design.** Hidden text and instruction-like text are removed, and the LLM call is protected by delimiters, a canary token and strict output checks.
- **Cost-aware and robust.** Duplicates are detected before any paid call, and failed calls are retried with back-off.
- **Flexible.** The LLM provider and model can be changed through configuration, and the project is covered by automated tests.

8.2 Limitations

- The system depends on external paid cloud services and needs an internet connection.
- Poor photographs, decorative fonts or covers without a printed ISBN reduce the quality of the extracted data.
- The job queue runs inside the web server process and the database is a single SQLite file, which suits a small library but not a large, distributed installation.
- The free Render plan has an ephemeral file system, so data stored in SQLite and in the uploads folder is not permanent across redeployments, and an idle service needs time to start again.
- The API has no user login, and cross-origin requests are allowed from any origin.
- Accuracy has not yet been measured on a large labelled dataset; the output screens and test cases demonstrate behaviour but are not a formal benchmark.

8.3 Future Scope

- Add user accounts and roles, so that only authorised librarians can confirm or delete records.
- Look up the verified ISBN in a bibliographic database such as Open Library to complete or cross-check publisher, year and edition.
- Decode the barcode directly as an additional source of the ISBN.

- Replace SQLite and the in-process queue by PostgreSQL and a distributed task queue for large installations.
- Export records in library standards such as MARC21 or to systems such as Koha.
- Provide a mobile-friendly camera capture mode.
- Evaluate the pipeline on the Open Library dataset collected by the project script and publish accuracy per field.
- Support more languages and scripts, and evaluate self-hosted models for offline use.

9. Conclusion

LibraScan shows that a complete, practical cataloging tool can be built by combining pretrained OCR and language models with careful engineering. A librarian photographs the front and back cover of a book, and the system cleans the images, reads the text with Azure Document Intelligence, extracts ten metadata fields with a large language model and returns a structured record with confidence scores and bounding boxes.

The main lesson of the project is that model output must not be trusted blindly. The guard layer, the grounding of every value in the OCR text, the mathematical check of ISBNs and the rules that send doubtful records to a review queue turn two powerful but fallible models into a dependable workflow. The bulk upload queue with duplicate detection, retries and crash recovery makes the system usable for real collections, and the Verification Studio, catalog, CSV export and analytics dashboard give librarians full control over the result.

The project met its objectives: it accepts and validates cover photographs, extracts and verifies the metadata, flags uncertain records, processes large uploads in the background and is deployed online at https://libra-scan.onrender.com. With the improvements listed as future scope, such as authentication, bibliographic look-ups and a production-grade database, LibraScan can grow from a working prototype into a system for everyday library use.

10. References

[1] D. Savaliya, H. Patel and A. Mandani, "LibraScan: AI-powered library cataloging", source code repository, https://github.com/darshil2032007/Libra-Scan.

[2] LibraScan live application, https://libra-scan.onrender.com.

[3] Microsoft, "Azure AI Document Intelligence documentation: Read model", https://learn.microsoft.com/azure/ai-services/document-intelligence/.

[4] Google, "Gemini API documentation", https://ai.google.dev/gemini-api/docs.

[5] OpenAI, "API documentation", https://platform.openai.com/docs.

[6] S. Ramírez, "FastAPI documentation", https://fastapi.tiangolo.com.

[7] SQLAlchemy documentation, https://docs.sqlalchemy.org.

[8] G. Bradski, "The OpenCV Library", Dr. Dobb's Journal of Software Tools, 2000.

[9] K. Zuiderveld, "Contrast Limited Adaptive Histogram Equalization", in Graphics Gems IV, Academic Press, 1994, pp. 474–485.

[10] C. Tomasi and R. Manduchi, "Bilateral filtering for gray and color images", in Proceedings of the IEEE International Conference on Computer Vision (ICCV), 1998, pp. 839–846.

[11] International Organization for Standardization, ISO 2108: Information and documentation, International standard book number (ISBN).

[12] OWASP, "OWASP Top 10 for Large Language Model Applications: Prompt Injection", https://owasp.org/www-project-top-10-for-large-language-model-applications/.

[13] Open Library, "Search API", https://openlibrary.org/dev/docs/api/search.

[14] Render documentation, "Deploy a Python web service", https://render.com/docs.