

[← Go Back to Advanced Machine Learning](#)

[☰ Course Content](#)

2.6 Test your understanding

Type	:	Practice Quiz
Questions	:	5
Scoring Policy	:	Highest Score
Your Marks	:	4/5

Instructions

RETAKE

Attempt History

Attempt #1	Marks: 4	^
Aug 11, 7:40 AM		

Q No: 1

Correct Answer

Marks: 1/1

Which of the following predictive model(s) do not have an option to give more weightage(class_weight) to a certain class for classification problems?

☐ Decision Tree

☐ Random Forest

☒ Gradient Boost

You Selected

☒ XGBoost

You Selected

Gradient Boost and XGB do not have an option to give more weightage to a certain class using class_weight.

Q No: 2

Correct Answer

Marks: 1/1

Select True or False for the following statement:

In XGBoost, gamma is a hyperparameter that specifies the minimum loss reduction required to make a split.

☒ True

You Selected

☐ False

Gamma is a hyperparameter available in XGB that specifies the minimum loss reduction required to make a split.

Q No: 3

Incorrect Answer

Marks: 0/1

Select True or False for the following statement:

In Gradient Boosting, init is a hyperparameter that specifies the base estimator of the algorithm.

☒ True

You Selected

☐ False

Correct Option

In Gradient Boosting, init is a hyperparameter that specifies an estimator object that is used to compute the initial predictions.

Q No: 4

Correct Answer

Marks: 1/1

Which of the following statement(s) is/are correct for AdaBoost?

☒ An AdaBoost classifier is a meta-estimator that begins by fitting a classifier on the original dataset

You Selected

☒ The weights of incorrectly classified instances are adjusted such that subsequent classifiers focus more on difficult cases.

You Selected

☒ The default base estimator is a decision tree with max_depth=1

You Selected

☐ The base estimator can not be changed in AdaBoost implementation of sklearn.

Q No: 5

Correct Answer

Marks: 1/1

Which of the following hyperparameter(s) is/are common in AdaBoost, Gradient Boost, and XGBoost?

☒ random_state

You Selected

☒ learning_rate

You Selected

☐ subsample

☒ n_estimators

You Selected

The 'subsample' hyperparameter is available in Gradient Boost and XGBoost but not in AdaBoost.

