AI-powered phishing and scam detection

"Helping people spot phishing and scam messages early, using AI that checks a message or link and explains the risk in simple words. give me the best way and resources so i can do it fast" *Generated by LeapSpace*

Fast AI Detection of Phishing and Scam Messages at a Glance

Key Findings Table

Topic	Best-supported practical finding	Who/where it applies	Key citations
Fastest usable architecture	A **layered pipeline** works better than a single model: fast message screening, URL/domain enrichment, then plain-language explanation [1] [2] [3] [4] [5] [6] [7] [8]	Browser extensions, email checking, SMS/link scanning tools [7] [8] [9] [10]	[1] [4] [7]
Best v1 for speed	For a fast first version, **classic ML** such as TF-IDF + Logistic Regression or linear SVM for message text, plus tree/boosting models for URL features, is often the fastest and easiest to deploy [11] [12] [13] [14] [15] [16] [17]	Small teams, limited compute, near-real-time systems [6] [14] [18]	[11] [14] [16]
When to add transformers	**DistilBERT/RoBERTa-class models** usually improve benchmark performance on phishing text, but cost more and are less necessary for an MVP [1] [2] [19] [20] [21] [22]	Harder text, multilingual or generalized phishing detection [23] [24]	[1] [21] [22]

Topic	Best-supported practical finding	Who/where it applies	Key citations
URL detection	Strong first-line URL signals are lexical and structural: length, entropy, digits/symbols, token structure, subdomain depth, punycode/homograph cues, shortening/redirection clues [16] [17] [25] [26]	Any tool that checks pasted or clicked links [8] [17]	[16] [25]
Domain confidence	Domain-age, DNS/history, SSL/TLS, registrar and internet-presence/history features improve confidence beyond text-only or URL-only scoring [3] [4] [5] [27] [28] [29] [30]	High-confidence warnings and link triage [4] [5]	[3] [29]
Explainable warnings	The most useful warnings are **brief, concrete, and action-oriented**: risk label + 2-3 reasons + next step [31] [32] [33] [34]	Consumer-facing inbox, browser, and mobile warning flows [31] [32] [35]	[31] [33]
Real-world evaluation	Accuracy alone is not enough; teams should optimize **precision, false-positive rate, PR-AUC, and calibrated thresholds** to avoid alert fatigue [36] [37] [38] [39] [40] [41]	Any production or user-facing deployment [37] [41]	[39] [41]
Biggest weakness	Benchmark-strong systems often degrade under obfuscation, homoglyphs, shortening, code-mixing, and adversarial perturbation [11] [12] [23] [25] [42] [43] [44] [45] [46]	SMS scams, deceptive URLs, multilingual scams [23] [43] [44]	[42] [46]

Direct Answer

The best fast way is to build a **3-step AI checker**:

1. **Message classifier** for text risk,
2. **URL/domain scorer** for every extracted link,

3. **Simple explanation generator** that tells the user why it looks risky and what to do next [3] [4] [6] [7] [14] [31].

For speed, build **v1 with classic ML**, not a large model: use **TF-IDF + Logistic Regression or linear SVM** for email/SMS text, and **XGBoost, SVC, or Random Forest** for URL/domain features [11] [12] [13] [15] [16] [17]. This is the fastest route to something usable because classic models are cheaper, easier to calibrate, and still competitive on many phishing datasets [14] [15] [47].

Add **DistilBERT or RoBERTa** only if you already have labeled data and need better generalization on harder phishing text or multilingual content [1] [19] [21] [23]. For the link checker, prioritize **lexical URL features plus domain-age/DNS/SSL/history signals** before anything more complex [3] [4] [17] [27] [28].

For user trust, return warnings like: **"High risk: urgent language; sender doesn't match claimed brand; link uses a newly registered lookalike domain. Do not click. Open the official app or website instead."** That pattern is better supported than vague warnings [31] [32] [33] [34].

Fastest deployment path: ship it first as a **browser extension or message-check API**, because the literature strongly supports low-latency near-user scanning with immediate warnings and better privacy trade-offs [8] [10] [48].

Confidence level: High - the layered architecture, classic-ML-first recommendation, and brief action-oriented warnings are all directly supported across multiple parts of the evidence base [4] [7] [11] [31].

Study Scope

This report synthesizes research on phishing/scam detection across **email, SMS/smishing, URLs, phishing domains, explainable warnings, deployment architectures, and evaluation methods** from older foundational pipeline work through **2020-2025 model and deployment studies** [8] [21] [22] [49] [50] [51]. Methods covered include **classic ML, transformers, hybrid systems, lexical URL analysis, domain reputation, XAI methods, and low-latency deployment studies** [1] [6] [11] [16] [29] [52].

Assumptions & Limitations

- Many papers report strong accuracy/F1 but do **not** give deployment-grade false-positive rates or calibrated operating thresholds, which limits direct product decisions [21] [22] [41] [53].
- There is **no single verified end-to-end documented package** in the supplied evidence that already combines message classification, URL/domain scoring, threat-intel feeds, and consumer warning text in one reproducible system [54] [55].
- User-tested comparisons of explanation styles for ordinary end users remain sparse, so the best universal warning format is not fully established [52] [56] [57] [58].
- Reported performance depends heavily on dataset realism, class balance, and label quality [41] [59] [60] [61].

Suggested Further Research

- Run head-to-head tests of **rule-based vs SHAP/LIME vs LLM-written warnings** for ordinary users, not just analysts [56] [57] [58].
- Build stronger **multilingual and code-mixed smishing benchmarks** [23] [43] [62].
- Study **full-pipeline adversarial robustness** across message text, deceptive URLs, and reputation evasion together [45] [46] [63].
- Publish more **deployment-grade latency, memory, and false-positive measurements** for complete systems [64] [65] [66].
- Develop reproducible **privacy-preserving browser/mobile systems** with local inference and user-friendly warnings [8] [48].

Full Report

Foundational Context

Phishing/scam detection for end users is not one problem but **three linked problems**: detecting suspicious language, detecting suspicious links/domains, and communicating the result clearly enough that the user acts safely [1] [4] [67]. The research consistently indicates that success in production depends less on a single model's benchmark score and more on how these three parts are combined into a usable pipeline [2] [5] [7].

A practical system therefore needs four layers:

1. **Text understanding** - detect urgency, impersonation, credential requests, and scam-like wording in the message body [1] [19] [67].
2. **Link/domain analysis** - detect suspicious lexical patterns and weak domain reputation signals in links [3] [4] [17].
3. **Risk scoring/calibration** - combine evidence and choose thresholds that keep false alarms tolerable [4] [37] [41].
4. **User explanation** - turn technical evidence into short reasons plus a safe next action [31] [34] [52].

This framing matters because benchmark-leading text models alone are not enough when attackers use short links, homoglyphs, or code-mixed text, and because users often fail at manual URL inspection [42] [45] [68].
Confidence level: High - multiple cross-topic sources support the multi-layer framing [2] [4] [7] [67].

What to Build First

Recommended end-to-end pipeline

The strongest practical pattern in the evidence is a **layered system**, not a monolithic one [1] [4] [6] [7]. For fast implementation:

- **Step 1: Fast message screening**
  - Extract text from email/SMS/pasted message and score it with a lightweight classifier [11] [14].
  - Output a probability plus top suspicious cues such as urgency or account-verification language [34] [67].
- **Step 2: URL extraction and link scoring**
  - Parse all URLs and score them using lexical/structural features such as URL length, entropy, digit/symbol ratio, token structure, shortening clues, subdomain depth, and punycode/homograph indicators [16] [17] [25].
  - Enrich higher-risk links with domain-age, DNS, SSL/TLS, registrar, and internet-presence/history features [3] [28] [29] [30].
- **Step 3: Decision and explanation**
  - Fuse the text score and link score into a single calibrated risk output [4] [5] [37].
  - Show a full warning only when confidence is high or when both text and link signals agree; otherwise show a softer “verify first” warning [37] [41].
  - Generate a short explanation: **risk label + 2-3 reasons + safe next action** [31] [32] [33].

Taken together, these findings suggest the fastest robust product pattern is a **copilot warning card** rather than an opaque pass/fail classifier [8] [31] [34].
Confidence level: High - this architecture is the clearest recurring theme across message, URL, deployment, and explanation studies [1] [4] [7].

Best model families for quick deployment

The literature shows a tension: **transformers often win benchmarks**, but **classic ML is often the better deployment starting point** [1] [11] [12] [13] [20].

Best for MVP speed

- TF-IDF + Logistic Regression [11] [13]
- TF-IDF + linear SVM [12] [13]
- Random Forest / XGBoost / SVC for URL features [16] [17]

Why this is attractive:

- lower compute and simpler operation [14]
- easier interpretability and integration [15]
- still strong on structured or moderate-sized datasets [47] [69]

Best for upgraded v2

- DistilBERT, RoBERTa, TinyBERT, hybrid BERT systems [1] [2] [19] [21]
- Especially useful for hard text, multilingual data, or unseen variations [23] [43]

This implies a sensible build path: **ship classic ML first, then selectively replace the text stage with a compact transformer if data and latency budget justify it** [6] [14] [21].

Message and SMS Scam Detection

Transformer detectors for phishing email

Recent phishing-email studies report very strong benchmark performance from BERT-family models and hybrids [21] [22] [36] [53]. Examples include:

- BERT-BiLSTM hybrid: **F1 0.97** [53]
- RoBERTa-based detector: **95.0% accuracy, phishing F1 92.9%, near-zero false positives** [36]
- Fine-tuned DistilBERT/TinyBERT/RoBERTa: all above **0.985** on major metrics, with RoBERTa best overall [21]
- BERT-based anti-phishing system: **97.7% accuracy**, phishing recall **0.98**, phishing F1 **0.97** [22]

These results support transformers as strong performers, but most abstracts still omit detailed false-positive reporting or full held-out deployment settings [21] [22] [53]. That limits direct operational comparison despite high scores [41].

SMS and smishing under obfuscation

SMS detection is harder because messages are shorter and more frequently obfuscated [42] [43]. Important findings:

- DistilBERT and RoBERTa can be brittle under small perturbations [42].
- Prototype-based DistilBERT methods improve robustness on homoglyphs and code-switching [43].
- A compact multilingual BERT pipeline for Bangla smishing stays robust under romanized and lightly obfuscated text and beats TF-IDF + LogReg and XLM-RoBERTa in that setting [23].
- In one multi-class smishing dataset, a **Bag-of-Words + 6 lexical features** setup outperformed transformer baselines [70].

So for smishing, compact transformers are useful, but **character-level and lexical robustness features remain essential** [23] [43] [46].

When classic machine learning still wins

Classic ML is still preferable when:

- latency and throughput matter most [14]
- interpretability matters [15]
- training data are limited or only moderate-sized [47]
- the task has strong engineered features [69] [71]

This is especially relevant for a fast user-facing product. You do not need LLM-scale infrastructure to get a useful first release [14] [18].

Confidence level: High - the evidence consistently shows both transformer strength and classic-ML practicality, with a clear deployment trade-off [1] [11] [14].

URL and Domain Risk Detection

URL lexical and sequence-based detection

For pure link checking, lexical URL analysis is one of the most established starting points [16] [17]. Strong features include:

- URL length [16]
- entropy [16]
- digits and special-character patterns [16]
- token structure and path composition [17]
- subdomain depth and structural anomalies [17] [25]

On purely URL-based data, both camps perform well:

- **SVC** led one lexical-feature study with **97.5% mean accuracy** [16]
- **XGB** performed best in a feature-builder comparison reaching **99.5% accuracy** [17]
- URL-string transformers also performed strongly, including BERT-style tokenization and contextual URL models [24] [72] [73]

For a quick build, tree/boosting models on handcrafted features remain the simplest starting point [16] [17].

Domain reputation and host intelligence

Lexical features help, but reputation/history features improve confidence [3] [4] [5]. Useful signals include:

- domain age [28] [30]
- DNS records/history [28] [74]
- SSL/TLS properties [28] [30]
- registrar and WHOIS/RDAP metadata [30] [75]
- broader internet-presence/history features [29] [76]

Representative performance:

- over **92% accuracy at under 8% false-positive rate** from public internet-presence/history features [29]
- **94% accuracy** on future malicious domains in another classifier [76]
- DNS-based reputation with **60.71% detection at 0.35% false-positive rate** in one low-FPR setup [74]

A practical caveat: WHOIS and RDAP can disagree on important fields in **7.6% of domains**, so metadata should be treated as helpful but imperfect [75].

Lookalikes, homographs, and shortened links

This is one of the biggest failure points for naive systems [45] [68]. Better-documented defenses include:

- visual similarity plus ML [25] [77]
- OCR-based homograph detection [44]
- rendered-string/image methods such as Siamese CNNs [78]
- adversarially aware URL classifiers [79] [80]

Because users correctly identified only **40% of obfuscated URLs** in one study, automated detection is much safer than expecting users to inspect links manually [68].

Confidence level: High - URL lexical features and domain history are among the most consistently supported fast-deploy signals [3] [4] [17].

Explainable User Warnings

The evidence favors explanations that are **simple, specific, and directive** [31] [32] [33]. Good warning design includes:

- **Risk label**: low / medium / high [34]
- **Concrete reasons**: “urgent language,” “sender mismatch,” “suspicious link,” “newly registered domain” [52] [67]
- **Next action**: “do not click,” “verify in the official app,” “contact support through the official website” [32] [33]

Example format supported by the literature:

- **High risk**
- asks for urgent action
- sender and claimed brand do not match
- link appears deceptive
- **Do not click. Open the official app or website instead.** [31] [32] [33] [34]

XAI tools such as SHAP and LIME can help generate these reasons, and EXPLICATE combines LIME/SHAP with an LLM to translate technical signals into natural-language rationales [52]. But the current literature mostly evaluates explanation consistency or analyst usefulness, not broad end-user comprehension [52] [58].

Evidence on impact is still meaningful:

- explanations plus warnings reduce click-through, though overly complex explanations can hurt usability [81]
- users prefer interpretable systems even with slightly lower accuracy [82] [83]
- composite explanation reports improved analyst triage accuracy by **14%** and reduced decision time by **20 seconds per alert** [84]

So the safest product choice is **not maximal explanation**, but **minimal useful explanation** [58] [81]. **Confidence level: Medium-High** - the direction is clear, but end-user comparative studies are still limited [56] [57].

Low-Latency Deployment and Benchmarks

Fast deployment patterns

The literature supports fast deployment in:

- **browser extensions** [8] [10] [48] [85]
- **email/inbox pipelines** [6] [7]
- **mobile or SMS tools** [18]

A strong example is **PhishingLess**, which uses an XGBoost-based browser detector plus hover/click previews, warning overlays, and whitelisting to reduce warning fatigue while preserving immediate warnings [8]. Some extension-based systems also favor on-device analysis for privacy and report interactive notifications with sub-1.2-second delay [48].

Runtime, batching, and alert fatigue

Deployment papers emphasize that latency is not just model inference; feature extraction, queueing, batching, and alert dispatch all matter [66]. One analysis reported:

- **4.34 ms latency** at batch size 1
- about **19,000 URLs/sec** at batch size 128
- limited gains beyond moderate batching [86]

For user-facing systems, threshold tuning is crucial. Research recommends optimizing operating points that control false positives and alert fatigue rather than maximizing offline accuracy [37] [41].

Benchmark datasets and metrics

Common datasets in the supplied evidence include:

- **ISCX-URL-2016**
- **PhishTank-derived sets**
- **UCI, Kaggle, Mendeley, UNB, Ebbu2017**
- **Nazario, SpamAssassin, WikiLeaks** for email [61] [87] [88] [89] [90] [91]

But dataset realism strongly affects results:

- imbalanced datasets can depress or distort reported performance [59] [92] [93]
- older or narrow datasets can inflate performance [61]
- cross-paper comparisons are unreliable unless class skew and source diversity are controlled [41] [60]

For evaluation, the most decision-relevant metrics are:

- **precision**
- **recall**
- **F1**
- **false-positive rate**
- **PR-AUC/AUPRC**
- **calibrated operating points**, such as recall at high precision [38] [39] [40] [41]

Confidence level: High - the case for threshold calibration and dataset realism is repeatedly supported [37] [41] [61].

Best Resources to Use First

For a fast implementation plan, the most useful foundational reads in the supplied evidence are:

- **CANTINA** - foundational content-based phishing detection [49]
- **PhishNet** - URL-centric predictive blacklisting and URL variant discovery [51]
- **CANTINA+** - multi-feature pipeline with filters to reduce false positives [50]
- **CatchPhish** - lightweight modern URL-first baseline using hostname, full URL, TF-IDF, and phishing-hinted words [94]

For benchmarking resources, start with:

- **ISCX-URL-2016**
- **PhishTank-derived datasets**
- **Nazario**
- **SpamAssassin**
- **WikiLeaks-style email corpora** [61] [87] [88] [91]

Recommended Build Plan

1. **Ship v1 as a browser extension or API** with message paste + link paste checking [8] [10].
2. Use **TF-IDF + Logistic Regression/SVM** for message text [11] [12].
3. Use **XGBoost/SVC/Random Forest** on URL lexical + domain metadata features [16] [17] [29].
4. Show a warning only when calibrated thresholds are met; use softer “verify first” nudges otherwise [37] [41].
5. Format every warning as **risk level + 2-3 reasons + next action** [31] [33].
6. Upgrade later with **DistilBERT/RoBERTa** for harder text cases or multilingual coverage [21] [23].
7. Test robustness on **obfuscated SMS, shortened URLs, homoglyphs, and code-mixed text** before rollout [25] [42] [46].

Conclusion

The evidence supports a clear answer: the best fast approach is a **layered, low-latency phishing/scam checker** that combines lightweight message classification, URL lexical analysis, domain reputation/history signals, and very short plain-language warnings [1] [4] [7] [31]. For speed, **classic ML is the best first build path**; transformers are best treated as a later upgrade where harder text understanding is needed [11] [14] [21]. The main product risk is not low benchmark accuracy but **false positives, weak calibration, unrealistic datasets, and fragility under obfuscation** [37] [41] [45] [61]. The strongest user-facing design is a warning that is **brief, evidence-based, and action-oriented** [31] [32] [33].

Overall confidence level: High - the core architectural and deployment recommendations are strongly supported across multiple evidence streams, though exact end-to-end packaged implementations and user-tested explanation comparisons remain underdeveloped [4] [7] [11] [58].

References

1. Hasan, M., Nahar, N., Imam, M.H., Khandaker, M.U. (2025) PhisNet: Intelligent Detection of Phishing. *Eurasia Proceedings of Science, Technology, Engineering and Mathematics*. https://doi.org/10.55549/epstem.1357
2. Vasudevan, S., Govindan, V. (2025) Context-Aware Phishing: Leveraging Transformer and BiLSTM Networks for Cybersecurity. *Proceedings of the 9th International Conference on Inventive Systems and Control, ICISC 2025*. https://doi.org/10.1109/ICISC65841.2025.11188330
3. Nomani, K.M.S., Ehsan, S.B., Saquib, M.N. (2025) Cybersecurity Enhancement: Comprehensive Analysis of Machine Learning Models and Conventional Methods for Phishing URL Detection with Automated Domain Blocking. *2025 IEEE 4th International Conference on Computing and Machine Intelligence, ICMI 2025 - Proceedings*. https://doi.org/10.1109/ICMI65310.2025.11141042
4. Dalvi, A., Dhotre, V., Desai, K., (...), Inamdar, A. (2026) PhishNet: A Comprehensive System For Detecting Phishing Websites Using Machine Learning. *IET Conference Proceedings*. https://doi.org/10.1049/icp.2025.4772
5. Dhanalakshmi, R., Vijayaraghavan, N., Kumar, A., Prathiba, B.S. (2024) AI-Based Detection and Analysis of Phishing Domains: Leveraging Machine Learning for Enhanced Cybersecurity. *2024 International Conference on System, Computation, Automation and Networking, ICSCAN 2024*. https://doi.org/10.1109/ICSCAN62807.2024.10894038
6. Babala, L., Lipianina-Honcharenko, K., Osolinskyi, O. (2026) Deterministic Boolean-Algebra Framework for Interpretable and Energy-Efficient Phishing URL Detection in Real Time. *Applied Sciences (Switzerland)*. https://doi.org/10.3390/app16052170
7. Dhanalakshmi, B., Rajeshwari, R.R., Sanju, A.N., (...), Venkatesan, P. (2026) Email Spam Filtering Using Artificial Intelligence Techniques. *Diyala Journal of Engineering Sciences*. https://doi.org/10.24237/djes.2026.19102

8. Shi, F. (2026) Usable Phishing Defense in the Browser via Multi-Stage Detection and Trust Controls. *2026 IEEE 4th International Conference on Control, Electronics and Computer Technology, ICCECT 2026*. https://doi.org/10.1109/ICCECT68671.2026.11565112
9. Mun, H., Park, J., Kim, Y., (...), Kim, J. (2025) PhiShield: An AI-Based Personalized Anti-Spam Solution with Third-Party Integration. *Electronics (Switzerland)*. https://doi.org/10.3390/electronics14081581
10. Agoylo, J.C., Cerna, P.D. (2026) PhishBlock: Real-Time Phishing Detection Browser Extension with Monitoring System Using Hybrid Datasets Machine Learning Models. *2026 IEEE 18th International Conference on Computational Intelligence and Communication Networks, CICN 2026*. https://doi.org/10.1109/CICN70047.2026.11594162
11. Rączka, G., Plichta, A. (2026) Spam and Phishing Detection with Adversarial Attack Robustness Analysis Using Machine Learning Models. *Proceedings - European Council for Modelling and Simulation, ECMS*. https://www.scopus.com/pages/publications/105042236606
12. Alamoudi, K.F., Alghazali, M., Mohammed, A., (...), Alsulami, F.N. (2026) Comparative Analysis of Classical Machine Learning and Transformer-Based Models for Phishing URL Detection. *2026 IEEE 5th International Conference on Computing and Machine Intelligence, ICMI 2026*. https://doi.org/10.1109/ICMI68585.2026.11539839
13. Guo, Y., Mustafaoglu, Z., Koundal, D. (2023) Spam Detection Using Bidirectional Transformers and Machine Learning Classifier Algorithms. *Journal of Computational and Cognitive Engineering*. https://doi.org/10.47852/bonviewJCCE2202192
14. Wang, C., Jiao, W., Xing, W., (...), Zhang, G. (2026) Detection of imidacloprid in spinach using spectral technology and machine learning. *Journal of Food Composition and Analysis*. https://doi.org/10.1016/j.jfca.2025.108682
15. Bustio-Martínez, L., Herrera-Semenets, V., González-Ordiano, J.A., (...), van den Berg, J. (2026) Enhanced phishing detection using multimodal data. *Knowledge-Based Systems*. https://doi.org/10.1016/j.knosys.2025.115105
16. Sakib, M.N., Robin, K.H., Siddika, A., Nahar, S. (2024) A Novel Approach of Detecting Malicious Phishing URL Using Self-organizing Map. *Lecture Notes in Electrical Engineering*. https://doi.org/10.1007/978-981-97-0126-1_23
17. Oprea, S.-V., Bâra, A. (2024) Detecting Malicious Uniform Resource Locators Using an Applied Intelligence Framework. *Computers, Materials and Continua*. https://doi.org/10.32604/cmc.2024.051598
18. Birthriya, S.K., Kumar, D., Kishan Dewangan, R.K., (...), Tyagi, V. (2026) Smishing Detection: A Lightweight FastText-Based Architecture with Character-Level N-gram Analysis. *Proceedings of the 2026 4th International Conference on Secure Cyber Computing and Communications, ICSCCC 2026*. https://doi.org/10.1109/ICSCCC69031.2026.11600357

19. Aldoufani, Y., Eleyan, A., Bejaoui, T. (2025) An Intelligent Phishing Detection System Using Deep Learning and Explainable AI. *2025 International Symposium on Networks, Computers and Communications, ISNCC 2025*. https://doi.org/10.1109/ISNCC66965.2025.11250409

20. Tarapiah, S., Abbas, L., Mardawi, O., (...), Mansoor, W. (2025) Evaluating the Effectiveness of Large Language Models (LLMs) Versus Machine Learning (ML) in Identifying and Detecting Phishing Email Attempts. *Algorithms*. https://doi.org/10.3390/a18100599

21. Songailaite, M., Kankevičiūtė, E., Zhyhun, B., Mandravickaite, J. (2023) BERT-Based Models for Phishing Detection. *CEUR Workshop Proceedings*. https://www.scopus.com/pages/publications/85179627446

22. Fukarel, S.G., Edriatama, O.P., Aqila, M.R., (...), Chowanda, A. (2025) Phishing Detection with BERT: A Transformer-Based Approach for Cybersecurity. *Digest of Technical Papers - IEEE International Conference on Consumer Electronics*. https://doi.org/10.1109/ISCT66099.2025.11297271

23. Ahmed, M.I., Eazaz, A.H., Muradul Bashir, G.M. (2025) DV - mBERT: A Reproducible and Transparent Framework for Code-Mixed Bangla Smishing Detection with Meta-Feature Fusion and FGM Robustness. *2025 IEEE International Conference on Signal Processing, Information, Communication and Systems, SPICSCON 2025*. https://doi.org/10.1109/SPICSCON69221.2025.11504021

24. Goyal, D., Kumar, A., Mathur, P., (...), Gupta, A.K. (2025) Robust cybersecurity through discrete and large language models for effective phishing attack detection. *Journal of Discrete Mathematical Sciences and Cryptography*. https://doi.org/10.47974/JDMSC-2162

25. Thao, T.P., Nguyen-Son, H.-Q., Yamaguchi, R.S., Nakata, T. (2020) Boosting homograph attack classification using ensemble learning and n-gram model. *Proceedings - 2020 IEEE 19th International Conference on Trust, Security and Privacy in Computing and Communications, TrustCom 2020*. https://doi.org/10.1109/TrustCom50675.2020.00271

26. Naresh, R., Gupta, A., Giri, S. (2020) Malicious URL detection system using combined SVM and logistic regression model. *International Journal of Advanced Research in Engineering and Technology*. https://doi.org/10.34218/IJARET.11.4.2020.008

27. Hranický, R., Horák, A., Polisensky, J., (...), Rysavy, O. (2024) Unmasking the Phishermen: Phishing Domain Detection with Machine Learning and Multi-Source Intelligence. *Proceedings of IEEE/IFIP Network Operations and Management Symposium 2024, NOMS 2024*. https://doi.org/10.1109/NOMS59830.2024.10575573

28. Angel, O.-C., Melanie, P., Cristhian, P., (...), José, C. (2025) Analyzing website characteristics and their impact on web traffic and legitimacy classification for phishing detection: A structural equation modeling approach. *Issues in Information Systems*. https://doi.org/10.48009/2_iis_112

29. Le Page, S., Jourdan, G.-V., Bochmann, G.V., (...), Flood, J. (2019) Domain classifier: Compromised machines versus malicious registrations. *Lecture Notes in Computer Science (including subseries Lecture Notes in Artificial Intelligence and Lecture Notes in Bioinformatics)*. https://doi.org/10.1007/978-3-030-19274-7_20

30. Abinaya, A.M., Angeline Benita, D. (2025) Enhancing Web Security: A Multi-Layer Approach for Malicious URL Detection. *Proceedings of 8th International Conference on Inventive Computation Technologies, ICICT 2025*. https://doi.org/10.1109/ICICT64420.2025.11004756

31. Bouma-Sims, E., Liu, E., Li, A.X., Cranor, L.F. (2026) From "be Careful" to "here's Why": Investigating User Reasoning with Context-Specific SMS Scam Warnings. *Proceedings - IEEE Symposium on Security and Privacy*. https://doi.org/10.1109/SP63933.2026.00200

32. Carlson, E.J., Barbour, J.B. (2023) An Experimental Study of Message Strategies for Mobile Alerts and Warnings. *Natural Hazards Review*. https://doi.org/10.1061/NHREFO.NHENG-1721

33. Buono, P., Desolda, G., Greco, F., Piccinno, A. (2023) Let warnings interrupt the interaction and explain: designing and evaluating phishing email warnings. *Conference on Human Factors in Computing Systems - Proceedings*. https://doi.org/10.1145/3544549.3585802

34. Kalniņa, D., Norgaila, E., Daniela, L. (2026) Smishing risk assessment using RAG and its potential for pedagogical recontextualization for cybersecurity education. *Social Sciences and Humanities Open*. https://doi.org/10.1016/j.ssaho.2026.103485

35. Savanth, H.S., Pattar, A.P., Hegde, A.R., (...), Tah, A. (2025) A Comprehensive Approach for Phishing Detection and URL Blocking Using Browser Extensions and Mobile Applications. *2025 9th International Conference on Computational System and Information Technology for Sustainable Solutions, CSITSS 2025*. https://doi.org/10.1109/CSITSS67709.2025.11295663

36. John, J.W., Mohankumar, B. (2025) A Comparative Analysis of BERT and LLM Models for Advanced Phishing Detection. *2025 IEEE International Conference on Communication Networks and Computing, CNC 2025*. https://doi.org/10.1109/CNC68716.2025.11484704

37. K, S., Naik S, M. (2025) A novel framework for effective phishing URL detection using an LSTM-based siamese network. *Knowledge-Based Systems*. https://doi.org/10.1016/j.knosys.2025.114271

38. Chen, Zhen, Liu, Sheng-Zheng, Huang, Jia, (...), Long, Hai-Xia (2024) Ethereum Phishing Scam Detection Based on Data Augmentation Method and Hybrid Graph Neural Network Model. *Sensors (Basel, Switzerland)*. https://doi.org/10.3390/s24124022

39. Rasol Al Saidat, M., Shaalan, K., Yerima, S.Y. (2026) A hybrid deep learning framework for Arabic smishing detection: Dataset creation, model design, and explainability. *Natural Language Processing Journal*. https://doi.org/10.1016/j.nlp.2026.100222

40. Hussain, M., Abbas, J., Hussain, J., (...), Wu, H. (2027) ExpertFusion: Calibrated multi-expert decision fusion for phishing URL detection under distribution shift and target-prior uncertainty. *Expert Systems with Applications*. https://doi.org/10.1016/j.eswa.2026.134089

41. Kang, H., Lee, S.-G. (2026) TRACE: Transaction representation learning for large-scale Ethereum phishing detection under limited labels. *Decision Support Systems*. https://doi.org/10.1016/j.dss.2026.114753

42. Bajaj, A., Kumar Vishwakarma, D.K. (2023) Deceiving Deep Learning-based Fraud SMS Detection Models through Adversarial Attacks. *Proceedings - 17th International Conference on Signal-Image Technology and Internet-Based Systems, SITIS 2023*. https://doi.org/10.1109/SITIS61268.2023.00059

43. Yu, C.-Y., He, J., Zhang, W. (2025) TruScamBuster: Federated Latent-Thought Models for Zero-Shot Scam SMS Detection on Mobile Devices with Lightweight LLMs. *icARTi 2025 - Proceedings of the 2025 International Conference on Artificial Intelligence and its Applications*. https://doi.org/10.1145/3774791.3774799

44. Sawabe, Y., Chiba, D., Akiyama, M., Goto, S. (2019) Detection method of homograph internationalized domain names with OCR. *Journal of Information Processing*. https://doi.org/10.2197/ipsjjip.27.536

45. https://www.sciencedirect.com/science/article/pii/S2196111525000667

46. https://www.sciencedirect.com/science/article/pii/S1573048426003341

47. https://www.sciencedirect.com/science/article/pii/S2661890721000296

48. Satheesh Kumar, M., Jones, P., Ajay, M., (...), Priya, S. (2026) Client Side Session Hijacking Detection and Defense using Fingerprinting Based Anomaly Detection and Cookie Entropy Analysis. *2026 International Conference on Innovations in Emerging Technologies for Sustainable Development: Empowering Innovation for a Sustainable Future, ICIETSD 2026 - Conference Proceedings*. https://doi.org/10.1109/ICIETSD68684.2026.11584818

49. Zhang, Y., Hong, J.I., Cranor, L.F. (2007) Cantina: A content-based approach to detecting phishing web sites. *16th International World Wide Web Conference, WWW2007*. https://doi.org/10.1145/1242572.1242659

50. Xiang, G., Hong, J., Rosé, C.P., Cranor, L. (2011) CANTINA+: A feature-rich machine learning framework for detecting phishing web sites. *ACM Transactions on Information and System Security*. https://doi.org/10.1145/2019599.2019606

51. Prakash, P., Kumar, M., Rao Kompella, R., Gupta, M. (2010) PhishNet: Predictive blacklisting to detect phishing attacks. *Proceedings - IEEE INFOCOM*. https://doi.org/10.1109/INFCOM.2010.5462216

52. Kalniņa, D., Norgaila, E., Daniela, L. (2026) Smishing risk assessment using RAG and its potential for pedagogical recontextualization for cybersecurity education. *Social Sciences and Humanities Open*. https://doi.org/10.1016/j.ssaho.2026.103485

53. Seethawaka, R., Chathurya, N.E.G., Chandrasiri, D.K.W.G.G.T., (...), Wijesooriya, A. (2025) Intelligent Detection of Corporate Targeted Phishing Emails - A Hybrid Approach Combining Deep Learning Models with Domain Anomaly Detection. *2025 17th International Conference on Contemporary Computing, IC3 2025*. https://doi.org/10.1109/IC366947.2025.11290288

54. Cohen, A., Nissim, N., Elovici, Y. (2018) Novel set of general descriptive features for enhanced detection of malicious emails using machine learning methods. *Expert Systems with Applications*. https://doi.org/10.1016/j.eswa.2018.05.031
55. Vu Bui, L. (2025) Legally-aware AI moderation in Vietnam: A cybersecurity law-compliant framework for platform governance. *Journal of Economic Criminology*. https://doi.org/10.1016/j.jeconc.2025.100193
56. Ntim Yeboah, P., Kayes, A.S.M., Rahayu, W., (...), Mahbub, S. (2026) A systematic literature survey of machine learning approaches to cyber data breach detection: Current research issues and future directions. *Computer Networks*. https://doi.org/10.1016/j.comnet.2026.112179
57. Vimbi, Viswan, Shaffi, Noushath, Mahmud, Mufti (2024) Interpreting artificial intelligence models: a systematic review on the application of LIME and SHAP in Alzheimer's disease detection. *Brain Informatics*. https://doi.org/10.1186/s40708-024-00222-1
58. Setty, R., Elovici, Y., Schwartz, D. (2026) Building trust in AI-driven venture capital decisions: A comparative study of SHAP and GPT explanations. *Journal of Behavioral and Experimental Finance*. https://doi.org/10.1016/j.jbef.2026.101148
59. El Aassal, A., Baki, S., Das, A., Verma, R.M. (2020) An In-Depth Benchmarking and Evaluation of Phishing Detection Research for Security Needs. *IEEE Access*. https://doi.org/10.1109/ACCESS.2020.2969780
60. Champa, A.I., Rabbi, M.F., Zibran, M.F. (2024) Curated Datasets and Feature Analysis for Phishing Email Detection with Machine Learning. *2024 IEEE 3rd International Conference on Computing and Machine Intelligence, ICMI 2024 - Proceedings*. https://doi.org/10.1109/ICMI60790.2024.10585821
61. Sánchez-Paniagua, M., Fidalgo, E., González-Castro, V., Alegre, E. (2021) Impact of current phishing strategies in machine learning models for phishing detection. *Advances in Intelligent Systems and Computing*. https://doi.org/10.1007/978-3-030-57805-3_9
62. Dasari, K., Ganu, D., Reddy, B.L., (...), Reddy, K.S.T. (2025) Phishing Detection: A Comprehensive Survey of Methods and Trends. *Proceedings - 2025 IEEE DELCON: International Conference on Recent Smart Technologies in Engineering for Sustainable Development*. https://doi.org/10.1109/DELCON68055.2025.11400192
63. https://www.sciencedirect.com/science/article/pii/S1573754326005658
64. Alani, M.M., Tawfik, H. (2022) PhishNot: A Cloud-Based Machine-Learning Approach to Phishing URL Detection. *Computer Networks*. https://doi.org/10.1016/j.comnet.2022.109407
65. Bustio-Martínez, L., Álvarez-Carmona, M.A., Herrera-Semenets, V., (...), Cumplido, R. (2022) A lightweight data representation for phishing URLs detection in IoT environments. *Information Sciences*. https://doi.org/10.1016/j.ins.2022.04.059
66. Alqithami, S., Stiawan, D., Budiarto, R. (2026) On-the-fly, memory-aware unsupervised learning for network anomaly detection: A systematic literature review. *e-Prime - Advances in Electrical Engineering, Electronics and Energy*. https://doi.org/10.1016/j.prime.2025.101146

67. Gangrade, M., Sivasamy, S. (2026) Demystifying Phishing Detection: Using Explainable AI to Identify Suspicious Email Features. *Lecture Notes in Networks and Systems*. https://doi.org/10.1007/978-3-032-25631-7_25

68. Reynolds, J., Kumar, D., Ma, Z., (...), Bailey, M. (2020) Measuring Identity Confusion with Uniform Resource Locators. *Conference on Human Factors in Computing Systems - Proceedings*. https://doi.org/10.1145/3313831.3376298

69. Shaukat, Muhammad Waqas, Amin, Rashid, Muslam, Muhana Magboul Ali, (...), Xie, Jiang (2023) A Hybrid Approach for Alluring Ads Phishing Attack Detection Using Machine Learning. *Sensors (Basel, Switzerland)*. https://doi.org/10.3390/s23198070

70. Martínez-Mendoza, A., Jañez-Martino, F., Carofilis, A., (...), Fidalgo, E. (2024) Towards Multi-Class Smishing Detection: A Novel Feature Vector Approach and the Smishing-4C Dataset. *CEUR Workshop Proceedings*. https://www.scopus.com/pages/publications/85211964804

71. OJEWUMI, T.O., Ogunleye, G.O., Oguntunde, B.O., (...), Ogbu, N. (2022) Performance evaluation of machine learning tools for detection of phishing attacks on web pages. *Scientific African*. https://doi.org/10.1016/j.sciaf.2022.e01165

72. Su, M.-Y., Su, K.-L. (2023) BERT-Based Approaches to Identifying Malicious URLs. *Sensors (Basel, Switzerland)*. https://doi.org/10.3390/s23208499

73. Lakshmaiya, N., Kota, S.R., Rajkamal, M.D.R., (...), Rajendran, A. (2025) Context Embeddings-Based Self-Attention Mechanism for Lexical-Based Phishing URL Detection for Secured Communication. *2025 IEEE 5th International Conference on ICT in Business Industry and Government, ICTBIG 2025*. https://doi.org/10.1109/ICTBIG68706.2025.11323625

74. Paz, E., Gudes, E. (2020) Comparison of DNS Based Methods for Detecting Malicious Domains. *Lecture Notes in Computer Science (including subseries Lecture Notes in Artificial Intelligence and Lecture Notes in Bioinformatics)*. https://doi.org/10.1007/978-3-030-49785-9_14

75. Fernandez, S., Hureau, O., Duda, A., Korczyński, M. (2024) WHOIS Right? An Analysis of WHOIS and RDAP Consistency. *Lecture Notes in Computer Science (including subseries Lecture Notes in Artificial Intelligence and Lecture Notes in Bioinformatics)*. https://doi.org/10.1007/978-3-031-56249-5_9

76. Le Page, S., Jourdan, G.-V. (2019) Victim or Attacker? A Multi-dataset Domain Classification of Phishing Attacks. *2019 17th International Conference on Privacy, Security and Trust, PST 2019 - Proceedings*. https://doi.org/10.1109/PST47121.2019.8949038

77. Thao, T.P., Sawaya, Y., Nguyen-Son, H.-Q., (...), Kubota, A. (2019) Hunting brand domain forgery: A scalable classification for homograph attack. *IFIP Advances in Information and Communication Technology*. https://doi.org/10.1007/978-3-030-22312-0_1

78. Woodbridge, J., Anderson, H.S., Ahuja, A., Grant, D. (2018) Detecting homoglyph attacks with a siamese neural network. *Proceedings - 2018 IEEE Symposium on Security and Privacy Workshops, SPW 2018*. https://doi.org/10.1109/SPW.2018.00012

79. Afzal, S., Gebrehiwot, A., Khan, F.A., Lauria, F.M. (2025) Attacker-Aware Contrastive Learning for Robust Malicious URL Classification. *Proceedings of the 2025 International Conference on Computational Intelligence, Security, and Artificial Intelligence, IntelliSecAI 2025*. https://doi.org/10.1109/INTELLISECAI66368.2025.11472972

80. Sajeth Jonathan, S.W., Arunaasalam, R.H., Senarathne, A.N., (...), Yapa, K. (2021) Event-Driven Malicious URL Extractor. *ICAC 2021 - 3rd International Conference on Advancements in Computing, Proceedings*. https://doi.org/10.1109/ICAC54203.2021.9670883

81. Greco, F., Desolda, G., Buono, P., Piccinno, A. (2025) Enhancing Phishing Defenses: The Impact of Timing and Explanations in Warnings for Email Clients. *Computer Standards and Interfaces*. https://doi.org/10.1016/j.csi.2025.103982

82. Bustio-Martínez, L., Herrera-Semenets, V., González-Ordiano, J.A., (...), van den Berg, J. (2026) Enhanced phishing detection using multimodal data. *Knowledge-Based Systems*. https://doi.org/10.1016/j.knosys.2025.115105

83. Schuetz, S.W., Steelman, Z.R., Syler, R.A. (2022) It's not just about accuracy: An investigation of the human factors in users' reliance on anti-phishing tools. *Decision Support Systems*. https://doi.org/10.1016/j.dss.2022.113846

84. https://www.sciencedirect.com/science/article/pii/S2731080926007076

85. Thomas, R., Tahir, S., Bakhsh, S.T., Alotaibi, R. (2025) Implementing Deep Learning to Detect Malicious URLs. *Lecture Notes in Networks and Systems*. https://doi.org/10.1007/978-981-96-7400-8_2

86. Wangchuk, T., Gonsalves, T. (2026) A multi-branch hybrid architecture of Transformer, CNN, and a Deep Feedforward network with MoE for phishing URL detection. *Computer Networks*. https://doi.org/10.1016/j.comnet.2026.112670

87. Johnson, C., Khadka, B., Basnet, R.B., Doleck, T. (2020) Towards detecting and classifying malicious urls using deep learning. *Journal of Wireless Mobile Networks, Ubiquitous Computing, and Dependable Applications*. https://doi.org/10.22667/JOWUA.2020.12.31.031

88. Ashok, A., Rathis, D., Raghavendra, R., Umadevi, V. (2024) A Comparative Analysis of Traditional Machine Learning, Deep Learning and Boosting Algorithms on Phishing URL Detection. *2024 IEEE International Conference on Computer Vision and Machine Intelligence, CVMI 2024*. https://doi.org/10.1109/CVMI61877.2024.10782525

89. Asif, T., Mehmood, F., Gillani, S.A.M., (...), Dengel, A. (2025) RPCP-PURI: A robust and precise computational predictor for Phishing Uniform Resource Identification. *Journal of Information Security and Applications*. https://doi.org/10.1016/j.jisa.2024.103953

90. Aljammal, A.H., Taamneh, S., Qawasmeh, A., Bani-Salameh, H.B. (2023) Machine Learning Based Phishing Attacks Detection Using Multiple Datasets. *International Journal of Interactive Mobile Technologies*. https://doi.org/10.3991/ijim.v17i05.37575

91. Zeng, V., Baki, S., El Aassal, A., (...), Das, A. (2020) Diverse datasets and a customizable benchmarking framework for phishing. *IWSPA 2020 - Proceedings of the 6th International Workshop on Security and Privacy Analytics*. https://doi.org/10.1145/3375708.3380313

92. Thapa, C., Tang, J.W., Abuadbba, A., (...), Zheng, Y. (2023) Evaluation of Federated Learning in Phishing Email Detection. *Sensors*. https://doi.org/10.3390/s23094346

93. Subashini, K., Narmatha, V. (2023) Website Phishing Detection of Machine Learning Approach using SMOTE method. *2023 5th International Conference on Electrical, Computer and Communication Technologies, ICECCT 2023*. https://doi.org/10.1109/ICECCT56650.2023.10179745

94. Rao, R.S., Vaishnavi, T., Pais, A.R. (2020) CatchPhish: detection of phishing websites by inspecting URLs. *Journal of Ambient Intelligence and Humanized Computing*. https://doi.org/10.1007/s12652-019-01311-4