

PROGRAM :

```
#include <stdio.h>
#include <unistd.h>
#include <sys/wait.h>

int main() {
    int pipe1[2], pipe2[2];

    pipe(pipe1);
    pipe(pipe2);

    if (fork() == 0) {
        dup2(pipe1[1], STDOUT_FILENO);

        close(pipe1[0]);
        close(pipe1[1]);
        close(pipe2[0]);
        close(pipe2[1]);

        execlp("ls", "ls", NULL);
    }

    if (fork() == 0) {
        dup2(pipe1[0], STDIN_FILENO);
        dup2(pipe2[1], STDOUT_FILENO);

        close(pipe1[0]);
        close(pipe1[1]);
        close(pipe2[0]);
        close(pipe2[1]);

        execlp("grep", "grep", "txt", NULL);
    }

    if (fork() == 0) {
        dup2(pipe2[0], STDIN_FILENO);

        close(pipe1[0]);
        close(pipe1[1]);
        close(pipe2[0]);
        close(pipe2[1]);

        execlp("wc", "wc", "-l", NULL);
    }

    close(pipe1[0]);
    close(pipe1[1]);
    close(pipe2[0]);
    close(pipe2[1]);

    wait(NULL);
    wait(NULL);
    wait(NULL);

    return 0;
}
```

OUTPUT :

```
bhargav08@Bhargava:~/skill$ nano skill23.c
bhargav08@Bhargava:~/skill$ gcc skill23.c -o skill23
bhargav08@Bhargava:~/skill$ ./skill23
3
```