

12. Implement the Producer-Consumer problem using counting semaphores and POSIX threads. Evaluate synchronization correctness and system throughput under different buffer sizes.

Design a deadlock scenario involving multiple threads competing for shared resources. Demonstrate deadlock occurrence, identify the four necessary conditions for deadlock, and implement a deadlock prevention strategy using resource ordering.

OUTPUT :

```
#include <stdio.h>
#include <stdlib.h>
#include <pthread.h>
#include <semaphore.h>
#include <unistd.h>

#define BUFFER_SIZE 5

int buffer[BUFFER_SIZE];

int in = 0;
int out = 0;

sem_t empty;
sem_t full;

pthread_mutex_t mutex;

void *producer(void *arg)
{
    for (int i = 1; i <= 20; i++)
    {
        sem_wait(&empty);

        pthread_mutex_lock(&mutex);

        buffer[in] = i;

        printf("Produced: %d\n", i);

        in = (in + 1) % BUFFER_SIZE;

        pthread_mutex_unlock(&mutex);

        sem_post(&full);

        usleep(100000);
    }

    return NULL;
}

void *consumer(void *arg)
{
    for (int i = 1; i <= 20; i++)
    {
        sem_wait(&full);

        pthread_mutex_lock(&mutex);

        int item = buffer[out];

        printf("Consumed: %d\n", item);

        out = (out + 1) % BUFFER_SIZE;

        pthread_mutex_unlock(&mutex);

        sem_post(&empty);

        usleep(150000);
    }

    return NULL;
}

int main()
{
    pthread_t producer_thread;
    pthread_t consumer_thread;

    sem_init(&empty, 0, BUFFER_SIZE);
    sem_init(&full, 0, 0);

    pthread_mutex_init(&mutex, NULL);

    pthread_create(&producer_thread,
        NULL,
        producer,
        NULL);

    pthread_create(&consumer_thread,
        NULL,
        consumer,
        NULL);

    pthread_join(producer_thread, NULL);
    pthread_join(consumer_thread, NULL);

    sem_destroy(&empty);
    sem_destroy(&full);

    pthread_mutex_destroy(&mutex);

    return 0;
}
```

```
bhargav08@Bhargava:~/OS$ nano practical12A.c
bhargav08@Bhargava:~/OS$ gcc practical12A.c -o practical12A
bhargav08@Bhargava:~/OS$ ./practical12A
Produced: 1
Consumed: 1
Produced: 2
Consumed: 2
Produced: 3
Consumed: 3
Produced: 4
Produced: 5
Consumed: 4
Produced: 6
Consumed: 5
Produced: 7
Produced: 8
Consumed: 6
Produced: 9
Consumed: 7
Produced: 10
Produced: 11
```

12(B):

```
#include <stdio.h>
#include <pthread.h>
#include <unistd.h>

pthread_mutex_t resource1 = PTHREAD_MUTEX_INITIALIZER;
pthread_mutex_t resource2 = PTHREAD_MUTEX_INITIALIZER;

void *thread1(void *arg)
{
    pthread_mutex_lock(&resource1);
    printf("Thread 1 locked Resource 1\n");
    sleep(1);
    pthread_mutex_lock(&resource2);
    printf("Thread 1 locked Resource 2\n");
    pthread_mutex_unlock(&resource2);
    pthread_mutex_unlock(&resource1);
    return NULL;
}

void *thread2(void *arg)
{
    pthread_mutex_lock(&resource2);
    printf("Thread 2 locked Resource 2\n");
    sleep(1);
    pthread_mutex_lock(&resource1);
    printf("Thread 2 locked Resource 1\n");
    pthread_mutex_unlock(&resource1);
    pthread_mutex_unlock(&resource2);
    return NULL;
}

int main()
{
    pthread_t t1, t2;

    pthread_create(&t1, NULL, thread1, NULL);
    pthread_create(&t2, NULL, thread2, NULL);

    pthread_join(t1, NULL);
    pthread_join(t2, NULL);

    return 0;
}
```

```
bhargav08@Bhargava:~/OS$ nano practical12B.c
bhargav08@Bhargava:~/OS$ gcc practical12B.c -o practical12B
bhargav08@Bhargava:~/OS$ ./practical12B
Thread 1 locked Resource 1
Thread 2 locked Resource 2
```

12(C):

```
#include <stdio.h>
#include <pthread.h>

pthread_mutex_t resource1 = PTHREAD_MUTEX_INITIALIZER;
pthread_mutex_t resource2 = PTHREAD_MUTEX_INITIALIZER;

void *thread1(void *arg)
{
    pthread_mutex_lock(&resource1);
    printf("Thread 1 locked Resource 1\n");

    pthread_mutex_lock(&resource2);
    printf("Thread 1 locked Resource 2\n");

    printf("Thread 1 completed\n");

    pthread_mutex_unlock(&resource2);
    pthread_mutex_unlock(&resource1);

    return NULL;
}

void *thread2(void *arg)
{
    /* Same order: Resource 1 first */
    pthread_mutex_lock(&resource1);
    printf("Thread 2 locked Resource 1\n");

    pthread_mutex_lock(&resource2);
    printf("Thread 2 locked Resource 2\n");

    printf("Thread 2 completed\n");

    pthread_mutex_unlock(&resource2);
    pthread_mutex_unlock(&resource1);

    return NULL;
}

int main()
{
    pthread_t t1, t2;

    pthread_create(&t1, NULL, thread1, NULL);
    pthread_create(&t2, NULL, thread2, NULL);

    pthread_join(t1, NULL);
    pthread_join(t2, NULL);

    pthread_mutex_destroy(&resource1);
    pthread_mutex_destroy(&resource2);

    return 0;
}
```

```
bhargav08@Bhargava:~/OS$ nano practical12C.c
bhargav08@Bhargava:~/OS$ gcc practical12C.c -o practical12C
bhargav08@Bhargava:~/OS$ ./practical12C
Thread 1 locked Resource 1
Thread 1 locked Resource 2
Thread 1 completed
Thread 2 locked Resource 1
Thread 2 locked Resource 2
Thread 2 completed
```