


MOT

Trapping single atom



- D lines ≈ 589 nm
- D2 line (Cooling, Imaging)
- D1 line (Pumping, Cooling)
- Off resonance (Raman transition)

- D lines ≈ 589 nm
- D2 line (Cooling, Imaging)
- D1 line (Pumping, Cooling)
- Off resonance (Raman transition)

- D lines ≈ 589 nm
- D2 line (Cooling, Imaging)
- D1 line (Pumping, Cooling)
- Off resonance (Raman transition)

- D lines ≈ 589 nm
- D2 line (Cooling, Imaging)
- D1 line (Pumping, Cooling)
- Off resonance (Raman transition)

Sodium wavelengths


- D lines ≈ 589 nm
- D2 line (Cooling, Imaging)
- D1 line (Pumping, Cooling)
- Off resonance (Raman transition)

Using diode laser

- Diode laser spectrum
- Power requirement for frequency doubling
- Diode laser from Innolume / TimeBase
- Waveguide doubler

Sodium wavelengths

- D lines ≈ 589 nm
- D2 line (Cooling, Imaging)
- D1 line (Pumping, Cooling)
- Off resonance (Raman transition)




Using diode laser

- Diode laser spectrum
- Power requirement for frequency doubling
- Diode laser from Innolume / TimeBase
- Waveguide doubler

Sodium wavelengths

- D lines ≈ 589 nm
- D2 line (Cooling, Imaging)
- D1 line (Pumping, Cooling)
- Off resonance (Raman transition)




Using doubled diode laser

- Diode laser spectrum
- Power requirement for frequency doubling
- Diode laser from Innolume / TimeBase
- Waveguide doubler

Sodium wavelengths

- D lines ≈ 589 nm
- D2 line (Cooling, Imaging)
- D1 line (Pumping, Cooling)
- Off resonance (Raman transition)




Using doubled diode laser

- Diode laser spectrum
- Power requirement for frequency doubling
- Diode laser from Innolume / TimeBase
- Waveguide doubler

Sodium wavelengths

- D lines ≈ 589 nm
- D2 line (Cooling, Imaging)
- D1 line (Pumping, Cooling)
- Off resonance (Raman transition)




Using doubled diode laser

- Diode laser spectrum
- Power requirement for frequency doubling
- Diode laser from Innolume / TimeBase
- Waveguide doubler

Sodium wavelengths

- D lines ≈ 589 nm
- D2 line (Cooling, Imaging)
- D1 line (Pumping, Cooling)
- Off resonance (Raman transition)




Using doubled diode laser

- Diode laser spectrum
- Power requirement for frequency doubling
- Diode laser from Innolume / TimeBase
 Tunable from ...nm to ...nm
- Waveguide doubler

Sodium wavelengths

- D lines ≈ 589 nm
- D2 line (Cooling, Imaging)
- D1 line (Pumping, Cooling)
- Off resonance (Raman transition)




Using doubled diode laser

- Diode laser spectrum
- Power requirement for frequency doubling
- Diode laser from Innolume / TimeBase
 Tunable from ...nm to ...nm
- Waveguide doubler

Sodium wavelengths

- D lines ≈ 589 nm
- D2 line (Cooling, Imaging)
- D1 line (Pumping, Cooling)
- Off resonance (Raman transition)



Using doubled diode laser

 $589 \times 2 = 1178$ nm

- Diode laser spectrum
- Power requirement for frequency doubling
- Diode laser from Innolume / TimeBase
 Tunable from ...nm to ...nm
- Waveguide doubler

3/5

MOT stability

- Interference and stability issue with a small MOT
- Modulating the MOT beams

MOT stability

- Interference and stability issue with a small MOT
- Modulating the MOT beams

Members