



Apparatus for making dipolar NaCs molecules




Yichao Yu
May 3, 2015
Harvard/Ni Group

Apparatus for making dipolar NaCs molecules




Yichao Yu
May 3, 2015
Harvard/Ni Group

Apparatus for making dipolar NaCs molecules



Yichao Yu
May 3, 2015
Harvard/Ni Group

Apparatus for making dipolar NaCs molecules



Yichao Yu
May 3, 2015
Harvard/Ni Group

Current state



Current state


MOT



Current state

MOT

Trapping
single
atom





Current state

MOT

Trapping
single
atom

Single
atom
cooling





Current state

MOT

Trapping
single
atom

Single
atom
cooling



Laser system for Sodium

Sodium wavelengths

- D lines $\approx 589\text{nm}$
- D2 line (Cooling, Imaging)
- D1 line (Pumping, Cooling)
- Off resonance (Raman transition)

Laser system for Sodium

Sodium wavelengths

- D lines $\approx 589\text{nm}$
- D2 line (Cooling, Imaging)
- D1 line (Pumping, Cooling)
- Off resonance (Raman transition)

Laser system for Sodium

Sodium wavelengths

- D lines $\approx 589\text{nm}$
- D2 line (Cooling, Imaging)
- D1 line (Pumping, Cooling)
- Off resonance (Raman transition)

Laser system for Sodium

Sodium wavelengths

- D lines $\approx 589\text{nm}$
- D2 line (Cooling, Imaging)
- D1 line (Pumping, Cooling)
- Off resonance (Raman transition)

Laser system for Sodium

Sodium wavelengths

- D lines $\approx 589\text{nm}$
- D2 line (Cooling, Imaging)
- D1 line (Pumping, Cooling)
- Off resonance (Raman transition)


Using diode laser

- Diode laser spectrum
- Power requirement for frequency doubling
- Diode laser from Innolume / TimeBase
- Waveguide doubler

Laser system for Sodium

Sodium wavelengths

- D lines $\approx 589\text{nm}$
- D2 line (Cooling, Imaging)
- D1 line (Pumping, Cooling)
- Off resonance (Raman transition)




Using diode laser

- Diode laser spectrum
- Power requirement for frequency doubling
- Diode laser from Innolume / TimeBase
- Waveguide doubler

Laser system for Sodium

Sodium wavelengths

- D lines $\approx 589\text{nm}$
- D2 line (Cooling, Imaging)
- D1 line (Pumping, Cooling)
- Off resonance (Raman transition)



Using doubled diode laser


$$589 \times 2 = 1178\text{nm}$$

- Diode laser spectrum
- Power requirement for frequency doubling
- Diode laser from Innolume / TimeBase
- Waveguide doubler

Laser system for Sodium

Sodium wavelengths

- D lines $\approx 589\text{nm}$
- D2 line (Cooling, Imaging)
- D1 line (Pumping, Cooling)
- Off resonance (Raman transition)



Using doubled diode laser


$$589 \times 2 = 1178\text{nm}$$

- Diode laser spectrum
- Power requirement for frequency doubling
- Diode laser from Innolume / TimeBase
- Waveguide doubler

Laser system for Sodium

Sodium wavelengths

- D lines $\approx 589\text{nm}$
- D2 line (Cooling, Imaging)
- D1 line (Pumping, Cooling)
- Off resonance (Raman transition)



Using doubled diode laser


$$589 \times 2 = 1178\text{nm}$$

- Diode laser spectrum
- Power requirement for frequency doubling
- Diode laser from Innolume / TimeBase
- Waveguide doubler

Laser system for Sodium

Sodium wavelengths

- D lines $\approx 589\text{nm}$
- D2 line (Cooling, Imaging)
- D1 line (Pumping, Cooling)
- Off resonance (Raman transition)



Using doubled diode laser


$$589 \times 2 = 1178\text{nm}$$

- Diode laser spectrum
- Power requirement for frequency doubling
- Diode laser from Innolume / TimeBase
Tunable from ...nm to ...nm
- Waveguide doubler

Laser system for Sodium

Sodium wavelengths

- D lines $\approx 589\text{nm}$
- D2 line (Cooling, Imaging)
- D1 line (Pumping, Cooling)
- Off resonance (Raman transition)



Using doubled diode laser


$$589 \times 2 = 1178\text{nm}$$

- Diode laser spectrum
- Power requirement for frequency doubling
- Diode laser from Innolume / TimeBase
Tunable from ...nm to ...nm
- Waveguide doubler

Laser system for Sodium

Sodium wavelengths

- D lines $\approx 589\text{nm}$
- D2 line (Cooling, Imaging)
- D1 line (Pumping, Cooling)
- Off resonance (Raman transition)



Using doubled diode laser

$$589 \times 2 = 1178\text{nm}$$

- Diode laser spectrum
- Power requirement for frequency doubling
- Diode laser from Innolume / TimeBase
Tunable from ...nm to ...nm
- Waveguide doubler

MOT stability

- Interference and stability issue with a small MOT
- Modulating the MOT beams

MOT stability

- Interference and stability issue with a small MOT
- Modulating the MOT beams

Members