1 Simplifies Optical Bloch Equation for Sideband Cooling Simulation.

Rabi frequency between state m and n (assume to be real since the phase is not important for sidband cooling.): Ω_{mn}

Pumping rate from state n to m: Γ_{mn}

Diagonal terms,

$$\frac{\mathrm{d}\rho_{mm}}{\mathrm{d}t} = -\rho_{mm} \sum_{k} \Gamma_{km} + \sum_{k} \rho_{kk} \Gamma_{mk} + \mathrm{i} \sum_{k} \left(\rho_{mk} \Omega_{km} - \Omega_{mk} \rho_{km}\right)$$

Off-diagnal terms,

$$\frac{\mathrm{d}\rho_{mn}}{\mathrm{d}t} = -\frac{\rho_{mn}}{2} \sum_{k} (\Gamma_{km} + \Gamma_{kn}) + \mathrm{i} \sum_{k} (\rho_{mk} \Omega_{kn} - \Omega_{mk} \rho_{kn})$$

When only one sideband is driven,

$$\Omega_{mn} = \Omega_m \delta_{m,n-\Delta} + \Omega_n \delta_{n,m-\Delta}$$

where Delta include both the change in vibrational level and internal level.

Define $p_n = \rho_{nn}$, the equations becomes,

$$\frac{\mathrm{d}p_m}{\mathrm{d}t} = \sum_k \left(p_k \Gamma_{mk} - p_m \Gamma_{km} \right) + \mathrm{i}(\rho_{m,m-\Delta} \Omega_{m-\Delta} - \Omega_m \rho_{m+\Delta,m} + \rho_{m,m+\Delta} \Omega_m - \Omega_{m-\Delta} \rho_{m-\Delta,m})$$

$$\frac{\mathrm{d}\rho_{m,m+\Delta}}{\mathrm{d}t} = -\frac{\rho_{m,m+\Delta}}{2} \sum_k \left(\Gamma_{km} + \Gamma_{k,m+\Delta} \right) + \mathrm{i}\Omega_m (p_m - p_{m+\Delta})$$

 ρ_{mn} 's with $|m-n| \neq 0, \Delta$ are ignored since they are 0. In particular, since Δ includes change of internal levels, elements with $|m-n| \geq 2\Delta$ does not exist.

Define $q_n = i\rho_{n,n+\Delta}$,

$$\rho_{n,n+\Delta} = -iq_n$$

$$\rho_{n+\Delta,n} = iq_n^*$$

$$\frac{\mathrm{d}p_m}{\mathrm{d}t} = \sum_k \left(p_k \Gamma_{mk} - p_m \Gamma_{km} \right) + \mathrm{i} \left(\mathrm{i} q_{m-\Delta}^* \Omega_{m-\Delta} - \mathrm{i} \Omega_m q_m^* - \mathrm{i} q_m \Omega_m + \mathrm{i} \Omega_{m-\Delta} q_{m-\Delta} \right)$$

$$-\mathrm{i} \frac{\mathrm{d}q_m}{\mathrm{d}t} = \mathrm{i} \frac{q_m}{2} \sum_k \left(\Gamma_{km} + \Gamma_{k,m+\Delta} \right) + \mathrm{i} \Omega_m (p_m - p_{m+\Delta})$$

$$\frac{\mathrm{d}p_m}{\mathrm{d}t} = \sum_k \left(p_k \Gamma_{mk} - p_m \Gamma_{km} \right) + \Omega_m (q_m^* + q_m) - \Omega_{m-\Delta} \left(q_{m-\Delta}^* + q_{m-\Delta} \right)$$

$$\frac{\mathrm{d}q_m}{\mathrm{d}t} = -\frac{q_m}{2} \sum_k \left(\Gamma_{km} + \Gamma_{k,m+\Delta} \right) + \Omega_m (p_{m+\Delta} - p_m)$$

For a process starting with $q_m = 0$, q_m will always remain real.

$$\frac{\mathrm{d}p_m}{\mathrm{d}t} = \sum_k p_k \Gamma_{mk} - p_m \Gamma_m + 2\Omega_m q_m - 2\Omega_{m-\Delta} q_{m-\Delta}$$

$$\frac{\mathrm{d}q_m}{\mathrm{d}t} = -\frac{q_m}{2} (\Gamma_m + \Gamma_{m+\Delta}) + \Omega_m (p_{m+\Delta} - p_m)$$

where $\Gamma_m \equiv \sum_k \Gamma_{km}$ is the decay rate of state m.

After writing the two internal states (a and b) explicitly and adding a third state (c) to take into account m_F pumping,

$$\begin{split} \frac{\mathrm{d}p_m^a}{\mathrm{d}t} &= \sum_{\alpha = a,b,c;k} p_k^\alpha \Gamma_{mk}^{a\alpha} - p_m^a \Gamma_m^a + 2\Omega_m q_m \\ \frac{\mathrm{d}p_m^b}{\mathrm{d}t} &= \sum_{\alpha = a,b,c;k} p_k^\alpha \Gamma_{mk}^{b\alpha} - p_m^b \Gamma_m^b - 2\Omega_{m-\delta} q_{m-\delta} \\ \frac{\mathrm{d}p_m^c}{\mathrm{d}t} &= \sum_{\alpha = a,b,c;k} p_k^\alpha \Gamma_{mk}^{c\alpha} - p_m^c \Gamma_m^c \\ \frac{\mathrm{d}q_m}{\mathrm{d}t} &= -\frac{q_m}{2} \left(\Gamma_m^a + \Gamma_{m+\delta}^b \right) + \Omega_m \left(p_{m+\delta}^b - p_m^a \right) \end{split}$$

For sodium, states a, b and c corresponds to $|F=1, m_F=1\rangle$, $|F=2, m_F=2\rangle$ and $|F=2, m_F=1\rangle$.

When the trapping frequency is much smaller than the line width, Γ_m^{α} is independent with m and is proportional to the corresponding pumping power. $\Gamma_{mn}^{\alpha\beta}$ can be written as,

$$\begin{split} \Gamma_{mn}^{\alpha\beta} = & \Gamma^{\alpha\beta}\gamma_{mn} \\ = & \begin{pmatrix} \Gamma^{aa} & \Gamma^{ab} & \Gamma^{ac} \\ \Gamma^{ba} & \Gamma^{bb} & \Gamma^{bc} \\ \Gamma^{ca} & \Gamma^{cb} & \Gamma^{cc} \end{pmatrix} \gamma_{mn} \\ = & \begin{pmatrix} \Gamma^{a}B^{aa} & \Gamma^{b}B^{ab} & \Gamma^{c}B^{ac} \\ \Gamma^{a}B^{ba} & \Gamma^{b}B^{bb} & \Gamma^{c}B^{bc} \\ \Gamma^{a}B^{ca} & \Gamma^{b}B^{cb} & \Gamma^{c}B^{cc} \end{pmatrix} \gamma_{mn} \\ = & \begin{pmatrix} \Gamma_{1}B^{aa} & \varepsilon\Gamma_{2}B^{ab} & \Gamma_{2}B^{ac} \\ \Gamma_{1}B^{ba} & \varepsilon\Gamma_{2}B^{bb} & \Gamma_{2}B^{bc} \\ \Gamma_{1}B^{ca} & \varepsilon\Gamma_{2}B^{cb} & \Gamma_{2}B^{cc} \end{pmatrix} \gamma_{mn} \end{split}$$

where $B^{\alpha\beta}$ is the branching ratio, Γ_1 is the F pumping power $((1,1) \to (2,2)'$ light), Γ_2 is the m_F pumping power $((2,1) \to (2,2)'$ light) and ε is the off-resonance coupling of the m_F pumping light to the $(2,2) \to (2,3)'$ transition.