# Parallel balanced minimum evolution search in Phylo2Vec coordinates

**Abstract**

Balanced minimum evolution (BME) provides a distance-based criterion for phylogenetic inference, but searching large tree spaces requires repeated evaluation of many candidate rearrangements. We develop a shared evaluator that computes all valid single-coordinate BME changes for an $N$-leaf tree in an ordered Phylo2Vec representation in $O(N^2)$ work and supports parallel GPU execution. For larger trees, we optimize the connections between fixed components on a smaller skeleton tree. Balanced averages of the original distances make the skeleton objective equal to the full-tree objective up to a constant. Every skeleton change therefore gives the corresponding full-tree BME change, with an $O(K^2)$ coordinate sweep once the distances between its $K$ components are available. Independent CPU checks agree with direct BME differences to maximum absolute discrepancies of $3.553 \times 10^{-14}$ for coordinate evaluation and $1.564 \times 10^{-13}$ for condensation. In 120 small-tree comparisons, the CPU optimizer matches or improves the reference BME score in 119 cases. A full coordinate sweep at $N = 40{,}000$ takes 158.36 ms on eight H100 GPUs. The reduction preserves the specified BME objective. Numerical evaluation uses floating-point arithmetic, and topology search remains heuristic.

## 1 Introduction

Distance-based phylogenetic inference first estimates pairwise evolutionary distances and then searches for a tree that explains them. Balanced minimum evolution (BME) scores a topology using a weighted sum of those distances, with weights determined by the branching structure along each leaf-to-leaf path [1, 2, 3]. The computational challenge is to evaluate many possible rearrangements repeatedly as the tree changes. Classical subtree-prune-and-regraft (SPR) recurrences already permit quadratic-time neighborhood sweeps [4, 5]. At large scales, their practical cost depends on how calculations are shared, how distance tables are stored, and how work is distributed across processors.

For a tree with $N$ leaves, we organize BME search around a table of coordinate changes in the Phylo2Vec representation. Each entry gives the change in the objective when one integer in the tree's encoding is replaced. The table is evaluated through shared subtree-distance calculations, exposing independent work for parallel execution. Relabeling the current tree changes which rearrangements are represented by single-coordinate updates while preserving the tree and its objective.

The same evaluator operates on a smaller tree when some internal structure is held fixed. We replace each fixed component by one skeleton leaf and retain its contribution through an exact balanced average of the original distances. The full objective then equals the skeleton objective plus a constant that depends only on the fixed components. Consequently, every change evaluated on the skeleton has the same BME change in the full tree. We call this block of component connections a *minibatch*: it restricts the structures being optimized while retaining all leaves in the objective calculation.

We develop three algorithmic contributions:

1. **Shared coordinate evaluation.** All $(N-1)^2$ valid entries are computed in $O(N^2)$ work, matching the size of the explicit table. A map from coordinate values to regraft edges avoids separately scoring candidate trees.

2. **BME preservation in blocks.** The same computation applies to a $K$-component skeleton in $O(K^2)$ work after its balanced distances are available. The reduction includes the entire complement of a subtree window and specifies the updates required between windows.

3. **Parallel execution.** Independent distance columns and SPR rows support GPU distribution and selection of the best update in each row. Reconstructing rows when needed reduces the balanced-distance table from approximately $4N^2$ to $N^2$ entries while retaining quadratic sweep work.

The contribution builds on established representation and BME results. Phylo2Vec introduced coordinate differences and ordered relabeling [6, Section 1.3.2], and its ordered coordinate neighborhood is a subset of the SPR neighborhood. Our evaluator retains the quadratic sweep complexity of classical BME SPR calculations. Balanced subtree averages [2, 3] and the fixed-clade reduction of the BME polytope [10, Section 2.4] provide the basis for exact skeleton evaluation. We state the objective identity and prove the conditions needed by the block algorithm.

GradME uses a cubic-time recurrence and automatic differentiation to optimize an expected BME objective over ordered coordinates [7]. Here evaluation is specialized to a discrete tree, including its full coordinate range. Appendix B.4 gives the connection to GradME's vertex derivatives. Parallel taxon-addition BME [8] and learned SPR selection [9] address tree construction and search policy, respectively. Our experiments assess coordinate accuracy, CPU optimization, and GPU sweep throughput.

# 2 Methods

## 2.1 Overview

The method takes a tree and a fixed matrix of distances between its leaves. A full-tree sweep computes the objective change for every valid coordinate replacement of the current encoding. A minibatch sweep applies the same evaluator to a skeleton of fixed components (Figure 1). After selecting and accepting a skeleton update, the components are expanded back into the full tree before the next block is constructed. The full-tree case is recovered by taking every component to be a single leaf. Algorithms 1 and 2 specify the complete optimisation procedure in Section 2.6.


The minibatch reduction preserves full-tree BME score differences in real arithmetic. The distances may be estimates, numerical evaluation uses floating-point arithmetic, and topology search is heuristic.

## 2.2 BME and Phylo2Vec coordinates

Let $T$ be an unrooted binary tree on $N \geq 3$ labeled leaves, and let $D$ be a fixed, finite, symmetric matrix with zero diagonal. Write $q_T(x, y)$ for the number of internal degree-three vertices on the path from $x$ to $y$. The BME objective is

$$L(T; D) = \sum_{0 \leq x < y < N} D_{xy}\, 2^{-q_T(x,y)}. \tag{1}$$

If the path has $e_T(x, y)$ edges, then $q_T(x, y) = e_T(x, y) - 1$. Thus the unordered-pair coefficient is $2^{1-e_T(x,y)}$. An artificial degree-two root used to encode the tree is suppressed before evaluating these path lengths. No additivity assumption on $D$ is needed for the identities below.




**Balanced component distances** $\widetilde{D}_{ab} = \sum_{x \in S_a} \sum_{y \in S_b} \omega_a(x)\omega_b(y) D_{xy} \quad (a \neq b)$

**Identical objective changes** $L(T'; D) - L(T; D) = L(G'; \widetilde{D}) - L(G; \widetilde{D})$

Figure 1: Block evaluation preserving BME, illustrated with $K = 4$ fixed components. **(a)** Triangles represent components $S_a$ of the full tree, each attached at its apex. **(b)** Each component becomes one skeleton leaf. The condensed distance $\widetilde{D}_{ab}$ retains all leaf pairs between $S_a$ and $S_b$, with balanced weights $\omega$ obtained by halving mass at each binary split. **(c)** Search changes the connections between components while reusing $\widetilde{D}$. **(d)** Expanding the candidate preserves each component's internal topology and attachment root. Within-component contributions cancel, so the skeleton and full-tree objective changes agree. A proper subtree window includes its entire complement as an additional component.

The Phylo2Vec domain for rooted binary trees is

$$\mathcal{V}_N = \{(v_0, \ldots, v_{N-2}) : 0 \leq v_i \leq 2i\}, \qquad |\mathcal{V}_N| = (2N-3)!!. \tag{2}$$

We use the ordered, or cherry-first, subset $\mathcal{V}_N^{\text{cf}} = \{v : 0 \leq v_i \leq i\}$ as the baseline for coordinate evaluation. Every rooted binary tree can be represented in this subset after a suitable leaf permutation. The relabeling construction and its proof are given in Appendix B. If $\pi(a)$ is the original leaf represented by current index $a$, the distance matrix in these coordinates is $D_\pi[a, b] = D[\pi(a), \pi(b)]$. Permuting both axes in this way preserves the objective. Constructing the permutation takes $O(N)$ time from a decoded tree, while explicitly copying a dense permuted matrix takes $O(N^2)$ time.

Write $T(v)$ for the unrooted tree obtained by decoding $v$ and suppressing its artificial root. For an ordered baseline $v$, define the discrete coordinate difference

$$\Delta_{i,j} = L(T(v^{(i \leftarrow j)}); D_\pi) - L(T(v); D_\pi), \qquad 0 \leq j \leq 2i. \tag{3}$$

Here $v^{(i \leftarrow j)}$ replaces only entry $i$ by $j$. Row $i$ of the table therefore enumerates the allowed replacements of one coordinate, and $\Delta_{i,j} < 0$ identifies an improving move. We use *discrete gradient* as a synonym for this table of finite objective differences, and *coordinate sweep* for one evaluation of the table at a fixed tree. There are $(N-1)^2$ valid coordinate entries, including unchanged coordinates and entries that can represent the same unrooted topology. This count is not a count of distinct SPR neighbors. General candidate values $j > i$ are allowed even though the baseline is ordered. After accepting such a move, the resulting tree is decoded and relabeled before the next ordered evaluation. Relabeling changes computational indices and permutes both axes of $D$ together, so the observations remain attached to their original leaves.

## 2.3 Quadratic-time coordinate evaluation

For two distinct vertices $u, w$, define $A(u, w)$ as the balanced average distance between the two components oriented away from the path joining $u$ and $w$. At an internal vertex, the two outward

branches each receive weight 1/2. At a leaf, the corresponding distribution is concentrated on that leaf. Consequently, when the component at $u$ has children $a, b$,

$$A(u, w) = \tfrac{1}{2}\{A(a, w) + A(b, w)\}. \tag{4}$$

The direction is important when one vertex is an ancestor of the other in a computational rooting. In that case, the component away from $w$ combines the sibling branch and the parent branch:

$$A(u, w) = \tfrac{1}{2}\{A(\mathrm{sib}_u(w), w) + A(\mathrm{parent}(u), w)\}. \tag{5}$$

At the degree-three computational root, the analogous average uses the two branches not containing $w$. Bottom-up and top-down passes construct the required table in $O(N^2)$ arithmetic operations.

For a fixed pruned component, the standard BME SPR recurrence propagates score differences across regraft edges in $O(N)$ time [4]. Each propagation step is an adjacent interchange of four directed components. Its score change is a linear combination of their balanced distances, with coefficient 1/4. Successive steps accumulate the change relative to the original attachment. Phylo2Vec supplies the mapping from each valid coordinate value to one of these regraft edges. The explicit mapping, including the collapsed-root boundary, is in Appendix B.3.

**Proposition 2.1** (Cost and scope of a coordinate sweep)**.** *Given an ordered baseline and its leaf permutation, all entries in Equation (3) can be computed in $O(N^2)$ time. In exact arithmetic, these entries equal the corresponding full-tree BME differences.*

*Proof.* The balanced-distance table costs $O(N^2)$. For each of $O(N)$ coordinates, pruning its associated component and traversing the two remaining half-trees visits $O(N)$ edges. The SPR recurrence evaluates the score at each edge, and the coordinate mapping selects the appropriate values without evaluating the candidate trees independently. The mapping costs at most $O(N)$ per row. The recurrence preserves the Pauplin score difference at each traversal step, so selecting a mapped edge gives Equation (3). □

The proposition concerns the coordinate neighborhood of the current labeling. It does not assert that this neighborhood is the entire SPR neighborhood, or that coordinate descent finds a global BME optimum. There are $\sum_{i=0}^{N-2}(2i+1) = (N-1)^2$ valid entries. Any algorithm that explicitly writes one scalar per entry requires $\Omega(N^2)$ work in the standard unit-cost model, so the evaluator matches this output-size lower bound. This observation does not give a lower bound for returning only the best move, and does not improve the asymptotic sweep cost of classical BME SPR evaluation.

## 2.4 Condensed distances and BME preservation

Partition all $N$ leaves into $K \geq 3$ fixed components $S_1, \ldots, S_K$. Each component has a fixed internal binary topology and a single attachment to the rest of the tree. A component can consist of one leaf. For a non-singleton component, let $r_a$ be the internal vertex adjacent to its attachment edge, and let $h_a(x)$ count the branching vertices from $r_a$ to leaf $x$, including $r_a$. For a singleton, set $h_a(x) = 0$. Define its balanced leaf weights by

$$\omega_a(x) = 2^{-h_a(x)}, \qquad x \in S_a. \tag{6}$$

The weights sum to one within each component (Lemma A.1 in Appendix A).

Let $G$ be an unrooted binary skeleton with one leaf for each component. Construct $T_G$ by replacing skeleton leaf $a$ with $S_a$, retaining the attachment edge. Define a condensed distance matrix by

$$\widetilde{D}_{ab} = \sum_{x \in S_a} \sum_{y \in S_b} \omega_a(x)\omega_b(y) D_{xy} \quad (a \neq b), \qquad \widetilde{D}_{aa} = 0. \tag{7}$$

These are exact balanced averages of the original pairwise distances. They can be formed by the weighted sum above or, equivalently, by recursively averaging over the two children of each component root. All leaf contributions are retained. This is an objective-level form of the fixed-clade reduction discussed by Haws et al. [10, Section 2.4]. We include the proof to specify the weights and the scope of exactness needed by the algorithm.

**Theorem 2.2** (BME decomposition over fixed components)**.** *There is a constant $C$, independent of the skeleton topology, such that*

$$L(T_G; D) = C + L(G; \widetilde{D}). \tag{8}$$

*Consequently, for any two skeletons $G$ and $G'$,*

$$L(T_{G'}; D) - L(T_G; D) = L(G'; \widetilde{D}) - L(G; \widetilde{D}). \tag{9}$$

The proof in Appendix A separates the fixed within-component terms from the between-component terms, whose weights factor through the skeleton.

The constant $C$ contains the contributions of pairs within the same fixed component. It cancels when comparing skeletons, so the reduction preserves every objective change even though the skeleton's absolute score omits $C$. The result applies to every reconnection that preserves the components and to arbitrary fixed dissimilarities, including non-additive estimated distances.

**Corollary 2.3** (Exact minibatch coordinate differences)**.** *Let $v$ encode an ordered skeleton $G$, keep the attached components fixed, and index $\widetilde{D}$ by the same leaf labeling. Evaluating a coordinate replacement $v_i \leftarrow j$ using the exact matrix $\widetilde{D}$ gives*

$$\Delta^{\mathrm{skel}}_{i,j} = L(T_{G(v^{(i\leftarrow j)})}; D) - L(T_{G(v)}; D). \tag{10}$$

*Once $\widetilde{D}$ is available, all valid skeleton coordinate differences can be evaluated in $O(K^2)$ time.*

*Proof.* Apply Proposition 2.1 to the $K$-leaf skeleton with input $\widetilde{D}$. Equation (9) identifies each resulting skeleton difference with the corresponding full-tree difference. □

**Corollary 2.4** (A proper subtree window)**.** *For a window attached to the rest of a binary tree by one edge, treat its entire complement as an additional component oriented away from that edge. If its internal topology and exact balanced distances to the other components are retained, Equation (9) applies to rearrangements of the window skeleton.*

*Proof.* Cutting the attachment edge produces two components. The endpoint in the complement has two outward branches unless the complement is a singleton. It therefore defines precisely a binary component of the type used in the theorem. Including it completes the partition of all leaves, so both within-window and window-to-complement contributions are included. □

The outside component retains distances between leaves inside and outside the window. Deleting the complement would change the objective being optimized. The weights entering the outside distances are determined by the current topology of the complement and its attachment edge. They must be updated when a preceding rearrangement changes that topology.

### 2.5 Minibatch evaluation and sequential updates

With the fixed components and exact condensed matrix in place, candidate skeletons are evaluated against the full-tree objective through Corollary 2.3. The same matrix can be reused throughout a skeleton search because its component topologies and attachment roots remain fixed. For a candidate $G'$, let $\mathcal{P}(G, G') = \{(a, b) : a < b,\ q_G(a, b) \neq q_{G'}(a, b)\}$. Its full-tree BME change can also be computed directly from the changed pairs:

$$\delta = \sum_{(a,b)\in\mathcal{P}(G,G')} \left(2^{-q_{G'}(a,b)} - 2^{-q_G(a,b)}\right) \widetilde{D}_{ab}. \tag{11}$$

Unchanged pairs contribute zero, and the within-component constant cancels. Theorem 2.2 therefore identifies $\delta$ with the full-tree BME change. Thus both coordinate selection and the evaluation of a combined candidate can use the same exact condensed distances.

Windows are committed sequentially. After a commit, affected ancestor summaries are updated and the next window's outside distances are constructed from the current tree. Node-disjoint windows need not have additive BME changes because both updates can alter the coefficients of distances between their leaves. For consecutive accepted trees $T^{(0)}, \dots, T^{(M)}$, exact arithmetic gives

$$L(T^{(M)}; D) - L(T^{(0)}; D) = \sum_{m=1}^{M} \left[ L(T^{(m)}; D) - L(T^{(m-1)}; D) \right]. \tag{12}$$

If each increment is negative, so is the cumulative increment. This argument requires that each acceptance calculation uses the current tree, rather than a shared pre-update tree.

On sufficiently deep trees, finite-precision leaf weights can also underflow.

### 2.6 Optimisation algorithm

Algorithm 1 separates block construction from candidate search. Its inputs are a starting tree $T_0$, fixed distances $D$, a schedule $\mathcal{W}$, and a skeleton solver $\mathcal{A}$. Skeleton returns a partition $\mathcal{S}$ of all leaves into fixed rooted components and their current skeleton $G$. For a proper subtree window, $\mathcal{S}$ includes the entire oriented complement. Condense evaluates Equation (7) without truncation, and Expand restores the same components with their original leaf identities. The components and their attachment roots remain fixed during each solver call. Full-tree search is the special case of one block containing $N$ singleton components.

**Algorithm 1** Full-tree and minibatch BME search

**Input:** $T_0$, $D$, schedule $\mathcal{W}$, solver $\mathcal{A}$, block and sweep budgets $B, I$, margin $\varepsilon \geq 0$.
**Output:** tree $T$ and accumulated score change $s$.

$T \leftarrow T_0$; $s \leftarrow 0$
**for** $b = 0, \dots, B-1$ **do**
  $w \leftarrow \mathcal{W}(T, b)$; **if** $w = \perp$ **then break**
  $(G, \mathcal{S}) \leftarrow \mathsf{Skeleton}(T, w)$
  $M \leftarrow \mathsf{Condense}(\mathcal{S}, D)$
  $G' \leftarrow \mathcal{A}(G, M; I)$
  $\delta \leftarrow L(G'; M) - L(G; M)$
  **if** $\delta < -\varepsilon$ **then**
    $T \leftarrow \mathsf{Expand}(G', \mathcal{S})$; $s \leftarrow s + \delta$
    $\mathsf{Refresh}(T)$
**return** $(T, s)$

Each block is constructed from the current tree. Refresh updates affected ancestor summaries, and outside distances are rebuilt before the next window. The acceptance test evaluates the joint candidate, including interactions between its coordinate updates. By Theorem 2.2, every committed change decreases the full-tree objective in real arithmetic. A schedule may expose overlapping local windows and larger backbone connections. Its construction and implementation parameters are specified in Appendix F.1.

Algorithm 2 gives the CPU skeleton solver. The persistent state $(v, \pi)$ contains the encoding and its map to original component identities, with $M_\pi[a, b] = M[\pi(a), \pi(b)]$. Normalise leaves an ordered encoding unchanged and otherwise relabels it, composing the permutation. Sweep returns the current score and coordinate differences. RankMin sorts the improving row minima. BatchStep tests compatible batches by their joint score, halves a rejected batch, and falls back to the best single move. Best selects the lower-scoring tree, retaining its first argument on a tie.

Here $\perp$ denotes failure to find a candidate, and $r$ records whether the reversed ordered labeling has been tried since the last topology change. ExtraSPR checks additional regrafts for

**Algorithm 2** CPU skeleton search

**Input:** $G_0$, component matrix $M$, sweep and escape budgets $I, E$, margin rule $\epsilon(\ell)$.
**Output:** best scored skeleton in its original component labeling.

$(v, \pi) \leftarrow \mathsf{Order}(G_0)$; $G_\star \leftarrow G_0$; $r \leftarrow 0$; $e \leftarrow 0$
**for** $t = 1, \ldots, I$ **do**
  $(v, \pi) \leftarrow \mathsf{Normalise}(v, \pi)$
  $(\ell, \Delta) \leftarrow \mathsf{Sweep}(v, M_\pi)$; $\eta \leftarrow \epsilon(\ell)$
  $G_\star \leftarrow \mathsf{Best}(G_\star, \mathsf{Decode}(v, \pi); M)$
  $R \leftarrow \mathsf{RankMin}(\Delta, -\eta)$
  **if** $R \neq \varnothing$ **then**
    $v \leftarrow \mathsf{BatchStep}(v, M_\pi, R, \eta)$; $r \leftarrow 0$; **continue**
  $u \leftarrow \mathsf{ExtraSPR}(v, M_\pi, \eta)$
  **if** $u = \perp$ **and** $r = 0$ **then**
    $(v, \pi) \leftarrow \mathsf{Reverse}(v, \pi)$; $r \leftarrow 1$; **continue**
  **if** $u = \perp$ **then** $u \leftarrow \mathsf{RemainingSPR}(v, M_\pi, \eta)$
  **if** $u = \perp$ **and** $e < E$ **and** $t < I$ **then**
    $e \leftarrow e + 1$; $u \leftarrow \mathsf{Escape}(v, \Delta, e, \eta)$
  **if** $u = \perp$ **then break**
  $v \leftarrow u$; $r \leftarrow 0$
**return** $\mathsf{Best}(G_\star, \mathsf{Decode}(v, \pi); M)$

the pruned components already scanned, while RemainingSPR completes the unrooted SPR scan, including complement-side prunes. Both require a change below $-\eta$. Reverse changes the ordered labeling and composes $\pi$ without changing the tree. Escape proposes a deterministic pair of uphill coordinate replacements, with the best scored tree retained across such trials. Appendix F.1 defines the batch and escape rules.

The GPU solver is an alternative $\mathcal{A}$: it packs row-minimum SPR proposals, rescores the trial trajectory, and retains its best skeleton without the CPU completion scan. The sequence variant's approximate proposal distances are described in Appendix D. The objective-preservation guarantee requires complete distances for acceptance and current outside information. A block or sweep budget limits the search, and only a completed unsuccessful SPR scan establishes SPR-local optimality up to the numerical margin. Neither solver guarantees a global BME optimum.

## 2.7 Parallel evaluation and computational cost

Equation (4) has an independent recurrence for each fixed column. Assigning columns to threads lets neighboring threads access consecutive entries while following the same traversal order. The top-down correction for column $w$ follows its ancestor path. Depth-first entry intervals determine the next child without a traversal stack. Its total work over columns is $O(\sum_w \mathrm{depth}(w))$, bounded by $O(N^2)$ and reduced to $O(N \log N)$ for trees of logarithmic height.

A full balanced-distance table stores approximately $4N^2$ entries. The column-tiled variant retains the internal-to-leaf block and reconstructs required internal rows on demand. This reduces that table to approximately $N^2$ entries, while the input matrix and other buffers still contribute to total memory. A row-wise reduction can return the best coordinate replacement in each row without storing the full coordinate table. Columns and SPR rows can also be distributed across GPUs. Appendix C gives the dependency and workspace arguments.

For a skeleton with $K$ leaves, a coordinate sweep costs $O(K^2)$ once its distances are available. This does not make arbitrary distance construction independent of $N$. Direct evaluation of one condensed pair can require $|S_a||S_b|$ original distances. Explicit leaf weights use $O(N)$ entries, and constructing exact condensed distances can dominate runtime for large component pairs. When $D_{xy} = \phi(x)^\top \psi(y)$ has a fixed-dimensional bilinear representation, weighted component embeddings give $\widetilde{D}_{ab} = (\sum_x \omega_a(x)\phi(x))^\top (\sum_y \omega_b(y)\psi(y))$. That shortcut is exact for the specified bilinear distance. It does not justify averaging embeddings before applying a nonlinear sequence-distance

correction.

# 3 Experimental design

The evaluation addresses three questions: whether computed changes agree with the BME objective, how the CPU optimizer behaves from a common starting tree, and how coordinate sweeps scale on GPUs. Table 1 identifies the computation measured by each experiment.

Table 1: Scope of the experiments. A coordinate sweep evaluates candidates at one fixed tree. Optimization includes successive accepted updates.

| Experiment | Computation | Evidence supplied |
|---|---|---|
| Objective checks | Coordinate and condensed changes against direct BME | Numerical agreement on independently evaluated cases |
| CPU optimization | Search from identical starting trees and distance matrices | Final objective, topology, and optimization time |
| GPU sweeps | Full-tree coordinate evaluation | Evaluation time and memory at a fixed tree |
| Embedding blocks | Exact bilinear condensation and skeleton sweeps | Cost of these two stages under a bilinear distance |
| Sequence variant (Appendix D) | Approximate proposals followed by full-objective acceptance | Refinement time for that proposal-and-check procedure |

The CPU comparison uses additive distances from trees whose branch lengths are uniform on $(0.05, 0.55)$ and a noisy variant $D'_{xy} = D_{xy}\exp(0.15Z_{xy})$, with symmetric standard-normal $Z_{xy}$. There are respectively 20, 20, 10, 5, and 5 replicates at $N = 20, 50, 100, 150, 200$ in each regime. The reference is our in-memory C implementation of the FastME BME-SPR algorithm. Agreement with the external FastME executable is assessed separately. A score tolerance of $10^{-9}$ defines wins, ties, and losses. Single-core timings are reported for Apple M5 and AMD Threadripper PRO 5995WX processors.

GPU evaluation uses NVIDIA RTX A6000 and H100 devices, with additional CPU/Metal measurements in the supplement. The GPU coordinate path uses FP32 working arrays in the reported comparisons, whereas independent score calculations use FP64. The embedding workload constructs condensed distances through the bilinear factorization in Section 2.7. The sequence variant instead uses approximate condensed distances for proposals and full-tree calculations for acceptance, as detailed in Appendix D. Its timings measure that procedure rather than exact condensed-distance construction for every proposal.

We assess topological error by counting inferred nontrivial splits absent from the reference tree. For binary trees on the same leaves, normalized Robinson–Foulds (RF) distance is this count divided by $N - 3$.

# 4 Results

## 4.1 Agreement with independent objective calculations

Table 2 compares coordinate and condensed changes with independent objective calculations. The largest discrepancy in the CPU coordinate tests is $3.553 \times 10^{-14}$, and the condensation tests agree to $1.564 \times 10^{-13}$. These are observed absolute errors on the tested cases, not universal error bounds. Rooted-vector round trips recover all 1,000 tested vectors at $N = 40$. Unrooted round trips preserve the split sets in a further 1,000 cases. Exhaustive rooted-tree enumeration at $N = 4, \ldots, 7$ checks 11,460 encodings.

Independent enumeration also identifies the scope of the coordinate neighborhood. On 30 random trees at each tested size from $N = 8$ to 20, a single ordered orientation covers

Table 2: Agreement with independent BME calculations. Errors are maximum absolute discrepancies over the stated tests.

| Calculation | Test scope | Maximum error |
|---|---|---|
| CPU coordinate differences | 36,000 changes, $N = 20$ | $3.553 \times 10^{-14}$ |
| Ordered-tree enumeration | 28,488 changes, $N = 4$–$7$ | $2.776 \times 10^{-15}$ |
| Relabeling, first orientation | 200 trees, $N = 25$ | $1.776 \times 10^{-14}$ |
| Relabeling, reversed orientation | Same 200 trees | $2.665 \times 10^{-14}$ |
| Condensed SPR differences | 16,231 changes, $N = 40$, $K = 16$ | $1.564 \times 10^{-13}$ |
| FP32 CUDA gradient | Reported sizes $N = 100$–$4{,}000$ | $1.11 \times 10^{-6}$ |

Table 3: Single-core optimization at $N = 200$. Times are mean ± standard deviation in milliseconds over five replicates.

| Processor | Distances | Reference | Phylo2Vec | Ratio |
|---|---|---|---|---|
| Apple M5 | Additive | $75.46 \pm 2.42$ | $18.14 \pm 0.74$ | 4.16 |
| Apple M5 | Noisy | $85.16 \pm 2.06$ | $24.67 \pm 2.79$ | 3.45 |
| AMD 5995WX | Additive | $160.64 \pm 5.51$ | $27.96 \pm 1.18$ | 5.74 |
| AMD 5995WX | Noisy | $181.97 \pm 4.30$ | $36.91 \pm 3.94$ | 4.93 |

approximately 27–33% of distinct SPR neighbors. Two orientations together cover approximately 52–56%. Neither constitutes an exhaustive SPR search. The full CPU optimizer's additional SPR scan is therefore material: independent enumeration found no improving SPR move in 90 returned trees at $N = 10, 16, 24$. This observation concerns that tested configuration, not the minibatch variant.

### 4.2 CPU optimization

Both methods recover the reference topology in all 60 noiseless trials. On the 60 noisy trials, Phylo2Vec obtains two lower BME scores, 57 ties, and one higher score than the in-memory reference. Thus it matches or improves the reference objective in 119 of 120 cases overall. A better BME score need not imply a smaller RF distance when the input distances are noisy. For example, the $N = 200$ noisy comparison has a lower mean reference RF error despite one BME-score win for Phylo2Vec.

At $N = 200$, the noiseless Apple M5 comparison requires 63.6 coordinate sweeps on average, versus 211.0 reference SPR iterations. The corresponding mean times are 18.14 and 75.46 ms. Table 3 gives the largest-size timings for both processors. Supplementary Tables 5 and 6 give results at all sizes. External FastME comparisons at the same five sizes produce identical final unrooted splits and BME differences below $10^{-8}$ in the reported checks. These checks support the reference implementation on those inputs without making the in-memory timings measurements of the external executable.

### 4.3 Coordinate sweep throughput and memory

At $N = 4{,}000$, a full coordinate sweep takes 6.219 ms on one H100, compared with 701.375 ms for its CPU reference. At $N = 40{,}000$, distributing the full-table computation across eight H100s reduces time from 816.34 to 158.36 ms, a factor of 5.15. The SPR stage alone falls from 756.26 to 98.28 ms. Column tiling reduces storage at the cost of recomputation: the reported one-GPU memory requirement falls from 31,142 to 13,614 MB, while the eight-GPU tiled evaluation takes 1,032.83 ms at this size. Thus the reduced-memory variant is useful when capacity, rather than latency, is limiting.

Distributed and streamed configurations extend a single full-tree sweep to $N = 380{,}000$, taking 205.450 s with 72,946 MB reported per GPU on eight H100s. All these times measure evaluation

at a fixed tree.

For the separate embedding workload with $N = 10{,}000{,}000$ and $K = 20{,}000$, average condensation and coordinate-sweep times are 10.20 and 48.57 ms per batch on eight H100s. The reported epoch estimate, 39.20 s, is the sum of those stage times multiplied by 667 batches. It measures the projected cost of those stages over the prescribed blocks, excluding additional search work and optimization to convergence. The complete scaling tables are in Appendix H.

## 5 Discussion

The method separates the size of a search block from the objective it evaluates. A skeleton can optimize connections among a few components while retaining the contribution of every original leaf through exact condensed distances. The same coordinate evaluator therefore supports both full-tree sweeps and restricted block searches. This links the established BME component identity to a common computational interface for parallel tree search.

The main computational tradeoff is between reuse and reconstruction. Dense tables permit rapid sweeps but require quadratic memory. Column tiling trades memory for repeated arithmetic. Skeletons reduce the dimension of the optimization problem, but exact construction of their distances can retain a dependence on the full leaf set. This becomes particularly visible in nonlinear sequence-distance refinement and in candidates involving large condensed components. Bilinear embedding benchmarks therefore establish a different scaling regime from the sequence experiments.

The experiments support faster coordinate evaluation and competitive CPU optimization on the tested instances. Their scope leaves three limitations. First, the tested relabeling and block schedules do not establish exhaustive coverage or global convergence, and the total number of sweeps remains instance-dependent. Second, the numerical checks give observed discrepancies rather than universal error bounds, and a lower BME score under estimated distances need not imply a more accurate topology. Third, the large sequence comparisons use approximate proposals with full-objective acceptance and do not report replicate uncertainty at the largest sizes. Those measurements do not establish the end-to-end cost of a sequence search using exact condensed distances for every proposal.

## 6 Conclusion

Shared coordinate evaluation and exact component reduction give a common basis for full-tree and block BME search. A quadratic sweep evaluates all valid coordinate updates, and the same computation on an exactly condensed skeleton preserves their full-tree objective changes. The resulting parallel algorithms let a search trade the scope of its candidate set against evaluation cost while retaining the specified BME objective.

## References


[1] Y. Pauplin. Direct calculation of a tree length using a distance matrix. *Journal of Molecular Evolution*, 51(1):41–47, 2000.

[2] R. Desper and O. Gascuel. Fast and accurate phylogeny reconstruction algorithms based on the minimum-evolution principle. *Journal of Computational Biology*, 9(5):687–705, 2002.

[3] R. Desper and O. Gascuel. Theoretical foundation of the balanced minimum evolution method of phylogenetic inference and its relationship to weighted least-squares tree fitting. *Molecular Biology and Evolution*, 21(3):587–598, 2004. doi:10.1093/molbev/msh049.

[4] W. Hordijk and O. Gascuel. Improving the efficiency of SPR moves in phylogenetic tree search methods based on maximum likelihood. *Bioinformatics*, 21(24):4338–4347, 2005. doi:10.1093/bioinformatics/bti713.

[5] V. Lefort, R. Desper, and O. Gascuel. FastME 2.0: A comprehensive, accurate, and fast distance-based phylogeny inference program. *Molecular Biology and Evolution*, 32(10):2798–2800, 2015.

[6] M. J. Penn, N. Scheidwasser, M. P. Khurana, D. A. Duchêne, C. A. Donnelly, and S. Bhatt. Phylo2Vec: a vector representation for binary trees. *Systematic Biology*, 74(2):250–266, 2025. Advance access 2024. doi:10.1093/sysbio/syae030.

[7] M. J. Penn, N. Scheidwasser, J. Penn, C. A. Donnelly, D. A. Duchêne, and S. Bhatt. Leaping through tree space: continuous phylogenetic inference for rooted and unrooted trees. *Genome Biology and Evolution*, 15(12):evad213, 2023. doi:10.1093/gbe/evad213.

[8] C. Tapo and Q. Zhu. Parallel and scalable balanced minimum evolution algorithm for large-scale phylogenetic inference. *bioRxiv*, 2026. Preprint. doi:10.64898/2026.07.27.740982.

[9] F. J. Camerota Verdù, A. Gasparin, L. Bortolussi, and L. Castelli. Learning to explore tree neighbourhoods for phylogenetic inference. *Briefings in Bioinformatics*, 27(1):bbaf732, 2026. doi:10.1093/bib/bbaf732.

[10] D. C. Haws, T. L. Hodge, and R. Yoshida. Optimality of the neighbor joining algorithm and faces of the balanced minimum evolution polytope. *Bulletin of Mathematical Biology*, 73(11):2627–2648, 2011. doi:10.1007/s11538-011-9640-x.

[11] C. Piñeiro, J. M. Abuín, and J. C. Pichel. VeryFastTree: speeding up the estimation of phylogenies for large alignments through parallelization and vectorization strategies. *Bioinformatics*, 36(17):4658–4659, 2020.

[12] S. Mirarab, N. Nguyen, S. Guo, L.-S. Wang, J. Kim, and T. Warnow. PASTA: Ultra-large multiple sequence alignment for nucleotide and amino-acid sequences. *Journal of Computational Biology*, 22(5):377–386, 2015.

[13] M. J. Penn, N. Scheidwasser, C. A. Donnelly, D. A. Duchêne, and S. Bhatt. Bayesian inference of phylogenetic distances: revisiting the eigenvalue approach. *Bulletin of Mathematical Biology*, 87:32, 2025.

# A Proof of the exact block reduction

We use the component weights and attachment convention from Section 2.4.

**Lemma A.1** (Normalization of leaf weights)**.** *For each component,* $\sum_{x \in S_a} \omega_a(x) = 1$.

*Proof.* A singleton has weight one. At a binary root, every leaf weight in each child component is multiplied by $1/2$. Induction over the component therefore gives total mass $\frac{1}{2} \cdot 1 + \frac{1}{2} \cdot 1 = 1$. □

## A.1 Proof of Theorem 2.2

*Proof.* Separate the unordered leaf pairs into pairs within a component and pairs between components. For $x, y \in S_a$, the path stays inside $S_a$ and is unchanged by rearranging the skeleton. The sum of all such terms is

$$C = \sum_a \sum_{\substack{x<y \\ x,y \in S_a}} D_{xy}\, 2^{-q_{T_G}(x,y)},$$

which is independent of $G$.

For $x \in S_a$ and $y \in S_b$ with $a \neq b$, the path contains the branching vertices inside $S_a$, those on the skeleton path, and those inside $S_b$. These sets of vertices are disjoint, giving

$$q_{T_G}(x, y) = h_a(x) + q_G(a, b) + h_b(y).$$

Therefore its weight factors as $2^{-q_{T_G}(x,y)} = \omega_a(x)\, 2^{-q_G(a,b)}\, \omega_b(y)$. Summing between-component terms gives

$$\begin{aligned} \sum_{a<b} \sum_{\substack{x \in S_a \\ y \in S_b}} D_{xy}\, 2^{-q_{T_G}(x,y)} &= \sum_{a<b} 2^{-q_G(a,b)} \sum_{\substack{x \in S_a \\ y \in S_b}} \omega_a(x)\omega_b(y) D_{xy} \\ &= L(G; \widetilde{D}). \end{aligned}$$

Adding the within-component constant proves Equation (8). Subtracting two such decompositions cancels $C$ and proves Equation (9). □

# B Ordered representation and coordinate mapping

## B.1 Linear-time decoding

For $v_i \leq i$, initialize a component-root array by $r[x] = x$. Process $i = N-2, \ldots, 0$. At step $i$, join the components with roots $r[v_i]$ and $r[i+1]$ at a new node $m = 2N - 2 - i$, then replace $r[v_i]$ by $m$. Before this step, the active components have distinct minimum labels $0, \ldots, i+1$. Joining the two specified components removes minimum label $i+1$ and preserves minimum label $v_i$. Induction therefore establishes the invariant and the correctness of the construction. Each step uses constant work, giving an $O(N)$ decoder. This argument depends on the ordered condition and does not apply unchanged to a general vector with $v_i > i$.

## B.2 Relabeling a decoded tree

**Proposition B.1** (Ordered representation after relabeling)**.** *Given a decoded rooted binary tree, a parent-before-child ordering of its internal nodes constructs an ordered vector and a leaf permutation in* $O(N)$ *time. The represented labeled tree and its BME score are unchanged.*

*Proof.* Give the root temporary label zero and initialize a counter $t = 1$. At each internal node, choose an ordering $(a, b)$ of its children. Pass the node's label to $a$, give $b$ label $t$, record $v_{t-1}$ as the inherited label, and increment $t$. Each newly issued label follows a unique chain of inheriting

children to a leaf. Every leaf receives exactly one label, so the resulting labels form a permutation of $0, \ldots, N-1$.

The inherited label was issued at an ancestor and is smaller than $t$, hence $v_{t-1} \leq t-1$. To verify decoding, process the recorded splits in reverse order. All descendants of a node were assigned their new labels later than that node, so both child components have already been assembled when its recorded merge is reached. The merge therefore recreates that node's original clade. Induction reconstructs the entire tree. Permuting both axes of $D$ by the inverse leaf-label map preserves all terms in Equation (1). Each vertex is processed a constant number of times. □

The implementation chooses the child order from the minimum original leaf label in each child component, with a second orientation reversing that choice. These are two deterministic coordinate systems for the same current tree. Their existence proves representational coverage after suitable relabeling, not coverage by a particular optimizer trajectory. For general candidate vectors, the implementation also uses a tree-to-vector encoder. Its unrooted version first inserts a degree-two root on the edge incident to leaf zero, so round-trip correctness is assessed by unrooted splits rather than root placement.

### B.3 Mapping coordinate values to regraft edges

The ordered decoder numbers leaves $0, \ldots, N-1$ and internal nodes $N, \ldots, 2N-2$. The last index is the artificial root. Suppressing it leaves a computational root $R = 2N-3$ and the top edge joining $R$ to the artificial root's other child, denoted $c_{\text{other}}$. Index ordinary edges by their child endpoints.

For row $i$, let $E_i[u]$ be the score change from pruning the component associated with leaf $i+1$ and regrafting it on the edge indexed by $u$. The half-tree SPR traversal supplies these values. Let $b_i(j)$ be the root of the component containing leaf $j$ after the merges with coordinate index greater than $i$. Then the edge-to-coordinate map is

$$\Delta_{i,j} = \begin{cases} E_i[b_i(j)], & 0 \leq j \leq i, \\ E_i[(2N-2) - 2i + j], & i+1 \leq j \leq 2i-2, \\ E_i[c_{\text{other}}], & j \in \{2i-1, 2i\} \cap [i+1, 2i]. \end{cases} \tag{13}$$

The first case identifies the component on the corresponding pendant edge of the prefix tree. In the ordered decoder's node numbering, the remaining non-root prefix edges occupy consecutive indices $2N-1-i, \ldots, 2N-4$, giving the affine map in the second case. The last two rooted edge choices collapse onto the same unrooted top edge. At $i = 1$, the middle case is empty and $j = 1$ belongs to the first case. Only $j = 2$ takes the collapsed-root value. Coordinate zero has no nontrivial alternative.

On a CPU, the array $b_i$ can be maintained incrementally as the merge order advances. On a GPU, independent rows reconstruct their mappings using the latest eligible merge for each minimum leaf. When several merges have the same minimum leaf, only the latest eligible merge may write that destination. This avoids concurrent writes that would otherwise depend on thread scheduling.

### B.4 Connection to continuous vertex derivatives

GradME defines an expected objective $F(W) = \mathbb{E}[f(V)]$ for independent ordered coordinates [7]. For comparison, take $f(v) = L(T(v); D_\pi)$ with the same unrooted convention as Equation (1). Let $W^v$ put probability one on each entry of an ordered vector $v$. For $j \leq i$, change only row $i$ to $(1-t)e_{v_i} + te_j$, where $e_j$ is a unit vector. Only two vectors then have nonzero probability, giving

$$F(W(t)) = (1-t)f(v) + tf(v^{(i \leftarrow j)}), \qquad \left.\frac{dF(W(t))}{dt}\right|_{t=0} = \Delta_{i,j}. \tag{14}$$

This is a direct consequence of the expected-objective definition, not a new exactness property. The computational distinction is the shared quadratic evaluator at a discrete tree. It also evaluates $j > i$, outside the ordered domain of this relaxation. It does not evaluate gradients at arbitrary interior $W$ in quadratic time.

# C Parallel dependencies and workspace

## C.1 Column ownership and ancestor traversal

For a fixed column $w$, the bottom-up update in Equation (4) reads only earlier entries of that column. Thus the recurrence has no cross-column dependency once its initial entries are available. The implementation separates the necessary transpose from the recurrence rather than writing both triangular copies concurrently. Top-down correction visits ancestors of $w$ in order from the computational root. If a node's children have contiguous depth-first intervals, comparing the entry time of $w$ with their interval boundary selects the child containing $w$. Only the current node and the fixed target are required as traversal state. The initial degree-three root update uses the other two root branches.

## C.2 Autonomous row reconstruction

Store the balanced distances from internal vertices to leaves. For a requested row $w$, these entries supply its leaf values. For leaf $w$, the leaf values instead come directly from $D$. Average child entries bottom-up to fill internal positions, then overwrite ancestors of $w$ top-down using the sibling and parent directions. Initialize the degree-three root correction explicitly and set the diagonal to zero.

For an internal position $u$ in a disjoint component, the bottom-up average is the required balanced distance by linearity. For a descendant $u$ of $w$, the stored leaf values already use the component at $w$ directed away from that descendant, so averaging within the descendant gives the correct value. Ancestors of $w$ require the complementary direction and are supplied by the top-down overwrite. These cases exhaust the row. The reconstruction costs $O(N + \mathrm{depth}(w)) = O(N)$. Reconstructing a constant number of rows per pruned component therefore retains quadratic sweep complexity. The approximately fourfold reduction concerns the balanced-distance table only.

## C.3 Traversal stack size

When a traversal reaches two outward components, push the larger component first and the smaller second on a last-in-first-out stack. The smaller component is processed next. Each extra pending larger component is associated with descent into a component at most half the size of its predecessor. Hence the number of simultaneously pending components is logarithmic in the number of tree vertices. Including the active traversal state gives a safe bound $\lfloor \log_2(2N-2) \rfloor + 2$. This is a workspace bound, not a statement that the traversal visits fewer vertices.

# D Sequence-refinement variant and recorded benchmarks

## D.1 Implementation used for the recorded measurements

The sequence implementation used for the measurements in this appendix differs from the exact-distance search described in Section 2.6. For trees larger than 2,048 leaves, it caps the weighted leaf lists used for proposal distances at 64 entries per component. These lists are called profiles in the implementation. Above the cap, unresolved subtree mass is assigned to representative leaves, producing an approximate matrix $\widetilde{D}^{\mathrm{cap}}$. For smaller trees, the proposal calculation is uncapped.

Table 4: Archived RNASim refinement comparison, preceding the later acceptance-kernel optimizations. Both methods use the same starting topology. VFT denotes 64-thread VeryFastTree minimum-evolution refinement. P2V denotes the sequence variant on one RTX A6000, using capped proposal distances above 2,048 leaves and full-tree acceptance checks. Times exclude the shared initialization and characterize this proposal-and-check variant.

| $N$ | Initial | Wrong splits | | Refinement (s) | | Init. (s) |
|---|---|---|---|---|---|---|
| | wrong splits | VFT | P2V | VFT | P2V | |
| 1,000 | 214 | 178 | 176 | 6.88 | 0.06 | 0.58 |
| 5,000 | 890 | 703 | 696 | 33.38 | 0.68 | 3.40 |
| 10,000 | 1,667 | 1,313 | 1,320 | 65.98 | 1.55 | 7.82 |
| 50,000 | 6,729 | 4,980 | 4,950 | 313.53 | 16.84 | 63.01 |
| 100,000 | 12,375 | 8,857 | 8,802 | 593.50 | 104.45 | 179.03 |

The approximate matrix guides the inner skeleton search. Before accepting an update, the implementation recomputes affected condensed distances involving truncated components using every leaf contribution. Distances for untruncated pairs can be reused. It then evaluates Equation (11), with FP64 accumulation and a numerical acceptance margin of $10^{-6}$. Outside weights are rebuilt from the current tree before each window, and ancestor summaries are updated after a commit. The acceptance calculation therefore evaluates the full-tree BME change, subject to rounding. It does not make the earlier proposal gradients exact, and the numerical margin is not a proved floating-point error bound.

These measurements characterize that implementation variant. They are not timings for constructing exact condensed distances and using them throughout every minibatch search.

### D.2 Sequence data and comparison protocol

The recorded comparisons use the RNASim benchmark associated with PASTA [12], with simulated sequences and a known reference tree. The reported alignments have 1,596 columns. The minibatch comparison uses gap-aware JC69 distances. Selected full-tree experiments also use the eigenvalue-based distance approach [13], which changes the input objective and is identified separately. The CPU tools are 64-thread FastME 2.1.6 and VeryFastTree 4.0.5 [5, 11]. VeryFastTree's minimum-evolution refinement is run without its likelihood-refinement phase. Refinement time is reported separately from starting-tree construction. The minibatch times include the final full-tree acceptance calculation and sequential maintenance of the outside distances.

### D.3 Archived refinement comparison

Table 4 retains the archived comparison of this minibatch variant with VeryFastTree refinement from the same initial topology. These measurements precede the subsequent acceptance-kernel optimizations and characterize that recorded implementation. At $N = 50{,}000$, the minibatch method returns 4,950 incorrect splits in 16.84 s, compared with 4,980 in 313.53 s. At $N = 100{,}000$, the corresponding results are 8,802 in 104.45 s and 8,857 in 593.50 s. The refinement-time ratios are 18.6 and 5.7 respectively. These exclude the shared initialization, which takes 63.01 and 179.03 s. Adding that initialization to both methods gives approximately 4.72-fold and 2.73-fold ratios, rather than the refinement-only ratios.

The topological advantage is not uniform. At $N = 10{,}000$, the minibatch result has 1,320 incorrect splits, compared with 1,313 for VeryFastTree. A full-tree run with eigenvalue-based distances reaches 1,309 in 4.57 s, but uses a different distance estimate. The full-tree JC69 run returns 1,320 in 3.71 s. These variants should therefore not be combined into a single claim of consistently better topological accuracy.

At $N = 1{,}000$, FastME applied to the GPU-computed JC69 distance matrix returns 177 incorrect splits in 21.68 s with its own BIONJ initialization. Its shared-start refinement returns 178 in 11.27 s. The corresponding full-tree GPU result is 176 in 0.01 s, and minibatch refinement returns 176 in 0.06 s. The experiments differ in initialization and timing scope, so the ratios between their raw elapsed times are not interchangeable.

# E Truncation and stale outside-distance counterexamples

Two constructions illustrate the need for exact condensed distances and current outside information. The first concerns the approximate-proposal variant in Appendix D. On a 4,102-leaf tree containing a balanced 4,096-leaf component, an adversarial split distance can give a capped proposal change of $-0.25$ while its true full-profile change is $+0.2421875$ for a cap of 64, or $+0.234375$ for a cap of 128. The proposal sign alone is therefore insufficient. Full-profile acceptance rejects both changes.

Separately, consider two disjoint windows whose internal rearrangements change their root-to-leaf weight vectors from $p_A, p_B$ to $p_A + \delta p_A, p_B + \delta p_B$. With a fixed path coefficient $\kappa$ between their attachment points, their cross contribution contains $\kappa p_A^\top D_{AB} p_B$. The jointly changed contribution includes the additional term

$$\kappa\, \delta p_A^\top D_{AB} \delta p_B,$$

which is absent from the sum of two changes computed against the original surroundings. In a 1,540-leaf test with two 768-leaf windows, changes $-0.0032945313$ and $-0.0254489835$ computed against frozen surroundings combine to an actual increase of $+0.0505258348$. Rebuilding the outside profile after the first commit makes the other proposal positive: $+0.0538203660$ or $+0.0759748183$, depending on the processing order. It is then rejected. These values come from controlled CPU replay of the acceptance and window-controller paths. They do not constitute a native-GPU concurrency test.

# F Implementation and reproducibility

The CPU evaluator, tree encoders, and full-tree optimizer are implemented in `phylo2vec_fastme.c`, with input validation and Python bindings in `discrete_gradient.py`. The lower-triangular and full-coordinate interfaces require an ordered baseline. The multi-GPU evaluator and its tiled variants are implemented in `phylo2vec_cuda_8xh100.cu`. Sequence refinement is exercised by `bench_rnasim_gpu.cu`. The distinct distance-oracle recovery workload is implemented in `bench_minibatch_recovery.cu`.

Independent checks include `verify_all.c` for objective identities and encoding boundaries, `verify_spr_coverage.py` for neighborhood enumeration, and `compare_with_fastme_cli.py` for the external reference. The profile-completeness and window-composition constructions are recorded with their reproduction commands in the discrete-gradient review artifacts. CPU-emulated tests exercise the window controller, complete component-weight arithmetic, and a shared-input batching path. Separate native CUDA comparisons of the later split-launch implementation and its final-tree hashes are recorded in `GEMINI_REPORT_REFINE_KERNEL.md` and the artifacts under `handoff_refine_kernel/`. These tests cover different execution paths and are identified separately in their records.

The archived sequence measurements in Appendix D are preserved in `paper/restructure_chatgpt/original.tex`. The later kernel report measures additional implementation optimizations, whose timings have not been substituted into that archived comparison. The sequence records use approximate proposals with full-objective acceptance. They therefore do not supply an end-to-end benchmark with exact condensed distances throughout candidate selection.

### F.1 Search policies and parameters

The procedures in Algorithms 1 and 2 specify the search at the level of trees, coordinate encodings, and component distances. The following policies instantiate their scheduling and candidate-selection steps. The score $L$ always uses component identities restored by the recorded permutation.

**CPU block schedule.** Full-tree search uses a single block with $K = N$ singleton components, so $G = T$ and $M = D$. For requested size $3 \le K_\star < N$, the CPU minibatch implementation exposes $w = \min\{K_\star - 2, \max\{4, \lfloor 2K_\star/3 \rfloor\}\}$ consecutive leaves in the current depth-first leaf order. Block $b$ starts at offset $b \max\{1, \lfloor w/2 \rfloor\}$ modulo $N$. Maximal inactive subtrees become fixed components. The largest such component is split while the skeleton has fewer than $K_\star$ leaves and a further split is possible. Thus $K_\star$ is a construction target, while $K$ is the resulting skeleton size. The leaf order and components are reconstructed from the updated tree for every block. A hierarchical schedule instead combines a global backbone, local component windows, and staggered or larger windows crossing preceding component boundaries. Regardless of schedule, the sequential driver constructs each block's outside information from the current tree.

**Ordered representations and row selection.** Order produces an ordered encoding and its component permutation by the construction in Appendix B. Normalise invokes this construction only when the current encoding contains a value $v_i > i$, composing the new map with $\pi$. Decode$(v, \pi)$ restores original component identities and suppresses the artificial root. For each row, RankMin selects $j_i \in \arg\min_{0 \le j \le 2i} \Delta_{i,j}$, keeps rows with $\Delta_{i,j_i} < -\eta$, and sorts them by increasing change. The CPU policy uses deterministic traversal and row order to resolve ties. It uses $I = 500$ and $\epsilon(\ell) = 10^{-12}(|\ell| + 1)$.

**Joint batch acceptance.** Let $d_{\min} < 0$ be the best single change. BatchStep greedily packs at most eight rows, excluding shared marked pruned-subtree nodes and attachment endpoints. After the first row, it retains only rows with $\Delta_{i,j_i} < 0.05 d_{\min}$. It tests a batch only if its predicted changes sum to less than $1.05 d_{\min}$. Every trial applies the selected replacements to the same pre-trial encoding $v$ and evaluates the complete candidate $v'$. A batch is accepted when $L(T(v'); M_\pi) < \ell + d_{\min} - \eta$. If rejected, the retained ranked prefix is halved and evaluated again, down to two moves. If no batch is accepted, the best single replacement is used. The predicted sum screens a batch but does not determine its acceptance.

**SPR completion and deterministic escapes.** When no improving coordinate row remains, the CPU solver first tests additional regraft edges for its already-scanned pruned components. If this fails, it tries the reversed ordered labeling. Only after both stages fail does it scan the remaining unrooted SPR moves, including complement-side prunes. ExtraSPR and RemainingSPR return an updated encoding in the current component labeling, or $\perp$ when no change is below $-\eta$.

Following an unsuccessful completion scan, Escape permits at most $E = 2$ attempts, each with at least one subsequent sweep available. For each row it retains the smallest change strictly between $\eta$ and 0.05, then sorts these candidates by increasing change. Attempt $e \in \{1, 2\}$ combines the first and $(e + 1)$th candidates if both exist and their predicted changes sum to less than 0.02. Otherwise it returns $\perp$. These thresholds are in objective units. An escape may increase the working score. The return rule compares the final trial with the retained best scored tree. Consequently, a completed scan and a budget-limited exit represent different stopping conditions.

**GPU skeleton solver.** The GPU policy performs a bounded sequence of trial updates, packs SPR moves whose marked paths are disjoint, and rescores each combined tree on the next sweep. It retains the best scored skeleton and tries the reversed labeling when no improving row remains. It does not use the CPU batch-halving or full SPR completion steps. The best trial is compared with the entry skeleton before committing the block. Intermediate trial scores can increase, so

only the retained best score and accepted block changes have a monotonicity interpretation. For the approximate-proposal sequence variant, the acceptance conditions and measurement scope are given in Appendix D.

# G Supplementary CPU comparisons

Tables 5 and 6 give the full Apple M5 comparisons. FME denotes the in-memory reference implementation. P2V denotes Phylo2Vec. RF denotes normalized Robinson–Foulds distance. Wins and ties refer to the BME objective, with tolerance $10^{-9}$. Timings and evaluation counts are means, with standard deviations and the reported P2V median and interquartile range retained.

Table 5: Additive distance comparison on Apple M5.

*Objective and topology*

| $N$ | FME $L$ | P2V $L$ | Win/tie/loss | FME RF | P2V RF |
|---|---|---|---|---|---|
| 20 | 11.12739 | 11.12739 | **0 / 20 / 0** | 0.0000 | 0.0000 |
| 50 | 29.42572 | 29.42572 | **0 / 20 / 0** | 0.0000 | 0.0000 |
| 100 | 59.52693 | 59.52693 | **0 / 10 / 0** | 0.0000 | 0.0000 |
| 150 | 89.04365 | 89.04365 | **0 / 5 / 0** | 0.0000 | 0.0000 |
| 200 | 116.32398 | 116.32398 | **0 / 5 / 0** | 0.0000 | 0.0000 |

*Computational cost*

| $N$ | FME iters. | P2V evals. | FME ms | P2V ms | P2V med. [IQR] | Ratio |
|---|---|---|---|---|---|---|
| 20 | 13.4 | 11.2 | $0.12 \pm 0.02$ | $0.08 \pm 0.01$ | 0.07 [0.02] | **1.54**× |
| 50 | 42.2 | 19.4 | $1.58 \pm 0.35$ | $0.57 \pm 0.13$ | 0.59 [0.16] | **2.78**× |
| 100 | 97.7 | 35.4 | $9.05 \pm 0.84$ | $2.63 \pm 0.26$ | 2.65 [0.44] | **3.44**× |
| 150 | 156.2 | 49.4 | $31.47 \pm 0.77$ | $7.92 \pm 0.86$ | 7.75 [0.64] | **3.97**× |
| 200 | 211.0 | 63.6 | $75.46 \pm 2.42$ | $18.14 \pm 0.74$ | 18.05 [1.17] | **4.16**× |

Table 6: Noisy distance comparison on Apple M5.

*Objective and topology*

| $N$ | FME $L$ | P2V $L$ | Win/tie/loss | FME RF | P2V RF |
|---|---|---|---|---|---|
| 20 | 11.19777 | 11.19777 | **0 / 20 / 0** | 0.0500 | 0.0500 |
| 50 | 29.25507 | 29.25607 | **1 / 18 / 1** | 0.0660 | 0.0649 |
| 100 | 59.25471 | 59.25471 | **0 / 10 / 0** | 0.0526 | 0.0526 |
| 150 | 92.14846 | 92.14846 | **0 / 5 / 0** | 0.0395 | 0.0395 |
| 200 | 120.94220 | 120.94220 | **1 / 4 / 0** | 0.0467 | 0.0487 |

*Computational cost*

| $N$ | FME iters. | P2V evals. | FME ms | P2V ms | P2V med. [IQR] | Ratio |
|---|---|---|---|---|---|---|
| 20 | 14.4 | 12.4 | $0.07 \pm 0.01$ | $0.05 \pm 0.01$ | 0.04 [0.02] | **1.60**× |
| 50 | 46.1 | 25.9 | $1.07 \pm 0.07$ | $0.49 \pm 0.09$ | 0.49 [0.10] | **2.18**× |
| 100 | 102.6 | 41.0 | $10.62 \pm 2.53$ | $3.32 \pm 0.56$ | 3.18 [0.52] | **3.19**× |
| 150 | 166.0 | 61.0 | $33.97 \pm 1.01$ | $10.15 \pm 1.35$ | 10.17 [1.35] | **3.35**× |
| 200 | 235.8 | 84.4 | $85.16 \pm 2.06$ | $24.67 \pm 2.79$ | 24.51 [4.48] | **3.45**× |

# H Supplementary scaling measurements

The tables below retain the reported sweep measurements, separating CPU/Metal, CUDA, sharded, and embedding-based workloads. The single-GPU speedups use their respective host CPU references. They should not be interpreted as comparisons against one common host baseline. Stage timings measure balanced-distance construction and SPR evaluation, rather than optimization to convergence. The $2N^2$ column in the sharded table is the original rectangular-workload size proxy. It is not the number of valid Phylo2Vec coordinate entries, which is $(N-1)^2$, nor a count of distinct neighboring trees. Reported memory units are retained from the benchmark records.

For the embedding workload, each batch has 20,000 skeleton leaves, comprising 15,000 expanded leaves and 5,000 condensed components. Its epoch columns multiply average condensation-plus-gradient time by $\lceil N/15{,}000 \rceil$. They are workload estimates rather than measured convergence times. The largest listed validation discrepancy in this workload is $1.4 \times 10^{-5}$, and the listed validation outcomes refer to the benchmark's own checks.

Table 7: CPU and Metal gradient timings on Apple M5. All times are milliseconds.

*FP64 full sweep*

| $N$ | 1 CPU | 10 CPU | Ratio | 10 CPU tiled |
|---|---|---|---|---|
| 100 | 0.055 | 0.068 | 0.80× | 0.096 |
| 250 | 0.332 | 0.322 | 1.03× | 0.246 |
| 500 | 1.273 | 0.433 | **2.94**× | 0.508 |
| 1,000 | 5.860 | 1.878 | **3.12**× | 2.081 |
| 2,000 | 27.399 | 10.230 | **2.68**× | 10.806 |
| 3,000 | 85.815 | 24.428 | **3.51**× | **23.777 ms** |
| 4,000 | 132.225 | 51.265 | **2.58**× | **43.329 ms** |

*Balanced-distance construction*

| $N$ | CPU FP64 | CPU FP32 | Metal FP32 | Ratio |
|---|---|---|---|---|
| 100 | 0.012 | 0.011 | 0.517 | 0.02× |
| 250 | 0.076 | 0.058 | 0.906 | 0.08× |
| 500 | 0.312 | 0.223 | 1.216 | 0.26× |
| 1,000 | 1.565 | 1.344 | 2.699 | 0.58× |
| 2,000 | 8.954 | 9.533 | 4.462 | **2.01**× |
| 3,000 | 22.504 | 35.030 | 8.970 | **2.51**× |
| 4,000 | 68.188 | 59.289 | 7.571 | **9.01**× |

*Hybrid sweep and absolute errors*

| $N$ | Hybrid FP32 | Ratio | FP64 error | FP32 error |
|---|---|---|---|---|
| 100 | 0.524 | 0.10× | 0.00e+00 | 4.35e-07 |
| 250 | 0.934 | 0.36× | 0.00e+00 | 5.24e-07 |
| 500 | 1.742 | 0.73× | 5.55e-17 | 6.63e-07 |
| 1,000 | 3.097 | **1.89**× | 4.44e-16 | 8.11e-07 |
| 2,000 | 6.312 | **4.34**× | 4.44e-16 | 8.93e-07 |
| 3,000 | 14.359 | **5.98**× | 5.27e-16 | 9.84e-07 |
| 4,000 | 26.922 | **4.91**× | 5.00e-16 | 1.13e-06 |

Table 8: Single-GPU gradient timings and agreement with the CPU reference. Times are milliseconds.

*RTX A6000 timings and reported maximum errors*

| $N$ | A6000 full | Ratio | A6000 tiled | Max. error |
|---|---|---|---|---|
| 100 | 0.061 | **8.44**× | 0.078 | 3.68e-07 |
| 250 | 0.186 | **15.92**× | 0.207 | 6.22e-07 |
| 500 | 0.382 | **32.95**× | 0.511 | 6.48e-07 |
| 1,000 | 1.035 | **33.69**× | 1.988 | 9.29e-07 |
| 2,000 | 3.851 | **40.15**× | 7.288 | 1.11e-06 |
| 4,000 | 11.053 | **62.48**× | 43.124 | 1.07e-06 |

*H100 timings*

| $N$ | CPU ref. | H100 avg. | H100 SPR | H100 total | Ratio | H100 tiled |
|---|---|---|---|---|---|---|
| 100 | 0.249 | 0.044 | 0.027 | 0.071 | **3.51**× | 0.095 |
| 250 | 1.964 | 0.116 | 0.048 | 0.164 | **11.98**× | 0.205 |
| 500 | 8.176 | 0.227 | 0.077 | 0.304 | **26.89**× | 0.460 |
| 1,000 | 32.336 | 0.661 | 0.105 | 0.766 | **42.21**× | 1.030 |
| 2,000 | 154.091 | 1.557 | 0.726 | 2.283 | **67.50**× | 4.273 |
| 4,000 | 701.375 | 3.565 | 2.654 | 6.219 | **112.78**× | 22.327 |

The maximum-error column is the reported combined check across the GPU paths. All listed checks pass their benchmark tolerance. CPU baselines differ between hosts.

Table 9: Full-table and tiled multi-GPU sweeps. Times are milliseconds and memory is reported in MB.

*A6000 timings and memory columns*

| $N$ | 2 A6000 full | 2 A6000 tiled | Full memory | Tiled memory |
|---|---|---|---|---|
| 1,000 | 0.93 | 5.75 | 27 | 39 |
| 2,000 | 4.89 | 13.90 | 92 | 93 |
| 4,000 | 14.69 | 56.85 | 336 | 247 |
| 10,000 | 90.45 | 249.59 | 1,985 | 1,076 |
| 20,000 | 422.73 | 1,212.27 | 7,785 | 3,677 |
| 40,000 | *OOM* | 5,628.62 | 31,142 | 13,614 |

*Full-table H100 sweep*

| $N$ | 1 H100 [avg.+SPR] | 8 H100 | Ratio |
|---|---|---|---|
| 1,000 | 0.76 [0.65 + 0.11] | 0.79 | 0.96× |
| 2,000 | 2.21 [1.47 + 0.74] | 1.71 | **1.29**× |
| 4,000 | 6.01 [3.57 + 2.44] | 3.98 | **1.51**× |
| 10,000 | 29.61 [10.10 + 19.50] | 13.03 | **2.27**× |
| 20,000 | 155.93 [23.23 + 132.70] | 41.06 | **3.80**× |
| 40,000 | 816.34 [60.08 + 756.26] | **158.36** | **5.15**× |

*Tiled H100 sweep*

| $N$ | 1 H100 tiled | 8 H100 tiled | Top-1 check |
|---|---|---|---|
| 1,000 | 1.46 | 4.47 | **PASS** (0.00e+00) |
| 2,000 | 6.14 | 5.21 | **PASS** (2.38e-07) |
| 4,000 | 30.78 | 10.98 | **PASS** (0.00e+00) |
| 10,000 | 250.69 | 57.53 | **PASS** (0.00e+00) |
| 20,000 | 1,123.43 | 244.13 | **PASS** (4.77e-07) |
| 40,000 | 4,768.31 | **1,032.83** | **PASS** (0.00e+00) |

Table 10: Distributed sweeps on eight H100 GPUs.

*Timing*

| $N$ | Work proxy $2N^2$ | Distance ms | SPR ms | Total s |
|---|---|---|---|---|
| 40,000 | $3.20 \times 10^9$ | 514.54 | 517.92 | **1.032** |
| 80,000 | $1.28 \times 10^{10}$ | 2,112.82 | 2,321.28 | **4.434** |
| 120,000 | $2.88 \times 10^{10}$ | 4,785.75 | 4,803.60 | **9.589** |
| 180,000 | $6.48 \times 10^{10}$ | 10,848.67 | 13,977.73 | **24.826** |
| 250,000 | $1.25 \times 10^{11}$ | 39,981.55 | 43,721.48 | **83.703** |
| 350,000 | $2.45 \times 10^{11}$ | 76,240.05 | 96,515.83 | **172.756** |
| 380,000 | $2.89 \times 10^{11}$ | 89,992.00 | 115,457.57 | **205.450** |

*Memory and execution mode*

| $N$ | MB/GPU | Aggregate GB | Mode and check |
|---|---|---|---|
| 40,000 | 2,386 | 18.6 | `Full-Shard` [**PASS**] |
| 80,000 | 7,824 | 61.1 | `Shard+Calib` [**PASS**] |
| 120,000 | 16,314 | 127.5 | `Shard+Calib` [**PASS**] |
| 180,000 | 34,770 | 271.6 | `Shard+Calib` [**PASS**] |
| 250,000 | 62,296 | 486.7 | `Shard+Calib` [**PASS**] |
| 350,000 | 62,180 | 485.8 | `StreamD+Calib` [**PASS**] |
| 380,000 | 72,946 | 569.9 | `StreamD+Calib` [**PASS**] |

At $N = 400{,}000$, the reported requirement is 80,600 MB/GPU (629.7 GB aggregate), exceeding available device memory. Full-Shard and Shard+Calib retain distance shards. StreamD+Calib generates distance tiles as required. The work proxy is not a count of distinct moves.

Table 11: Embedding-based condensed sweeps with $K = 20{,}000$ skeleton leaves. The epoch columns are batch-count times mean condensation-plus-gradient time.

*Two A6000 GPUs*

| $N$ | Batches | 2 A6000 cond.+grad. (ms) | Epoch (s) |
|---|---|---|---|
| 1,000,000 | 67 | $4.45 + 284.44$ | 19.36 |
| 5,000,000 | 334 | $8.42 + 283.02$ | 97.34 |
| 10,000,000 | 667 | $17.29 + 281.58$ | 199.35 |

*Eight H100 GPUs*

| $N$ | Cond. ms | Grad. ms | Epoch s | MB/GPU | Check |
|---|---|---|---|---|---|
| 1,000,000 | 2.69 | 48.53 | **3.43** | 7,793 | **PASS** (1.4e-05) |
| 5,000,000 | 4.86 | 48.48 | **17.82** | 7,824 | **PASS** (2.1e-06) |
| 10,000,000 | 10.20 | 48.57 | **39.20** | 7,862 | **PASS** (2.2e-06) |

This workload uses a bilinear embedding distance and is separate from sequence-distance refinement. The validation figures are observed discrepancies, not universal error bounds.