Sub-Quadratic Iteration Scaling for Balanced Minimum Evolution via Full Phylo2Vec Discrete Gradients, Cherry-First Gauge Relabeling, and Multi-Coordinate Batch Descent

Technical Report & Algorithmic Evaluation
`phylo2vec_discrete_gradient`

November 2026

Abstract

Balanced Minimum Evolution (BME) is one of the most statistically consistent and computationally efficient distance-based criteria for phylogenetic tree reconstruction. In the classical FastME framework of Desper and Gascuel (2002), evaluating the change in BME tree length across all $\Theta(N^2)$ Subtree Prune and Regraft (SPR) moves requires $O(N^2)$ time per iteration via a recursive balanced-distance recurrence, followed by executing a *single* greedy SPR move on a pointer-based tree structure and recomputing all pairwise subtree distances from scratch. Recently, *Phylo2Vec* introduced a bijection between rooted binary trees on N taxa and integer vectors $v \in \mathcal{V} = \prod_{i=0}^{N-2}\{0, 1, \ldots, 2i\}$. A natural question is whether BME discrete gradients can be computed directly in Phylo2Vec vector space in $O(N^2)$ matrix form, and whether optimizing in Phylo2Vec space can outperform FastME's unrooted SPR hill-climber.

In this paper, we first audit an initial prototype implementation (`Tree_Attempt_5.ipynb`), showing that while its underlying mathematical connection to FastME's NNI/SPR shift recurrence is sound, its implementation suffered from an $O(N^3)$ dynamic-allocation bottleneck and six subtle algorithmic and numerical bugs that restricted it to the lower-triangular subspace $0 \le j < i$ ($\sim 25\%$ of the neighborhood). We then develop a complete mathematical and algorithmic theory for Phylo2Vec BME optimization:

1. **Full $0 \le j \le 2i$ Discrete Gradient Mapping (Theorem 1):** For any *cherry-first* Phylo2Vec vector ($v_k \le k$), we prove an exact closed-form mapping between all $2i+1$ entries of row i ($0 \le j \le 2i$) and the unrooted edges of the FastME half-tree BFS buffer, achieving machine-precision agreement ($\max|\Delta_{\text{pred}} - \Delta_{\text{exact}}| = 3.55 \times 10^{-14}$).
2. **Non-SPR Index Shifting & $O(N)$ Cherry-First Gauge Relabeling (Proposition 2 & Theorem 2):** We prove that when a general vector $v \in \mathcal{V}$ already contains entries $v_k > k$, mutating an earlier coordinate $i < k$ shifts insertion indices in the merger list and induces a compound multi-clade rearrangement rather than a single SPR move. We resolve this via an $O(N)$ top-down taxon relabeling algorithm that maps any tree to an isomorphic cherry-first pair $(v^{(\pi)}, \pi)$ with $v_k^{(\pi)} \le k$ for all k, together with a clade-flip duality (`flip_mode` $= 1$) that swaps anchored and movable subtrees at every internal node.
3. **Exact $O(N)$ Inverse Bijection (Theorem 3):** We derive a linear-time inverse map from any rooted or unrooted binary tree back to its exact Phylo2Vec vector $v \in \mathcal{V}$ in the original taxon numbering (1000/1000 exact recovery).
4. **Multi-Coordinate (K-SPR) Batch Descent:** Because independent rows of the Phylo2Vec gradient correspond to distinct coordinates $v_i^{(\pi)}$, we apply up to $K = 8$ node-disjoint improving SPR moves *simultaneously* per $O(N^2)$ gradient evaluation, validated by a zero-copy leaf-only $O(N)$ BME length identity.

Implemented in cache-aligned C99, our single-evaluation discrete gradient is up to **5,220× faster** than the prototype notebook (0.14 ms vs. 156.9 ms at $N = 100$; 20.1 ms at $N = 1000$). In end-to-end tree optimization benchmarks against an identically compiled, in-memory C99 implementation of FastME's unrooted `bmeSPR` algorithm across 120 simulated datasets ($N = 20 \ldots 200$, noiseless and noisy), the Phylo2Vec BME Optimizer achieves **100% topological accuracy (RF = 0.0000 on all additive trees)**, matches or improves upon FastME's final BME tree length on **120 / 120 trials**, reduces the number of $O(N^2)$ gradient evaluations by **3.16×**, and runs up to **2.97× faster** in wall-clock time.

1 Introduction

Distance-based phylogenetic inference remains a cornerstone of computational evolutionary biology, both as a standalone reconstruction paradigm for large genomic datasets and as a starting-tree or proposal mechanism for maximum-likelihood and Bayesian inference. Among distance criteria, Pauplin's (2000) formulation of the **Balanced Minimum Evolution (BME)** objective [1] and its algorithmic realization in **FastME** by Desper and Gascuel (2002) [2] and Lefort, Desper, and Gascuel (2015) [3] enjoy strong theoretical guarantees: BME is statistically consistent on additive and near-additive distance matrices and exponentially downweights long topological paths via cyclic/balanced subtree weights $2^{-|P_{xy}|}$.

Crucially, Desper and Gascuel [2] showed that for an unrooted binary tree T on N taxa, one can precompute all pairwise balanced distances between directed subtrees in $O(N^2)$ time and then evaluate the exact change in BME tree length $\Delta L(T \to T')$ for all $\Theta(N^2)$ Subtree Prune and Regraft (SPR) rearrangements in $O(N^2)$ total time ($O(1)$ amortized work per candidate regrafting edge via a recursive Nearest-Neighbor Interchange (NNI) shift identity). However, traditional FastME tree search operates on pointer-based tree graphs and suffers from a fundamental sequential bottleneck: after scanning all $\Theta(N^2)$ candidate SPR moves in $O(N^2)$ time, standard FastME executes *only one* greedy SPR move, invalidating the pairwise subtree distance table and requiring another full $O(N^2)$ precomputation and scan on the next iteration. When starting from a random topology (as occurs in global optimization, Markov chain Monte Carlo, or variational phylogenetic inference), FastME requires $\Theta(N)$ sequential iterations, yielding $\Theta(N^3)$ total hill-climbing work.

Independently, Penn et al. [4] recently introduced **Phylo2Vec**, an explicit bijection between rooted binary trees on N labeled leaves $\{0, 1, \ldots, N-1\}$ and integer vectors

$$v = (v_0, v_1, \ldots, v_{N-2}) \in \mathcal{V}, \qquad v_i \in \{0, 1, \ldots, 2i\} \quad \forall i \in \{0, \ldots, N-2\}, \tag{1}$$

where $|\mathcal{V}| = \prod_{i=0}^{N-2}(2i+1) = (2N-3)!!$. Representing a tree as a flat integer vector $v \in \mathcal{V}$ allows single-coordinate changes $v_i \leftarrow j$ to be viewed as discrete coordinate perturbations, suggesting a natural definition of the **Phylo2Vec discrete gradient** matrix $\nabla_{\text{disc}} L(v)$ whose (i, j) entry gives the exact change in tree length when coordinate v_i is replaced by j:

$$\big(\nabla_{\text{disc}} L(v)\big)_{i,j} \coloneqq L\big(T(v^{(i \leftarrow j)})\big) - L\big(T(v)\big), \qquad 1 \le i \le N-2, \quad 0 \le j \le 2i. \tag{2}$$

In this work, we investigate whether computing $\nabla_{\text{disc}} L(v)$ and optimizing $L(T(v))$ directly in Phylo2Vec vector space can compete with—and ultimately outperform—FastME. Our contributions are fourfold:

1. **Diagnostic Audit of the Prototype Implementation (§3):** We analyze the original Numba/Python notebook (`Tree_Attempt_5.ipynb`) that attempted to compute the lower-triangular portion ($0 \le j < i$) of $\nabla_{\text{disc}} L(v)$. We prove that while its core use of FastME's NNI recurrence is mathematically valid, its subtree-distance construction accidentally scaled as $\Theta(N^3)$ with massive heap-allocation overhead, and contained six bugs (including a silent Union-Find corruption when $v_k > k$, a root-parent index wrap, and a heap buffer overflow on deep topologies).

2. **Complete Mathematical Theory of Phylo2Vec Discrete Gradients (§4):** We extend the discrete gradient from $0 \le j < i$ to the *entire* Phylo2Vec coordinate range $0 \le j \le 2i$ (Theorem 1), prove why general vectors with $v_k > k$ experience non-SPR index shifts when earlier coordinates are mutated (Proposition 2), and introduce an $O(N)$ **Cherry-First Gauge Relabeling** algorithm (Theorem 2) and an $O(N)$ **Exact Inverse Bijection** (Theorem 3) that together allow full unrooted SPR exploration within the cherry-first gauge $v_k^{(\pi)} \le k$.

3. **Multi-Coordinate (K-SPR) Batch Optimization (§5):** Exploiting the coordinate structure of $v^{(\pi)}$, we show how to select up to $K = 8$ node-disjoint improving rows from a single $O(N^2)$ discrete gradient evaluation and apply them simultaneously in one vector update, verified by a fast zero-copy leaf-only BME evaluator (Proposition 1).

4. **Extensive Empirical Verification and Benchmarking (§6):** We verify every theorem to IEEE-754 machine precision ($< 4 \times 10^{-14}$) and benchmark our C99 Phylo2Vec BME Optimizer head-to-head against a vectorized C99 implementation of FastME's full unrooted `bmeSPR` algorithm.

2 Preliminaries: BME, FastME, and Phylo2Vec

2.1 The Balanced Minimum Evolution (BME) Objective

Let $D \in \mathbb{R}_{\ge 0}^{N \times N}$ be a symmetric pairwise evolutionary distance matrix over N taxa $X = \{0, 1, \dots, N-1\}$ with $D_{xx} = 0$. For any unrooted binary tree T with leaf set X, let $|P_T(x, y)|$ denote the number of edges on the unique path between leaves x and y in T (so $|P_T(x, y)| - 1$ is the number of internal nodes on the path). By Pauplin's formula [1], the Balanced Minimum Evolution tree length $L(T)$ is given by

$$L(T) = \sum_{0 \le x < y < N} 2^{-\left(|P_T(x,y)|-1\right)} D_{xy} = \frac{1}{2} \sum_{x=0}^{N-1} \sum_{y \ne x} 2^{-\left(|P_T(x,y)|-1\right)} D_{xy}. \tag{3}$$

For any directed edge $e = (u \to v)$ in T, removing the edge (u, v) partitions T into two disjoint rooted subtrees: $T_u^{(v)}$ (rooted at u, pointing away from v) and $T_v^{(u)}$ (rooted at v, pointing away from u). The **balanced subtree distance** $D^{\text{bal}}(T_u^{(v)}, T_w^{(z)})$ between two disjoint directed subtrees is defined recursively by

$$D^{\text{bal}}(x, y) = D_{xy} \quad (x, y \in X), \qquad D^{\text{bal}}(T_u^{(v)}, S) = \frac{1}{2}\Big(D^{\text{bal}}(T_{c_1}^{(u)}, S) + D^{\text{bal}}(T_{c_2}^{(u)}, S)\Big), \tag{4}$$

where c_1, c_2 are the two neighbors of internal node u other than v.

Proposition 1 (Leaf-to-Parent BME Length Identity)**.** *For any unrooted binary tree T with leaf set $X = \{0, \dots, N-1\}$, let $p(x)$ denote the unique internal node adjacent to leaf x, and let $T_{p(x)}^{(x)}$ denote the complement subtree of leaf x (containing all $N-1$ leaves other than x). Then the BME tree length (3) is given exactly by the $O(N)$ sum*

$$L(T) = \frac{1}{2} \sum_{x=0}^{N-1} D^{bal}(x, T_{p(x)}^{(x)}). \tag{5}$$

Proof. In the rooted binary tree $T_{p(x)}^{(x)}$ rooted at $p(x)$ away from leaf x, every other leaf $y \ne x$ lies at depth $d_{p(x)}(y) = |P_T(x, y)| - 1$ bifurcations below $p(x)$. Unrolling the recursive average (4) from $p(x)$ down to the leaves of $T_{p(x)}^{(x)}$ weights each leaf $y \ne x$ by $2^{-(|P_T(x,y)|-1)}$. Summing over all $x \in \{0, \dots, N-1\}$ and dividing by 2 yields (3). □

2.2 FastME's $O(N^2)$ Recursive SPR Shift Formula

Suppose a subtree S is pruned from T (collapsing its attachment node p, thereby joining p's other two neighbor subtrees O_0 and O_1 directly) and regrafted onto a target edge e of $T \setminus S$. If S is moved across an internal node u of $T \setminus S$ from edge $e_1 = (C, u)$ to an adjacent edge $e_2 = (u, B)$ (where the third neighbor of u is A), this single-edge hop is a Nearest-Neighbor Interchange (NNI) between S and A. Desper and Gascuel [2] proved that the change in BME length for this hop is

$$\Delta L(e_1 \to e_2) = \frac{1}{4}\Big((D^{\text{bal}}(A, C') + D^{\text{bal}}(S, B)) - (D^{\text{bal}}(A, B) + D^{\text{bal}}(S, C'))\Big), \tag{6}$$

where C' denotes the subtree on the C-side of u *after* S has been pruned from C'. Specifically, if S was originally attached at topological distance $h \geq 1$ edges inside C from u, removing S from C modifies the balanced distance from A to C by

$$D^{\text{bal}}(A, C') = D^{\text{bal}}(A, C) + 2^{-h}(D^{\text{bal}}(A, O_{\text{opp}}) - D^{\text{bal}}(A, S)), \tag{7}$$

and updates $D^{\text{bal}}(S, C')$ along the traversal path via $D^{\text{bal}}(S, C'_{\text{next}}) = \frac{1}{2}(D^{\text{bal}}(S, C') + D^{\text{bal}}(S, A))$. Starting from the two branches O_0 and O_1 adjacent to S's original attachment node p (where $h = 1$, $\Delta L(e_{\text{orig}}) = 0$), two breadth-first traversals over $T \setminus S$ compute the cumulative SPR objective change $\Delta L(S \to e)$ for every edge $e \in T \setminus S$ in $O(N)$ time per pruned subtree S, or $O(N^2)$ time across all $\Theta(N)$ subtrees.

2.3 The Phylo2Vec Representation

Given $v = (v_0, \ldots, v_{N-2}) \in \mathcal{V}$ with $0 \leq v_i \leq 2i$, Phylo2Vec constructs a rooted binary tree on leaves $\{0, \ldots, N-1\}$ via an ordered list of $N-1$ cherry/branch merger pairs $\texttt{pairs}[0 \ldots N-2]$:

- Initialize $\texttt{pairs} \leftarrow [(0, 1)]$ (corresponding to $v_0 = 0$).
- For $i = 1, 2, \ldots, N-2$ (adding leaf $i+1$):
  - If $v_i \leq i$: prepend $(v_i, i+1)$ at index 0 of $\texttt{pairs}$.
  - If $v_i > i$: let $\text{idx} = v_i - i \in \{1, \ldots, i\}$, let $c_0 = \texttt{pairs}[\text{idx} - 1][0]$, and insert $(c_0, i+1)$ into $\texttt{pairs}$ at position idx.

Processing $\texttt{pairs}[0 \ldots N-2]$ sequentially with a disjoint-set (Union-Find) forest assigns internal node IDs $N, N+1, \ldots, 2N-2$ (where $2N-2$ is the rooted tree root). Contracting the two root edges incident to $2N-2$ into a single edge produces an unrooted binary tree $T(v)$ with $2N-2$ nodes ($0 \ldots N-1$ leaves and $N \ldots 2N-3$ internal nodes) and $2N-3$ unrooted edges.

3 Audit of the Prototype Notebook (`Tree_Attempt_5.ipynb`)

The prototype notebook (`Tree_Attempt_5.ipynb`) sought to compute the lower-triangular discrete gradient $\Delta_{i,j} = L(T(v^{(i \leftarrow j)})) - L(T(v))$ for $1 \leq i \leq N-2$ and $0 \leq j < i$. Our diagnostic evaluation uncovered both severe complexity bottlenecks and six correctness bugs:

3.1 Asymptotic Complexity Bottlenecks ($O(N^3)$ vs. $O(N^2)$)

Although the notebook used FastME's $O(N^2)$ BFS traversal in `find_objective_changes`, its preprocessing pipeline scaled as $\Theta(N^3)$:

1. **Repeated Dynamic Array Reallocation ($O(N^3)$ memory copies):** Inside the loop over all $2N-3$ edges, the notebook called `np.append(subtrees_all, ...)` at every step. Appending to a growing $(kN) \times N$ array $2N-3$ times copies $\sum_{k=1}^{2N-3} O(kN^2) = \Theta(N^3)$ floats ($\sim 91\%$ of total runtime at $N = 200$).

2. **Explicit Subtree Node-Set Enumeration ($O(N^3)$):** For each of the $2N-3$ edges, `make_subtree_distances` constructed $(2N-2)\times N$ leaf-membership tables and computed powers of two across all N leaves ($\Theta(N^2)$ work per edge, $\Theta(N^3)$ total).

3. **Quadratic Subtree Lookup ($O(N^2)$ with $72\times$ constant factor):** `find_moving_subtree` ran a nested triple loop of size $2N \times 3N$ per taxon to locate the rooted node $v_{\text{map}}[i+1]$ whose clade is pruned when v_i changes.

3.2 Six Algorithmic and Numerical Bugs Identified and Fixed

1. **Cell 3 Rooted/Unrooted Indexing Mismatch:** In `DiscreteGradient.calculate_discrete_gradi` `make_subtree` was called with `edge_locations_r` (rooted) instead of `edge_locations_u` (unrooted) for the unrooted half-tree, producing a 0.58 error in `subdist` even at $N = 9$.

2. **Heap Buffer Overflow in `find_moving_subtree` ($N \geq 50$):** The temporary buffer `outputs` was allocated with length $3(N-1)$, but a subtree with K internal nodes writes $4K-3$ entries (3 neighbors per internal node plus 1 per leaf), overflowing the heap whenever $K > \frac{3}{4}N$ and crashing Python with `malloc: Incorrect checksum for freed object`.

3. **Unrooted Root Parent Wrap (`parent == -1`):** When the moving clade $v_{\text{map}}[k]$ equals the unrooted trifurcating node $2N-3$, its parent in `parent_u` was -1 (wrapping to the last row of `edge_locations_u` in Python). In the unrooted topology, pruning the tworooted children of $2N-3$ leaves `other_root_child` as the attachment parent.

4. **Initial BFS Branch Overwrite:** In `find_objective_changes`, `if initial:` was left `True` for both branches leaving the starting node of each half-tree BFS, causing the second branch at depth 2 to use the unpruned distance D_{AB} instead of applying the 2^{-h} correction (7).

5. **Off-by-One Omission of $j = i$ in `destinations`:** The inner loop in `find_subtree_destinations` ran for `n in range(l_min + 1, l_max)` instead of `range(l_min, l_max - 1)`, leaving column $j = i$ unpopulated and restricting the gradient to $j < i$.

6. **Union-Find Corruption in `get_ancestry` When $v_k > k$:** To avoid Union-Find root lookups, the notebook tracked `siblings[c1] = c2` and updated `parents` only for `c1, c2, siblings[c1], siblings[c2], p1, p2`. Whenever a clade accumulates ≥ 3 leaves and a subsequent step has $v_k > k$ (referencing a leaf inside that clade), `siblings` only remembers the *most recent* sibling, leaving earlier leaves with stale `parents` pointers and producing a disconnected tree! Replacing `siblings` with a 2-line path-halving Union-Find (`while (p != parent[p]) { parent[p] = parent[parent[p]]; p = parent[p]; }`) eliminates the bug completely in $O(N)$ time.

4 Mathematical Theory of Full Phylo2Vec Discrete Gradients

Fixing the $O(N^3)$ bottlenecks yields an $O(N^2)$ two-pass dynamic program for `subdist`, but a deeper structural problem remains: the notebook only evaluated $0 \leq j < i$, covering $\binom{N-1}{2} \approx \frac{1}{2}N^2$ moves out of the $\sum_{i=1}^{N-2} 2i = (N-1)(N-2) \approx N^2$ coordinate changes in $0 \leq j \leq 2i$, and only prunes the $N-2$ clades in v_{map} rather than all $2N-3$ unrooted subtrees. We now solve both limitations rigorously.

4.1 Closed-Form Mapping for All $0 \leq j \leq 2i$ on Cherry-First Vectors

Definition 1 (Cherry-First Phylo2Vec Vector)**.** A Phylo2Vec vector $v \in \mathcal{V}$ is called *cherry-first* if $0 \leq v_i \leq i$ for all $i \in \{0, 1, \ldots, N-2\}$.

When v is cherry-first, every step $i = 1, \ldots, N-2$ in `get_rooted_edges` prepends $(v_i, i+1)$ to the front of `pairs`. Consequently, without any `memmove` shifts, the merger list is given directly in $O(N)$ closed form by

$$\texttt{pairs}[k] = \big(v_{N-2-k},\ N-1-k\big), \qquad k = 0, 1, \ldots, N-2, \tag{8}$$

and the k-th merger creates rooted internal node $m_k = N + k$.

Theorem 1 (Exact Full $0 \le j \le 2i$ Discrete Gradient Mapping)**.** *Let $v \in \mathcal{V}$ be a cherry-first Phylo2Vec vector ($0 \le v_k \le k$ for all k), and let $T(v)$ be its unrooted binary tree with internal nodes $\{N, \ldots, 2N-3\}$ and trifurcating root $r_u = 2N-3$, where $c_{other} = \min\big(child_1(2N-2), child_2(2N-2)\big)$ denotes the third neighbor of r_u. For any row $i \in \{1, \ldots, N-2\}$, let $S_i = v_{map}[i{+}1]$ be the rooted subtree pruned when mutating v_i, and let $\texttt{edge_delta}[u]$ ($0 \le u < r_u$) denote the FastME BME length change when regrafting S_i onto the unrooted edge $(u, p_u(u))$. Then for every $j \in \{0, 1, \ldots, 2i\}$, replacing $v_i \leftarrow j$ performs a single valid SPR move of S_i onto edge $\big(dest(i,j), p_u(dest(i,j))\big)$, and*

$$L\big(T(v^{(i \leftarrow j)})\big) - L\big(T(v)\big) = \texttt{edge_delta}\big[dest(i,j)\big], \tag{9}$$

where the target edge node $dest(i,j) \in \{0, \ldots, 2N-4\}$ is given in closed form by three regimes:

$$dest(i,j) = \begin{cases} \texttt{destinations}[i,j], & \text{if } 0 \le j \le i \quad \textit{(leaf-clade pendant edges)}, \\ (2N-2) - 2i + j, & \text{if } i < j \le 2i-2 \quad \textit{(internal edges)}, \\ c_{other}, & \text{if } j \in \{2i-1, 2i\} \quad \textit{(root edge)}. \end{cases} \tag{10}$$

Here $\texttt{destinations}[i,j]$ is initialized to j for $0 \le j \le i$ and updated in a single bottom-up pass over $m \in \{N, \ldots, 2N-3\}$ by setting $\texttt{destinations}[n_{idx}, l_{\min}(m)] \leftarrow m$ for all $l_{\min}(m) \le n_{idx} \le l_{\max}(m) - 2$.

Proof. Because $v_k \le k$ for all $k \ne i$, just before step i in `get_rooted_edges`, the i pairs formed by steps $1, \ldots, i-1$ have been prepended in reverse order, and the $N-2-i$ pairs formed by steps $i+1, \ldots, N-2$ will be prepended *in front of* step i's pair after step i. Thus:

1. If $0 \le j \le i$, step i prepends $(j, i+1)$ at the front of the current i-pair list, which subsequently shifts to index $k_i = N-2-i$ in the final `pairs` array. Any later merger $m \in \{N, \ldots, 2N-3\}$ that merges leaf $j = l_{\min}(m)$ with a leaf $l_{\max}(m) \le i+1$ was formed at step $l_{\max}(m) - 1 < i$ and therefore appears *after* index k_i in `pairs` (i.e., below m_{k_i} in the tree). The highest such node m is precisely $\texttt{destinations}[i,j]$, so $(j, i+1)$ attaches S_i directly above $\texttt{destinations}[i,j]$.

2. If $i < j \le 2i-2$, step i inserts $(c_0, i+1)$ at position idx $= j - i \in \{1, \ldots, i-2\}$ of the current i-pair list. Because all $N-2-i$ subsequent steps ($k > i$) have $v_k \le k$, they all prepend at index 0, shifting step i's insertion index by exactly $N-2-i$ to final index

$$k_{\text{final}} = (N-2-i) + (j-i) = (N-2) - 2i + j.$$

   The pair immediately preceding k_{final} in `pairs` is at index $k_{\text{final}} - 1$, which creates rooted internal node $m = N + (k_{\text{final}} - 1)$ before step i's pair merges m with S_i (shifting node indices $\ge m$ up by 1 so that in the original tree $T(v)$, that clade root is node $N + k_{\text{final}} = (2N-2) - 2i + j$). Hence S_i regrafts onto the parent edge of node $u = (2N-2) - 2i + j$.

3. Finally, if $j \in \{2i-1, 2i\}$, step i's pair is placed at the very end of `pairs` (index $N-3$ or $N-2$), which subdivides the rooted root edge connecting the two top clades $\text{child}_1(2N-2)$ and $\text{child}_2(2N-2)$. In the unrooted tree $T(v)$, this single edge is represented by node $c_{\text{other}} = \min(\text{child}_1(2N-2), \text{child}_2(2N-2))$.

□

4.2 Why General Vectors ($v_k > k$) Require Cherry-First Relabeling

What happens if we attempt to evaluate $\nabla_{\text{disc}} L(v)$ directly on a vector $v \in \mathcal{V}$ that *already* has $v_k > k$ at some later coordinate $k > i$?

Proposition 2 (Non-SPR Index Shifting When $v_k > k$)**.** *Suppose $v \in \mathcal{V}$ has $v_k > k$ for some $k \in \{2, \ldots, N-2\}$. Then mutating an earlier coordinate $v_i \leftarrow j$ $(1 \le i < k)$ changes the relative order of clades in* `pairs`$[0 \ldots k-1]$ *at step k. Because step k selects its target branch by positional offset $idx_k = v_k - k$ in* `pairs`*, mutating v_i simultaneously alters which branch step k splits, inducing a compound multi-clade topological rearrangement rather than a single SPR move.*

Proof. At step i, changing v_i from $v_i \le i$ (inserted at index 0) to $j > i$ (inserted at index $j - i > 0$), or even changing v_i between two values $j_1 < j_2 \le i$ when an intermediate step $m \in (i, k)$ has $v_m > m$, alters the elements occupying indices $0, \ldots, k-1$ of `pairs` when step k executes. Since step k reads $c_0 =$ `pairs`$[v_k - k - 1][0]$, shifting the contents of `pairs` causes leaf $k+1$'s clade to detach from its original branch and reattach to a different clade simultaneously with S_i's move. □

Proposition 2 explains why optimizing directly in raw coordinates $v \in \mathcal{V}$ without relabeling breaks the FastME single-SPR gradient after the first move with $v_i > i$. Fortunately, we can canonicalize *any* binary tree into a cherry-first vector in $O(N)$ time:

Theorem 2 ($O(N)$ Cherry-First Gauge Relabeling & Clade-Flip Duality)**.** *For any rooted binary tree T on N leaves $\{0, \ldots, N-1\}$ (including any tree decoded from a general Phylo2Vec vector $v \in \mathcal{V}$ with $0 \le v_i \le 2i$), there exists an $O(N)$ top-down traversal (*`relabel_cherry_first`*) that produces a leaf permutation $\pi \in S_N$ and a cherry-first Phylo2Vec vector $v^{(\pi)} \in \mathcal{V}$ satisfying*

$$0 \le v_i^{(\pi)} \le i \quad \forall i \in \{0, 1, \ldots, N-2\}, \qquad T(v^{(\pi)}) \cong \pi^{-1}(T(v)), \qquad L(T(v^{(\pi)}), D_\pi) = L(T(v), D), \tag{11}$$

where $(D_\pi)_{ab} = D_{\pi(a),\pi(b)}$. Furthermore, at every internal node m with children c_1, c_2, choosing which child retains the parent's representative label $x = rep[m]$ and which receives the new label $y = i + 1$ defines two dual cherry-first gauges:

- ***Standard Gauge (*`flip_mode` $= 0$*):** Assigns x to the child with smaller minimum leaf and $y = i + 1$ (the movable clade $v_{map}[i+1]$) to the child with larger minimum leaf.*
- ***Flipped Gauge (*`flip_mode` $= 1$*):** Swaps the roles of the two children at every internal node, turning the $N-2$ previously anchored sibling clades into the $N-2$ movable clades $v_{map}[2 \ldots N-1]$.*

Proof. At the root $r = 2N-2$ with children rc_1, rc_2, assign representative leaf labels $\text{rep}[c_{\text{stay}}] = 0$, $\text{rep}[c_{\text{move}}] = 1$, and set $v_0^{(\pi)} = 0$. Processing the remaining $N-2$ internal nodes m in reverse topological (top-down) order $m = 2N-3, 2N-4, \ldots, N$, node m has already been assigned a representative label $x = \text{rep}[m] \in \{0, \ldots, i\}$ where $i = 2N-2-m \in \{1, \ldots, N-2\}$. Assigning $\text{rep}[c_{\text{stay}}] \leftarrow x$ and $\text{rep}[c_{\text{move}}] \leftarrow i+1$ and setting $v_i^{(\pi)} \leftarrow x \le i$ guarantees that in the bottom-up reconstruction from `pairs`$[k] = (v_{N-2-k}^{(\pi)}, N-1-k)$, node m merges the exact clades c_{stay} and c_{move}. When the top-down pass reaches the leaves $l \in \{0, \ldots, N-1\}$, $\text{rep}[l] \in \{0, \ldots, N-1\}$ defines a bijection $\pi(\text{rep}[l]) = l$. Since each of the $N-1$ internal nodes is visited once in $O(1)$ time, the total time complexity is $O(N)$. □

Theorem 3 (Exact $O(N)$ Inverse Bijection `encode_rooted_to_v`)**.** *Given any rooted binary tree T with leaf labels $\{0, \ldots, N-1\}$ and internal node children $(child_1[u], child_2[u])$, let $l_{\min}(u) = \min(\min leaf(c_1), \min leaf(c_2))$, $l_{\max}(u) = \max(\min leaf(c_1), \min leaf(c_2))$, and let $c_{stay}(u)$ be the*

child achieving $l_{\min}(u)$*. Then the unique Phylo2Vec vector* $v \in \mathcal{V}$ *(*$0 \le v_i \le 2i$*) such that* $decode(v) = T$ *is recovered in* $O(N)$ *time (or* $O(N^2)$ *worst-case list insertion) by setting* $u_i =$ *node_of_lmax*$[i+1]$ *for each* $i = 1, \ldots, N-2$*, walking down* $w \leftarrow c_{stay}(w)$ *while* $w \ge N$ *and* $l_{\max}(w) > i+1$*, and setting:*

$$v_i = \begin{cases} w, & \text{if } w < N \quad (\textit{prepend } i+1 \textit{ at index } 0 \textit{ of } \texttt{pair_lmax_order}), \\ i + idx(l_{\max}(w)), & \text{if } w \ge N \quad (\textit{insert } i+1 \textit{ at } idx(l_{\max}(w)) \textit{ of } \texttt{pair_lmax_order}), \end{cases} \tag{12}$$

where $idx(l_{\max}(w)) - 1$ *is the position of* $l_{\max}(w)$ *in* `pair_lmax_order`*. For an unrooted tree* `adj_u`*, rooting canonically at the pendant edge of leaf* 0 *recovers a valid vector* $v \in \mathcal{V}$ *whose unrooted tree is isomorphic to* `adj_u`*.*

5 The Phylo2Vec Multi-Coordinate BME Optimizer

Combining Theorems 1–3 with Proposition 1 yields an end-to-end BME tree optimizer (`optimize_phylo2vec_bme` that overcomes FastME's one-move-per-iteration bottleneck:

1. **Cherry-First Gauge Maintenance ($O(N)$):** The optimizer maintains the current tree as a cherry-first pair $(v^{(\pi)}, \pi)$ with $v_i^{(\pi)} \le i$ and cached permuted distance matrix D_π. Whenever a move introduces entries $v_i^{(\pi)} > i$, `relabel_from_rooted_tree` (`flip_mode`=0) restores $v_i^{(\pi)} \le i$ in $O(N)$ time.

2. **Two-Pass $O(N^2)$ Matrix DP for `subdist`:** Using stackless forward and backward array passes over $u = N \ldots 2N-3$ and contiguous DFS interval slices `dfs_order`[`tin`$[c] \ldots$ `tin`$[c]+$ `sub_size`$[c]-1$], all $(2N-2) \times (2N-2)$ balanced subtree distances are computed in contiguous L1/L2 cache lines.

3. **Full $0 \le j \le 2i$ Discrete Gradient Scan ($O(N^2)$):** For each $v_{\text{index}} \in \{2, \ldots, N-1\}$, two non-recursive half-tree BFS traversals (`run_half_tree_bfs`) populate `edge_delta`$[0 \ldots 2N-4]$, and Theorem 1 extracts the best move $j_i^* \in \{0, \ldots, 2i\}$ and its BME change $\Delta_i^* = \min_j \nabla_{\text{disc}} L(v^{(\pi)})_{i,j}$ for every row i.

4. **Node-Disjoint Multi-Coordinate (K-SPR) Batch Update:** Unlike FastME, which can only apply a single SPR move per $O(N^2)$ scan, Phylo2Vec allows simultaneous updates $v_{r_m}^{(\pi)} \leftarrow j_{r_m}^*$ across multiple rows $r_1, \ldots, r_K$. We sort all improving rows ($\Delta_r^* < -10^{-12}$) from most negative to least negative and greedily select up to $K = 8$ rows whose pruned subtrees $T_{v_{\text{map}}[r+1]}$, anchor parents, and destination edges are mutually node-disjoint (checked in $O(1)$ amortized time via `tin`$[u]$ interval marking). We evaluate the batch candidate v_{cand} using our zero-copy leaf-only evaluator `evaluate_bme_length_fast` (which requires $\sim 8\times$ fewer memory writes than full `subdist`), halving the batch size $K \leftarrow K/2$ if higher-order SPR interaction terms reduce the gain below the best single move.

5. **Clade-Flip Duality & Full-Neighborhood Verification:** When no improving move exists in $0 \le j \le 2i$ ($\Delta_i^* \ge 0$ for all i), the optimizer applies `flip_mode` $= 1$ relabeling (Theorem 2) to swap anchored and movable clades, checks any remaining unpruned subtrees using the already-computed `subdist` matrix, and tests a 2-coordinate (2-SPR) basin-hopping kick along the two flattest positive-gradient coordinates ($\Delta_{r_1}^+ + \Delta_{r_2}^+ < 0.02$) to escape shallow local minima on noisy distance matrices.

6 Experimental Evaluation

All algorithms were implemented in C99 and compiled with Apple Clang (`/usr/bin/clang -O3 -march=native -ffast-math`) on macOS.

6.1 Methodological Note on the FastME Comparison

To ensure a rigorous, apples-to-apples comparison of the topological search algorithms without confounding text-file disk I/O or compiler differences, we implemented FastME's exact unrooted BME-SPR algorithm (`BMEAveragesTable` + `bmeSPR` from Desper & Gascuel 2002 [2] and Lefort et al. 2015 [3], scanning all $2N-3$ downward subtrees and $N-3$ upward subtrees at every iteration) directly in the same C99 translation unit (`optimize_fastme_bme_c`), using the exact same flat L1-cache-resident array layout, non-recursive half-tree BFS kernel (`run_half_tree_bfs`), memory workspace, and compiler flags. Both optimizers are initialized from the **exact same random starting tree** $T(v_{\text{init}})$ on every trial. (We also provide `compare_with_fastme_cli.py` to invoke the external `fastme` CLI binary via PHYLIP/Newick files when installed.)

6.2 Numerical Verification of Theorems 1–3

Table 1 summarizes the output of our automated verification suite (`verify_all.c`), comparing our closed-form $O(N^2)$ discrete gradients and $O(N)$ relabeling/bijection algorithms against brute-force $O(N^3)$ Pauplin topological path-length evaluations (3). Every test passes to IEEE-754 double-precision machine epsilon.

Table 1: Empirical verification of mathematical identities (`verify_all.c`).

Test Suite	Property Verified	Trials / Entries	Max Error / Success Rate
Theorem 1 ($0 \le j < i$)	Lower-triangular discrete gradient vs. Pauplin (3)	100 trees (17,100 moves)	3.375×10^{-14}
Theorem 1 ($0 \le j \le 2i$)	Full $0 \le j \le 2i$ discrete gradient vs. Pauplin (3)	100 trees (36,000 moves)	3.553×10^{-14}
Theorem 2 (`flip_mode` = 0)	Cherry-first relabeling $0 \le v_i^{\text{new}} \le i$ & $L(T)$ invariance	200 general trees ($N = 25$)	1.776×10^{-14} (100% valid)
Theorem 2 (`flip_mode` = 1)	Clade-flip relabeling $0 \le v_i^{\text{new}} \le i$ & $L(T)$ invariance	200 general trees ($N = 25$)	2.665×10^{-14} (100% valid)
Theorem 3 (Rooted)	Exact recovery encode_rooted(decode(v)) = v	1,000 general trees ($N = 40$)	**1000/1000** (100.0%)
Theorem 3 (Unrooted)	Isomorphic unrooted recovery from `adj_u`	1,000 general trees ($N = 40$)	**1000/1000** (0.000×10^{0})

6.3 Single-Evaluation Discrete Gradient Speedup

Table 2 compares the wall-clock time to compute a single discrete gradient matrix $\nabla_{\text{disc}} L(v)$ across tree sizes $N = 9$ to $N = 1{,}000$ between the original notebook (`Tree_Attempt_5.ipynb`), our pure-matrix Numba rewrite, and our C99 kernel (`phylo2vec_fastme.c`). Removing the $O(N^3)$ dynamic array appends and recursive masks yields a **1,089× speedup at** $N = 100$ and **5,220× speedup at** $N = 200$, computing a full $N = 1{,}000$ discrete gradient in just 20.1 ms.

Table 2: Wall-clock runtime for a single $O(N^2)$ discrete gradient evaluation.

Taxa N	Original Notebook (ms)	Matrix Numba (ms)	C99 Kernel (ms)	Speedup vs. Orig	Max Abs. Diff
9	0.454	0.0044	0.0018	**252**×	2.78×10^{-17}
20	1.922	0.0148	0.0061	**315**×	1.11×10^{-16}
50	12.492	0.0772	0.0329	**380**×	1.11×10^{-15}
100	156.880	0.3015	0.1440	**1,089**×	3.55×10^{-15}
200	3,059.100	1.2180	0.5860	**5,220**×	1.42×10^{-14}
500	—	9.8400	4.3500	—	—
1000	—	46.2000	20.1200	—	—

6.4 End-to-End Tree Optimization: Phylo2Vec BME vs. FastME SPR

We evaluated end-to-end tree reconstruction from random starting trees across $N \in \{20, 50, 100, 150, 200\}$ under two regimes:

1. **Benchmark 1 (Noiseless Additive Distance Matrices, $\sigma = 0.00$):** Ground-truth trees T^* were generated with uniform branch lengths $w_e \sim \text{Uniform}(0.05, 0.55)$ and exact

additive pairwise distances $D_{xy} = \sum_{e \in P_{T^*}(x,y)} w_e$. Since D is additive, the unique global minimum of the BME objective is the ground-truth topology T^* (RF = 0).

2. **Benchmark 2 (Noisy Phylogenetic Distance Matrices, $\sigma = 0.15$):** Realistic distance estimation noise was applied via symmetric log-normal perturbation $\tilde{D}_{xy} = D_{xy} \exp(\sigma Z_{xy})$, $Z_{xy} \sim \mathcal{N}(0, 1)$, creating rugged BME landscapes with local minima.

Tables 3 and 4 report the mean final BME tree length $L(T)$, the fraction of trials in which Phylo2Vec achieved a BME length less than or equal to FastME (P2V $\leq$ FME), the normalized Robinson-Foulds topological error (RF $\in [0, 1]$) against the ground-truth tree T^*, the number of $O(N^2)$ SPR iterations/gradient evaluations, and the wall-clock runtime in milliseconds.

Table 3: Benchmark 1: Noiseless Additive Tree Distances ($\sigma = 0.00$, Exact Ground-Truth Recovery).

N	FastME L	P2V L	P2V $\leq$ FME	FME RF	P2V RF	FME Iters	P2V Evals	FME (ms)	P2V (ms)	Speedup
20	5.45825	5.45825	**20 / 20**	0.0000	0.0000	13.7	11.5	0.117	0.084	**1.40**×
50	14.83082	14.83082	**20 / 20**	0.0000	0.0000	42.4	19.1	1.125	0.546	**2.06**×
100	29.56817	29.56817	**10 / 10**	0.0000	0.0000	97.7	33.7	8.131	3.337	**2.44**×
150	44.92155	44.92155	**5 / 5**	0.0000	0.0000	152.6	50.0	27.159	9.194	**2.95**×
200	58.90105	58.90105	**5 / 5**	0.0000	0.0000	211.2	66.8	63.285	21.314	**2.97**×

Table 4: Benchmark 2: Noisy Phylogenetic Distances ($\sigma = 0.15$, Log-Normal Estimation Noise).

N	FastME L	P2V L	P2V $\leq$ FME	FME RF	P2V RF	FME Iters	P2V Evals	FME (ms)	P2V (ms)	Speedup
20	5.48180	5.48180	**20 / 20**	0.0147	0.0147	13.9	11.7	0.066	0.052	**1.26**×
50	14.55934	14.55934	**20 / 20**	0.0149	0.0149	44.2	22.4	1.282	0.787	**1.63**×
100	29.52291	29.52291	**10 / 10**	0.0124	0.0124	100.4	38.0	7.747	3.259	**2.38**×
150	43.87382	43.87382	**5 / 5**	0.0068	0.0068	157.2	58.4	26.948	10.833	**2.49**×
200	59.13711	59.13711	**5 / 5**	0.0051	0.0051	228.6	78.6	68.383	25.124	**2.72**×

6.5 Discussion of Results

Three key findings emerge from Tables 3 and 4:

1. **100% Exact Ground-Truth Recovery on Additive Trees:** Across all 60 noiseless trials ($N = 20 \ldots 200$), the Phylo2Vec BME Optimizer recovers the exact ground-truth tree (RF = 0.0000) on 60/60 runs, proving that our full $0 \leq j \leq 2i$ gradient + $O(N)$ cherry-first gauge relabeling completely eliminates the neighborhood-restriction problem of the original $j < i$ formulation.

2. **100% Win/Tie Rate on Noisy Landscapes (**120/120 **Total Trials):** Across all 60 noisy trials ($\sigma = 0.15$), Phylo2Vec reaches the exact same optimal BME tree length and Robinson-Foulds accuracy as full unrooted FastME on every single instance (60/60).

3. **Up to 3.16× Fewer Gradient Evaluations and 2.97× Wall-Clock Speedup:** Whereas FastME requires 211.2 sequential $O(N^2)$ iterations at $N = 200$ (one SPR move per iteration), Phylo2Vec's node-disjoint multi-coordinate (K-SPR) batch updates converge in just 66.8 gradient evaluations, reducing wall-clock optimization time from 63.3 ms to 21.3 ms (**2.97× faster**). Moreover, the speedup grows monotonically with N (1.40× at $N = 20 \rightarrow 2.06\times$ at $N = 50 \rightarrow 2.44\times$ at $N = 100 \rightarrow 2.97\times$ at $N = 200$), because larger trees admit more mutually node-disjoint improving coordinates per batch step.

6.6 Large-N Multi-Core CPU and Metal GPU Acceleration ($N = 100 \ldots 4{,}000$)

As N scales beyond 1,000 leaves, the $(2N-2) \times (2N-2)$ clade distance matrix `subdist` exceeds CPU L2 cache (128 MB at $N = 2{,}000$; 512 MB in FP64 at $N = 4{,}000$). To unlock massive SIMT GPU and multi-core CPU parallelism without strided scatter writes or per-level kernel launch overhead, we proved and implemented four architectural reformulations in `bench_parallel_gpu.m`:

1. **Column-Independence Theorem for `subdist`:** In the bottom-up recurrence $\texttt{subdist}[u, x] = \frac{1}{2}(\texttt{subdist}[c_1(u), x] + \texttt{subdist}[c_2(u), x])$, each column x depends exclusively on entries within column x. Assigning GPU thread $\texttt{gid} = x$ allows all 32 threads in a SIMD-group to iterate over $u = N \ldots 2N-3$ in lockstep with 100% coalesced cache-line reads/writes and zero per-level barriers, separated by a single 2D tiled transpose between leaf columns $(0 \ldots N-1)$ and internal columns $(N \ldots 2N-3)$.

2. $O(N \log N)$ **Stackless Ancestor-Walk Top-Down Pass:** Because $\texttt{subdist}[p, v]$ is updated in the top-down pass if and only if p is a strict ancestor of v, thread v walks directly from `root_u` to v using a single Euler-tour comparison ($\texttt{tin}[v] < \texttt{tin}[c_2(p)]$) per step, reducing top-down work from $O(N^2)$ to $O(N \log N)$ and symmetrizing $\texttt{subdist}[v, p] = \texttt{subdist}[p, v]$ in-place.

3. **Heavy-First $\lceil \log_2(2N) \rceil$-Slot Register Stack:** By pushing the heavier subtree (`sub_size`) onto a LIFO stack first during the Stage 3 SPR traversal, stack depth is bounded by $\lfloor \log_2(2N-2) \rfloor + 2 \leq 16$ slots for any binary tree topology, replacing a 320 KB BFS queue with a 1 KB L1/register-resident stack.

4. $O(1)$ **Incremental Destination Mapping:** Because bottom-up Phylo2Vec merges satisfy $l_{\max}(N+k) = N-1-k$, stepping from row i to $i-1$ modifies only a single entry $\texttt{dest_row}[l_{\min}(k)] = N+k$, eliminating the $O(N^2)$ `destinations` matrix completely.

Table 5 benchmarks our 1-Core CPU baseline, 10-Core CPU parallel kernel, Apple M5 Metal GPU `subdist` shader, and Zero-Copy Hybrid GPU+CPU Unified Memory pipeline across $N = 100 \ldots 4{,}000$.

Table 5: Large-N Discrete Gradient Scaling on Apple M5 (10-Core CPU + 8-Core Metal GPU with Unified Memory).

N	1-Core Total	10-Core Total	CPU Spdup	1-Core `subdist`	GPU `subdist`	GPU Spdup	Hybrid Total	Hybrid Spdup
100	0.051 ms	0.073 ms	0.69×	0.013 ms	0.692 ms	0.02×	0.711 ms	0.07×
250	0.313 ms	0.234 ms	1.34×	0.081 ms	0.951 ms	0.08×	1.132 ms	0.28×
500	1.216 ms	0.503 ms	**2.42**×	0.317 ms	1.600 ms	0.20×	1.679 ms	0.72×
1,000	5.792 ms	2.186 ms	**2.65**×	1.561 ms	2.620 ms	0.60×	3.299 ms	**1.76**×
2,000	26.343 ms	9.278 ms	**2.84**×	8.861 ms	3.269 ms	**2.71**×	6.202 ms	**4.25**×
3,000	70.338 ms	30.692 ms	**2.29**×	23.210 ms	4.797 ms	**4.84**×	13.946 ms	**5.04**×
4,000	165.287 ms	46.283 ms	**3.57**×	41.183 ms	6.179 ms	**6.67**×	26.832 ms	**6.16**×

7 Conclusion

We have shown that computing BME discrete gradients in Phylo2Vec space not only matches FastME's $O(N^2)$ single-sweep complexity, but—when combined with our full $0 \leq j \leq 2i$ edge mapping (Theorem 1), $O(N)$ cherry-first gauge relabeling (Theorem 2), and node-disjoint multi-coordinate (K-SPR) batch updates—actually **beats FastME in end-to-end topological optimization speed by up to 2.97**× while achieving identical or superior BME tree lengths across 100% of tested datasets. Beyond distance-based hill-climbing, the ability to compute the full $(N-1) \times (2N-3)$ discrete gradient matrix $\nabla_{\text{disc}} L(v)$ in 0.14 ms ($N = 100$) to 20 ms

($N = 1000$) provides an ultra-fast, exact topological gradient oracle for variational phylogenetic inference, discrete Langevin MCMC proposals, and hybrid neural-phylogenetic optimizers.

References

[1] Y. Pauplin. Direct calculation of a tree length using a distance matrix. *Journal of Molecular Evolution*, 51(1):41–47, 2000.

[2] R. Desper and O. Gascuel. Fast and accurate phylogeny reconstruction algorithms based on the minimum-evolution principle. *Journal of Computational Biology*, 9(5):687–705, 2002.

[3] V. Lefort, R. Desper, and O. Gascuel. FastME 2.0: A comprehensive, accurate, and fast distance-based phylogeny inference program. *Molecular Biology and Evolution*, 32(10):2798–2800, 2015.

[4] M. J. Penn, N. Scheidwasser, M. P. Khurana, D. A. Duchêne, C. A. Donnelly, and S. Bhatt. Phylo2Vec: a vector representation for binary trees. *Systematic Biology*, 73(6):871–886, 2024.