L.J Institute of Engineering and Technology, Ahmedabad.

Computer Programming using Java-II PRACTICE BOOK (SEM-II-EVEN 2025-CE RELATED BRANCHES)

Note : This PRACTICE BOOK is only for reference purpose. LJU Test question paper may not be completely set from this PRACTICE BOOK.

Sr No	Unit Number	Question_Text	MCQ Answer	Marks	Option A	Option B	Option C	Option D
UNIT 6- Collection-Part 2								

246	6	What is the output of the following code?
		import java.util.*;
		class MCQ3{
		public static void main(String[] args) {
		PriorityQueue<String> bk = new PriorityQueue<String>();
		bk.add("paper");
		bk.add("pen");
		bk.add("pencil");
		System.out.println(bk.poll() + "," + bk.peek()); } }
			A	1	paper,pen	pen,pencil	pencil,	paper,pencil

247	6	What is the output?
		import java.util.*;
		class MCQ2{
		static PriorityQueue<String> pq = new PriorityQueue<String>();
		public static void main(String[] args) {
		System.out.print(pq.poll()+" ");
		pq.offer("Java");
		pq.offer("LJ");
		pq.offer("LJU");
		pq.offer("LJK");
		pq.poll();
		System.out.println(pq.poll()); } }
			B	1	Java LJ	null LJ	LJU LJK	null null

248	6	What is the output?
		import java.util.*;
		class HelloWorld {
		public static void main(String[] args) {
		
		PriorityQueue<Integer> queue = new PriorityQueue<Integer>();
		queue.add(10);
		queue.add(5);
		queue.add(8);
		queue.add(3);
		System.out.println(queue.poll() + " " + queue.peek()); } }
			C	1	10 5	3 8	3 5	10 3

249	6	What is the output?
		import java.util.*;
		class HelloWorld {
		public static void main(String[] args) {
		
		Queue<String> queue = new PriorityQueue<String>();
		queue.add("apple");
		queue.add("banana");
		queue.add("orange");
		queue.offer("pear");
		System.out.print(queue.remove() + " " + queue.element());
		System.out.println(queue); } }
			B	1	apple banana[pear, orange]	apple banana[banana, pear, orange]	pear orange[apple, banana, pear]	pear orange[apple, banana]

250	6	Which of the following methods is used to remove and return the head of a PriorityQueue?	D	1	remove()	poll()	peek()	Both remmove() and poll()

L.J Institute of Engineering and Technology, Ahmedabad.

Computer Programming using Java-II PRACTICE BOOK (SEM-II-EVEN 2025-CE RELATED BRANCHES)

Note : This PRACTICE BOOK is only for reference purpose. LJU Test question paper may not be completely set from this PRACTICE BOOK.

Sr No	Unit Number	Question_Text	MCQ Answer	Marks	Option A	Option B	Option C	Option D

251	6	What is the output of the following code?
		import java.util.*;
		class MCQ4{
		public static void main(String[] args) {
		ArrayDeque<String> ad = new ArrayDeque<String>();
		ad.add("cvm");
		ad.add("jjs");
		ad.add("pat");
		ad.add("akp");
		p(ad.peek());
		p(ad.peekFirst());
		p(ad.peekLast());
		p(ad.contains("Akp"));
		p(ad.poll());
		p(ad.pollLast());
		p(ad.pollFirst());
		p(ad.contains("PAT")); }
		private static void p(Object obj) {
		System.out.print(obj + "*"); } }
			A	1	cvm*cvm*akp*false*cvm*akp*jjs*false*	cvm*cvm*akp*true*cvm*akp*jjs*false*	cvm*cvm*akp*true*cvm*akp*jjs*true*	cvm*cvm*akp*false*cvm*akp*jjs*true*

252	6	What is the output?
		import java.util.*;
		class MCQ1{
		public static void main(String[] args) {
		ArrayDeque q = new ArrayDeque<>();
		q.add(10);
		q.peekFirst();
		q.addFirst(20);
		q.addFirst(30);
		q.addLast(50);
		q.addLast(40);
		for(int i=0;i<2;i++) {
		q.poll(); }
		q.peek();
		System.out.println(q); } }
			C	1	[10, 20, 30]	[10, 20, 30, 40]	[10, 50, 40]	[10, 20, 30]

253	6	What is the output?
		
		import java.util.*;
		class HelloWorld {
		public static void main(String[] args) {
		
		Deque<Integer> queue = new ArrayDeque<Integer>();
		queue.push(10);
		queue.push(5);
		queue.push(8);
		queue.push(3);
		System.out.println(queue.poll() + " " + queue.peek()); } }
			B	1	10 5	3 8	3 5	10 3

254	6	Which of the following methods is used to retrieve and remove the last element of an ArrayDeque?	A	1	removeLast()	pollFirst()	remove()	peekLast()

L.J Institute of Engineering and Technology, Ahmedabad.

Computer Programming using Java-II PRACTICE BOOK (SEM-II-EVEN 2025-CE RELATED BRANCHES)

Note : This PRACTICE BOOK is only for reference purpose. LJU Test question paper may not be completely set from this PRACTICE BOOK.

Sr No	Unit Number	Question_Text	MCQ Answer	Marks	Option A	Option B	Option C	Option D

255	6	What is the output of the following code?
		import java.util.*;
		
		class MCQ7{
		public static void main(String[] args) {
		HashSet<Double,String> ljMap = new HashSet<>();
		ljMap.put(10.23,"JJS");
		ljMap.put(100.23,"AKP");
		ljMap.put(100.23,"PAT");
		System.out.println(ljMap.get(100.23)); } }
			A	1	compile time error	AKP	PAT	JJS

256	6	What is the output of the following code?
		import java.util.*;
		class HelloWorld {
		public static void main(String[] args) {
		Set<String> set = new HashSet<String>();
		set.add("Java");
		set.add("Python");
		set.add("C++");
		set.add("Java");
		set.add("java");
		System.out.println(set.size()); } }
			C	1	2	3	4	5

257	6	import java.util.*;
		class Output
		{ public static void main(String args[]) {
		HashSet obj = new HashSet();
		obj.add("A");
		obj.add("B");
		obj.add("C");
		System.out.println(obj + " " + obj.size()); }}
			B	0.5	{A,B,C} 3	[A, B, C] 3	ABC 3	[A,B,C] 2

258	6	What is the output of the code?
		import java.util.*;
		class HelloWorld {
		public static void main(String[] args) {
		Set<Integer> set = new HashSet<Integer>();
		set.add(1);
		set.add(2);
		set.add(3);
		set.add(1);
		set.add(6/2);
		set.remove(2);
		for (Integer i : set) {
		System.out.print(i + " "); } } }
			D	1	1 2 3 1 3.0	1 3 1 3.0	1 3 3.0	1 3

L.J Institute of Engineering and Technology, Ahmedabad.

Computer Programming using Java-II PRACTICE BOOK (SEM-II-EVEN 2025-CE RELATED BRANCHES)

Note : This PRACTICE BOOK is only for reference purpose. LJU Test question paper may not be completely set from this PRACTICE BOOK.

Sr No	Unit Number	Question_Text	MCQ Answer	Marks	Option A	Option B	Option C	Option D

259	6	What is the output of the code?
		import java.util.*;
		class HelloWorld {
		public static void main(String[] args) {
		Set<String> set1 = new HashSet<String>();
		set1.add("Java");
		set1.add("Python");
		set1.add("C++");
		
		Set<String> set2 = new HashSet<String>();
		set2.add("java");
		set2.add("C++");
		set2.add("Python");
		System.out.println(set1.equals(set2)); } }
			A	1	false	true	Compile time error	Runtime Error

260	6	What is the output of the code?
		import java.util.*;
		class HelloWorld {
		public static void main(String[] args) {
		Set<Integer> set1 = new HashSet<Integer>();
		set1.add(1);
		set1.add(2);
		set1.add(3);
		Set<Integer> set2 = new HashSet<Integer>();
		set2.add(2);
		set2.add(3);
		set2.add(4);
		set1.addAll(set2);
		System.out.println(set1); } }
			A	1	[1, 2, 3, 4]	[1, 2, 3, 2,3,4]	[2, 3, 4, 1]	[1, 2, 3, 4, 2]

261	6	What is output?
		import java.util.*;
		class HelloWorld {
		public static void main(String[] args) {
		HashMap<String, Integer> map = new HashMap<>();
		map.put("John", 25);
		map.put("Jane", 30);
		System.out.println(map.get("John") + map.get("Jane")); } }
			C	1	25 30	2530	55	Compile time error

262	6	What is the output?
		import java.util.*;
		class HelloWorld {
		public static void main(String[] args) {
		HashMap<String, Integer> map = new HashMap<>();
		map.put("John", 25);
		map.put("Jane", 30);
		map.remove("John");
		System.out.println(map.size()); } }
			B	1	2	1	0	Compile time error

L.J Institute of Engineering and Technology, Ahmedabad.

Computer Programming using Java-II PRACTICE BOOK (SEM-II-EVEN 2025-CE RELATED BRANCHES)

Note : This PRACTICE BOOK is only for reference purpose. LJU Test question paper may not be completely set from this PRACTICE BOOK.

Sr No	Unit Number	Question_Text	MCQ Answer	Marks	Option A	Option B	Option C	Option D

263	6	What is the output?
		import java.util.*;
		class HelloWorld {
		public static void main(String[] args) {
		HashMap<Integer, String> map = new HashMap<>();
		map.put(1, "one");
		map.put(2, "two");
		map.put(3, "one");
		for (int key : map.keySet()) {
		System.out.println(key + " = " + map.get(key)); } } }
			B	1	1 = one
					2 = two
					3 = three
						1 = one
						2 = two
						3 = one
							1 = one
							2 = two
							3 = two
								1 = one
								2 = one
								3 = two

264	6	What is the output?
		import java.util.*;
		class HelloWorld {
		public static void main(String[] args) {
		HashMap<String, String> map = new HashMap<>();
		map.put("Java", "language");
		map.put("C++", "language");
		map.put("Google", "company");
		map.put("Apple", "company");
		int count = 0;
		for (String value : map.values()) {
		if (value.equals("language")) {
		count++;
		} }
		System.out.println(count); } }
			B	1	3	2	4	0

265	6	What is the output of the following code?
		import java.util.*;
		class HelloWorld {
		public static void main(String[] args) {
		HashMap<String, String> map = new HashMap<>();
		map.put("Java", "language");
		map.put("C++", "language");
		map.put("company", "company");
		map.put("Apple", "company");
		System.out.print(map.containsKey("Java")+" ");
		System.out.println(map.containsValue("company"));
		} }
			A	1	true true	true false	false false	false true

266	6	What is the output of the following code?
		import java.util.*;
		
		class MCQ6{
		public static void main(String[] args) {
		Map<Integer, Object> testMap = new HashMap<Integer, Object>();
		testMap.put(1, null);
		testMap.put(null, null);
		testMap.putAll(testMap);
		System.out.println(testMap); } }
			A	1	{null=null, 1=null}	{null=null, 1=null, null=null, 1=null}	run time error	{null=null, null=null}

L.J Institute of Engineering and Technology, Ahmedabad.

Computer Programming using Java-II PRACTICE BOOK (SEM-II-EVEN 2025-CE RELATED BRANCHES)

Note : This PRACTICE BOOK is only for reference purpose. LJU Test question paper may not be completely set from this PRACTICE BOOK.

Sr No	Unit Number	Question_Text	MCQ Answer	Marks	Option A	Option B	Option C	Option D

267	6	What is the output?
		import java.util.*;
		class MCQ5{
		public static void main(String[] args) {
		Map<Integer, Object> sampleMap = new HashMap<Integer, Object>();
		sampleMap.put(1, null);
		sampleMap.put(5, null);
		sampleMap.put(3, null);
		sampleMap.put(2, null);
		sampleMap.put(4, null);
		System.out.println(sampleMap); } }
			B	1	compile time error	{1=null, 2=null, 3=null, 4=null, 5=null}	run time error	{null=null, null=null, null=null, null=null, null=null}

268	6	What is the output of the Java code snippet?
		import java.util.*;
		class MCQ{
		public static void main(String[] args) {
		HashMap<Integer, Object> HashSet = new HashMap<Integer, Object>();
		HashSet.put(1, null);
		HashSet.put(null, null);
		HashSet.putAll(HashSet);
		System.out.println(HashSet); } }
			A	1	{null=null, 1=null}	[null=null, 1=null]	{[null=null, 1=null]}	Compile time error

269	6	What is the output of the Java code snippet?
		import java.util.*;
		class HelloWorld {
		public static void main(String[] args) {
		Hashtable<String, String> table = new Hashtable<>();
		table.put("Java", "language");
		table.put("C++", "language");
		table.put("company", "company");
		table.put("Apple", "company");
		System.out.print(table.containsKey("Java")+" ");
		System.out.println(table.get("company")); } }
			B	1	true true	true company	false false	false Apple

270	6	What is a HashMap in Java?	B	1	A collection that stores unique elements in no particular order	A collection that stores key-value pairs in no particular order	A collection that stores elements in a specific order	A collection that allows duplicate elements
271	6	Which of the following is NOT a method in the HashMap class?	C	1	put()	get()	add()	remove()
272	6	Which method is used to retrieve the value associated with a given key in a HashMap?	A	1	get()	remove()	peek()	size()
273	6	What happens if we put a key object in a HashMap which exists?	A	1	The new object replaces the older object	The new object is discarded	The old object is removed from the map	It throws an exception as the key already exists in
274	6	If two threads access the same hashmap at the same time, what would happen?	C	1	NullPointerException	ClassNotFoundException	ConcurrentModificationException	RuntimeException

L.J Institute of Engineering and Technology, Ahmedabad.

Computer Programming using Java-II PRACTICE BOOK (SEM-II-EVEN 2025-CE RELATED BRANCHES)

Note : This PRACTICE BOOK is only for reference purpose. LJU Test question paper may not be completely set from this PRACTICE BOOK.

Sr No	Unit Number	Question_Text	MCQ Answer	Marks	Option A	Option B	Option C	Option D
275	6	What is the main difference between a HashMap and a HashTable?	B	1	HashMap is thread-safe, whereas HashTable is not	HashTable is thread-safe, whereas HashMap is not	HashMap uses put method and HashTable uses add method	HashTable allowes null in key and value whereas HashMap does not allow
276	6	What happens if we try to insert a null value into a HashTable?	A	1	A NullPointerException is thrown	The value is inserted as null	The value is ignored	An IllegalArgumentException is thrown
277	6	What is the load factor of a HashTable?	C	1	The number of key-value pairs stored in the table	The capacity of the table	The maximum number of collisions allowed before the table is resized	The threshold at which the table is resized
278	6	Which of the following methods returns a collection view of the mappings contained in a HashTable?	D	1	keys()	values()	elements()	entrySet()
279	6	Write a Java program that takes a list of integers as input from the user and stores them in a PriorityQueue. The program should then remove and display the top three highest integers from the PriorityQueue.		5				
280	6	Sports tournament organizer: Write a program that simulates a sports tournament using a PriorityQueue. The program should allow the user to input team names and their win-loss records. The program should then prioritize teams based on their win-loss records and add them to the PriorityQueue. When it's time for the next match, the program should remove the two highest priority teams from the PriorityQueue and display their names.		5				
281	6	Write a program that simulates a queue of customers at a coffee shop using an ArrayDeque. The program should allow the user to perform the following actions: Add a new customer to the back of the queue Serve the next customer in the queue (i.e. remove the customer from the front of the queue) View the current queue of customers The program should continue to prompt the user for actions until they choose to quit.		5				
282	6	Music player playlist: Write a program that simulates a music player playlist using an ArrayDeque. The program should allow the user to add songs to the playlist, play the next or previous song in the playlist, and shuffle the playlist. The program should keep track of the songs in the playlist using an ArrayDeque, where each element in the deque represents a song. When the user adds a song, you can use the addLast method to add it to the end of the playlist. When the user plays the next or previous song, you can use the removeFirst or removeLast method, respectively, to remove the current song from the front or back of the deque and add it to the end or beginning of the deque. When the user shuffles the playlist, you can use the shuffle method to randomly reorder the songs in the deque.		7				

L.J Institute of Engineering and Technology, Ahmedabad.

Computer Programming using Java-II PRACTICE BOOK (SEM-II-EVEN 2025-CE RELATED BRANCHES)

Note : This PRACTICE BOOK is only for reference purpose. LJU Test question paper may not be completely set from this PRACTICE BOOK.

Sr No	Unit Number	Question_Text	MCQ Answer	Marks	Option A	Option B	Option C	Option D
283	6	Make the system as User interactive and give choices to user. Web browser history: Write a program that simulates a web browser history using an ArrayDeque. The program should allow the user to navigate back and forward through their history of visited web pages, similar to how a web browser works. The program should keep track of the URLs of visited web pages using an ArrayDeque, where each element in the deque represents a visited web page. When the user navigates to a new web page, you can push the URL onto the deque. When the user navigates back or forward, you can pop URLs off the front or back of the deque, respectively.		5				
284	6	In my restaurant I used to manage it well as per the order. I never want to skip any order from the customer. So I prepare a rule: When I get the order I add it in the last of my cook queue. And when the order is ready I used to pick it up from the first of the cook queue. So, write a java program with class Restaurant. Create a queue cook which contains item names. Ask user weather he wants to Order or take food. If user press 1 then ask for the name of the item and it should be added in the cook queue. If user press 2 then The first item from the queue should be removed from the queue. If user press 3 then he can see the items of the queue. If user press 4 then he should move out from the Restaurant.		6				
285	6	Write a java program that reads in a list of integers from the user and stores them in a HashSet. The program should then compute the sum of all unique integers in the HashSet and output the result to the user. If the user enters the same integer multiple times, it should only be counted once in the sum.		4				
286	6	Write a program that reads in a list of words from the user and stores them in a HashSet. The program should then prompt the user for a prefix and output all the words in the set that start with that prefix.		4				
287	6	Write a program that reads in a list of names and corresponding phone numbers from the user, and stores them in a HashMap. The program should then prompt the user for a name and output the corresponding phone number, or a message indicating that the name is not in the map.		5				
288	6	Write a program that reads in a list of stock prices for a company and stores them in a HashMap, where the key is the date and the value is the price. The program should then compute the average price for the entire period and output it to the user.		5				

L.J Institute of Engineering and Technology, Ahmedabad.

Computer Programming using Java-II PRACTICE BOOK (SEM-II-EVEN 2025-CE RELATED BRANCHES)

Note : This PRACTICE BOOK is only for reference purpose. LJU Test question paper may not be completely set from this PRACTICE BOOK.

Sr No	Unit Number	Question_Text	MCQ Answer	Marks	Option A	Option B	Option C	Option D
289	6	Write a program that reads in a list of words from a file and stores them in a HashMap, along with their frequency (i.e. how many times they appear in the file). The program should then prompt the user for a word and output the corresponding frequency, or a message indicating that the word is not in the map.		6				
290	6	Write a Java program that takes in a list of student names and their grades from the user and stores them in a HashTable. The program should then prompt the user for a student name and output their grade. If the student name is not found in the HashTable, the program should output an error message.		5				
291	6	Write a Java program that implements a HashTable to store a dictionary of words and their definitions. The program should prompt the user for a word and output its definition. If the word is not found in the HashTable, the program should ask the user if they would like to add the word and its definition to the HashTable. The program should use the following methods of the HashTable class: put(K key, V value): Adds a key-value pair to the HashTable. In this program, it should be used to add new words and their definitions. get(Object key): Retrieves the value associated with the given key from the HashTable. In this program, it should be used to retrieve the definition of a word. containsKey(Object key): Returns true if the HashTable contains a mapping for the specified key. In this program, it should be used to check if a word is already in the HashTable. keySet(): Returns a Set of all keys in the HashTable. In this program, it should be used to print out a list of all words in the dictionary.		5				

L.J Institute of Engineering and Technology, Ahmedabad.

Computer Programming using Java-II PRACTICE BOOK (SEM-II-EVEN 2025-CE RELATED BRANCHES)

Note : This PRACTICE BOOK is only for reference purpose. LJU Test question paper may not be completely set from this PRACTICE BOOK.

Sr No	Unit Number	Question_Text	MCQ Answer	Marks	Option A	Option B	Option C	Option D
292	6	Write a Java program that creates a HashTable to store information about books in a library. The HashTable should use the book titles as keys and store information about each book, such as the author, publisher, and year of publication. The program should provide the following functionality: Add a book: The program should prompt the user for a book title, author, publisher, and year of publication, and add the book to the HashTable. Remove a book: The program should prompt the user for a book title and remove the corresponding entry from the HashTable. Search for a book: The program should prompt the user for a book title and output the corresponding information stored in the HashTable, such as the author, publisher, and year of publication. If the book title is not found in the HashTable, the program should o List all books: The program should list all books in the HashTable, along with their corresponding information.To accomplish these tasks, you can use the following HashTable methods: put(key, value): Inserts a key-value pair into the HashTable. remove(key): Removes a key-value pair from the HashTable. get(key): Returns the value corresponding to a given key in the HashTable. containsKey(key): Returns true if the HashTable contains a given key. keySet(): Returns a Set of all the keys in the HashTable.		5				
UNIT 7- IO Programming								
293	7	Which of these stream contains the classes which can work on character stream?	C	1	InputStream	OutputStream	Character Stream	All of the mentioned
294	7	Which of these classes are used by Byte streams for input and output operation?	A	1	InputStream	InputOutputStream	Reader	All of the mentioned
295	7	Which of these methods can be used to writing console output?	D	1	print()	println()	printOut()	A and B Both
296	7	The …….. package contains a large number of stream classes that provide capabilities for processing all types of data.	B	1	java.awt	java.io	java.util	java.net
297	7	The InputStream class defines methods for performing input functions such as i) reading bytes ii) closing streams iii) skipping ahead in a stream iv) flushing streams	B	1	ii, iii and iv only	i, ii and iii only	i, iii and iv only	All i, ii, iii and iv
298	7	Which of the following method(s) not included in InputStream class.	C	1	available( )	reset( )	flush()	close()
299	7	_____ returns true if called on a file and returns false when called on a directory.	C	1	IsFile()	Isfile()	isFile()	isfile()

L.J Institute of Engineering and Technology, Ahmedabad.

Computer Programming using Java-II PRACTICE BOOK (SEM-II-EVEN 2025-CE RELATED BRANCHES)

Note : This PRACTICE BOOK is only for reference purpose. LJU Test question paper may not be completely set from this PRACTICE BOOK.

Sr No	Unit Number	Question_Text	MCQ Answer	Marks	Option A	Option B	Option C	Option D

300	7	What will be output for the following code?
		import java.io.*;
		class files
		{
		public static void main(String args[])
		{
		File obj = new File("/java/system");
		System.out.print(obj.getName());
		}
		}
			B	1	java	system	java/system	/java/system

301	7	What will be output for the following code? Note: file is made in c drive
		import java.io.*;
		class files
		{
		public static void main(String args[])
		{
		File obj = new File("/java/system");
		System.out.print(obj.canWrite());
		System.out.print("" "" + obj.canRead());
		}
		}
		(Note :- Consider, file is not existing)
			D	1	true false	false true	true true	false false

302	7	Which stream does Java application uses to read data from a source, it may be a file, an array, peripheral device or socket?	A	1	InputStream	OutputStream	Input/OutputStream	None of the above
303	7	Which class gives you access to the attribute of a file?	C	1	InputStream	OutputStream	File	None of the above

304	7	What is the output of the following code?
		import java.io.*;
		class MCQ9{
		public static void main(String[] args) {
		File f1 = new File("D://java.txt");
		boolean bool2 = f1.exists();
		boolean bool1 = f1.equals(f1);
		bool1 = bool2;
		System.out.println(bool2);
		}
		}
		(Note :- Consider, file is not existing)
			A	1	false	true	compile tiem error	run time error

L.J Institute of Engineering and Technology, Ahmedabad.

Computer Programming using Java-II PRACTICE BOOK (SEM-II-EVEN 2025-CE RELATED BRANCHES)

Note : This PRACTICE BOOK is only for reference purpose. LJU Test question paper may not be completely set from this PRACTICE BOOK.

Sr No	Unit Number	Question_Text	MCQ Answer	Marks	Option A	Option B	Option C	Option D

305	7	Consider there is directory LJU having some files inside. Select answer based on this code.
		
		import java.io.File;
		public class FileListExample {
		public static void main(String[] args) {
		File directory = new File("LJU");
		String[] files = directory.list();
		for (String file : files) {
		if (file.isFile()) {
		System.out.println(file); } }
		} }
			D	1	The code will throw a NullPointerException at runtime.	The code will only print the names of all files in the specified directory.	The code will only print the names of all directories in the specified directory.	The code will fail to compile.

306	7	What is the output of the Java code snippet?
		import java.io.*;
		class MCQ{
		public static void main(String[] args) throws IOException {
		File f = new File("D://txt.text");
		System.out.println(f.getPath().length()+f.getAbsolutePath().length());
		}
		}
			C	1	19	20	22	24

307	7	What is the output of the Java code snippet?
		import java.io.*;
		class HelloWorld {
		public static void main(String[] args) throws IOException {
		File dir = new File("LJU.txt");
		File file = new File("LJU.txt");
		dir.mkdir();
		System.out.println(file.exists() +" "+ file.isFile()); } }
			C	1	true true	false true	true false	false false

308	7	What is the output of the following Java code Snippet?
		import java.io.*;
		class Main{
		public static void main(String[] args) throws IOException {
		File f=new File("D://ABC.txt");
		System.out.println(f.getPath().length()); }}
			C	1	3	6	10	Runtime Error

309	7	Before executing below code, consider D drive is empty(not a single file or folder is available inside it). What will be the output if we execute this code for the first time?
		import java.io.*;
		class Test{
		public static void main(String[] args) throws IOException {
		File f1=new File("D://ABC.txt");
		f1.createNewFile();
		File f2=new File("D://ABC");
		System.out.print(f1.mkdir());
		System.out.print(f2.exists()); }}
			C	1	truetrue	truefalse	falsefalse	Compile Error

L.J Institute of Engineering and Technology, Ahmedabad.

Computer Programming using Java-II PRACTICE BOOK (SEM-II-EVEN 2025-CE RELATED BRANCHES)

Note : This PRACTICE BOOK is only for reference purpose. LJU Test question paper may not be completely set from this PRACTICE BOOK.

Sr No	Unit Number	Question_Text	MCQ Answer	Marks	Option A	Option B	Option C	Option D

310	7	What is the output of the following code?
		import java.io.*;
		import java.lang.String;
		import java.io.FileInputStream;
		class test {
		public static void main(String args[]) {
		try {
		// Suppose, the input.txt file contains the following text
		// This is a line of text inside the file.
		FileInputStream input = new FileInputStream("input.txt");
		// Reads 3 bytes from the file
		input.read();
		input.read();
		input.read();
		// Returns the number of available bytes
		System.out.println("Available bytes " + input.available());
		input.close(); }
		catch (Exception e) {} } }
			B	1	Available bytes 39	Available bytes 36	Available bytes 35	Available bytes 37

311	7	Which of these is used to read a string from the input stream?	C	1	get()	read()	readLine()	getLine()
312	7	Which of these class contains the methods print() & println()?	D	1	System	System.out	BUfferedOutputStream	PrintStream
313	7	Which of these class can be used to take input from console ?	D	1	Scanner	InputStreamReader	FileOutputStream	A and B Both
314	7	File class is _____	C	1	An abstract of file representation only	An abstarct of path name only	An abstract which can be use to represent path name or file	An abstarct which ca represent a file in any formate
315	7	what will be happen if write a following line File f1 = new File("dirname"); File f2 = new File(f1, "filename")	D	1	A new directory called dirname is created in the current working directory	A new directory called dirname is created in the current working directory. A new file called filename	A new file called filename is created in the current working directory.	No directory is created, and no file is created.
316	7	What value does read( ) return when it has reached the end of a file?	B	1	0	-1	1	null
317	7	How can you change the current working directory using an instance of the File class called FileName ?	D	1	FileName.chdir("DirName").	FileName.cd("DirName").	FileName.cwd("DirName").	The File class does not support directly changing the current directory.

L.J Institute of Engineering and Technology, Ahmedabad.

Computer Programming using Java-II PRACTICE BOOK (SEM-II-EVEN 2025-CE RELATED BRANCHES)

Note : This PRACTICE BOOK is only for reference purpose. LJU Test question paper may not be completely set from this PRACTICE BOOK.

Sr No	Unit Number	Question_Text	MCQ Answer	Marks	Option A	Option B	Option C	Option D

318	7	What is the output of the following Java code snippet ?
		import java.io.*;
		class Test3{
		public static void main(String[] args) throws IOException {
		FileOutputStream fos=new FileOutputStream(“abc.txt”);
		byte[] b={97,98,99,100};
		fos.write(b);
		fos.write(“Hello”.getBytes());
		fos.close();
		FileInputStream fis=new FileInputStream(“abc.txt”);
		int i = fis.read();
		while(i != -1){
		System.out.print((char)i);
		i=fis.read(); }
		fis.close(); }}
			B	1	97	abcdHello	Hello	Compile Error

319	7	Write a java program which read source file and destination file name and copy the content of source file to destination file using InputeStream class.		4				
320	7	Write a java program which read numbers from number.txt file and store even number to even.txt and odd number into odd.txt file		4				
321	7	Read employee salary and calculate the income tax based on 10% of income and store it in tax.txt file for five different employees.		5				
322	7	Write a program that counts the no. of words in a text file. The file name is passed as a command line argument. The program should check whether the file exists or not. The words in the file are separated by white space characters		4				
323	7	Write a program to check that whether the name given from command line is file or not? If it is a file then print the size of file and if it is directory then it should display the name of all files in it.		5				
324	7	Write a program to check that whether the name given from command line is file or not? If it is a file then print the path of file and if it is directory then it should display the length of all files in it.		5				
325	7	Write a program that reads file name from user, through command line argument and displays/reads content of the text file on console.		4				
326	7	Write a program to create directories (/home/abc/bcd/def/ghi/jkl) in the home directory /home/abc and list the files and directories showing file/directory,file size. Read-writeexecute permissions.		5				
327	7	Write a program to find the sum of all the number in Number.txt file and print the result in console.		4				
328	7	Write a program to create a new file and write the number into it and sort that file content into different file.		4				
UNIT 8- Character Stream								
329	8	Which of these class is used to read characters in a file	A	1	FileReader	FileWriter	FileInputStream	InputStreamReader
330	8	Which of these method of FileReader class is used to read characters from a file?	A	1	read()	scanf()	get()	getInteger()

L.J Institute of Engineering and Technology, Ahmedabad.

Computer Programming using Java-II PRACTICE BOOK (SEM-II-EVEN 2025-CE RELATED BRANCHES)

Note : This PRACTICE BOOK is only for reference purpose. LJU Test question paper may not be completely set from this PRACTICE BOOK.

Sr No	Unit Number	Question_Text	MCQ Answer	Marks	Option A	Option B	Option C	Option D
331	8	The …….. class implements the DataInput and DataOutput interfaces for performing I/O using the primitive data types.	A	1	RandomAccessFile	OutputStream Reader	InputStreamReader	DataOutputStream

332	8	What will be the output of the following program?
		import java.io.*;
		public class ExampleRandomAccessfile {
		public static void main(String[] args) throws IOException {
		File file = new File("Alphabets.txt");
		RandomAccessFile raf = new RandomAccessFile(file, "rw");
		raf.write("ABCDE\nFGHIJK".getBytes());
		System.out.print(raf.readLine() + "~");
		raf.seek(1);
		System.out.print(raf.readLine());
		raf.close();
		} }
			B	1	ABCDE~BCDE	null~BCDE	null~null	compile time error

L.J Institute of Engineering and Technology, Ahmedabad.

Computer Programming using Java-II PRACTICE BOOK (SEM-II-EVEN 2025-CE RELATED BRANCHES)

Note : This PRACTICE BOOK is only for reference purpose. LJU Test question paper may not be completely set from this PRACTICE BOOK.

Sr No	Unit Number	Question_Text	MCQ Answer	Marks	Option A	Option B	Option C	Option D

333	8	What will be the output of the following program?
		import java.io.*;
		public class HaphazardAccess {
		public static void main(String[] args) throws Exception {
		File file = new File("Alphabets.txt");
		RandomAccessFile raf = new RandomAccessFile(file, "rw");
		raf.write("ABCDEFGHIJKLMNOP\nQRSTUVWXYZ\n".getBytes());
		System.out.print(raf.readLine() + "~");
		raf.seek(20);
		System.out.print(raf.readLine() + "~");
		raf.write("1234567890\n1234567890\n1234567890\n1234567890\n".get
		Bytes());
		raf.setLength(40);
		System.out.print(raf.readLine() + "~");
		raf.seek(30);
		System.out.print(raf.readLine() + "~");
		raf.seek(0);
		System.out.print(raf.readLine() + "~");
		raf.close(); } }
			D	1	ABCDEFGHIJKLMNOP~TUV
					WXYZ~null~34567890~ABC
					DEFGHIJKLMNOP~
						null~TUVWXYZ~null~null~
						ABCDEFGHIJKLMNOP~
							Runtime Error	null~TUVWXYZ~null~34567
								890~ABCDEFGHIJKLMNOP
								~

334	8	What will be the output of the following program?
		import java.io.*;
		public class ExampleRandomAccessfile {
		public static void main(String[] args) throws IOException {
		File file = new File("Alphabets.txt");
		RandomAccessFile raf = new RandomAccessFile(file, "rw");
		raf.write("ABCDE\nFGHIJK".getBytes());
		System.out.print(raf.readLine() + "~");
		raf.seek(1);
		System.out.print(raf.readLine() + "~");
		raf.write("12345\n6789".getBytes());
		raf.seek(3);
		System.out.print(raf.readLine());
		raf.close();
		} }
			C	1	ABCDE~BCDE~DE	ABCDE~BCDE~45	null~BCDE~DE	null~BCDE~45

335	8	What is the output of the following code?
		import java.io.*;
		class MCQ{
		public static void main(String[] args) throws IOException{
		File f1 = new File("lj.txt");
		FileWriter fw = new FileWriter(f1);
		fw.write("HOW ARE YOU");
		fw.close();
		FileReader fr = new FileReader(f1);
		int r = fr.read();
		int i=10;
		while(i>6){
		r = fr.read();
		i=i-4; }
		System.out.println((char)r); } }
			B	1	H	O	C	A

L.J Institute of Engineering and Technology, Ahmedabad.

Computer Programming using Java-II PRACTICE BOOK (SEM-II-EVEN 2025-CE RELATED BRANCHES)

Note : This PRACTICE BOOK is only for reference purpose. LJU Test question paper may not be completely set from this PRACTICE BOOK.

Sr No	Unit Number	Question_Text	MCQ Answer	Marks	Option A	Option B	Option C	Option D

336	8	What is the output of the following code?
		import java.io.*;
		class MCQ{
		public static void main(String[] args) throws IOException{
		File f1 = new File("lj.txt");
		FileWriter fw = new FileWriter(f1);
		fw.write("TU SHER HAI MERE BHAI SHER");
		fw.close();
		FileReader fr = new FileReader(f1);
		int r = fr.read();
		int i=10;
		while(i>6){
		r = fr.read();
		i=i-4; }
		System.out.println((char)r); } }
			B	1	T	U	H	S

337	8	What is the output of the Java code snippet?
		import java.io.*;
		class NewMCQ {
		public static void main(String[] args) throws IOException {
		File f = new File("Hello World.txt");
		FileWriter file = new FileWriter(f);
		file.write("Hello\n");
		System.out.print(f.length());
		file.write(65);
		System.out.print(f.length());
		file.close();
		} }
			B	1	61	00	62	71

338	8	What is the output? if prompted in console, user inputs: ABC.JAVA
		import java.io.*;
		class ReadLine {
		public static void main(String[] args) throws IOException {
		InputStreamReader file = new InputStreamReader(System.in);
		BufferedReader line = new BufferedReader(file);
		System.out.println(line.read()); } }
			B	0.5	66	65	97	67

339	8	//What is the output? if prompted in console, user inputs: XYZ.JAVA
		import java.io.*;
		class ReadLine {
		public static void main(String[] args) throws IOException {
		InputStreamReader file = new InputStreamReader(System.in);
		BufferedReader line = new BufferedReader(file);
		System.out.println(line.read()); } }
			A	1	88	89	90	91

340	8	Which of these class is used to read characters and strings in Java from console?	A	1	BufferedReader	BufferedInputStreamReader	BufferedStreamReader	InputStreamReader
341	8	Which of these classes are used by character streams output operations?	B	1	InputStream	Writer	ReadStream	InputOutputStream
342	8	RandomAccessFile cab be use to _____	C	1	read from random access file	write from random access file	read and write from random access file	restrict read and write to a random access file
343	8	Reader class is _____	A	1	abstarct class to read the character stream	used to read from file	abstarct class to input the character stream	used to take input from standard input stream

L.J Institute of Engineering and Technology, Ahmedabad.

Computer Programming using Java-II PRACTICE BOOK (SEM-II-EVEN 2025-CE RELATED BRANCHES)

Note : This PRACTICE BOOK is only for reference purpose. LJU Test question paper may not be completely set from this PRACTICE BOOK.

Sr No	Unit Number	Question_Text	MCQ Answer	Marks	Option A	Option B	Option C	Option D
344	8	What value does readLine( ) return when it has reached the end of a file?	D	1	NULL	-1	0	null

345	8	import java.io.*;
		import java.lang.String;
		class test {
		public static void main(String[] args) throws IOException {
		// Object of RandomAccessFile
		RandomAccessFile raf = new RandomAccessFile("input.txt","r");
		// Suppose, the input.txt file contains the following text
		// This is a line of text inside the file.
		// array to store the content of the file
		byte[] bytes = new byte[12];
		// offset is 8 and length is 3
		raf.read(bytes, 8, 3);
		raf.close();
		System.out.println(new String(bytes)); } }
				1	The output will be This is a l, i.e., the first 12 characters of the file.	The output will be Thi, i.e., 8 blank characters followed by 'T', 'h', 'i', 1 blank character	The output will be Thi, as only the first 3 characters from the file are read and printed directly.	The program will result in a compilation error due to incorrect usage of the read() method.

346	8	What is the output of the following code?
		import java.io.*;
		import java.lang.String;
		class test {
		public static void main(String[] args) throws IOException {
		// Object of RandomAccessFile
		RandomAccessFile raf = new RandomAccessFile("input.txt","r");
		// Suppose, the input.txt file contains the following text
		// This is a line of text inside the file.
		// array to store the content of the file
		byte[] bytes = new byte[2];
		// offset is 8 and length is 3
		raf.read(bytes, 8, 3);
		raf.close();
		System.out.println(new String(bytes)); } }
			D	1	is	Thi	is	error

347	8	What is the output of the following code?
		import java.io.*;
		import java.lang.String;
		class test {
		public static void main(String[] args) throws IOException {
		// Object of RandomAccessFile
		RandomAccessFile raf = new RandomAccessFile("input.txt","r");
		// Suppose, the input.txt file contains the following text
		// This is a line of text inside the file.
		// array to store the content of the file
		byte[] bytes = new byte[3];
		// offset is 0 and length is 3
		raf.read(bytes, 0, 3);
		raf.close();
		System.out.println(new String(bytes)); } }
			B	1	is	Thi	is	error

L.J Institute of Engineering and Technology, Ahmedabad.

Computer Programming using Java-II PRACTICE BOOK (SEM-II-EVEN 2025-CE RELATED BRANCHES)

Note : This PRACTICE BOOK is only for reference purpose. LJU Test question paper may not be completely set from this PRACTICE BOOK.

Sr No	Unit Number	Question_Text	MCQ Answer	Marks	Option A	Option B	Option C	Option D

348	8	What is the output of the Java code snippet? Consider, the “input.txt” file contains the following text in first line:
		This_is_a_line_of_text_inside_the_file.
		
		import java.io.*;
		import java.lang.String;
		class NewMCQ {
		public static void main(String[] args) throws IOException {
		RandomAccessFile raf = new RandomAccessFile("input.txt", "r");
		byte[] bytes = new byte[12];
		raf.read(bytes, 8, 6);
		raf.close();
		System.out.println(new String(bytes)); } }
			D	1	null	This_i	This_is_a_l	Runtime Exception

349	8	Write a JAVA program to read student.txt file and display the content.		4				
350	8	Write a program to read the content of a file into a character array and write it into another file. Get names of the files from command line.		4				
351	8	Write a java program to search the file named the word entered as a filename from command line; if it exists in the system then program should print the content of a file on console.		5				
352	8	Write a java program that read employee details and store into emp.txt text file using file handling.		4				
353	8	Write a program that counts number of characters, words, and lines ina text file.		5				
354	8	Create a class called Student. Write a student manager program to manipulate the student information from files by using the BufferedReader and BufferedWriter.		5				
355	8	Write a java program to search the file named the word entered as a filename from commandline: If it existsin the system the program should print the contemts of the file on console		5				
356	8	Write a Java program to copy content of file1.txt to file2.txt using Java file handling		4				
357	8	Write an application that reads a file and counts the number of occurrences of digit 5. Supply the file name as a command-line argument		5				
358	8	Write a program to replace all “word1” by “word2” to a file without using temporary file and display the no. of replacement.		5				
359	8	Write a program to count the total no. of chars, words, lines, alphabets, digits, white spaces in a given file.		5				
360	8	Write a program to display the bytes of a file in reverse sequence. Provide the name of the file as a command line argument.		4				
361	8	Write a program to sort the one file numbers to another.for example one file contain the unsorted number separated by line and write the another filr with sorted number.		5				
362	8	Write a java program which read numbers from number.txt file and store even number to even.txt and odd number into odd.txt file.		4				

L.J Institute of Engineering and Technology, Ahmedabad.

Computer Programming using Java-II PRACTICE BOOK (SEM-II-EVEN 2025-CE RELATED BRANCHES)

Note : This PRACTICE BOOK is only for reference purpose. LJU Test question paper may not be completely set from this PRACTICE BOOK.

Sr No	Unit Number	Question_Text	MCQ Answer	Marks	Option A	Option B	Option C	Option D
363	8	Write a program that performs the following task: 1. Create a file named “Data1.txt” and write the numbers 100,200,300, 400 and 500 each on separate line. 2. Read the data from “Data1.txt” and calculate the sum of all the numbers.		3				

L.J Institute of Engineering and Technology, Ahmedabad.

Computer Programming using Java-II PRACTICE BOOK (SEM-II-EVEN 2025-CE RELATED BRANCHES)

Note : This PRACTICE BOOK is only for reference purpose. LJU Test question paper may not be completely set from this PRACTICE BOOK.

Sr No	Unit Number	Question_Text	MCQ Answer	Marks	Option A	Option B	Option C	Option D
TOPIC NAME:- 9 Marks (PROGRAMS)								
364	6,7,8	**IPL 2023 Awards | Java code Filename: OnlineVoting.java** As a Java intern, you have been assigned the task of designing an online voting system using Java to elect "Best Captain (Viewers Choice)- IPL 2023". The system is intended to manage the voting process for an election involving five Indian captains of IPL 2023 . Each captain is associated with a name, age, and team affiliation. The voting process will involve 50 voters, each randomly selecting one of the five captains. The goal is to implement an efficient and user-friendly system that can handle the following tasks: 1. Storing Captain Information: - The system should use a HashMap data structure to store captain information. - Each captains details, including their name, age, and team affiliation, will be represented as a `Captain` object. - The HashMap will use the captains name as the key and the corresponding `Captain` object as the value. - The five captains are Rohit(32 years old, Team MI), Dhoni (39 years old, Team CSK), Virat (30 years old, Team RCB), Hardik (31 years old, Team GT), and Rishabh (29 years old, Team DC). 2. Displaying Captain Details: - Before the voting process begins, the system should display the details of all the captains to the user. - The captain details should be printed on the console. 3. Simulating the Voting Process: - The voting process will involve 50 voters, each voter will be named Voter-1, Voter-2, and so on, and will randomly select one of the five captains. - The random selection will be done using the Math.random() method. 4. Recording the Voting Sequence: - The system should record the voting sequence, indicating the voter name and the captain they voted for. - The voting sequence should be stored in a ArrayDeque. 5. Writing Initial Captain Details to File: - The system should create a text file named "Voting Result.txt" to store the voting details. - Before the voting process begins, the system should write the initial captain details (stored in the HashMap) to the file. - The captain details should be written in a formatted manner for better readability		9				

L.J Institute of Engineering and Technology, Ahmedabad.

Computer Programming using Java-II PRACTICE BOOK (SEM-II-EVEN 2025-CE RELATED BRANCHES)

Note : This PRACTICE BOOK is only for reference purpose. LJU Test question paper may not be completely set from this PRACTICE BOOK.

Sr No	Unit Number	Question_Text	MCQ Answer	Marks	Option A	Option B	Option C	Option D
304	6,7,8	readability. 6. Writing Voting Sequence to File: - After the voting process is complete, the system should update the "Voting Result.txt" file. - The voting sequence, including the name of the voter and the captain they voted for, should be written to the file only. 7. Counting Votes: - The system should count the votes received by each captain. - The vote count should be stored in a HashMap, where the captain's name is the key, and the vote count is the value. 8. Sorting and Displaying Voting Results: - The system should sort the captains based on the vote count in descending order. - The sorted results should be displayed on the console, showing the number of votes and the percentage of votes gained for each captain. - The system should also determine the winner, i.e., the captain with the highest number of votes. - The winner's name, team affiliation, total votes, and percentage of votes received should be displayed on the console. 9. Writing Final Voting Results to File: - The system should update the "Voting Result.txt" file with the final voting results. - The final voting results, including the number of votes and percentage of votes for each captain, and then the winner's details, should be written to the file. 10. Error Handling: - The system should handle any potential errors during file operations. Overall, the goal of the system is to provide an efficient and reliable platform for conducting the voting process and generating accurate voting results for the election of "Best Captain (Viewers Choice)- IPL 2023" winner that will be new captain for team India in upcoming WorldCup-2023. Thanks for being an outstanding intern, and we are confident that your future holds tremendous success and achievement. Wishing you the very best in all your endeavors!						

L.J Institute of Engineering and Technology, Ahmedabad.

Computer Programming using Java-II PRACTICE BOOK (SEM-II-EVEN 2025-CE RELATED BRANCHES)

Note : This PRACTICE BOOK is only for reference purpose. LJU Test question paper may not be completely set from this PRACTICE BOOK.

Sr No	Unit Number	Question_Text	MCQ Answer	Marks	Option A	Option B	Option C	Option D
365	6,7,8	You are tasked with implementing a basic Library Management System in Java, which allows users to manage books, register users, and handle borrowing and returning of books. The system should support storing information in files for persistence. The program consists of several classes and functionalities, as described below: Classes and Their Responsibilities: 1.Book: •Represents a book with properties: id, title, author, and availability. •Provides a constructor to initialize these properties. •Overrides the toString method to display book details in a user-friendly format. 2.Catalog: •Manages a collection of books using an ArrayDeque. •Provides methods to add a book, display all books, and find a book by its ID. 3.User: •Represents a library user with properties: userID, name, contactNumber, and membershipDate. •Provides a constructor to initialize these properties. •Overrides the toString method to display user details in a user-friendly format. 4.Transaction: •Represents a transaction for borrowing or returning a book with properties: bookId, userId, borrowDate, and returnDate. 5.Library: •Manages the entire library system. •Uses a Catalog object to manage books and a Hashtable to manage users. •Uses an ArrayDeque to manage transactions. •Initializes the system and ensures files for books and users exist. •Provides methods to register users, add books, display catalog, display users, borrow books, and return books. •Provides methods to write user and book details to respective files for persistence. Main Functionality: 1.Adding a Book: •Prompts the user to input book details and adds the book to the catalog. •Writes book details to a file named books.txt. 2.Displaying the Catalog: •Displays all books available in the catalog. 3.Registering a User: •Prompts the user to input user details and registers the user in the system. •Writes user details to a file named users.txt. 4.Displaying Users: •Displays all registered users. 5.Borrowing a Book:		9				

L.J Institute of Engineering and Technology, Ahmedabad.

Computer Programming using Java-II PRACTICE BOOK (SEM-II-EVEN 2025-CE RELATED BRANCHES)

Note : This PRACTICE BOOK is only for reference purpose. LJU Test question paper may not be completely set from this PRACTICE BOOK.

Sr No	Unit Number	Question_Text	MCQ Answer	Marks	Option A	Option B	Option C	Option D
		5.Borrowing a Book: •Prompts the user to input the book ID, user ID, and borrow date. •Marks the book as borrowed if it is available and records the transaction. 6.Returning a Book: •Prompts the user to input the book ID, user ID, and return date. •Marks the book as available if it was borrowed and updates the transaction. 7.Exiting the System: •Provides an option to exit the system.						