L.J Institute of Engineering and Technology, Ahmedabad.

Computer Programming using Java-II PRACTICE BOOK (SEM-II-EVEN 2025-CE RELATED BRANCHES)

Note : This PRACTICE BOOK is only for reference purpose. LJU Test question paper may not be completely set from this PRACTICE BOOK.

Sr No	Unit Number	Question_Text	MCQ Answer	Marks	Option A	Option B	Option C	Option D
UNIT 9- JDBC Part-1								
366	9	What are the major components of the JDBC?	A	1	DriverManager, Driver, Connection, Statement, and ResultSet	DriverManager, Driver, Connection, and Statement	DriverManager, Statement, and ResultSet	DriverManager, Connection, Statement, and ResultSet
367	9	Select the packages in which JDBC classes are defined?	D	1	jdbc and javax.jdbc	rdb and javax.rdb	jdbc and java.jdbc.sql	sql and javax.sql
368	9	What is the correct sequence to create a database connection? i. Import JDBC packages. ii. Open a connection to the database. iii. Load and register the JDBC driver. iv. Execute the statement object and return a query resultset. v. Create a statement object to perform a query. vi. Close the resultset and statement objects. vii. Process the resultset. viii. Close the connection.	A	1	i, iii, ii, v, iv, vii, vi, viii	i, ii, iii, v, iv, vii, viii, vi	ii, i, iii, iv, viii, vii, v, vi	i, iii, ii, iv, v, vi, vii, viii
369	9	Which of the following method is used to perform DML statements in JDBC?	C	1	executeResult()	executeQuery()	executeUpdate()	execute()
370	9	Which of the following method is static and synchronized in JDBC API?	C	1	prepareCall()	executeUpdate()	getConnection()	executeQuery()
371	9	Which methods are required to load a database driver in JDBC?	D	1	getConnection()	registerDriver()	forName()	Both b and c
372	9	Parameterized queries can be executed by?	B	1	ParameterizedStatement	PreparedStatement	CallableStatement and Parameterized Statement	All kinds of Statements
373	9	Which of the following is not a valid statement in JDBC?	C	1	Statement	PreparedStatement	QueryStatement	CallableStatement
374	9	Stored procedure can be called by using the ?	B	1	CallStatement	Statement	CalledStatement	PreparableStatement
375	9	What should be the correct order to close the database resource?What should be the correct order to close the database resource?	D	1	Connection, Statements, and then ResultSet	ResultSet, Connection, and then Statements	Statements, ResultSet, and then Connection	ResultSet, Statements, and then Connection
376	9	Which method is used to establish the connection with the specified url in a Driver Manager class?	D	1	public static void registerDriver(Driver driver)	public static void deregisterDriver(Driver driver)	public static Connection getConnection(String url)	public static Connection getConnection(String url,String userName,String password)
377	9	Which method is used for an SQL statement that is executed frequently?	A	1	prepareStatement	prepareCall	createStatement	None of the above
378	9	JDBC stands for?	A	1	Java database connectivity	Java database connection	java Data and Bios Connectivity	java database communication
379	9	Which of the following statements is true about PreparedStatement in Java?	D	1	It is used for executing dynamic SQL statements.	It is used for executing static SQL statements.	It is used for executing stored procedures.	It is used for executing both static and dynamic SQL statements.
380	9	Which of the following is true about CallableStatement in Java?	C	1	It is used for executing static SQL statements.	It is used for executing dynamic SQL statements.	It is used for executing stored procedures.	It is used for executing both static and dynamic SQL statements.

L.J Institute of Engineering and Technology, Ahmedabad.

Computer Programming using Java-II PRACTICE BOOK (SEM-II-EVEN 2025-CE RELATED BRANCHES)

Note : This PRACTICE BOOK is only for reference purpose. LJU Test question paper may not be completely set from this PRACTICE BOOK.

Sr No	Unit Number	Question_Text	MCQ Answer	Marks	Option A	Option B	Option C	Option D
381	9	_____ method can be used for any SQL statements(Select and Update both).	C	1	executeQuery	executeUpdate	execute	All of the above

382	9	What is the output of the following Java code that uses Statement to execute a SQL query?
		import java.sql.*;
		public class Main {
		public static void main(String[] args) throws SQLException {
		Connection conn = DriverManager.getConnection("jdbc:mysql://localhost:3306/mydatabase", "root", "password");
		Statement stmt = conn.createStatement();
		ResultSet rs = stmt.executeQuery("SELECT * FROM customers");
		while (rs.next()) {
		System.out.println(rs.getString("name"));
		}
		conn.close();
		} }
			D	1	The code will throw an SQLException because the SQL query is invalid.	The code will throw a ClassNotFoundException because the MySQL JDBC driver is not found.	The code will throw a NullPointerException because the ResultSet is not initialized.	The names of all customers in the "customers" table will be printed to the console.

383	9	What is the output of the following Java code that uses PreparedStatement to execute a SQL query with a parameter?
		import java.sql.*;
		class Main {
		public static void main(String[] args) throws SQLException {
		Connection conn = DriverManager.getConnection("jdbc:mysql://localhost:3306/mydatabase", "root", "password");
		String sql = "SELECT * FROM customers WHERE country = ?";
		PreparedStatement pstmt = conn.prepareStatement(sql);
		pstmt.setString(1, "USA");
		ResultSet rs = pstmt.executeQuery();
		while (rs.next()) {
		System.out.println(rs.getString("name")); }
		conn.close(); } }
			A	1	. The names of all customers in the "customers" table whose country is "USA" will be printed to the console.	The code will throw an SQLException because the SQL query is invalid.	The code will throw a ClassNotFoundException because the MySQL JDBC driver is not found.	The code will throw a NullPointerException because the ResultSet is not initialized.

384	9	What is the output of the following Java code that uses CallableStatement to execute a stored procedure?
		import java.sql.*;
		public class Main {
		public static void main(String[] args) throws SQLException {
		Connection conn = DriverManager.getConnection("jdbc:mysql://localhost:3306/mydatabase", "root", "password");
		CallableStatement cstmt = conn.prepareCall("{call myprocedure(?, ?)}");
		cstmt.setString(1, "John");
		boolean hasResults = cstmt.execute();
		if (hasResults) {
		ResultSet rs = cstmt.getResultSet();
		while (rs.next()) {
		System.out.println(rs.getString("result"));
		} }
			B	1	The code will throw an SQLException because the stored procedure is not found.	The code will throw an Missing Parameter Exception because the parameters are missing	The code will throw a ClassNotFoundException because the MySQL JDBC driver is not found.	The value of the "result" column for the "John" input parameters will be printed to the console.

L.J Institute of Engineering and Technology, Ahmedabad.

Computer Programming using Java-II PRACTICE BOOK (SEM-II-EVEN 2025-CE RELATED BRANCHES)

Note : This PRACTICE BOOK is only for reference purpose. LJU Test question paper may not be completely set from this PRACTICE BOOK.

Sr No	Unit Number	Question_Text	MCQ Answer	Marks	Option A	Option B	Option C	Option D
		conn.close(); }}						

385	9	What is the output of the following Java code that uses PreparedStatement to execute an insert SQL query with multiple parameters?
		import java.sql.*;
		public class Main {
		public static void main(String[] args) throws SQLException {
		Connection conn = DriverManager.getConnection("jdbc:mysql://localhost:3306/mydatabase", "root", "password");
		String sql = "INSERT INTO customers (name, address, city, country) VALUES (?, ?, ?, ?)";
		PreparedStatement pstmt = conn.prepareStatement(sql);
		pstmt.setString(1, "John Doe");
		pstmt.setString(2, "123 Main St");
		pstmt.setString(3, "New York");
		pstmt.setString(4, "USA");
		int rowsInserted = pstmt.executeUpdate();
		System.out.println(rowsInserted + " rows inserted");
		conn.close(); } } // Assume that the "customers" table has columns "name", "address", "city", and "country".
			A	1	One row with the specified values will be inserted into the "customers" table and the number of rows inserted will be printed to the console.	The code will throw an SQLException because the SQL query is invalid.	The code will throw a ClassNotFoundException because the MySQL JDBC driver is not found.	The code will throw a NullPointerException because the ResultSet is not initialized.

386	9	What is the output of the following Java code that uses CallableStatement to execute a stored procedure with OUT parameters?
		import java.sql.*;
		public class Main {
		public static void main(String[] args) throws SQLException {
		Connection conn = DriverManager.getConnection("jdbc:mysql://localhost:3306/mydatabase", "root", "password");
		CallableStatement cstmt = conn.prepareCall("{call myprocedure(?, ?, ?)}");
		cstmt.setString(1, "John");
		cstmt.setString(2, "Doe");
		cstmt.registerOutParameter(3, Types.INTEGER);
		cstmt.execute();
		System.out.println(cstmt.getInt(3));
		conn.close();
		}
		}
		Assume that the "myprocedure" stored procedure takes two IN parameters "firstname" and "lastname" and one OUT parameter "result" of type INTEGER.
			A	1	The value of the "result" OUT parameter for the "John Doe" input parameters will be printed to the console.	The code will throw an SQLException because the stored procedure is not found.	The code will throw a ClassNotFoundException because the MySQL JDBC driver is not found.	The code will throw a NullPointerException because the ResultSet is not initialized.

387	9	Which statement is the correct one for MySQL jdbc connection?	D	1	getConnection(“jdbc.mysql.localhost://3306/dbName”, “root”, “”);	getconnection(“mysql.jdbc.localhost://3306/dbName”, “root”, “”);	getconnection(“jdbc:Mysql://localhost:3306/dbName”, “root”, “”);	getConnection(“jdbc:mysql://localhost:3306/dbName”, “root”, “”);

L.J Institute of Engineering and Technology, Ahmedabad.

Computer Programming using Java-II PRACTICE BOOK (SEM-II-EVEN 2025-CE RELATED BRANCHES)

Note : This PRACTICE BOOK is only for reference purpose. LJU Test question paper may not be completely set from this PRACTICE BOOK.

Sr No	Unit Number	Question_Text	MCQ Answer	Marks	Option A	Option B	Option C	Option D
388	9	Which line contains an ERROR? [Assume all the necessary lines before line 1 is already there in the code] 1. String sql = “insert into table values(?,?,?)”; 2. PreparedStatement pst = con.preparedStatement(sql); 3. pst.setInt(1,1324); 4. pst.setString(2, “1324”); 5. pst.setString(3, “1324”); 6. pst.executeQuery();	D	1	1,2,5	2,5,6	2,4,5,6	2, 6
389	9	Which lines are correct? [Assume all the necessary lines before line 1 is already there in the code & table have 4 columns – facId(int), facName(String), salary(float), number(String)] 1. String sql = "insert into faculty (facName, salary, number) values(?,?,?)"; 2. PreparedStatement pst = con.prepareCall(sql); 3. pst.setString(1, "JKJKJKJKJKJ"); 4. pst.setFloat(2, 789); 5. pst.setString(3, "888"); 6. pst.execute();	B	1	1,3,4,5,6	1,2,3,4,5,6	2,3,4,5,6	4,5,6
390	9	What is the correct syntax to store data of .java file to database. Consider the default PreparedStatement and FileReader is there.	C	1	pst.getCharacterStream(colIndex, fileReaderObj, file.length());	pst.getByteStream(colIndex, fileReaderObj, file.length());	pst.setCharacterStream(colIndex, fileReaderObj, file.length());	pst.setByteStream(colIndex, fileInputStreamObj, file.length());
391	9	What will be the output of the following? [Assume all the methods and necessary code is written there] DatabaseMetaData dbmd = con.getMetaData(); System.out.println(dbmd.getDatabaseProductName());	C	1	jdbc	MySQL Connector/J	MySQL	root

392	9	What is the output of the following Java code?
		/* Assume that the "faculty" table has columns "facid(INT)(AUTO_INCREMENT)", "facName(VARCHAR)", "salary(FLOAT)", and "number(VARCHAR)".*/
		import java.sql.*;
		class Managnment {
		public static void main(String[] args) throws Exception {
		Class.forName("com.mysql.cj.jdbc.Driver");
		Connection con = DriverManager.getConnection("jdbc:mysql://localhost:3306/lju", "root", "");
		String sql = "insert into faculty values('Patel',2500,9999)";
		PreparedStatement pst = con.prepareStatement(sql);
		int r = pst.executeUpdate();
		if (r >= 0) {
		System.out.print(r + " Sucessessful ");
		} else {
		System.out.print(r + " Fail "); }
		} }
			C	1	1 Sucessessful	Sucessessful 1	Exception in thread "main" java.sql.SQLException	Compile Time Error

L.J Institute of Engineering and Technology, Ahmedabad.

Computer Programming using Java-II PRACTICE BOOK (SEM-II-EVEN 2025-CE RELATED BRANCHES)

Note : This PRACTICE BOOK is only for reference purpose. LJU Test question paper may not be completely set from this PRACTICE BOOK.

Sr No	Unit Number	Question_Text	MCQ Answer	Marks	Option A	Option B	Option C	Option D
393	9	What is the correct sequence to insert Data in a database by using PreparedStstement? i. Import JDBC packages. ii. Create connection to the database. iii. Load and register the JDBC driver. iv. Execute Sql Query v. Create a PreparedStatement object & pass sql query. vi. Write Sql Query (Insert into table name…….).	A	1	i , iii, ii, vi, v, iv	i , iii, ii, v, vi, iv	i , iv, ii, vi, v, iii	i , iii, ii, vi, iv, v

394	9	
		Server: 127.0.0.1 » Database: lju » Table: faculty
		facID facName salary number
		Edit Copy Delete 1 DBP 121212 123456
		Edit Copy Delete 2 VVP 25000 989898
		Edit Copy Delete 3 MCD 145263 212121
		
		What is the output of the following Java code?
		/* Assume that the "faculty" table has columns "facid(INT)(AUTO_INCREMENT)", "facName(VARCHAR)", "salary(FLOAT)", and "number(VARCHAR)".*/
		
		import java.sql.*;
		class Managnment {
		public static void main(String[] args) throws Exception {
		Class.forName("com.mysql.cj.jdbc.Driver");
		Connection con = DriverManager.getConnection("jdbc:mysql://localhost:3306/lju", "root", "");
		String sql = "select * from faculty where facid = 1";
		PreparedStatement pst = con.prepareStatement(sql);
		ResultSet rs = pst.executeQuery();
		System.out.print(rs.getInt(1));
		System.out.print(rs.getString(2));
		System.out.print(rs.getFloat(3));
		System.out.print(rs.getString(4)); } }
			D	1	1DBP121212123456	2VVP25000989898	1121212123456DBP	Run time Exception

L.J Institute of Engineering and Technology, Ahmedabad.

Computer Programming using Java-II PRACTICE BOOK (SEM-II-EVEN 2025-CE RELATED BRANCHES)

Note : This PRACTICE BOOK is only for reference purpose. LJU Test question paper may not be completely set from this PRACTICE BOOK.

Sr No	Unit Number	Question_Text	MCQ Answer	Marks	Option A	Option B	Option C	Option D

395	9	Server: 127.0.0.1 » Database: lju » Table: faculty
		facID facName salary number
		Edit Copy Delete 1 DBP 121212 123456
		Edit Copy Delete 2 VVP 25000 989898
		Edit Copy Delete 3 MCD 145263 212121
		
		What is the output of the following Java code?
		/* Assume that the "faculty" table has columns "facid(INT)(AUTO_INCREMENT)", "facName(VARCHAR)", "salary(FLOAT)", and "number(VARCHAR)".*/
		Direction | Name | Type | Length/Values
		IN | FAC_ID | INT | 10
		OUT | FAC_NAME | VARCHAR | 50
		
		/* Routine name: getFacId Type: Procedure
		
		BEGIN
		SELECT facName INTO FAC_NAME FROM faculty WHERE facId = FAC_ID;
		END */
		import java.sql.*;
		class Managnment {
		public static void main(String[] args) throws Exception {
		Class.forName("com.mysql.cj.jdbc.Driver");
		Connection con = DriverManager.getConnection("jdbc:mysql://localhost:3306/lju", "root", "");
		String sql = "{call getFacId(?,?)}";
		CallableStatement cst = con.prepareCall(sql);
		cst.setInt(1, 3);
		cst.executeQuery();
		System.out.println(cst.getString(2)); } }
			B	1	DBP	MCD	VVP	Exception in thread "main" java.sql.SQLException

		Consider this Table student already available on database java2t4 for the below questions.(Q.396-400) RollNo (int) | Name (varchar (30)) | Branch (varchar (30)) | JAVAT1 (double) | JAVAT2 (double) | JAVAT3 (double) 1 | Raj | CSE | 9 | 6 | 3 27 | Raju | CE | 22.5 | 21 | 23 35 | Shyam | IT | 18 | 19 | 18.5 44 | Ghanshyam | CSE | 15 | 16 | 11 48 | raju | IT | 15 | 16 | 9 (Table Name : student) (DataBase Name : java2t4) Note: RollNo coloumn is assigned as Primary Key and also Auto increment.						

L.J Institute of Engineering and Technology, Ahmedabad.

Computer Programming using Java-II PRACTICE BOOK (SEM-II-EVEN 2025-CE RELATED BRANCHES)

Note : This PRACTICE BOOK is only for reference purpose. LJU Test question paper may not be completely set from this PRACTICE BOOK.

Sr No	Unit Number	Question_Text	MCQ Answer	Marks	Option A	Option B	Option C	Option D

396	9	How many rows will remain in given Table after execution of below given java code (Consider Table student) ?
		import java.sql.*;
		class trial
		{
		public static void main(String[] args) throws Exception
		{
		// assume successful database connection with con object
		String sql = "delete from student where name = 'rAju' ";
		PreparedStatement pst = con.prepareStatement(sql);
		pst.executeUpdate();
		
		}
		}
			C	1	5	4	3	Error

397	9	What will be the output of following java code (Consider Table student) ?
		import java.sql.*;
		class trial {
		public static void main(String[] args) throws Exception
		{
		// assume successful database connection with con object
		String sql = "select javat3 from student where name = 'Ghanshyam' ";
		PreparedStatement pst = con.prepareStatement(sql);
		ResultSet rs =pst.executeQuery();
		while(rs.next()) {
		System.out.println(rs.getInt(1));
		}
		} }
			B	1	44	11	15	error

398	9	What is the output after execution of below given java code (Consider Table student) ?
		import java.sql.*;
		class trial {
		public static void main(String[] args) throws Exception
		{
		// assume successful database connection with con object
		String sql = "select * from student where name = 'SRK' ";
		PreparedStatement pst = con.prepareStatement(sql);
		boolean r = pst.execute();
		if (r) {
		System.out.print(r);
		} else {
		System.out.print(r); }
		} }
			A	1	true	false	compile error	runtime error

L.J Institute of Engineering and Technology, Ahmedabad.

Computer Programming using Java-II PRACTICE BOOK (SEM-II-EVEN 2025-CE RELATED BRANCHES)

Note : This PRACTICE BOOK is only for reference purpose. LJU Test question paper may not be completely set from this PRACTICE BOOK.

Sr No	Unit Number	Question_Text	MCQ Answer	Marks	Option A	Option B	Option C	Option D

399	9	What will be the output of following java code (Consider Table student) ?
		import java.sql.*;
		class trial {
		public static void main(String[] args) throws Exception
		{
		// assume successful database connection with con object
		String sql = "delete from student where name = 'RAJ' ";
		PreparedStatement pst = con.prepareStatement(sql);
		boolean r = pst.execute();
		System.out.println(r);
		}
		}
			B	1	true	false	compile error	runtime error

400	9	What will be the output of following java code (Consider Table student) ?
		import java.sql.*;
		class trial{
		public static void main(String[] args) throws Exception
		{
		// assume successful database connection with con object
		String sql = "select branch and javat1 from student where name = 'SRK' ";
		PreparedStatement pst = con.prepareStatement(sql);
		ResultSet r = pst.executeQuery();
		while(r.next()) {
		System.out.print(r.getInt(55));
		}
		} }
			C		Compile Error	0	No output	ArrayIndexOutOfBoundsException

401	9	Consider a table with name – student and database as admission. The student table have fields like stdId, stdName, stdMarks(float). Write a java program that adds 2 records using PreparedStatement. [have to write connection code here.]		4				
402	9	Write the java program that do connection with database		3				
403	9	Write a java program to insert book_id, book_name, book_price in the book table with LJU database. Do this using Statement		4				
404	9	Write a java program to insert book_name, book_price in the book table with LJU database. Do this using Statement. Here, Book id is auto incremented. So do accordingly.		4				
405	9	Write a java program to insert brochure_id brochure_name, brochure_pages in the brochure table with LJU database. Do this using Statement Interface. Take necessary data from user for inserting atleast 5 records.		4				

L.J Institute of Engineering and Technology, Ahmedabad.

Computer Programming using Java-II PRACTICE BOOK (SEM-II-EVEN 2025-CE RELATED BRANCHES)

Note : This PRACTICE BOOK is only for reference purpose. LJU Test question paper may not be completely set from this PRACTICE BOOK.

Sr No	Unit Number	Question_Text	MCQ Answer	Marks	Option A	Option B	Option C	Option D
406	9	Write a java program to update book_price by book_name in the book table with LJU database. Do this using Statement. Here, Book id is auto incremented. So do accordingly.		4				
407	9	Write a java program to update book_price and book_name in the book table with LJU database. Do this using Statement. To do this, First ask user to enter book_id. And then ask new book name and price to be updated.		4				
408	9	Write a java program to delete books from the book table book_name in the book table with LJU database. Do this using Statement.		4				
409	9	Write a java program to display all brochures from the brochure table where table contains columns like : brochure_id, brochure_name, brochure_pages.		4				
410	9	Write a java program that inserts record of employees like emp_id, emp_name, emp_designation, emp_salary. Here emp_id is primary key and auto incremented. Table name is employee. And Database is : LJU. Now, insert one record using PreparedStatement		4				
411	9	Write a java program that inserts record of employees like emp_id, emp_name, emp_designation, emp_salary. Here emp_id is primary key and auto incremented. Table name is employee. And Database is : LJU. Now, insert one record using PreparedStatement. Ask User how many records you want to enter. And insert n - records using prepared statement		5				
412	9	Write a java program for the above same employee table - to do upate emp designation and salary BY emp_name. Take all details from user and update this by using PreparedStatement		4				
413	9	Write a java program for the above same employee table - to do delete employee those having salary more than salary entered by user. from the table. Take all details from user and update this by using PreparedStatement. - Take salary from user.		4				
414	9	Write a java program that fetch all details of employees from employee table. Table name is employee. And Database is : LJU. Now, fetch record using CallableStatement. - Create procedure with name : getEmployees() Emp id is auto incremented.		5				

L.J Institute of Engineering and Technology, Ahmedabad.

Computer Programming using Java-II PRACTICE BOOK (SEM-II-EVEN 2025-CE RELATED BRANCHES)

Note : This PRACTICE BOOK is only for reference purpose. LJU Test question paper may not be completely set from this PRACTICE BOOK.

Sr No	Unit Number	Question_Text	MCQ Answer	Marks	Option A	Option B	Option C	Option D
415	9	Write a java program that inserts record of employees like emp_id, emp_name, emp_designation, emp_salary. Here emp_id is primary key and auto incremented. Table name is employee. And Database is : LJU. Now, insert one record using CallableStatement. - Create procedure with name : insertEmployee(?,?,?) Emp id is auto incremented. Consider all parameters as IN parameter		5				
416	9	Write a java program that update record of emp_designation, and emp_salary where emp_name is rahul. Here emp_id is primary key and auto incremented. Table name is employee. And Database is : LJU. Now, update record using CallableStatement. - Create procedure with name : updateEmployeeByName(?,?,?) Emp id is auto incremented. Consider all parameters as IN parameter.		5				
417	9	Consider Bank table with attributes AccountNo,CustomerName, Balance, Phone and Address. Write a database application which allows insertion, updation and deletion of records in Bank table. Print values of all customers whose balance is greater than 20,000.		5				
418	9	Write a program using JDBC for getting personal information – name, birthdate, sex, address, phone no, email-id & store it in database. Also provide list of all records, all male, all female & all minors (age below 18).		5				
419	9	Write Java application program to change the basic = basic + 500 of all the employees whose age is greater then 40 from employee table then display how many record updated.		5				
420	9	Write a java code that used to insert Products in the product table and update product price by product name.		5				
421	9	Write a stroed procedure with name multiProduct(?,?,?) This do the follwong. - update product price by product id - return the product name which is updated by us in previous query. - So here write both queries in a single procedure call. Use 3 - IN and OUT parameter as per your understanding.		3				

L.J Institute of Engineering and Technology, Ahmedabad.

Computer Programming using Java-II PRACTICE BOOK (SEM-II-EVEN 2025-CE RELATED BRANCHES)

Note : This PRACTICE BOOK is only for reference purpose. LJU Test question paper may not be completely set from this PRACTICE BOOK.

Sr No	Unit Number	Question_Text	MCQ Answer	Marks	Option A	Option B	Option C	Option D
422	9	Write a java code for the below tasks. - Table Name : student : std_id, std_roll_no, std_name, std_marks, std_div - DB Name : LJU - Write tow callable stored procedure with below names. A) getMakrs(): this procedure will give you marks of students from name. B) updateRollNo() : this procedure will update the roll no by giving the name of the student.		6				
423	9	Write a java code to fetch all student's marks from the table and do addition of all marks.		3				
424	9	Write a java code to update student's marks in the follwing manner. Students having makrs > 50 add + 5 in total marks > 60 add + 10 marks > 80 add + 15 in the marks and update the table in it.		4				
425	9	Management of the LJ wants to do compilation of total marks of the students. For this they do the following process. 1. Table - mse_marks with columns - roll_no, t1, t2, bonus. 2. Table – final_marks with roll_no, total (where total = (t1+t2)/2 + bonus) Process 1: Need to fetch all the details from the table mse_marks using CallableStatement. Write SQL code an Java code for the same. Procedure name is getMarks(). Process 2: Need to insert same roll_no fetched from the mse_marks to final_marks table and total after calculating it perfectly from the table mse_marks. This insertion query you have to write using PreparedStatement.		6				
426	9	Ask User to do the following taks in book table. All the details of table are given in above examples. 1 - for insertion 2 - for deletion by book name 3 - for update book name and price both BY book id. 4. for show all books from the table. Do above program using switch case and untill user press - 5 - ask them again do the above operations.		6				

L.J Institute of Engineering and Technology, Ahmedabad.

Computer Programming using Java-II PRACTICE BOOK (SEM-II-EVEN 2025-CE RELATED BRANCHES)

Note : This PRACTICE BOOK is only for reference purpose. LJU Test question paper may not be completely set from this PRACTICE BOOK.

Sr No	Unit Number	Question_Text	MCQ Answer	Marks	Option A	Option B	Option C	Option D
427	9	Write a java program that select record emp_designation, and emp_salary where emp_name is rahul. Here emp_id is primary key and auto incremented. Table name is employee. And Database is : LJU. Now, update record using CallableStatement. - Create procedure with name : selectEmployeeByName(?,?,?) Emp id is auto incremented. Here : emp_name is IN parameter. emp_designation and emp_salary are OUT parameter.		5				
428	9	Write a Java code for the following task. - Table Name : student : std_id, std_roll_no, std_name, std_marks, std_div - DB : LJU - Insert 5 Records using prepared statement. - Update Div of students having marks > 50 - To - Div B - Use callable statement for this		6				
		Assume you are building an online bookstore application that allows customers to purchase books. You have decided to use JDBC to handle database operations. The application should have the following functionality: Add books to the database Retrieve a list of books from the database Update book information in the database Delete a book from the database Requirements: The program should establish a connection to the database using JDBC. The program should allow users to enter book information such as title, author, publisher, and price. The program should use PreparedStatement to insert, update and delete data from the database. The program should use Statement to retrieve data from the database. The program should display the list of books retrieved from the database		6				

L.J Institute of Engineering and Technology, Ahmedabad.

Computer Programming using Java-II PRACTICE BOOK (SEM-II-EVEN 2025-CE RELATED BRANCHES)

Note : This PRACTICE BOOK is only for reference purpose. LJU Test question paper may not be completely set from this PRACTICE BOOK.

Sr No	Unit Number	Question_Text	MCQ Answer	Marks	Option A	Option B	Option C	Option D
429	9	The program should display the list of books retrieved from the database. The program should handle exceptions such as SQLException and ClassNotFoundException. Functionality: The program should provide a menu to the user to perform CRUD operations on the book database. The program should handle input validation for book information such as non-null values, valid prices, and book title length. The program should display a success or failure message after each CRUD operation.						
430	9	Suppose you are working on a project for a banking system that requires you to implement JDBC CRUD operations. You need to create a Java application that allows users to add, view, update, and delete customer accounts from the database. The program should establish a connection to the database using JDBC and use PreparedStatement to execute SQL statements. Requirements: The program should establish a connection to the database using JDBC. The program should allow users to add, view, update, and delete customer accounts from the database. The program should use PreparedStatement to execute SQL statements. The program should display appropriate messages to the user indicating the success or failure of the operation. Functionality: The program should provide a menu to the user to add, view, update, and delete customer accounts. The program should handle exceptions such as SQLException and ClassNotFoundException.		6				

L.J Institute of Engineering and Technology, Ahmedabad.

Computer Programming using Java-II PRACTICE BOOK (SEM-II-EVEN 2025-CE RELATED BRANCHES)

Note : This PRACTICE BOOK is only for reference purpose. LJU Test question paper may not be completely set from this PRACTICE BOOK.

Sr No	Unit Number	Question_Text	MCQ Answer	Marks	Option A	Option B	Option C	Option D
431	9	Create one database named LJUADMISSION in phpMyAdmin. LJUADMISSION database received 10 applications for admission. Data of this applications are stored in table named application in database as follow. id | name | rank 1 | Raju | 1205 2 | Shyam | 1508 3 | Anant | 1009 4 | Radhika | 879 5 | Shivya | 403 6 | Yuvraj | 1800 7 | Mrunal | 2214 8 | Pritam | 1212 9 | Arijit | 1785 10 | Krunal | 456 -->Write necessary code to make connection with the database LJUADMISSION. --> Write code upon executing which two tables named confirmed and rejected will be created and data of top five students as per the rank will be stored in table confirmed and remaining in table rejected. --> After that provide following repeating menu to user. 1.Press 1 to display names of admission confirmed student. (Fetch data from confirmed table through query and print it on consol.) 2.Press 2 to display name of admission rejected students. (Fetch data from rejected table through query and print it on consol.) 3.Press 3 to remove any student from confirmed table through id. (Before removing data of particular student take confirmation (use setAutoCommit and commit methods)) 4. Press 4 to print additional data of database. (Driver name , URL , Database product name) 5. Exit		9				
UNIT 10- JDBC Part-2								
432	10	What is the correct syntax to fetch image content data from database table?	C	1	ImageContent ic = rs.getImageContent("fileContent");	Clob cb = rs.getClob("fileContent");	Blob bb = rs.getBlob("fileContent");	BlobContent bc = rs.getBlobContent("file");
433	10	What does the setAutoCommit(false) ?	D	1	Never commit the transactions.	Transaction is explicitly committed.	Transactions will not be committed automatically after each query.	B & C
434	10	Which of the following methods is used to get the data type of a column in a ResultSet using ResultSetMetaData in Java?	A	1	getColumnTypeName()	getColumnType()	getColumnTypeNameData()	getColumnName()

L.J Institute of Engineering and Technology, Ahmedabad.

Computer Programming using Java-II PRACTICE BOOK (SEM-II-EVEN 2025-CE RELATED BRANCHES)

Note : This PRACTICE BOOK is only for reference purpose. LJU Test question paper may not be completely set from this PRACTICE BOOK.

Sr No	Unit Number	Question_Text	MCQ Answer	Marks	Option A	Option B	Option C	Option D
435	10	Which of the following methods is used to determine the size of a Blob in Java?	A	1	length()	size()	getSize()	getLength()
436	10	Which of the following methods is used to retrieve a file as a byte array from a database using JDBC in Java?	C	1	executeUpdate()	executeQuery()	getBytes()	getBinaryStream()
437	10	Which of the following data types is used to store binary data in a database using JDBC in Java?	D	1	DATE	VARCHAR	CLOB	BLOB
438	10	Which of the following methods is used to insert a file into a database as a CLOB using JDBC in Java?	C	1	setBlob()	setBinaryStream()	setCharacterStream()	All the above
439	10	Which of the following methods is used to retrieve a file stored as a BLOB from a database using JDBC in Java?	A	1	getBlob()	setClob()	setCharacterStream()	All the above
440	10	Which of the following methods is used to insert a file into a database as a BLOB using JDBC in Java?	A	1	setBlob()	getBinaryStream()	getBytes()	setCharacterStream()
441	10	Which of the following interfaces provides methods for retrieving metadata about a ResultSet object?	A	1	ResultSetMetaData	DatabaseMetaData	StatementMetaData	DBMetaData
442	10	Which of the following interfaces provides methods for retrieving metadata about a database?	B	1	ResultSetMetaData	DatabaseMetaData	StatementMetaData	DBMetaData

443	10	What is the output of the following Java code that uses DatabaseMetaData to retrieve the database product name?
		import java.sql.*;
		public class Main {
		public static void main(String[] args) throws SQLException {
		Connection conn =
		DriverManager.getConnection("jdbc:mysql://localhost:3306/mydatabase"
		, "root", "password");
		DatabaseMetaData metadata = conn.getMetaData();
		System.out.println(metadata.getDatabaseProductName());
		conn.close();
		}
		}
		Assume that the JDBC driver is for a MySQL database.
			D	1	"Java Database Connectivity" will be printed to the console.	The code will throw an SQLException because the JDBC driver is not compatible with MySQL.	The code will throw a ClassNotFoundException because the MySQL JDBC driver is not found.	"MySQL" will be printed to the console.

L.J Institute of Engineering and Technology, Ahmedabad.

Computer Programming using Java-II PRACTICE BOOK (SEM-II-EVEN 2025-CE RELATED BRANCHES)

Note : This PRACTICE BOOK is only for reference purpose. LJU Test question paper may not be completely set from this PRACTICE BOOK.

Sr No	Unit Number	Question_Text	MCQ Answer	Marks	Option A	Option B	Option C	Option D

444	10	What is the output of the following Java code that uses ResultSetMetaData to retrieve the column names of a ResultSet?
		import java.sql.*;
		public class Main {
		public static void main(String[] args) throws SQLException {
		Connection conn = DriverManager.getConnection("jdbc:mysql://localhost:3306/mydatabase", "root", "password");
		Statement stmt = conn.createStatement();
		ResultSet rs = stmt.executeQuery("SELECT * FROM customers");
		ResultSetMetaData rsmd = rs.getMetaData();
		for (int i = 1; i <= rsmd.getColumnCount(); i++) {
		System.out.println(rsmd.getColumnName(i));
		}
		conn.close(); } }
		Assume that the "customers" table has columns "id", "name", "address", "city", and "country".
			A	1	The column names "id", "name", "address", "city", and "country" will be printed to the console.	The code will throw an SQLException because the SQL query is invalid.	The code will throw a ClassNotFoundException because the MySQL JDBC driver is not found.	The code will throw a NullPointerException because the ResultSet is not initialized.

445	10	What is the output of the following Java code that uses ResultSetMetaData to retrieve the number of columns in a ResultSet?
		import java.sql.*;
		
		public class Main {
		public static void main(String[] args) throws SQLException {
		Connection conn = DriverManager.getConnection("jdbc:mysql://localhost:3306/mydatabase", "root", "password");
		Statement stmt = conn.createStatement();
		ResultSet rs = stmt.executeQuery("SELECT * FROM customers");
		ResultSetMetaData rsmd = rs.getMetaData();
		System.out.println(rsmd.getColumnCount());
		conn.close();
		} }
		Assume that the "customers" table has columns "id", "name", "address", "city", and "country".
			A	1	5 will be printed to the console.	4 will be printed to the console.	The code will throw an SQLException because the SQL query is invalid.	The code will throw a ClassNotFoundException because the MySQL JDBC driver is not found.

446	10	DatabaseMetaData interface is used to get?	A	1	Comprehensive information about the database as a whole.	Comprehensive information about the table as a whole.	Comprehensive information about the column as a whole.	Both b and c

L.J Institute of Engineering and Technology, Ahmedabad.

Computer Programming using Java-II PRACTICE BOOK (SEM-II-EVEN 2025-CE RELATED BRANCHES)

Note : This PRACTICE BOOK is only for reference purpose. LJU Test question paper may not be completely set from this PRACTICE BOOK.

Sr No	Unit Number	Question_Text	MCQ Answer	Marks	Option A	Option B	Option C	Option D

447	10	What is the output of the following Java code?
		/* Assume that the "faculty" table has columns "facid(INT)(AUTO_INCREMENT)", "facName(VARCHAR)", "salary(FLOAT)", and "number(VARCHAR)".*/
		import java.sql.*;
		class TransactionManagnment {
		public static void main(String[] args) throws Exception {
		Class.forName("com.mysql.cj.jdbc.Driver");
		Connection con = DriverManager.getConnection("jdbc:mysql://localhost:3306/lju", "root", "");
		con.setAutoCommit(false);
		String sql = "insert into faculty(facName, salary, number) values('deep',2500,9999)";
		PreparedStatement pst = con.prepareStatement(sql);
		int r = pst.executeUpdate();
		con.commit();
		con.rollback();
		if (r >= 0) {
		System.out.print(r+ " Sucessessful ");
		} else {
		System.out.print(r+ " Fail ");
		}
		con.close(); } }
			A	1	1 Sucessessful	0 Sucessessful	1 Fail	0 Fail

448	10	Which data type is used to store files in the database table?	B	1	BLOB	CLOB	File	Both a and b
449	10	What is blob in the following statement? create table profilepic(photo blob);	C	1	Variable	Object	Data type	Keyword
450	10	Which statement(s) is/ are true about transactions? i. A transaction is a set of one or more SQL statements that make up a logical unit of work. ii. A transaction ends with either a commit or a rollback, depending on whether there are any problems with data consistency or data concurrency. iii. A lock is a mechanism that allows two transactions from manipulating the same data at the same time. iv. To avoid conflicts during a transaction, a DBMS uses locks, mechanisms for blocking access by others to the data that is being accessed by the transaction.	C	1	Only i and ii	Only i and iii	Only i, ii, and iv	All the above
451	10	Which method Drops all changes made since the previous commit/rollback?	A	1	public void rollback()	public void commit()	public void close()	public Statement createStatement()
452	10	Which methods returns a stream that simply provides the raw bytes from the database without any conversion?	B	1	getCharacterStream	getBinaryStream	getAsciiStream	getUnicodeStream

L.J Institute of Engineering and Technology, Ahmedabad.

Computer Programming using Java-II PRACTICE BOOK (SEM-II-EVEN 2025-CE RELATED BRANCHES)

Note : This PRACTICE BOOK is only for reference purpose. LJU Test question paper may not be completely set from this PRACTICE BOOK.

Sr No	Unit Number	Question_Text	MCQ Answer	Marks	Option A	Option B	Option C	Option D

453	10	What is the output of the following Java code?
		/* Assume that the "faculty" table has columns "facid(INT)(AUTO_INCREMENT)", "facName(VARCHAR)", "salary(FLOAT)", and "number(VARCHAR)".*
		Table as given below */
		facID facName salary number
		1 DBP 70000 98989898
		2 VVP 75000 999999
		import java.sql.*;
		class RSMD {
		public static void main(String[] args) throws Exception {
		Class.forName("com.mysql.cj.jdbc.Driver");
		Connection con = DriverManager.getConnection("jdbc:mysql://localhost:3306/lju", "root", "");
		String sql = "select * from faculty";
		PreparedStatement pst = con.prepareStatement(sql);
		ResultSet rs = pst.executeQuery();
		ResultSetMetaData rsmd = rs.getMetaData();
		while (rs.next()) {
		System.out.print(rsmd.getColumnCount()+",");
		System.out.print(rsmd.getColumnName(1)+",");
		System.out.print(rsmd.getColumnTypeName(1)+",");
		System.out.print(rsmd.getTableName(2)+","); } } }
			D	1	4,facID,INT,faculty,	5,facID,INT,faculty,	1,DBP,70000,98989898,	None of the Above

454	10	What is the output of the following Java code?
		/* Assume that the "faculty" table has columns "facid(INT)(AUTO_INCREMENT)", "facName(VARCHAR)", "salary(FLOAT)", and "number(VARCHAR)".*/
		import java.sql.*;
		class TransactionManagnment {
		public static void main(String[] args) throws Exception {
		Class.forName("com.mysql.cj.jdbc.Driver");
		Connection con = DriverManager.getConnection("jdbc:mysql://localhost:3306/lju", "root", "");
		con.setAutoCommit(true);
		String sql = "insert into faculty(facName, salary, number) values('abc',2500,9999)";
			C	1	Sucessessful	Fail	Sucessessful Exception in thread "main" java.sql.SQLException	Fail Exception in thread "main" java.sql.SQLException

L.J Institute of Engineering and Technology, Ahmedabad.

Computer Programming using Java-II PRACTICE BOOK (SEM-II-EVEN 2025-CE RELATED BRANCHES)

Note : This PRACTICE BOOK is only for reference purpose. LJU Test question paper may not be completely set from this PRACTICE BOOK.

Sr No	Unit Number	Question_Text	MCQ Answer	Marks	Option A	Option B	Option C	Option D

		PreparedStatement pst = con.prepareStatement(sql);
		int r = pst.executeUpdate();
		if (r > 0) {
		System.out.print("Sucessessful ");
		} else {
		System.out.print("Fail ");
		}
		con.commit();
		con.close(); } }						

455	10	What is the output of the following Java code?
		/* Assume that the "faculty" table has columns "facid(INT)(AUTO_INCREMENT)", "facName(VARCHAR)", "salary(FLOAT)", and "number(VARCHAR)".*/
		import java.sql.*;
		class Transaction {
		public static void main(String[] args) throws Exception {
		Class.forName("com.mysql.cj.jdbc.Driver");
		Connection con = DriverManager.getConnection("jdbc:mysql://localhost:3306/lju", "root", "");
		String sql = "insert into faculty(facName, salary, number) values('abc',2500,9999)";
		PreparedStatement pst = con.prepareStatement(sql);
		int i = pst.executeUpdate();
		con.rollback();
		con.close(); } }
			D	1	Exception in thread "main" java.io.FileNotFoundException	Exception in thread "main" java.lang.ArrayIndexOutofBoundException	Exception in thread "main" java.lang.StringIndexOutofBoundException	Exception in thread "main" java.sql.SQLNonTransientConnectionException

456	10	What is the output of the following Java code that uses ResultSetMetaData to retrieve the number of columns in a ResultSet?
		import java.sql.*;
		public class Main {
		public static void main(String[] args) throws SQLException {
		Connection conn = DriverManager.getConnection("jdbc:mysql://localhost:3306/mydatabase", "root", "password");
		Statement stmt = conn.createStatement();
		ResultSet rs = stmt.executeQuery("SELECT * FROM customers");
		ResultSetMetaData rsmd = rs.getMetaData();
		System.out.println(rsmd.getColumnCount());
		conn.close();
		}
			C	0.5	3	4	5	None of given

L.J Institute of Engineering and Technology, Ahmedabad.

Computer Programming using Java-II PRACTICE BOOK (SEM-II-EVEN 2025-CE RELATED BRANCHES)

Note : This PRACTICE BOOK is only for reference purpose. LJU Test question paper may not be completely set from this PRACTICE BOOK.

Sr No	Unit Number	Question_Text	MCQ Answer	Marks	Option A	Option B	Option C	Option D
		} } Assume that the "customers" table has columns "id", "name", "address", "city", and "country".						

457	10	What will be the output of following java code (Consider Table student) ?
		import java.sql.*;
		class trial {
		public static void main(String[] args) throws Exception
		{
		// assume successful database connection with con object
		String sql = "select branch , javaT1 from studentdata where name = 'ramesh' ";
		PreparedStatement pst = con.prepareStatement(sql);
		ResultSet r = pst.executeQuery();
		ResultSetMetaData rsm = r.getMetaData();
		int c = rsm.getColumnCount();
		System.out.println(c);
		} }
			C	0.5	0	1	2	None of given

458	10	How many rows will remain in given Table after execution of below given java code (Consider Table student) ?
		import java.sql.*;
		class trial
		{
		public static void main(String[] args) throws Exception
		{
		// assume successful database connection with con object
		
		con.setAutoCommit(false);
		String sql = "delete from student where name = 'Shyam' ";
		PreparedStatement pst = con.prepareStatement(sql);
		pst.executeUpdate();
		}
		}
			C	0.5	3	4	5	None of given

L.J Institute of Engineering and Technology, Ahmedabad.

Computer Programming using Java-II PRACTICE BOOK (SEM-II-EVEN 2025-CE RELATED BRANCHES)

Note : This PRACTICE BOOK is only for reference purpose. LJU Test question paper may not be completely set from this PRACTICE BOOK.

Sr No	Unit Number	Question_Text	MCQ Answer	Marks	Option A	Option B	Option C	Option D

459	10	What will be the output of following java code (Consider Table student) ?
		import java.sql.*;
		class trial
		{
		public static void main(String[] args) throws Exception
		{
		// assume successful database connection with con object
		
		con.setAutoCommit(false);
		String sql = "select name, branch from student where name = 'RAJ' ";
		PreparedStatement pst = con.prepareStatement(sql);
		ResultSet rs =pst.executeQuery();
		ResultSetMetaData rsm = rs.getMetaData();
		for(int i=1 ; i < 2 ; i++)
		{
		System.out.println(rsm.getColumnName(i+1));
		}
		con.commit();
		}
		}
			A	1	branch	name	raj	None of given

460	10	What is the output of the following Java code?
		/* Assume that the "faculty" table has columns
		"facid(INT)(AUTO_INCREMENT)",
		"facName(VARCHAR)", "salary(FLOAT)", and "number(VARCHAR)".*/
		import java.sql.*;
		class Transaction {
		public static void main(String[] args) throws Exception {
		Class.forName("com.mysql.cj.jdbc.Driver");
		Connection con =
		DriverManager.getConnection("jdbc:mysql://localhost:3306/lju",
		"root", "");
		String sql = "insert into faculty(facName, salary, number)
		values('abc',2500,9999)";
		PreparedStatement pst = con.prepareStatement(sql);
		int i = pst.executeUpdate();
		con.rollback();
		con.close(); } }
			B	1	Null	No output	CE	RE

461	10	Write a java code snippet that checks weather the database connection is established or not? If the connection is established perfectly then it should give us the version of the driver which I have used for the connection.		4				

L.J Institute of Engineering and Technology, Ahmedabad.

Computer Programming using Java-II PRACTICE BOOK (SEM-II-EVEN 2025-CE RELATED BRANCHES)

Note : This PRACTICE BOOK is only for reference purpose. LJU Test question paper may not be completely set from this PRACTICE BOOK.

Sr No	Unit Number	Question_Text	MCQ Answer	Marks	Option A	Option B	Option C	Option D
462	10	Write database application that prints different records from a table. Find out the name of table, no. of columns, no. of records and type of the columns. Here DB name is LJU and Table is employee with emp_id, emp_name, emp_designation, emp_salary		4				
463	10	Write a java code to insert image in table with name img_table where columns are img_id, img_name, img_size, img_content.		4				
464	10	Write a java code to retrive image in table with name img_table where columns are img_id, img_name, img_size, img_content.		4				
465	10	Write a java code to insert text file or java file in table with name file_table where columns are file_id, file_name, file_size, file_content, file_extension		5				
466	10	Write a java code to retrieval text file or java file in table with name file_table where columns are file_id, file_name, file_size, file_content, file_extension		5				
467	10	Table name: product Columns: pId, pName, pPrice, pCategory Create a java program through which user can ask for the following. Enter 1 to know Number of Column Enter 2 to know the Table Name Enter 3 to know Column Name & Ask for Index of column Enter 4 to know the type of column of Index given by user		5				
468	10	DB Name : LJU Create a java program through which user can ask for the following. Enter 1 to know Driver Name Enter 2 to know the USer Name Enter 3 to know Database Product Name Enter 4 to know the Driver Version		5				
469	10	Write a java code that stores .java file in the file table		4				
470	10	Write a java code that retreives file with .java extension only from the table and create a new file.		4				
		Project Definition: You are developing a Java program for a small business that requires storing and retrieving employee data and their profile images using JDBC. The program should allow authorized HR staff to add, retrieve, and delete employee data from the database. Additionally, the program should store and retrieve profile images for each employee.		7				

L.J Institute of Engineering and Technology, Ahmedabad.

Computer Programming using Java-II PRACTICE BOOK (SEM-II-EVEN 2025-CE RELATED BRANCHES)

Note : This PRACTICE BOOK is only for reference purpose. LJU Test question paper may not be completely set from this PRACTICE BOOK.

Sr No	Unit Number	Question_Text	MCQ Answer	Marks	Option A	Option B	Option C	Option D
471	10	Requirements: The program should establish a connection to the database using JDBC. The program should create a table if it doesn't exist and use the table for storing and retrieving employee data. The program should allow authorized HR staff to add employee data to the table. The program should allow authorized HR staff to retrieve employee data from the table based on a specified employee ID. The program should allow authorized HR staff to delete employee data from the table based on a specified employee ID. The program should store and retrieve profile images using the Blob data type in JDBC. The program should handle exceptions such as SQLException and IOException. Functionalities: Add employee data (employee ID, name, department, designation, and profile image) Retrieve employee data (employee ID, name, department, designation, and profile image) Delete employee data (employee ID) Exit the program						
472	10	Write a java program for the following tasks The program should establish a connection to the database using JDBC. The program should allow users to enter the source account number, destination account number, and the amount to be transferred. The program should begin a transaction and deduct the amount from the source account and add the amount to the destination account. The program should commit the transaction if the transaction is successful. The program should rollback the transaction if any exception occurs during the transaction. Functionality: The program should provide a menu to the user to perform the transfer of funds. The program should handle exceptions such as SQLException and ClassNotFoundException. Create Two Tables:		5				

L.J Institute of Engineering and Technology, Ahmedabad.

Computer Programming using Java-II PRACTICE BOOK (SEM-II-EVEN 2025-CE RELATED BRANCHES)

Note : This PRACTICE BOOK is only for reference purpose. LJU Test question paper may not be completely set from this PRACTICE BOOK.

Sr No	Unit Number	Question_Text	MCQ Answer	Marks	Option A	Option B	Option C	Option D
472	10	Create Two Tables: account : acc_no & acc_balance transaction : trans_id, ,src_acc_no, dest_acc_no, trans_amt OUTPUT Welcome to the Fund Transfer System. 1. Transfer Funds 2. Exit Enter your choice: 1 Enter source account number: 123456 Enter destination account number: 987654 Enter amount to be transferred: 5000 Transaction successful. 1. Transfer Funds 2. Exit Enter your choice: 2						
473	10	Create a Transaction Management System that uses Thread, Where one thread is used to deposite in account and other thread is used to withdraw from the account. You need to run both thread on the wishes of user in database. Try to use synchronized keywotrd to avoid deadlock.		5				
474	10	Write a java code that is retrive file that contains .txt file from table and convert new file in d:/java location with same name stored in table but extension with .java		5				
475	10	I try to hack the system of Adhar card. For this somehow, I got the access of the database – “aadhar” and it’s table – “aadharDetails”. Now can you help me with the following? 1 – To find the total number of columns in this table 2 – To find the name of the column 1 and 2 3 – To find the name of the column type of column 3 and 4. Write the java code for the above mentioned tasks. [No need to write code for connection]		4				
		Create one database named LJUADMISSION in phpMyAdmin. LJUADMISSION database received 10 applications for admission. Data of this applications are stored in table named **application** in database as follow. **id** | **name** | **rank** 1 | Raju | 1205 2 | Shyam | 1508 3 | Anant | 1009 4 | Radhika | 879 5 | Shivya | 403 6 | Yuvraj | 1800 7 | Mrunal | 2214 8 | Pritam | 1212 9 | Arijit | 1785 10 | Krunal | 456 (Note: create this table directly into the database without using query in VScode)		9				

L.J Institute of Engineering and Technology, Ahmedabad.

Computer Programming using Java-II PRACTICE BOOK (SEM-II-EVEN 2025-CE RELATED BRANCHES)

Note : This PRACTICE BOOK is only for reference purpose. LJU Test question paper may not be completely set from this PRACTICE BOOK.

Sr No	Unit Number	Question_Text	MCQ Answer	Marks	Option A	Option B	Option C	Option D
476	10	Write necessary code to make connection with the database LJUADMISSION. Write code upon executing which two tables named confirmed and rejected will be created and data of top five students as per the rank will be stored in table confirmed and remaining in table rejected. After that provide following repeating menu to user. 1.Press 1 to display names of admission confirmed student. (Fetch data from confirmed table through query and print it on consol.) 2.Press 2 to display name of admission rejected students. (Fetch data from rejected table through query and print it on consol.) 3.Press 3 to remove any student from confirmed table through id. (Before removing data of particular student take confirmation (use setAutoCommit and commit methods)) 4. Press 4 to print additional data of database. (Driver name , URL , Database product name) 5. Exit						
		id | name | gender | age | occupation | salary | biodata | photo 1 | Raju | Male | 26 | Artist | 50000 | Raju.txt | Raju.jpg 2 | Sunita | Female | 25 | Teacher | 70000 | Sunita.txt | Sunita.jpg 3 | Rohan | Male | 26 | Actor | 60000 | Rohan.txt | Rohan.jpg Write necessary code to make connection with the database: Create one repeating menu as given below: 1.Press 1 to Insert data in database. 2.Press 2 to update data in database. 3.Press 3 to delete data from database. 4.Press 4 to Read data from database. 5.Press 5 to get information about happyWedding table. 6.Press 6 to exit from menu All the Cases should me made according to given instruction as below: Case 1: To Insert Data in Table: •Here, user have to insert data by using PreparedStatement. (Don't use Scanner Class) •Values to be inserted are given below Note: All the txt files and jpg files are provided in soft copy of Question, Use those files only.		9				

L.J Institute of Engineering and Technology, Ahmedabad.

Computer Programming using Java-II PRACTICE BOOK (SEM-II-EVEN 2025-CE RELATED BRANCHES)

Note : This PRACTICE BOOK is only for reference purpose. LJU Test question paper may not be completely set from this PRACTICE BOOK.

Sr No	Unit Number	Question_Text	MCQ Answer	Marks	Option A	Option B	Option C	Option D
477	10	Case 2: To Update Data in Table: •Here, age & salary (both together) should be updated as per given name. •age, salary and name will be given by user by using Scanner Class only. •Data should be updated by using Statement Interface Only. Case 3: To Delete Data from Table: •Data should be deleted by given id. •id will be given by user by using Scanner class. •Use Transaction concept to delete data. After writing query ask user that whether he want to commit or rollback. If user choose commit then 1 row will be deleted and if user choose rollback, then Query will be rollback and no change in table. •Data should be deleted by using PreparedStatement only. Case 4: To Read Data from Table •All the data of particular person should be printed in the console by given age & salary. •age and salary should be given by user by using Scanner Class •Data should be Read by using Statement Interface Only. Case 5: To Get Information about happyWedding Table: •Write a code to print total no of column, name of particular column and Data type of particular column on the console. Here, column index will be inserted by user by using Scanner class. •Use PreparedStatement in this case. Case 6: To exit from menu: •Use System class to get exit from the menu.						