Architectural Trade-Offs in Distributed Quantum Repeaters: Distillation Scheduling Under Memory Coherence Constraints

Bhavagna Bathula

Independent Researcher / Department of Electronics and Communication Engineering

bhavagnabathula@gmail.com

Abstract

Long-distance quantum communication relies on quantum repeaters to overcome exponential photon attenuation in optical fiber links. Connecting adjacent elementary links requires entanglement swapping, while preserving end-to-end fidelity above cryptographic thresholds requires entanglement distillation. In physical hardware, however, quantum memories suffer from decoherence during the classical round-trip signaling intervals mandated by distillation protocols. This work investigates the architectural trade-off between two core operational strategies in a dual-hop quantum repeater: **Strategy A (Purify-then-Swap)**, wherein elementary links are distilled prior to swapping, and **Strategy B (Swap-then-Purify)**, wherein raw links are swapped immediately and distillation is executed end-to-end. We develop an analytical and numerical simulation pipeline tracking Werner state transformations under bilateral CNOT purification and non-Markovian memory dephasing. Our results reveal an exact crossover tipping point at $\tau_{\mathrm{RTT}}/T_2 \approx 0.018$: whenever classical signaling delay exceeds 1.8% of the memory coherence time, Strategy B strictly outperforms Strategy A. Furthermore, we show that local purification becomes actively destructive beyond $\tau_{\mathrm{RTT}}/T_2 \approx 0.070$, delivering fidelities inferior to unpurified swapping. Finally, we establish the minimum hardware boundary, showing that raw elementary links must achieve $F_{\mathrm{init}} \geq 0.880$ for single-round purification to cross the threshold for secret key distillation ($F > 0.810$).

1 Introduction

Quantum networks enable fundamentally secure communication through quantum key distribution (QKD), distributed quantum computation, and high-precision quantum sensing [1, 2]. Over terrestrial fiber links, optical transmission loss scales exponentially with channel length: $P_{\mathrm{trans}} = 10^{-\alpha L/10}$, where $\alpha \approx 0.2$ dB/km at telecommunication wavelengths (1550 nm). Because the quantum no-cloning theorem prohibits the use of classical optical amplifiers, direct fiber transmission of photonic qubits is practically constrained to distances below a few hundred kilometers.

To surpass this limit, quantum repeaters divide a long-distance channel into N shorter elementary segments [3, 4]. In each segment, elementary entangled pairs are generated and stored in stationary quantum memories (such as trapped ions, neutral atoms, or nitrogen-vacancy color centers). Intermediate nodes then execute Bell-state measurements (BSMs) to perform *entanglement swapping*, sequentially entangling the uncoupled endpoints [6].

However, elementary link generation, gate operations, and environmental couplings introduce state degradation. If the end-to-end entanglement fidelity F falls below 0.50, the state becomes unentangled (separable); if it falls below $F \approx 0.81$, it cannot support positive secret key distillation under collective eavesdropping attacks [7]. Consequently, practical repeaters must incorporate *entanglement distillation* (purification), such as the bilateral CNOT protocol proposed by Bennett et al. (BBPSSW) [5].

Because entanglement distillation is inherently probabilistic and conditioned on two-way classical acknowledgment, stationary qubits must idle within local quantum memories during the classical round-trip time ($\tau_{\mathrm{RTT}} = 2L_0/c$, where L_0 is segment length and $c \approx 2 \times 10^8$ m/s). During this waiting interval, memory dephasing (T_2) steadily degrades quantum coherence. This introduces an architectural dilemma:

1. **Strategy A (Purify-then-Swap):** Distill high-fidelity elementary pairs first, pay the memory waiting penalty locally, and then execute swapping.

2. **Strategy B (Swap-then-Purify):** Swap raw elementary links immediately, avoiding intermediate memory idle periods, and purify the degraded end-to-end state once at the terminal nodes.

In this paper, we construct a rigorous analytical framework to resolve this scheduling trade-off, determine the exact crossover threshold as a function of the memory ratio τ_{RTT}/T_2, and identify the minimum initial fidelity required for operational quantum key distribution.

2 System Model and Protocols

2.1 Werner State Channel Representation

We model the noisy entangled states distributed across elementary links as two-qubit Werner states [5]:

$$\rho_W(F) = F|\Phi^+\rangle\langle\Phi^+| + \frac{1-F}{3}\sum_{k=1}^{3}|\psi_k\rangle\langle\psi_k| \tag{1}$$

where $|\Phi^+\rangle = \frac{1}{\sqrt{2}}(|00\rangle + |11\rangle)$ is the target Bell state, $|\psi_k\rangle \in \{|\Psi^+\rangle, |\Phi^-\rangle, |\Psi^-\rangle\}$, and $F = \langle\Phi^+|\rho_W|\Phi^+\rangle \in [0.25, 1.0]$ denotes the state fidelity. Equation (1) can be expressed compactly in terms of the depolarizing parameter $w \in [0,1]$:

$$\rho_W(w) = w|\Phi^+\rangle\langle\Phi^+| + \frac{1-w}{4}\mathbb{I}_4, \quad w = \frac{4F-1}{3} \tag{2}$$

2.2 Entanglement Swapping Formulation

Consider a two-hop repeater chain with endpoints Alice (A), Bob (B), and an intermediate relay node (R). Two independent pairs are generated: Link 1 between A (q_0) and R (q_1), and Link 2 between R (q_2) and B (q_3). The relay node executes a BSM on qubits q_1 and q_2 via a local CNOT gate followed by a Hadamard on q_1 and projective measurement in the computational basis $\{|0\rangle, |1\rangle\}$.

Applying classical feedforward Pauli corrections ($Z^{m_1}X^{m_2}$) to qubit q_3 projects the remaining uncoupled qubits q_0 and q_3 into an entangled state. For two Werner states with fidelities F_1 and F_2 (depolarizing parameters w_1 and w_2), the swapped state remains a Werner state with parameter:

$$w_{\text{swap}} = w_1 \cdot w_2 = \left(\frac{4F_1-1}{3}\right)\left(\frac{4F_2-1}{3}\right) \tag{3}$$

The resulting end-to-end fidelity is given by:

$$F_{\text{swap}}(F_1, F_2) = \frac{1+3w_{\text{swap}}}{4} = F_1F_2 + \frac{(1-F_1)(1-F_2)}{3} \tag{4}$$

2.3 BBPSSW Entanglement Purification

Entanglement distillation combines two identical copies of a noisy Werner state $\rho_1 \otimes \rho_2$ to output a single pair of higher fidelity. Alice and Bob perform bilateral CNOT operations:

$$U_{\text{pur}} = \text{CNOT}_{A_1\to A_2} \otimes \text{CNOT}_{B_1\to B_2} \tag{5}$$

Following the interaction, Alice and Bob measure the target pair (A_2, B_2) in the computational Z-basis and exchange the outcomes over a classical channel. The protocol succeeds if and only if the measurement outcomes coincide (00 or 11). The probability of success P_{succ} and output fidelity F_{pur} are:

$$P_{\text{succ}}(F) = F^2 + \frac{2}{3}F(1-F) + \frac{5}{9}(1-F)^2 \tag{6}$$

$$F_{\text{pur}}(F) = \frac{F^2 + \frac{1}{9}(1-F)^2}{P_{\text{succ}}(F)} \tag{7}$$

Purification yields a fidelity improvement ($F_{\text{pur}} > F$) whenever $F > 0.50$.

2.4 Quantum Memory Decoherence Model

While qubits await the outcome of purification or feedforward signals, stationary memories experience phase relaxation. Over a waiting duration τ, memory dephasing causes the fidelity to decay toward the fully mixed state:

$$F_{\text{dec}}(F, \tau) = Fe^{-\tau/T_2} + \frac{1-e^{-\tau/T_2}}{4} \tag{8}$$

where T_2 is the transverse coherence time of the quantum memory.

3 Scheduling Strategy Formulations

3.1 Strategy A: Purify-then-Swap

In Strategy A, local nodes perform BBPSSW purification on Link 1 and Link 2 independently. To execute the protocol, two pairs must be generated across each link, and the kept qubits must be held in memory for a round-trip time τ_{RTT} until classical parity bits are verified.

$$F_{\text{pur,local}} = F_{\text{pur}}(F_{\text{init}}) \tag{9}$$

$$F_{\text{hold,A}} = F_{\text{dec}}(F_{\text{pur,local}}, \tau_{\text{RTT}}) \tag{10}$$

$$F_{\text{final,A}} = F_{\text{swap}}(F_{\text{hold,A}}, F_{\text{hold,A}}) \tag{11}$$

Total successful distillation requires both elementary links to succeed simultaneously, yielding an aggregate success probability of $P_{\text{succ,A}} = [P_{\text{succ}}(F_{\text{init}})]^2$.

3.2 Strategy B: Swap-then-Purify

In Strategy B, the relay node performs entanglement swapping immediately on raw links as soon as elementary pairs are established. Because the relay node executes local operations, the memory waiting time is dominated solely by one-way feedforward. Once two raw end-to-end links are generated, Alice and Bob apply BBPSSW purification directly across the full distance:

$$F_{\text{swap,raw}} = F_{\text{swap}}(F_{\text{init}}, F_{\text{init}}) \tag{12}$$

$$F_{\text{hold,B}} = F_{\text{dec}}(F_{\text{swap,raw}}, 0.5\,\tau_{\text{RTT}}) \tag{13}$$

$$F_{\text{final,B}} = F_{\text{pur}}(F_{\text{hold,B}}) \tag{14}$$

The overall success probability is governed by a single purification step on the swapped state: $P_{\text{succ,B}} = P_{\text{succ}}(F_{\text{hold,B}})$.

4 Simulation Results and Analysis

4.1 Discovery of the Memory Latency Crossover

We evaluated the final end-to-end fidelity F against the normalized memory latency ratio τ_{RTT}/T_2 for an initial elementary link fidelity $F_{\text{init}} = 0.860$.




Figure 1: End-to-end Bell state fidelity vs. memory latency to coherence ratio (τ_{RTT}/T_2). The crossover tipping point occurs at $\tau_{\mathrm{RTT}}/T_2 \approx 0.018$, beyond which Strategy B dominates.

Table 1: Quantitative Performance Comparison ($F_{\mathrm{init}} = 0.860$)

Protocol	$\tau/T_2 = 0$	$\tau/T_2 = 0.018$	$\tau/T_2 = 0.070$	$\tau/T_2 = 0.20$
Strategy A	**0.801**	0.781	0.746	0.612
Strategy B	0.784	**0.781**	**0.763**	**0.734**
Raw Swap	0.746	0.746	0.746	0.746
Optimal	**Strategy A**	**Crossover**	**Strategy B**	**Strategy B**

Critical Tipping Point: When $\tau_{\mathrm{RTT}}/T_2 \leq 0.018$, Strategy A outperforms Strategy B by purifying cleaner inputs. However, for $\tau_{\mathrm{RTT}}/T_2 > 0.018$, Strategy B provides strictly superior fidelity due to reduced memory exposure.

A vital phenomenon appears at $\tau_{\mathrm{RTT}}/T_2 \approx 0.070$: at this point, Strategy A drops below the unpurified baseline ($F = 0.746$). This demonstrates that in high-latency or low-coherence environments, *local purification is actively destructive*, burning extra resources while delivering worse entanglement than raw swapping.

4.2 Minimum Hardware Viability for QKD

In quantum cryptography, secure key generation under collective eavesdropping requires $F > 0.810$ [7]. We evaluated end-to-end fidelity as a function of raw elementary link quality $F_{\mathrm{init}} \in [0.82, 0.99]$ under realistic operational memory delay ($\tau_{\mathrm{RTT}}/T_2 = 0.010$).

As demonstrated in our analysis, unpurified swapping fails to reach the QKD threshold across all physical link qualities up to $F_{\mathrm{init}} = 0.890$. Single-round distillation under Strategy A achieves the security threshold at:

$$F_{\mathrm{init}}^{\mathrm{threshold}} \approx 0.880 \tag{15}$$

For hardware implementations operating below $F_{\mathrm{init}} = 0.880$, multi-round distillation or quantum error-correcting codes must be incorporated.




Figure 2: End-to-end fidelity across elementary link fidelities $F_{\mathrm{init}} \in [0.82, 0.99]$. Single-round purification crosses the secret-key distillation threshold ($F > 0.810$) at $F_{\mathrm{init}} \geq 0.880$.

4.3 Resource Overhead and Distillation Yield

Purification protocols are inherently probabilistic. Table 2 details the distillation success probability and ebit yield across both strategies.




Figure 3: Total purification success probability as a function of raw link fidelity. Strategy B exhibits higher overall yield than Strategy A due to requiring only a single distillation round.

Table 2: Distillation Success Probability vs. Link Quality

F_{init}	$P_{\mathrm{succ,local}}$ (Single Link)	$P_{\mathrm{succ,A}}$ (Dual Hop)	$P_{\mathrm{succ,B}}$ (End-to-End)
0.820	0.788	0.621	0.638
0.860	0.828	0.686	0.697
0.900	0.871	0.759	0.768
0.950	0.930	0.865	0.870

Because Strategy A requires two independent links to succeed simultaneously ($P_{\mathrm{succ,A}} = P_1 \times P_2$), its net throughput is lower than Strategy B across all parameter ranges, demonstrating that Strategy B is both more resilient to memory decoherence and more resource-efficient.

5 Discussion and Limitations

5.1 Engineering Guidelines for Quantum Routing

Our findings offer clear architectural rules of thumb for quantum network protocols:

- **Low-Latency Regime ($\tau_{\text{RTT}}/T_2 < 0.018$):** Implement link-level purification before swapping. This applies to short-distance metropolitan quantum networks utilizing long-lived atomic memories ($T_2 > 100$ ms).
- **High-Latency Regime ($\tau_{\text{RTT}}/T_2 \geq 0.018$):** Bypass local purification entirely; execute deterministic swapping immediately and perform distillation at the end nodes. This applies to inter-city links or solid-state memories with limited coherence ($T_2 < 1$ ms).

5.2 Limitations and Future Extensions

While this model captures the leading-order physical mechanisms, several engineering factors invite future exploration:

1. **Channel Noise Asymmetry:** We modeled noise via isotropic Werner states. Real fibers exhibit polarization-mode dispersion and asymmetric amplitude damping.
2. **Imperfect Swapping Gates:** We assumed idealized Bell-state measurements. Finite photon-detector efficiencies introduce dark counts and probabilistic swapping failures.
3. **Stochastic Queuing Delays:** Real repeater nodes experience asynchronous link establishment, requiring buffer queue management.

6 Conclusion

This paper presented an architectural evaluation of entanglement distillation scheduling in quantum repeater networks. By modeling the trade-off between quantum memory dephasing and non-local purification operations, we identified a definitive crossover point at $\tau_{\text{RTT}}/T_2 \approx 0.018$, established that local purification becomes counterproductive beyond $\tau_{\text{RTT}}/T_2 \approx 0.070$, and calculated the hardware boundary of $F_{\text{init}} \geq 0.880$ for QKD viability. These insights provide actionable guidelines for scheduling protocols in the emerging Quantum Internet.

References

[1] H. J. Kimble, "The quantum internet," *Nature*, vol. 453, no. 7198, pp. 1023–1030, 2008.

[2] A. K. Ekert, "Quantum cryptography based on Bell's theorem," *Physical Review Letters*, vol. 67, no. 6, pp. 661–663, 1991.

[3] H.-J. Briegel, W. Dür, J. I. Cirac, and P. Zoller, "Quantum repeaters: The role of imperfect local operations in quantum communication," *Physical Review Letters*, vol. 81, no. 26, pp. 5932–5935, 1998.

[4] W. Dür, H.-J. Briegel, J. I. Cirac, and P. Zoller, "Quantum repeaters based on entanglement purification," *Physical Review A*, vol. 59, no. 1, pp. 169–181, 1999.

[5] C. H. Bennett, G. Brassard, S. Popescu, B. Schumacher, J. A. Smolin, and W. K. Wootters, "Purification of noisy entanglement and faithful teleportation via noisy channels," *Physical Review Letters*, vol. 76, no. 5, pp. 722–725, 1996.

[6] M. Ghaderibaneh, C. Zhan, H. Gupta, and C. R. Ramakrishnan, "Efficient quantum network communication using optimized entanglement swapping trees," *IEEE Transactions on Quantum Engineering*, vol. 3, pp. 1–14, 2022.

[7] A. Acín, N. Brunner, N. Gisin, S. Massar, S. Pironio, and V. Scarani, "Device-independent security of quantum cryptography against collective attacks," *Physical Review Letters*, vol. 98, no. 23, p. 230501, 2007.