

CURSOR

NAME: V.C.Bhavan Bairav

REG NO: 192511369

1) PROGRAM:

```
MySQL 8.0 Command Line Client
1 row in set (0.00 sec)

mysql> CREATE TABLE employees (
->     id INT,
->     Name VARCHAR(100),
->     email VARCHAR(100)
-> );
Query OK, 0 rows affected (0.06 sec)

mysql>
mysql> INSERT INTO employees VALUES
-> (1, 'Harry Potter', 'pharry@warnerbros.com'),
-> (2, 'Clark Kent', 'kclark@dccomics.com'),
-> (3, 'Tony Stark', 'stony@marvel.com');
Query OK, 3 rows affected (0.01 sec)
Records: 3  Duplicates: 0  Warnings: 0

mysql>
mysql> DELIMITER $$
mysql>
mysql> CREATE PROCEDURE build_email_list(
->     INOUT email_list VARCHAR(4000)
-> )
-> BEGIN
->     DECLARE v_finished INTEGER DEFAULT 0;
->     DECLARE v_email VARCHAR(100) DEFAULT '';
->
->     DECLARE email_cursor CURSOR FOR
->         SELECT email FROM employees;
->
->     DECLARE CONTINUE HANDLER FOR NOT FOUND
->         SET v_finished = 1;
->
->     OPEN email_cursor;
->
->     get_email: LOOP
->         FETCH email_cursor INTO v_email;
->
->         IF v_finished = 1 THEN
->             LEAVE get_email;
->         END IF;
->
->         SET email_list = CONCAT(email_list, v_email, ';');
->     END LOOP get_email;
->
->     CLOSE email_cursor;
-> END$$
Query OK, 0 rows affected (0.01 sec)

mysql>
mysql> DELIMITER ;
mysql>
```

OUTPUT:

```
mysql>
mysql> SET @email_list = '';
Query OK, 0 rows affected (0.00 sec)

mysql>
mysql> CALL build_email_list(@email_list);
Query OK, 0 rows affected (0.00 sec)

mysql>
mysql> SELECT @email_list AS Email_List;
+-----+
| Email_List                                     |
+-----+
| pharry@warnerbros.com;kclark@dccomics.com;stony@marvel.com; |
+-----+
1 row in set (0.00 sec)

mysql>
```