

* HTML *

- 1) Introduction
- 2) History
- 3) Structure of HTML
- 4) Tags
- 5) Heading Tags
- 6) paragraph Tag
- 7) commands
- 8) Formatic tags
- 9) Elements
- 10) List
- 11) Attributes
- 12) Tables
- 13) Forms
- 14) media tag
- 15) Anchor Tag
- 16) I frame
- 17) semantic tags
- 18) Marquee tag
- 19) Entities
- 20) Additional Tag

Introduction :-

- HTML stands for Hyper Text Markup language
- HTML is used to provide structure of our webpage
- To create a HTML file (or) htm prefer .HTML Extension.
html (or) htm prefer .HTML Because more readability to user
- HTML is not case sensitive i.e the code can be written in either in (uppercase or lowercase) preferable lowercase

History

HTML was designed by "Tim Berners Lee" in the year 1991

HTML 1.0 → 1993

2.0 → 1995

3.2 → 1997

4.01 → 1999

5.0 → 2014

Note :- Currently we are using HTML 5.0 version.

Structure of HTML (or) Template (or) Boilexplate

`<!doctype html>` → tells us that we are using
html 5.0 version

opening
tag

`<html>` - root element

`<head>` `</head>` details of our webpage

`<body>` } contents that needs to displayed
`</body>`

closing
tag

`</html>`

Tags :-

Any predefined word enclosed in angular braces are referred to tags

There are 2 type of tags in HTML

→ paired tags

→ unpaired tags

1) paired tags :- These are the tags that has both opening tag and closing tag

Ex:- html, Body, title, head.

2) unpaired tags :- These are the tags that has only opening tag

Ex:- doctype html.

Heading Tag

To display Heading on web page we have 6 different type head tags Ranging from h1 to h6

<h1></h1>

<h2></h2>

<h3></h3>

<h4></h4>

<h5></h5>

<h6></h6>

decrease
in
Font size

paragraph tag :-

To display a paragraph on our web page we use

<p></p>

Note :-

* To generate
specify as

random content
lorem 50

of 50 words we

* To generate
specify as

random content
lorem * 50

of 50 lines we

ctrl + space (Suggestions)

ctrl + B (Side Bar)

Formatting Tags

Formatting Tags are used to add the changes in the appearance of Text content.

i) `<b></b>` (or) `<strong></strong>`

Makes the content appear in Bold

ii) `<i></i>` (or) `<em></em>` (Emphasize)

Makes the content appear in Italic (tilt/slant)

iii) `<u></u>` (or) `<ins></ins>` (insert)

provides underline for the specific text content

iv) `<strike></strike>` (or) `<del></del>` (delete)

It passes a line through the content

v) `<mark></mark>`

used to highlight the text content

vi) `<sub></sub>`

Makes text appear slightly below the content level

vii) `<sup></sup>` (superscript)

Makes text appear slightly above the content level

viii) `<big></big>`

Makes the text appear in Bigger font size when compared to the default font size

ix) `<small></small>`

Makes the text appear in smaller font size when compared to the default font size

* Deprecated → No more in use

Ex:- `strike`, `big`

Elements

* Elements are the combination of opening tag and closing tag along with the content in between.

Tags

<h1> </h1>

<p> </p>

<mark> </mark>

Elements

<h1> chicken </h1>

<p> rutton </p>

<mark> fish </mark>

Tags

There are two types of element in html

→ Block level element

→ Inline level element

1) Block level element :- These are the elements that take entire width of the webpage

Ex:- ~~entire~~ or Heading tags, paragraph tag

2) Inline level element :-

These are the elements that take only the content width

Ex:- formatting tags . etc

Comments

→ Comments are the piece of code that is not executed on the browser

→ Comments are mainly used to improve the readability of code

SYNTAX :-

<!-- comment -->

Ctrl + / →
comment
uncomment

LIST

→ It is group of related items

TYPES

There are three types of list in HTML

- 1) Ordered list
- 2) unordered list
- 3) definition / Description list

1) Ordered List :-

It is a type of list that maintains a proper Sequence.

→ Sequence can be Numerical (Default), Alphabetical (uppercase or lowercase) and Roman Number Sequence (uppercase or lowercase).

→ To create an ordered list in HTML we use `<ol></ol>` and to display the data into it we use `<li></li>` (list item).

Attributes used

1) type - This attribute is used to modify the Sequence of ordered list.

It can take the values like "1/a/A/i/I"

2) Start - This attribute specifies which character or the number should start with

It will only take Numerical values

3) Reversed - This attribute converts the list sequence in Reversed order.

Ex :- <ol type = "a" start = "5" reversed>

 AZEEBO

 GHOST

 CHIRAG

 SNAP

 MATTAM AL ARABIA

 GIRLFRIEND

 PISTAHOUSE

 QISMAT JAIL

 SHAH GHOUSE

 JUNGLE

2) unordered list :-

It is a type of list that doesn't maintain any sequence
→ Sequences can be disc (default), circle, square
→ To create an unordered list, we use
to specify the data into it we use
(list item)

Attributes used

1) type :- It is used to change the sequence of list item.

→ It can take the values like disc, circle, square.

Ex:-

<ul type = "square">

 TOP 5 CAFES IN HYDERABAD

 MAKAN

 LAVEIN ROSE

 TREE STORIES

 RUBABU

 JUIC HOLIC

&

3) Description / Definition List :-

It ~~at~~ is a list of terms and description
→ To create a description / Definition list we use
<dl></dl> and to specify the term into
it <dt></dt> (data term) and to specify
the description about the term we use
<dd></dd> (data description)

<! -- Description / Definition List -->

<dl>

<dt> HTML </dt>

<dd> Hyper Text Markup Language </dd>

<dt> CSS </dt>

<dd> Cascading Style Sheets </dd>

<dt> JS </dt>

<dd> JavaScript </dd>

</dl>

<body>

</html>

Nested List

It is a way of creating the list inside another list.

Note :-

1) Analyse the first list item

2) Analyse the Spaces

• having space - create a new list

• coming out of space - come out of list

<ol type="1">

Tollywood

<ol type="a">

Prabhas

<ul type="circle">

Salaa

Bahubali 2

Mahesh Babu

<ul type="circle">

Pokiri

Khaleja

Bollywood

<ol type="a">

Shah Rukh Khan

<ul type="circle">

Chennai Express

K3G

Deepika Padukone

<ul type="circle">

Kalki

Padmaavat

1. Tollywood

a. Prabhas

a. Salaa

o. Bahubali 2

b. Mahesh Babu

o. Pokiri

o. Khaleja

2. Bollywood

a. Shah Rukh Khan

o. Chennai Express

o. K3G

b. Deepika Padukone

o. Kalki

o. Padmaavat

Attributes :-

- Attributes are those which provide extra information about a tag
- Attributes should always be specified inside the opening tag
- Most of the attributes will follow the syntax

`attribute-name = "value"`

TYPES :- There are two types of Attributes in HTML

1) Global / Core Attributes

2) Element Specific Attributes

1) Global / Core Attributes :- These are the attributes that can be specified for most of HTML Elements.
Ex:- id, class, style, title.

Note :- title attribute is used to provide tooltip.

Ex:- `<mark title = "Hyper Text Markup Language">HTML</mark>`

2) Element Specific Attributes :- These are the attributes that should specify the particular element

Ex:- type, start, reversed

Ex:- `<!DOCTYPE html>
<html lang = "en">
<head>`

`<meta charset = "UTF-8">`

`<meta name = "viewport" content = "width = device-width, initial-scale = 1.0">`

`<title> ATTRIBUTES = /title>`


```

</head>
<body>
  <h1 title="Pahul">Anushka Shetty </h1>
  <mark title="HyperText Markup Language">HTML </mark>
</body>
</html>

```

Tables

- Tables are the combination of rows and columns
- To create the table we use `<table>` `</table>`
- To provide title for the table `<caption>` `</caption>`
- Tables in HTML should be created with respect to row by row using `<tr>` `</tr>` (table row)
- To specify the data inside the table row
- We use `<td>` `</td>` (table data) and `<th>` `</th>` (table header) will make the data appear in Bold and center with respect to its cell

Attributes used

- 1) Border :- It is used to deal with the outer Border of table
 - It takes in a Numerical Value that decides a thickness of the Border
- 2) Cell padding :- It is used to add the Space inside the cell
- 3) Cell spacing :- It is used to add the Space around the cell
- 4) Rules :- It is used to deal with the inner Border of a table

• It can take the value like - rows/cols/all.

Note :- cell spacing should be used only when the border attribute is not defined.

5) rowspan :-

This attribute is used to extend the cell across the rows.

6) colspan :-

This attribute is used to extend the cell across the columns.

```
<table border="1" cellpadding="10" cellspacing="5" rules="all">
```

```
<caption> Subjects </caption>
```

```
<tr>
```

```
<td rowspan="2" colspan="2" align="center"> HTML </td>
```

```
<td colspan="2" align="center"> CSS </td>
```

```
</tr>
```

```
<tr>
```

```
<td> JavaScript </td>
```

```
<td> React JS </td>
```

```
</tr>
```

```
<tr>
```

```
<td rowspan="2"> Java </td>
```

```
<td> SQL </td>
```

```
<td rowspan="2" align="center"> Python </td>
```

```
<td> Django </td>
```

```
</tr>
```

```
<tr>
```

```
<td> JSP </td>
```

```
<td> Selenium </td>
```

Forms

Forms are used to collect the data from the user.

- To create a form in html we use `<form></form>`
- `<fieldset></fieldset>` provides border for the Form
- `<legend></legend>` displays a text that passes through the field set.
- `<label></label>` provides naming or the suggestion, so has what to be entered in the corresponding input field.
- `<input>` provides rectangular area where user can enter the data.

Note :- To link label and input we use `for=" "` and `id=" "` respectively and specify with the same value.

* type attribute specifies the kind of data a input field is collect.

Ex:- Text (default), Email, password, Submit

Form input types

1) type = "text"

It is a default value that specifies the input field to accept plain text, such as names etc.

2) type = "email"

It adds a validation by checking if @ symbol is missing in the given email address.

3) type = "password"

Password is hidden while entering into the field.

4) type = "Number"

It restricts the input to numbers only.

5) type = "Tel"

Special design for entering telephone numbers with specific characters like +, #, *

6) type = "date"

It displays a calendar through which user can select the date

7) type = "datetime-local"

It displays a calendar and clock through which user can select the date as well as time.

8) type = ~~radio~~ "radio"

Mainly design to select one among the given choices which can be achieved along with the combination name attribute for the input fields.

9) type = "checkbox"

It is mainly designed to select one or more from the given choices.

10) type = "file"

used to create a file upload button allowing the user to select and upload the file from their device

11) type = "Submit"

It creates a Submit button for the form and value attribute is used to change the text inside Submit button.

12) type = "Reset"

It creates a Reset button which clears out all of the data of an input field and sets it to the initial value

Droddown :- `<select>` `</select>` is used to create a dropdown and `<option>` `</option>` is used to fill the choices

Text Area :- `<textarea>` `</textarea>` creates a multiline input control whose dimensions can be manipulated using rows and columns attributes.