

```
#include <Wire.h>
```

```
#include <LiquidCrystal_I2C.h>
```

```
#include <DHT.h>
```

```
#define DHTPIN 3
```

```
#define DHTTYPE DHT11
```

```
DHT dht(DHTPIN, DHTTYPE);
```

```
LiquidCrystal_I2C lcd(0x27, 16, 2);
```

```
// Pins
```

```
int mq7 = A0;    // Display + send
```

```
int mq135 = A2;  // Display + send
```

```
void setup() {
```

```
    Serial.begin(9600);
```

```
    lcd.init();
```

```
    lcd.backlight();
```

```
    dht.begin();
```

```
}
```

```
void loop() {
```

```
    int mq7Value = analogRead(mq7);
```

```
    int mq135Value = analogRead(mq135);
```

```
    float temp = dht.readTemperature();
```

```
    float hum = dht.readHumidity();
```

```
// ♦ LCD (NO CHANGE STYLE)

lcd.clear();

lcd.setCursor(0,0);

lcd.print("T:");

lcd.print(temp);

lcd.print(" H:");

lcd.print(hum);


lcd.setCursor(0,1);

lcd.print("MQ7:");

lcd.print(mq7Value);

lcd.print(" AQ:");

lcd.print(mq135Value);


// ♦ Send to ESP32

Serial.print(temp);

Serial.print(",");

Serial.print(hum);

Serial.print(",");

Serial.print(mq7Value);

Serial.print(",");

Serial.println(mq135Value);

delay(2000);

}
```