



give me neat and detailed solutions for unit in easy language

draw text (markdown)diagram in chat where diagram is needed and draw table for difference que and differences

should be 7 points minimum and where definations are present give example also and all solution should be well detailed and explained

explain all questions in deatail minimum half page should be there as per sppu exam somequestions are as per 9 marks so give ans as per it

Sure Bhavesh! Please upload or type the Unit number and all the related questions you want detailed answers for.

As per your instructions, I will:

- Explain all questions in easy and clear language
- Include diagrams in markdown where required
- Create comparison tables for difference-based questions with at least 7 points
- Provide detailed definitions with examples
- 🔽 Ensure every 9-mark answer is minimum half a page, well explained

Just let me know:

- Which Unit are we working on?
- What are the questions? (You can upload a photo or type them)

Once I get that, I'll start preparing detailed and SPPU-style answers for each.



Write a note on:

i)

ii)

Database Modification using SQL

Set Operation

Here's a well-detailed and easy-to-understand answer as per SPPU exam format (suitable for 8–9 marks). It includes definitions, SQL syntax, examples, and clear explanation.

Question:

Write a note on:

- i) Database Modification using SQL
- ii) Set Operation
- i) Database Modification using SQL

Database modification refers to operations that change the data in a database. In SQL, modification includes inserting new records, updating existing records, and deleting records from a table.

There are mainly 3 types of data modification commands in SQL:

- 1. INSERT
- 2. UPDATE
- 3. DELETE

Let's understand each with definition, syntax, and example.

1. INSERT Statement
Used to add new records into a table.

Syntax:

```
INSERT INTO table_name (column1, column2, ...)
VALUES (value1, value2, ...);
```

Example:

```
INSERT INTO Employee (EmpID, Name, Salary)
VALUES (101, 'Amit', 45000);
```

2. UPDATE Statement

Used to modify existing records in a table.

Syntax:

```
UPDATE table_name
SET column1 = value1, column2 = value2
WHERE condition;
```

Example:

```
UPDATE Employee
SET Salary = 50000
WHERE EmpID = 101;
```

3. DELETE Statement

Used to delete records from a table.

Syntax:

```
DELETE FROM table_name
WHERE condition;
```

Example:

```
DELETE FROM Employee
WHERE EmpID = 101;
```

Note:

- Always use WHERE clause in UPDATE and DELETE to avoid affecting all rows.
- If WHERE is omitted, the entire table may be updated or deleted.

Use cases of database modification:

- Adding new employees (INSERT)
- Increasing salary (UPDATE)
- Removing terminated employees (DELETE)

These commands help in maintaining up-to-date and clean data.

ii) Set Operation in SQL

Set operations in SQL allow combining the results of two or more SELECT queries. These operations are similar to set theory in mathematics.

The major Set Operations in SQL are:

- 1. UNION
- 2. UNION ALL
- 3. INTERSECT
- 4. MINUS (or EXCEPT in some DBMS)

Let's understand them with explanation and examples.

1. UNION

Combines the result of two SELECT statements and removes duplicates.

Syntax:

```
SELECT column1 FROM table1
UNION
SELECT column1 FROM table2;
```

Example:

```
SELECT City FROM Customers
UNION
SELECT City FROM Suppliers;
```

2. UNION ALL

Same as UNION, but keeps duplicates.

Syntax:

```
SELECT column1 FROM table1
UNION ALL
SELECT column1 FROM table2;
```

3. INTERSECT

Returns only common rows from both SELECT queries.

Syntax:

```
SELECT column1 FROM table1
INTERSECT
SELECT column1 FROM table2;
```

Example:

```
SELECT ProductID FROM Orders
INTERSECT
SELECT ProductID FROM Products;
```

4. MINUS (or EXCEPT)

Returns rows from first SELECT that are not present in second SELECT.

Syntax (Oracle):

```
SELECT column1 FROM table1
MINUS
SELECT column1 FROM table2;
```

Syntax (SQL Server / PostgreSQL):

```
SELECT column1 FROM table1
EXCEPT
SELECT column1 FROM table2;
```

Rules for Set Operations:

- Number and data type of columns must match.
- Column names are taken from the first SELECT statement.
- ORDER BY can only be used at the end of the last SELECT.

***** Use cases:



- Find customers who are not suppliers (MINUS)
- Combine data from multiple branches (UNION)
- Get overlapping data from two tables (INTERSECT)

This explanation covers both parts with syntax, examples, and use cases. Let me know if you want diagrams or visual flowcharts for these commands as well.



Consider the following relation:

Customer(cid,cname,caddress,city,state)

Order(oid,odate,aamount)

[8]

[6]

Customer and order are related with one to many relationship. solve the following queries.

i)

ii)

iii)

List the name of customer who belong to Maharashtra state, sorted on city.

What are the name of all customer who placed the order between 01/01/2010 to 31/03/2011?

Define constraint on order amount such that it should be always greater than zero.

Here is the well-formatted, easy-to-understand and SPPU-style detailed solution for the given queries on the relation:

- Relation:
 - Customer(cid, cname, caddress, city, state)
 - Order(oid, odate, aamount)

Assumption: Since Customer and Order are in a one-to-many relationship, we assume the Order table contains a foreign key cid which refers to Customer.

Thus, modified Order table: Order(oid, odate, aamount, cid)

Let's now solve the queries:

i) List the name of customers who belong to Maharashtra state, sorted on city.

Explanation:

We need to retrieve customer names from the Customer table who live in Maharashtra, and sort the result based on city in ascending order.

✓ SQL Query:

sql
SELECT cname
FROM Customer



```
WHERE state = 'Maharashtra'
ORDER BY city ASC;
```

- Explanation of SQL:
 - SELECT cname: fetch customer names.
 - WHERE state = 'Maharashtra': filter only customers from Maharashtra.
 - ORDER BY city ASC: sort the results alphabetically based on city.
- **o** Example Output (Sample):

```
Cname

Anjali

Rahul

Sneha
```

- ii) What are the names of all customers who placed the order between 01/01/2010 and 31/03/2011?
- Explanation:

We need to join the Customer and Order tables using the common column cid and fetch customer names whose order dates lie between the given date range.

✓ SQL Query:

```
SELECT DISTINCT c.cname
FROM Customer c
JOIN Order o ON c.cid = o.cid
WHERE o.odate BETWEEN '2010-01-01' AND '2011-03-31';
```

- Explanation of SQL:
 - JOIN Customer and Order using cid.
 - o.odate BETWEEN '2010-01-01' AND '2011-03-31': filters only orders in the specified range.
 - SELECT DISTINCT: avoids duplicate names if a customer placed multiple orders.
- **©** Example Output (Sample):

cname	
Ravi	
Meena	
Sameer	

- Note: The date format used depends on the DBMS (use YYYY-MM-DD for MySQL/PostgreSQL).
- iii) Define constraint on order amount such that it should always be greater than zero.
- Explanation:

We need to apply a CHECK constraint on the aamount column of the Order table such that it does not allow any zero or negative values.



SQL Statement:

If we are creating the table:

```
sql
CREATE TABLE Order (
    oid INT PRIMARY KEY,
    odate DATE,
    aamount DECIMAL(10,2) CHECK (aamount > 0),
    cid INT,
    FOREIGN KEY (cid) REFERENCES Customer(cid)
);
```

If the table is already created and we want to alter it:

```
sql
ALTER TABLE Order
ADD CONSTRAINT chk_amount_positive
CHECK (aamount > 0);
```

- Explanation of SQL:
 - CHECK (aamount > 0): ensures value is greater than zero.
 - It restricts entry of invalid data like 0 or negative order amounts.
 - Naming the constraint (chk_amount_positive) helps in managing it later.

📝 Use case: Helps in maintaining data integrity by ensuring that every order placed has a valid positive amount.

Summary of All Queries:

Part	Description	SQL/Action
i)	Customers from Maharashtra sorted by city	SELECT cname FROM Customer WHERE state='Maharashtra' ORDER BY city ASC;
ii)	Customers who placed order between given dates	SELECT DISTINCT cname FROM Customer JOIN Order ON cid WHERE odate BETWEEN
iii)	Constraint on order amount (> 0)	CHECK constraint using CREATE TABLE or ALTER TABLE

Let me know if you'd like ER diagram or relational schema illustration to support this answer visually!



Explain the concept of Dynamic and Embedded SQL

Sure Bhavesh! Here's a detailed and easy-to-understand answer for the SPPU exam (suitable for 8-9 marks) explaining the concept of Dynamic and Embedded SQL. I'll include definitions, syntax, examples, differences, and when to use each — all explained in simple language.

Question:

Explain the concept of Dynamic and Embedded SQL.

1. What is Embedded SQL?

Embedded SQL is a method of combining SQL statements directly inside a high-level programming language such as C, C++, Java, or COBOL. The SQL statements are written within the code and are executed during the program's runtime.

Definition:

Embedded SQL is the process of embedding SQL statements within the code of a host programming language.

- Common Host Languages:
- C, C++, Java, Python, Pascal, etc.
- Syntax:

In C language (using preprocessor-style):

```
EXEC SQL SELECT cname INTO :name FROM Customer WHERE cid = :id;
```

- EXEC SQL: keyword used to indicate SQL inside C
- :name and :id → host language variables (bind variables)
- ✓ How it works:
 - SQL statements are precompiled before the actual code is compiled.
 - Values from variables in the programming language can be substituted in SQL.
- Example:

Suppose you want to get the name of a customer with id 101.

```
int id = 101;
char name[30];

EXEC SQL SELECT cname INTO :name FROM Customer WHERE cid = :id;
```

- Key Points:
 - Requires a precompiler (like Pro*C or SQLJ).
 - SQL syntax is static and fixed.
 - More secure and faster because queries are compiled before execution.
- 2. What is Dynamic SQL?

Dynamic SQL refers to SQL statements that are constructed and executed at runtime. The exact structure of the query may not be known during program compilation.

V Definition:

Dynamic SQL allows programs to construct and execute SQL queries dynamically at runtime.

- V Features:
 - Useful when SQL statements depend on user input or runtime conditions.



• Can create flexible applications (e.g., search filters, dashboards).

Syntax:

In most languages (e.g., using JDBC in Java):

```
string sql = "SELECT cname FROM Customer WHERE city = ?";
PreparedStatement ps = conn.prepareStatement(sql);
ps.setString(1, "Pune");
ResultSet rs = ps.executeQuery();
```

Or in PL/SQL:

```
sql

EXECUTE IMMEDIATE 'DELETE FROM Customer WHERE state = ''Maharashtra''';
```

Example:

Suppose a user enters a city name, and the application fetches all customers from that city. You can build the query dynamically:

```
java

String city = getInput(); // e.g., "Pune"
String query = "SELECT * FROM Customer WHERE city = '" + city + "'";
```

Key Points:

- More flexible but potentially less secure (risk of SQL injection if not handled carefully).
- Supports runtime decision-making.

Difference between Embedded SQL and Dynamic SQL:

No.	Embedded SQL	Dynamic SQL
1	SQL is written at compile-time	SQL is written/constructed at runtime
2	Used for fixed and known queries	Used when queries are not known in advance
3	Requires SQL preprocessor	Doesn't require SQL preprocessor
4	More secure (less prone to injection)	Needs extra care (may risk SQL injection)
5	Better performance due to pre-compilation	Slightly slower due to runtime parsing
6	Uses host variables (e.g., :var)	Uses string concatenation or parameter binding
7	Example: EXEC SQL SELECT	Example: EXECUTE IMMEDIATE 'SELECT'

When to Use What?

- Use Embedded SQL when queries are known beforehand and performance and security are a priority.
- Use Dynamic SQL when you need flexible queries depending on user input or logic conditions.



6 Summary:

- Embedded SQL allows integrating static SQL into application code using special syntax.
- Dynamic SQL helps create flexible programs where SQL queries are built at runtime.
- Both techniques are essential for building robust, real-world database applications.

Let me know if you'd like a diagram showing their working process or compiler stages!



Explain in detail with syntax Stored, procedure and Trigger 3-54

Certainly Bhavesh! Here's a detailed, well-structured explanation suitable for a 9-mark SPPU answer, covering:

- Stored Procedure
- Trigger
- Syntax and Examples
- Differences between Stored Procedure and Trigger in tabular form (at the end)

Let's begin:

1. STORED PROCEDURE

Definition:

A stored procedure is a named block of SQL code stored in the database that performs a specific task. It can take parameters (IN, OUT, INOUT) and can be called when needed.

It is used to encapsulate logic like insert, update, calculations, etc., which can be reused across multiple applications.

Benefits:

- Reduces code duplication
- Improves performance
- Increases security and maintainability
- **Syntax:**

In MySQL-style syntax:

```
CREATE PROCEDURE procedure_name(IN paraml datatype, OUT param2 datatype)
BEGIN
    -- SQL statements
END;
```

Example: Procedure to get customer name from ID

```
DELIMITER //
CREATE PROCEDURE GetCustomerName(IN cust_id INT, OUT cust_name VARCHAR(100))
BEGIN
    SELECT cname INTO cust_name FROM Customer WHERE cid = cust_id;
END;
//
DELIMITER;
```

Calling the procedure:

```
CALL GetCustomerName(101, @name);
SELECT @name;
```

- Notes:
 - IN: Accepts value from caller
 - OUT: Returns value to caller
 - INOUT: Does both
- 2. TRIGGER
- Definition:

A trigger is a special kind of stored procedure that is automatically executed (triggered) when certain events (INSERT, UPDATE, DELETE) happen on a table.

- Renefits:
 - Enforces business rules automatically
 - Ensures data consistency
 - Useful for audit logging
- Syntax:

MySQL-style syntax:

```
CREATE TRIGGER trigger_name
{BEFORE | AFTER} {INSERT | UPDATE | DELETE}
ON table_name
FOR EACH ROW
BEGIN
-- SQL statements
END;
```

Example: Trigger to prevent inserting orders with amount ≤ 0

```
create trigger CheckAmountBeforeInsert
BEFORE INSERT ON Orders
```



```
FOR EACH ROW

BEGIN

IF NEW.aamount <= 0 THEN

SIGNAL SQLSTATE '45000' SET MESSAGE_TEXT = 'Amount must be > 0';

END IF;

END;
```

Example: Trigger to log every deletion from Customer table

```
CREATE TRIGGER LogCustomerDeletion
AFTER DELETE ON Customer
FOR EACH ROW
BEGIN
INSERT INTO AuditLog(action, customer_id, deleted_at)
VALUES ('DELETE', OLD.cid, NOW());
END;
```

Trigger Timing Options:

- BEFORE INSERT
- AFTER INSERT
- BEFORE UPDATE
- AFTER UPDATE
- BEFORE DELETE
- AFTER DELETE

👔 3. Difference between Stored Procedure and Trigger

No.	Stored Procedure	Trigger
1	Executed explicitly using CALL command	Automatically executed on table events
2	Can take parameters (IN, OUT, INOUT)	Cannot take parameters
3	Called manually by user or application	Fired automatically by DBMS
4	Used for performing tasks like reporting, updates	Used for enforcing rules or auditing
5	Flexibility to handle multiple logic blocks	Bound to specific table and event
6	Can return values	Does not return values
7	More control in calling and error handling	Less flexible, tightly coupled with table operation

✓ Summary:

- A stored procedure is a reusable, named block of SQL that must be explicitly invoked and can take input/output parameters.
- A trigger is an event-driven procedure that executes automatically when certain database actions occur.
- Both help in managing business logic at the database level, ensuring consistency, performance, and integrity.

Let me know if you'd like a diagram of trigger flow or procedure execution!



```
Write the syntax for following SQL command:
i)
Create Table
ii)
iii)
iv)
v)
vi
vi
c)
Alter table
Drop table
Insert
Update
Delete
```

Sure Bhavesh! Here's a neat, detailed explanation of all the requested SQL commands along with proper syntax, examples, and simple explanations. This answer is suitable for an SPPU exam 8–9 mark question.

Question:

Write the syntax for the following SQL commands:

- i) Create Table
- ii) Alter Table
- iii) Drop Table
- iv) Insert
- v) Update
- vi) Delete

i) CREATE TABLE

Purpose:

Used to create a new table in the database.

Syntax:

```
CREATE TABLE table_name (
   column1 datatype [constraint],
   column2 datatype [constraint],
   ...
);
```

***** Example:

```
CREATE TABLE Customer (
   cid INT PRIMARY KEY,
   cname VARCHAR(50),
   city VARCHAR(50),
   state VARCHAR(30)
);
```

- ii) ALTER TABLE
- Purpose:

Used to modify the structure of an existing table (e.g., add, delete, or modify columns).

Syntax (Add column):

```
sql

ALTER TABLE table_name ADD column_name datatype;
```

📜 Syntax (Modify column):

```
sql

ALTER TABLE table_name MODIFY column_name new_datatype;
```

📜 Syntax (Drop column):

```
sql

ALTER TABLE table_name DROP COLUMN column_name;
```

***** Example:

```
ALTER TABLE Customer ADD phone VARCHAR(15);
```

- 🔃 iii) DROP TABLE
- 🖈 Purpose:

Used to delete a table and all its data from the database permanently.

Syntax:

```
prop Table table_name;
```

***** Example:

```
DROP TABLE Customer;
```

- Warning: All data and table structure will be lost permanently.
- iv) INSERT INTO
- 🖈 Purpose:

Used to insert a new record into a table.

📜 Syntax (Insert all columns):

```
sql
INSERT INTO table_name VALUES (value1, value2, ...);
```

📜 Syntax (Insert specific columns):

```
sql
INSERT INTO table_name (column1, column2) VALUES (value1, value2);
```

***** Example:

```
INSERT INTO Customer (cid, cname, city, state)
VALUES (101, 'Bhavesh', 'Pune', 'Maharashtra');
```

- v) UPDATE
- 📌 Purpose:

Used to modify existing records in a table.

I Syntax:

```
UPDATE table_name
SET column1 = value1, column2 = value2, ...
WHERE condition;
```

***** Example:

```
UPDATE Customer
SET city = 'Mumbai'
WHERE cid = 101;
```

Note: Always use WHERE to avoid updating all rows.



vi) DELETE

🖈 Purpose:

Used to delete existing records from a table.

Syntax:

```
DELETE FROM table_name
WHERE condition;
```

🖈 Example:

```
sql

DELETE FROM Customer
WHERE state = 'Maharashtra';
```

Warning: Omitting WHERE will delete all rows.

Summary Table:

Command	Purpose	Key Syntax Example
CREATE TABLE	Create a new table	CREATE TABLE Customer ()
ALTER TABLE	Modify existing table structure	ALTER TABLE Customer ADD phone VARCHAR(15);
DROP TABLE	Permanently delete a table	DROP TABLE Customer;
INSERT	Add new row to a table	INSERT INTO Customer VALUES ();
UPDATE	Change data in existing row	UPDATE Customer SET city='Mumbai' WHERE cid=101;
DELETE	Remove row from table	DELETE FROM Customer WHERE cid=101;

Let me know if you'd like a visual diagram or flowchart for any of these operations!



Describe Circumstances under which you would choose to use Embedded SQL than normal SQL or only a general purpose programming Language

Certainly, Bhavesh! Here's a detailed, well-explained answer suitable for 8–9 marks SPPU exam, covering when and why to choose Embedded SQL over Normal SQL or a General Purpose Programming Language, with examples and clear reasoning.

Question:

Describe the circumstances under which you would choose to use Embedded SQL rather than normal SQL or only a general purpose programming language.



Answer:

Introduction:

Embedded SQL is a programming technique where SQL commands are integrated directly inside a host programming language like C, Java, or Python. This technique allows developers to combine the power of SQL's database manipulation with the flexibility and control of a general-purpose programming language (GPL).

1. When to Choose Embedded SQL over Normal SQL

• Complex Business Logic:

When your application needs to perform complex operations that involve both database interaction and procedural logic (loops, conditionals), embedded SQL allows combining SQL commands with host language control structures.

Example: A banking system calculating interest, updating balances, and generating statements where SQL queries and program logic work together.

• Multiple Database Operations in Sequence:

Embedded SQL is useful if multiple SQL statements must be executed as part of a transaction or sequence, controlled by host language constructs.

Example: Processing an order might involve inserting order details, updating inventory, and logging activity in one go.

• Performance Optimization:

Embedded SQL supports pre-compilation of SQL statements with host program, which reduces parsing overhead compared to sending multiple ad-hoc SQL queries separately.

• Error Handling and Flow Control:

Host languages offer advanced error handling (try-catch, exceptions) and flow control, which normal SQL alone cannot handle well. Embedded SQL lets you handle database errors gracefully within your application.

2. When to Choose Embedded SQL over only a General Purpose Programming Language (GPL)

• Data Manipulation and Querying:

SQL is purpose-built for efficient data retrieval and manipulation. Writing raw data-handling logic in GPL is complex and inefficient. Embedded SQL lets you use SQL's power within the GPL, so you don't have to manually write complex data processing code.

Example: Selecting all customers from a particular city is simpler using SQL than writing file/database handling code in C or Java alone.

Portability and Standardization:

Embedded SQL adheres to standardized SQL syntax which can run on various database systems with minor changes, allowing easier maintenance and portability.

• Security and Injection Prevention:

Embedded SQL uses host variables and bind parameters which help prevent SQL injection attacks, unlike dynamically constructed queries in GPL without SQL support.

3. Specific Circumstances Favoring Embedded SQL

Circumstance	Explanation
Applications requiring both complex business logic and DB operations	Embedded SQL integrates SQL within host code for seamless logic + data manipulation
Need for strong transaction control and error handling	Host languages can manage transactions, exceptions, and rollback with embedded SQL
Large-scale enterprise applications with multiple DB interactions	Embedded SQL reduces communication overhead by embedding SQL calls
When pre-compilation and optimization of SQL is necessary	Embedded SQL statements are precompiled, improving performance
Requirement to maintain code clarity and modularity	Embedded SQL allows modular program design with clear separation of SQL and application logic
Need to prevent SQL injection and improve security	Using bind variables in embedded SQL improves security

4. Example to Illustrate Embedded SQL Use

Suppose you want to update a customer's city after checking some condition:

```
EXEC SQL BEGIN DECLARE SECTION;
int cust_id = 101;
char new_city[20] = "Mumbai";
int order_count;
EXEC SQL END DECLARE SECTION;

EXEC SQL SELECT COUNT(*) INTO :order_count FROM Orders WHERE cid = :cust_id;
if (order_count > 0) {
    EXEC SQL UPDATE Customer SET city = :new_city WHERE cid = :cust_id;
    EXEC SQL COMMIT;
} else {
    printf("No orders found for customer.\n");
}
```

This example clearly shows how SQL queries are embedded into host language C code, enabling both SQL and program logic to work together.

Summary:

Aspect	Embedded SQL	Normal SQL / GPL Alone
Handling complex logic	Excellent (embedded in host code)	Poor / Requires separate logic
Performance	Better (precompiled SQL)	Slower (ad-hoc queries or GPL code)
Error handling & transactions	Robust with host language	Limited in normal SQL
Security (SQL injection)	Better with bind variables	Risky if not carefully coded
Portability	Good (standard SQL syntax)	GPL may lack DB integration

In conclusion, Embedded SQL is chosen when an application requires a combination of complex program logic, secure and efficient database access, and maintainability — something neither plain SQL

nor general-purpose programming alone can provide easily.

Let me know if you want me to add diagrams or example programs!



Differentiate between:

i)

ii)

c)

Trigger & stored procedure Embedded SQL and Dynamic SQL

Certainly, Bhavesh! Below is a detailed, neat, and well-organized answer suitable for an 8–9 marks SPPU exam question. It covers **differences between Trigger & Stored Procedure**, and **Embedded SQL & Dynamic SQL**, with at least 7 points each, presented in clear markdown tables and explanations.

Differentiate between:

i) Trigger & Stored Procedure

Sr. No.	Trigger	Stored Procedure
1	Automatically executed in response to an event (INSERT, UPDATE, DELETE) on a table	Executed explicitly by calling it with a CALL statement
2	Cannot be called directly by the user or application	Called manually by user or application program
3	Does not accept parameters	Can accept input (IN), output (OUT), or inputoutput (INOUT) parameters
4	Used mainly to enforce business rules and data integrity automatically	Used for encapsulating reusable SQL logic or complex operations
5	Bound to a specific table and event	Independent of table events; can be used anywhere
6	Cannot return values directly	Can return values using OUT parameters or result sets
7	Limited control on error handling	Supports complex control flow and error handling
8	Executes once per affected row (FOR EACH ROW)	Executes once per call

Explanation:

- **Trigger** is event-driven and runs automatically on data changes to enforce integrity or audit data.
- **Stored Procedure** is user-invoked, reusable code block used to perform operations like insert, update, or reporting.

ii) Embedded SQL and Dynamic SQL

Sr. No.	Embedded SQL	Dynamic SQL
1	SQL statements are embedded directly inside a host programming language as static statements	SQL statements are constructed and executed dynamically at runtime
2	SQL queries are precompiled before execution	SQL queries are parsed and compiled at runtime
3	Better performance because of pre-compilation	Slightly slower due to runtime compilation
4	Suitable when SQL statements are fixed and known in advance	Suitable when SQL queries need to be flexible and constructed on-the-fly
5	Less prone to SQL injection when using host variables	Higher risk of SQL injection if queries are not properly sanitized
6	Easier to debug and maintain because of static code	More complex to debug due to dynamic query creation
7	Embedded SQL uses host variables for passing parameters	Dynamic SQL often uses string concatenation to build queries
8	Example: Static SELECT inside C program	Example: Building SELECT query based on user input at runtime

Explanation:

- **Embedded SQL** tightly couples SQL with a host language and is static and precompiled.
- **Dynamic SQL** allows more flexibility by building SQL commands dynamically but may have performance and security considerations.

If you want, I can also provide simple example snippets or diagrams for better understanding!