

[Open in app](#)

Search

**♦ Member-only story**

NLP FUNDAMENTALS

Introduction to Word2Vec (Skip-gram)

A brief introduction to word embeddings in Python



Zolzaya Luvsandorj · Follow

Published in Towards Data Science

11 min read · Dec 15, 2022

[Listen](#)[Share](#)[More](#)

When working with text data, we need to transform text into numbers. There are different ways to represent text in numerical data. Bag of words (a.k.a. BOW) is a popular and simple approach to represent text in numbers. However, there is no notion of word similarity in bag of words because each word is represented independently. As a result, embeddings of words like '*great*' and '*awesome*' are as similar to each other as they are to an embedding of the word '*book*'.

Word embedding is another great way of representing text with numbers. With this approach, each word is represented by an embedding, a dense vector (i.e. an array of numbers). The approach preserves relationship between words and is able to capture word similarity. Words that appear in similar contexts have closer vectors in the vector space. As a result, the word '*great*' is likely to have more similar embedding to '*awesome*' than '*book*'.



Photo by [Sebastian Svenson](#) on [Unsplash](#)

In this post, we will look at an overview of word embeddings, especially a type of embedding algorithm called Word2Vec, and look under the hood to understand how the algorithm operates on a toy example in Python.

Word2Vec (Skipgram) overview




Image by author | Comparison of preprocessing an example document: "Hello world!" with two approaches.
Assumed vocabulary size of 5 for bag of words approach and embedding size of 3 for word embedding.

When using the bag of words approach, we transform text into a document term matrix of m by n where m is the number of documents/text records and n is the

number of unique words across all documents. This usually results in a big sparse matrix. If you want to familiarise with the approach in detail, check out [this tutorial](#).

In word embeddings, each word is represented by a vector, usually with a size of 1 to 300. Word2Vec is a popular method to create embeddings. The basic intuition behind Word2Vec is this: *We can get useful information about a word by observing its context/neighbours.* In Word2Vec, there are two architectures or learning algorithms we can use to obtain vector representation (just another word for embedding) of words: *Continuous Bag of Words* (a.k.a. *CBOW*) and *Skip-gram*.

- **CBOW:** Predict *focus word* given surrounding *context words*
- **Skip-gram:** Predict *context words* given *focus word* (the focus of this post)

At this stage, this may not make much sense. We will soon look at an example of this and it will become clearer.

When training embeddings using the Skip-gram algorithm, we go through the following three steps at a high-level:

- **Obtain text:** We start with unlabelled text corpus — so it's an unsupervised learning problem.
- **Transform data:** Then, we preprocess the data and rearrange the preprocessed data into focus words as feature and context words as target for a fictitious supervised learning problem. So, it becomes a multiclassification problem where $P(\text{context word} \mid \text{focus word})$. Here's an example of what this might look like on a single document:

Text	"Hello world, word embedding is awesome and powerful!"																															
Tokens	<code>['hello', 'world', 'word', 'embedding', 'awesome', 'powerful']</code>																															
New supervised dataset	<table border="1" style="margin-left: auto; margin-right: auto;"> <tr> <td>'hello'</td><td>'world'</td><td>'word'</td><td></td></tr> <tr> <td>'hello'</td><td>'world'</td><td>'word'</td><td>'embedding'</td></tr> <tr> <td>'hello'</td><td>'world'</td><td>'word'</td><td>'embedding'</td><td>'awesome'</td></tr> <tr> <td></td><td>'world'</td><td>'word'</td><td>'embedding'</td><td>'awesome'</td><td>'powerful'</td></tr> <tr> <td></td><td></td><td>'word'</td><td>'embedding'</td><td>'awesome'</td><td>'powerful'</td></tr> <tr> <td></td><td></td><td></td><td>'embedding'</td><td>'awesome'</td><td>'powerful'</td></tr> </table>	'hello'	'world'	'word'		'hello'	'world'	'word'	'embedding'	'hello'	'world'	'word'	'embedding'	'awesome'		'world'	'word'	'embedding'	'awesome'	'powerful'			'word'	'embedding'	'awesome'	'powerful'				'embedding'	'awesome'	'powerful'
'hello'	'world'	'word'																														
'hello'	'world'	'word'	'embedding'																													
'hello'	'world'	'word'	'embedding'	'awesome'																												
	'world'	'word'	'embedding'	'awesome'	'powerful'																											
		'word'	'embedding'	'awesome'	'powerful'																											
			'embedding'	'awesome'	'powerful'																											
	focus word context word																															

Image by author | We first preprocess text into tokens. Then, for each token as focus word, we find the context words with a window size of 2. This means we consider 2 tokens before and after the focus word as

context words. We can see that not all tokens have 2 tokens before and after in a small example text like this.

In those cases, we use the available tokens. In this example, we use the term word and token loosely and interchangeably.

Having multiple targets for the same feature might be confusing to imagine. Here's another way to think about how to prepare the data:

Feature	Target
'hello'	'world'
'hello'	'word'
'world'	'hello'
'world'	'word'
'world'	embedding
...	...

Image by author

Essentially, we prepare feature and target pairs.

■ **Build a simple neural network:** Then, we train a simple neural network with a single hidden layer for the supervised learning problem using the newly constructed dataset. The main reason we are training a neural network is to get the trained weights from the hidden layer which becomes the word embeddings. The embedding for words that occur in similar contexts tend to be similar to each other.

Having covered the overview, it's time to implement it in Python to consolidate what we have learned.

Word2Vec in Python

Since the focus of this post is to develop better intuition of how the algorithm works, we will focus on building it ourselves rather than using pretrained Word2Vec embeddings to deepen our understanding.

 *Disclaimer: While developing the code for this post, I have heavily used the following repositories:*

■ [word-embedding-creation by Eligijus112 \(His Medium page: Eligijus Bujokas\)](#)

■ [word2vec_numpy by DerekChia](#)

I would like to thank these awesome authors for making their useful work available for others. Their repositories are great additional learning resources if you want to deepen your understanding of word2vec.

✍ Word2vec with Gensim

We will use [this sample toy dataset](#) from [Eligijus112's repository](#) with his permission. Let's import libraries and the dataset.

```
import numpy as np
import pandas as pd
from nltk.tokenize.regexp import RegexpTokenizer
from nltk.corpus import stopwords
from gensim.models import Word2Vec, KeyedVectors
from scipy.spatial.distance import cosine

import tensorflow as tf
from tensorflow.keras import Sequential
from tensorflow.keras.layers import Input, Dense

import matplotlib.pyplot as plt
import seaborn as sns
sns.set(style='darkgrid', context='talk')

text = ["The prince is the future king.",
        "Daughter is the princess.",
        "Son is the prince.",
        "Only a man can be a king.",
        "Only a woman can be a queen.",
        "The princess will be a queen.",
        "Queen and king rule the realm.",
        "The prince is a strong man.",
        "The princess is a beautiful woman.",
        "The royal family is the king and queen and their
children.",
        "Prince is only a boy now.",
        "A boy will be a man."]
```

We will now preprocess the text very lightly. Let's create a function that lowercases text, tokenises the documents into alphabetic tokens and removes stopwords.




Image by author

The level of preprocessing can vary from implementation to implementation. In some implementations, one may choose to do very little preprocessing keeping the text almost as it is. On the other spectrum, one can also choose to do a more thorough preprocessing than this example.

```

def preprocess_text(document):
    tokeniser = RegexpTokenizer(r"[A-Za-z]{2,}")
    tokens = tokeniser.tokenize(document.lower())
    key_tokens = [token for token in tokens
                  if token not in stopwords.words('english')]
    return key_tokens
  
```

```

corpus = []
for document in text:
    corpus.append(preprocess_text(document))
corpus
  
```

```

[['prince', 'future', 'king'],
 ['daughter', 'princess'],
 ['son', 'prince'],
 ['man', 'king'],
 ['woman', 'queen'],
 ['princess', 'queen'],
 ['queen', 'king', 'rule', 'realm'],
 ['prince', 'strong', 'man'],
 ['princess', 'beautiful', 'woman'],
 ['royal', 'family', 'king', 'queen', 'children'],
 ['prince', 'boy'],
 ['boy', 'man']]
  
```

Image by author

Now each document consists of tokens. We will build Word2Vec using Gensim on our custom corpus:

```
dimension = 2
window = 2

word2vec0 = Word2Vec(corpus, min_count=1, vector_size=dimension,
                     window=window, sg=1)
word2vec0.wv.get_vector('king')

array([0.25516748, 0.45046365], dtype=float32)
```

Image by author

We choose `window` size of 2 for the contexts. This means we will look 2 tokens before and after the focus token. `dimension` is also set to 2. This refers to the size of the vector. We chose 2 because we can easily visualise it in two-dimensional chart and we are working with a very small text corpus. These two hyperparameters can be tuned with different values to improve the usefulness of the word embeddings for a use case. While preparing Word2Vec, we ensured to use Skip-gram algorithm by specifying `sg=1`. Once the embedding is ready, we can see the embedding for a token 'king'.

Let's see how intuitive the embeddings are. We will pick a sample word: 'king' and see if the words that are most similar to it in the vector space makes sense. Let's find the most similar 3 words to 'king' :

```
n=3
word2vec0.wv.most_similar(positive=['king'], topn=n)

[('man', 0.9941185712814331),
 ('realm', 0.9008388519287109),
 ('son', 0.7788274884223938)]
```

Image by author

This list of tuples show the most similar words and their cosine similarity to 'king'. This result is not bad given we are working with a very small data.

Let's prepare a DataFrame of the embeddings for the vocabulary, the collection of unique tokens:

```
embedding0 = pd.DataFrame(columns=['d0', 'd1'])
for token in word2vec0.wv.index_to_key:
    embedding0.loc[token] = word2vec0.wv.get_vector(token)
embedding0
```

	d0	d1
queen	-0.026811	0.011822
king	0.255167	0.450464
prince	-0.465198	-0.355929
man	0.322944	0.448649
princess	-0.250771	-0.188169
woman	0.369025	-0.076674
boy	-0.226831	0.327703
royal	-0.243008	-0.090801
beautiful	0.143829	0.049594
strong	-0.414221	-0.472374
realm	0.365624	0.253538
rule	0.337920	0.038168
children	0.317544	-0.170268
son	-0.047320	0.288429
daughter	-0.376082	-0.196805
family	-0.375579	-0.046502
future	0.476906	-0.365958

Image by author

Now, we will visualise the tokens in two-dimensional vector space:

```
sns.lmplot(data=embedding0, x='d0', y='d1', fit_reg=False, aspect=2)
for token, vector in embedding0.iterrows():
    plt.gca().text(vector['d0']+.02, vector['d1']+.03, str(token),
```

```
size=14)
plt.tight_layout()
```




Image by author

🔗 If you want to learn more about Word2Vec in Gensim, [here's a tutorial by Radim Rehurek, the creator of Gensim.](#)

Alright, this was a nice warm-up. In the next section, we will create a Word2Vec embedding ourselves.

🔨 Manual Word2Vec — Approach 1

We will start by finding the vocabulary from the corpus. We will assign a value to each token in the vocabulary:

```
vocabulary = sorted([*set([token for document in corpus for token in
                           document])])
n_vocabulary = len(vocabulary)
token_index ={token: i for i, token in enumerate(vocabulary)}
token_index
```

```
{'beautiful': 0,
 'boy': 1,
 'children': 2,
 'daughter': 3,
 'family': 4,
 'future': 5,
 'king': 6,
 'man': 7,
 'prince': 8,
 'princess': 9,
 'queen': 10,
 'realm': 11,
 'royal': 12,
 'rule': 13,
 'son': 14,
 'strong': 15,
 'woman': 16}
```

Image by author

Now, we will make token pairs as a preparation for the neural network.




Image by author

```
token_pairs = []

for document in corpus:
    for i, token in enumerate(document):
        for j in range(i-window, i+window+1):
            if (j>=0) and (j!=i) and (j<len(document)):
                token_pairs.append([token] + [document[j]])
```

```
n_token_pairs = len(token_pairs)
print(f"{n_token_pairs} token pairs")

token_pairs[:5]
```

56 token pairs

```
[['prince', 'future'],
 ['prince', 'king'],
 ['future', 'prince'],
 ['future', 'king'],
 ['king', 'prince']]
```

Image by author

Token pairs are ready but they are still in text form. Now we need to one-hot-encode them so that they are suitable for the neural network.




Image by author

```
X = np.zeros((n_token_pairs, n_vocabulary))
Y = np.zeros((n_token_pairs, n_vocabulary))

for i, (focus_token, context_token) in enumerate(token_pairs):
    X[i, token_index[focus_token]] = 1
    Y[i, token_index[context_token]] = 1
print(X[:5])
```

```
[[0. 0. 0. 0. 0. 0. 0. 0. 1. 0. 0. 0. 0. 0. 0. 0. 0. 0. 0. 0.]
 [0. 0. 0. 0. 0. 0. 0. 0. 1. 0. 0. 0. 0. 0. 0. 0. 0. 0. 0. 0.]
 [0. 0. 0. 0. 0. 1. 0. 0. 0. 0. 0. 0. 0. 0. 0. 0. 0. 0. 0. 0.]
 [0. 0. 0. 0. 0. 1. 0. 0. 0. 0. 0. 0. 0. 0. 0. 0. 0. 0. 0. 0.]
 [0. 0. 0. 0. 0. 0. 1. 0. 0. 0. 0. 0. 0. 0. 0. 0. 0. 0. 0. 0.]]
```

Image by author

Now that the input data is ready, we can build a neural network with a single hidden layer:

```
tf.random.set_seed(42)
word2vec1 = Sequential([
    Dense(units=dimension, input_shape=(n_vocabulary,),,
          use_bias=False, name='embedding'),
    Dense(units=n_vocabulary, activation='softmax', name='output')
])
word2vec1.compile(loss='categorical_crossentropy', optimizer='adam')
word2vec1.fit(x=X, y=Y, epochs=100)
```

```
Epoch 1/100
2/2 [=====] - 0s 2ms/step - loss: 2.8544
Epoch 2/100
2/2 [=====] - 0s 2ms/step - loss: 2.8526
Epoch 3/100
2/2 [=====] - 0s 3ms/step - loss: 2.8511
Epoch 4/100
2/2 [=====] - 0s 2ms/step - loss: 2.8494
Epoch 5/100
2/2 [=====] - 0s 4ms/step - loss: 2.8479
```

Image by author

We specified hidden layer to have no bias terms. Since we want the hidden layer to have linear activation, we didn't need to specify. The number of units in the layer reflects the size of the vector: `dimension`.

Let's extract the weights, our embeddings, from the hidden layer.

```
embedding1 = pd.DataFrame(columns=['d0', 'd1'])
for token in token_index.keys():
    ind = token_index[token]
```

```
embedding1.loc[token] = word2vec1.get_weights()[0][ind]
embedding1
```

	d0	d1
beautiful	0.092135	0.072826
boy	-0.204392	0.109816
children	-0.519843	0.362591
daughter	0.308868	0.605441
family	-0.445764	-0.149214
future	-0.151797	0.408884
king	-0.479776	0.154406
man	0.146254	0.566848
prince	-0.388465	0.181566
princess	-0.000222	-0.464745
queen	0.414807	0.098460
realm	-0.330297	0.160567
royal	0.338819	-0.195321
rule	0.113495	-0.162586
son	0.268893	0.118907
strong	0.419248	-0.145344
woman	0.254568	-0.046650

Image by author

Using our new embeddings, let's see the most similar 3 words to 'king' :

```
vector1 = embedding1.loc['king']
similarities = {}

for token, vector in embedding1.iterrows():
    theta_sum = np.dot(vector1, vector)
    theta_den = np.linalg.norm(vector1) * np.linalg.norm(vector)
    similarities[token] = theta_sum / theta_den

similar_tokens = sorted(similarities.items(), key=lambda x: x[1],
                       reverse=True)
similar_tokens[1:n+1]
```

```
[('prince', 0.99208975), ('realm', 0.9900579), ('boy', 0.98354477)]
```

Image by author

Great, this makes sense. We can save the embeddings and load them using Gensim. Once loaded into Gensim, we can check our similarity calculation.

```
with open('embedding1.txt', 'w') as text_file:
    text_file.write(f'{n_vocabulary} {dimension}\n')
    for token, vector in embedding1.iterrows():
        text_file.write(f"{token} {' '.join(map(str, vector))}\n")
text_file.close()

embedding1_loaded =
KeyedVectors.load_word2vec_format('embedding1.txt', binary=False)
embedding1_loaded.most_similar(positive=['king'], topn=n)
```

```
[('prince', 0.9920897483825684),
 ('realm', 0.9900577664375305),
 ('boy', 0.9835447072982788)]
```

Image by author

The similarities calculated by Gensim matches our manual calculations.

We will now visualise the embeddings in the vector space:

```
sns.lmplot(data=embedding1, x='d0', y='d1', fit_reg=False, aspect=2)
for token, vector in embedding1.iterrows():
    plt.gca().text(vector['d0']+.02, vector['d1']+.03, str(token),
                   size=14)
plt.tight_layout()
```




Image by author

In the next section, we will manually create word embeddings while taking advantage of object oriented programming approach.

✍ Manual Word2Vec — Approach 2

We will start by creating a class called `Data` which centralises data-related tasks:

```
1  class Data():
2      def __init__(self, text):
3          self.text = text
4          self.corpus = self.extract_corpus()
5
6      def preprocess_text(self, document):
7          tokeniser = RegexpTokenizer(r"[A-Za-z]{2,}")
8          tokens = tokeniser.tokenize(document.lower())
9          key_tokens = [token for token in tokens if token not in stopwords.words('english')]
10         return key_tokens
11
12     def extract_corpus(self):
13         corpus = []
14         for document in self.text:
15             corpus.append(self.preprocess_text(document))
16         return corpus
17
18     def one_hot_encode(self, token):
19         ohe_vector = np.zeros(self.n_vocabulary)
20         ohe_vector[self.token_index[token]] = 1
21         return ohe_vector
22
23     def prepare_focus_context_data(self, window=2):
24         self.window = window
25         self.vocabulary = sorted([*set([token for document in self.corpus for token in document]))
26         self.n_vocabulary = len(self.vocabulary)
27         self.token_index ={token: i for i, token in enumerate(self.vocabulary)}
28         self.index_token = {i: token for token, i in self.token_index.items()}
29
30         self.focus_context_data = []
31         for sentence in self.corpus:
32             for i, token in enumerate(sentence):
33                 focus_token = self.one_hot_encode(token)
34                 context_tokens = []
35                 for j in range(i-window, i+window+1):
36                     if (j!=i) and (j<=len(sentence)-1) and (j>=0):
37                         context_tokens.append(self.one_hot_encode(sentence[j]))
38                 self.focus_context_data.append((focus_token, context_tokens))
39
40     data = Data(text)
41     data.prepare_focus_context_data()
42     data.corpus
```

```
[['prince', 'future', 'king'],
['daughter', 'princess'],
['son', 'prince'],
['man', 'king'],
['woman', 'queen'],
['princess', 'queen'],
['queen', 'king', 'rule', 'realm'],
['prince', 'strong', 'man'],
['princess', 'beautiful', 'woman'],
['royal', 'family', 'king', 'queen', 'children'],
['prince', 'boy'],
['boy', 'man']]
```

Image by author

We can see that the `corpus` attribute looks the same as in earlier sections.

```
len([token for document in data.corpus for token in document])
```

32

Image by author

There are 32 tokens in our toy corpus.

```
len(data.focus_context_data)
```

32

Image by author

Unlike before, `data.focus_context_data` is not formatted as token pairs. Instead, each of these 32 tokens have been mapped together with all of their context tokens.




Image by author

```
np.sum([len(context_tokens) for _, context_tokens in
       data.focus_context_data])
```

56

Image by author

Like before, we still have 56 context tokens in total. Now, let's centralise the code regarding Word2Vec in an object:

```
1  class Word2Vec():
2      def __init__(self, dimension):
3          self.dimension = dimension
4
5      def train(self, data, learning_rate, epochs, seed=24):
6          self.data = data
7          np.random.seed(seed)
8          self.w1 = np.random.uniform(-1, 1, (data.n_vocab, self.dimension))
9          self.w2 = np.random.uniform(-1, 1, (self.dimension, data.n_vocab))
10
11         for i in range(epochs):
12             self.loss = 0
13             for focus_token, context_tokens in data.focus_context_data:
14                 y_pred, hidden, output = self.forward_pass(focus_token)
15                 error = np.sum([np.subtract(y_pred, token) for token in context_tokens], axis=0)
16                 self.backprop(error, hidden, focus_token, learning_rate)
17                 self.loss += -np.sum([output[token.argmax()] for token in context_tokens]) + len(context_tokens) * (len(context_tokens) - 1) / 2
18             print(f"Epoch: {i} | Loss: {self.loss}")
19
20         def forward_pass(self, x):
21             hidden = np.dot(x, self.w1)
22             output = np.dot(hidden, self.w2)
23             y_pred = self.softmax(output)
24             return y_pred, hidden, output
25
26         def softmax(self, x):
27             e_x = np.exp(x - np.max(x))
28             return e_x / e_x.sum(axis=0)
29
30         def backprop(self, error, hidden, x, learning_rate):
31             dl_dw2 = np.outer(hidden, error)
32             dl_dw1 = np.outer(x, np.dot(self.w2, error.T))
33
34             self.w1 -= learning_rate * dl_dw1
35             self.w2 -= learning_rate * dl_dw2
36
37         def extract_vector(self, token):
38             index = self.data.token_index[token]
39             vector = self.w1[index]
40             return vector
41
42         def find_similar_words(self, token, n=3):
43             vector1 = self.extract_vector(token)
44             similarities = {}
45
46             for i in range(self.data.n_vocab):
47                 vector2 = self.w1[i]
48                 similarities[f'data_index_{token}'] = 1 - cosine(vector1, vector2)
```

```

49
50     similar_tokens = sorted(similarities.items(), key=lambda x: x[1], reverse=True)
51     return similar_tokens[1:n+1]
52
53 word2vec2 = Word2Vec(dimension=dimension)
54 word2vec2.train(data, learning_rate=0.01, epochs=50)

```

```

Epoch: 0 | Loss: 167.32393447944256
Epoch: 1 | Loss: 166.4644789481025
Epoch: 2 | Loss: 165.67349538552088
Epoch: 3 | Loss: 164.94241324581006
Epoch: 4 | Loss: 164.2638588460181

```

Image by author | Partial output only

We just trained our custom Word2Vec object. Let's inspect a sample vector:

```
word2vec2.extract_vector('king')
```

```
array([0.04105649, 0.46685478])
```

Image by author

We will now look at the most similar three words to 'king' :

```
word2vec2.find_similar_words("king")
```

```
[('realm', 0.9995501522496183),
 ('prince', 0.9869499174984389),
 ('children', 0.9105311842517781)]
```

Image by author

This is good. It's time to convert the embeddings to a DataFrame:

```
embedding2 = pd.DataFrame(word2vec2.wv, columns=['d0', 'd1'])
embedding2.index = embedding2.index.map(word2vec2.data.index_token)
```

embedding2

	d0	d1
beautiful	0.971068	0.177538
boy	0.436580	-0.482706
children	-0.389786	1.107146
daughter	0.712422	-0.279001
family	-0.613740	0.226625
future	-0.772410	-0.081598
king	0.041056	0.466855
man	-0.361068	-0.040430
prince	0.086255	0.338579
princess	0.413813	0.450000
queen	0.710800	0.633077
realm	0.055107	0.953644
royal	1.090737	0.746378
rule	0.527821	0.775301
son	-0.225745	-0.677317
strong	-0.308262	0.234048
woman	0.372758	0.181811

Image by author

We can now easily visualise the new embeddings:

```
sns.lmplot(data=embedding2, x='d0', y='d1', fit_reg=False, aspect=2)
for token, vector in embedding2.iterrows():
    plt.gca().text(vector['d0']+.02, vector['d1']+.03, str(token),
                  size=14)
plt.tight_layout()
```




Image by author

As we did previously, we can again save the embeddings and load it with Gensim and do checks:

```
with open('embedding2.txt', 'w') as text_file:
    text_file.write(f'{n_vocabulary} {dimension}\n')
    for token, vector in embedding2.iterrows():
        text_file.write(f'{token} {" ".join(map(str, vector))}\n')
text_file.close()

embedding2_loaded =
KeyedVectors.load_word2vec_format('embedding2.txt', binary=False)
embedding2_loaded.most_similar(positive=['king'], topn=n)

[('realm', 0.9995501041412354),
 ('prince', 0.9869499206542969),
 ('children', 0.9105312824249268)]
```

Image by author

When calculating cosine similarity to find similar words, we used `scipy` this time. This approach matches with Gensim's result except for the floating-point precision error.

That was it, for this post! Hope you have developed basic intuition on what word embeddings are and how Word2Vec using Skip-gram algorithm generates word embeddings. So far we have focused on Word2Vec for NLP, but this technique can

also be helpful for recommendation systems. [Here's](#) an insightful article on that. If you want to learn more about Word2Vec, here're some useful resources:

- [Lecture 2 | Word Vector Representations: word2vec – YouTube](#)
- [Google Code Archive – Long-term storage for Google Code Project Hosting](#)
- [word2vec Parameter Learning Explained](#)




Photo by [Milad Fakurian](#) on [Unsplash](#)

Would you like to access more content like this? Medium members get unlimited access to any articles on Medium. If you become a member using [my referral link](#), a portion of your membership fee will directly go to support me.

Thank you for reading my post. If you are interested, here are links to some of my posts:

- [Pipeline, ColumnTransformer and FeatureUnion explained](#)
- [FeatureUnion, ColumnTransformer & Pipeline for preprocessing text data](#)
- [Enrich your Jupyter Notebook with these tips](#)
- [Organise your Jupyter Notebook with these tips](#)
- [Explaining Scikit-learn models with SHAP](#)
- [Feature Selection in Scikit-learn](#)
- [Comparing Random Forest and Gradient Boosting](#)

Bye for now 🎉 ➡️

Data Science

Word Embeddings

NLP

Python

Hands On Tutorials



Follow



Written by Zolzaya Luvsandorj

2.6K Followers · Writer for Towards Data Science

Data Scientist 💡 | Growth Mindset 🔑 | Math Lover 12/34 | Melbourne, AU 🐾 | <https://zluvsand.github.io/>

More from Zolzaya Luvsandorj and Towards Data Science



 Zolzaya Luvsandorj in Towards Data Science

Pipeline, ColumnTransformer and FeatureUnion explained

What they do and when to use which

◆ · 8 min read · Sep 29, 2020

 1K

 9



...



 Cristian Leo in Towards Data Science

The Math behind Adam Optimizer

Why is Adam the most popular optimizer in Deep Learning? Let's understand it by diving into its math, and recreating the algorithm.

16 min read · Jan 30, 2024

👏 1.5K

💬 9



👤 Sheila Teo in Towards Data Science

How I Won Singapore's GPT-4 Prompt Engineering Competition

A deep dive into the strategies I learned for harnessing the power of Large Language Models (LLMs)

⭐ · 23 min read · Dec 28, 2023

👏 11.2K

💬 126



...



 Zolzaya Luvsandorj in Towards Data Science

Datasets in Python

5 packages that provide easy access to various datasets

◆ · 6 min read · Aug 10, 2020

 450




...

[See all from Zolzaya Luvsandorj](#)

[See all from Towards Data Science](#)

Recommended from Medium

PROJECTION**OUTPUT****INPUT****PROJECTION**


Merve Bayram Durna

Advanced Word Embeddings: Word2Vec, GloVe, and FastText

The Complete NLP Guide: Text to Context #6

9 min read · Jan 15, 2024

65



Everton Gomedé, PhD

Understanding the Continuous Bag of Words (CBOW) Model

Introduction

7 min read · Oct 14, 2023



15



Lists



Predictive Modeling w/ Python

20 stories · 896 saves



Coding & Development

11 stories · 445 saves



Practical Guides to Machine Learning

10 stories · 1047 saves



Natural Language Processing

1189 stories · 664 saves



Rahul S

NLP: Word Embeddings-Word2Vec and GloVe


In NLP, understanding the intricate relationships between words and context is a challenge. By harnessing the power of word embeddings, we...



· 10 min read · Aug 17, 2023

44
44


...


Cognitive Creator

Word2Vec: NLP's Gateway to Word Embeddings

Explore the world of Word2Vec and its significance in NLP

8 min read
Oct 5, 2023
51
51


...



Geoffrey Rathinapandi

Tokenization vs. Embedding: Understanding the Differences and Their Importance in NLP

Tokenization takes the text and maps input sequences to numbers. okenization Straight mapping from token to numbers (can be modeled but...

2 min read · Oct 30, 2023





Ido Leshem

Skip-Gram Word2Vec Algorithm Explained

A brief guide explaining how to apply a word-embedding model to any text you choose

11 min read · Nov 1, 2023

129



...

See more recommendations