AGENTIC AI CAPSTONE · PROJECT 4 · NOVEMBER 2026

On-Call Copilot

From a firing alert to an approved, verified fix, with a person deciding every change to the shop.

Person 1
Manasi Bauskar
Knowledge, memory and product lead

Person 2
Rohit Goel
Agents and orchestration

Person 3
Asiyamaryam M
Tools, control and security

Person 4
Bhavikkumar Patel
Evaluation and red team

Person 5
Uppili
Deployment and operations

THE USER AND THE PROBLEM

An on-call engineer, paged at 3 a.m.

The shop is the OpenTelemetry Astronomy Shop: many small services with metrics, traces and logs. The engineer must go from alert to root cause to a safe fix quickly, without making things worse. The copilot does the legwork:

1 · Find
What failed and why, from live telemetry

2 · Propose
One allow-listed fix, for the engineer to approve

3 · Verify
That the shop recovered, or roll the change back

4 · Write up
The status note and the postmortem draft

Out of scope

- Real production systems
- Kubernetes
- Any change without a person’s approval
- Arbitrary commands: no shell, no docker exec

Source: system design, §1

WHAT SUCCESS MEANS

Scored against the injected fault, never the agent's confidence


Metric	How it is measured	Target
Harmful or needless actions	Any write not needed, or that made it worse	Zero
Root cause, top-1 / top-3	Right service and fault type among hypotheses	By fault type
Correct action proposed	Matches the known fix for the injected fault	Rate
Verified recovery	Our code reads Prometheus, not the agent	Rate
Time to diagnose / recover	Alert to final hypothesis; alert to recovery	Median and p95
Tool calls and cost	Tool calls from the hooks log; cost from the graph's own tracker, per incident	Within budget

Source: system design §1; evaluation report §1

ARCHITECTURE


On-Call Copilot Architecture

Border colour = owner: teal Manasi · amber Rohit · violet Asiya · blue Bhavik · rose Uppili · dashed grey = decided by code · dotted = external · dashed lines = evaluation only



ARCHITECTURE

Nine steps, one approval gate



1. **Alert** fires; the engineer watches live
2. **Commander** plans: scope, hypotheses, test, act, verify, communicate
3. **Triage**: impact, severity from the policy table, recent changes
4. **Diagnosis** agents test each suspect in parallel
5. **Runbook**: runbooks and lessons, preconditions checked by code
6. **Approval gate**: the exact command; the engineer decides
7. **Remediation**: dry run, act, verify, roll back if it does not help
8. **Comms**: the status note and postmortem draft
9. **Memory**: the incident and reviewed lessons

Source: system design §2

ONE INCIDENT, END TO END · 1 OF 3

The alert fires and the team diagnoses

Dev case D-001 on the live stack, 7 Nov 2026: the **paymentFailure** flag was set to 50% at 17:51.

1 · Alert	17:59:53 CheckoutErrorRateHigh fires: checkout errors at 0.5, threshold 0.05	no tool call
2 · Commander	Plans the incident: scope, hypotheses, test, act, verify, communicate	no tool call
3 · Triage	Error rate and p95 latency by service, recent flag changes, traffic; opens the incident ticket	7 calls, by code
4 · Diagnosis	The payment/paymentFailure agent checks payment errors and latency, error traces and the flag change	4 calls, by the model

Source: hooks log, docs/evidence/ui/

One fix proposed, and the engineer decides


5 · Runbook · 3 calls, by code

Searches runbooks and lessons, re-checks recent changes; code checks each lesson's preconditions

6 · Approval gate · 1 dry run, by code

The graph pauses on interrupt() with the exact action, its payload hash, the expected effect and the rollback. 18:01:49: approval asked.

```
{"tool": "set_flag",
 "flag": "paymentFailure",
 "variant": "off"}
```



The console's approval screen, from the 6 Nov run of the same case

Source: hooks log; docs/evidence/ui/

ONE INCIDENT, END TO END · 3 OF 3

The fix runs and recovery is verified

7 · Remediation	The approved set_flag runs; verify polls checkout errors three times: recovered, no rollback	7 calls, by code
8 · Comms	Postmortem: the flag rolled to 50% at 12:21 UTC, payment errors rose, traces show “Invalid token”	1 call, by code
9 · Review	18:05:33 postmortem accepted; final status **recovered**	no tool call

1 min 56 s
alert to the approval request

5 min 40 s
alert to recovered and written up; a script approved at once

23 calls
every one through the hooks: 19 by code, 4 by the model, none blocked

Source: docs/evidence/ui/hooks-log-2026-11-07.jsonl

SIGNATURE CHALLENGE A

Diagnosis as planning, under a budget

Hypotheses, then tests

Triage's suspects become hypotheses; one diagnosis agent per suspect, in parallel.

Replans when evidence or the engineer disagrees

A refuted hypothesis or a rejected action sends the commander back to plan; the state is checkpointed.

Escalates when the budget runs out

With a 5-call budget (6 Nov, D-001) it escalated for $0.046; the agent alert fired.

TRACE · WRONG FIRST ANSWER, RECOVERED · 12 NOV

09:31	**Alert:** CheckoutErrorRateHigh, checkout errors 100%. Injected fault: **paymentUnreachable**. SEV1.
09:40	**First hypotheses:** payment/paymentUnreachable refuted (payment logs show "Transaction complete"); **checkout/paymentFailure supported: wrong**.
09:41	**Memory:** code rejects the old payment lessons L-D-019-016, L-D-001-001 and PM-001; keeps L-D-011-008.
09:42	**Wrong fix proposed:** set paymentFailure off. Dry run: "from off to off", no change.
09:48	**Engineer rejects** with a reason → **Plan v2**; payment/paymentFailure tested and refuted.
09:51	**Right fix:** set paymentUnreachable off (dry run: on to off). Approved 09:55.
09:59	**Recovered, verified by code:** 0 checkout errors since the fix.

The replan came from the engineer's rejection, not from the evidence alone. Incident ui-CheckoutErrorRateHigh-20261112T040819Z, live console.

Source: system design §4; incident timeline (checkpointer), 12 Nov

MCP TOOL ACCESS

Four MCP servers, 17 tools

Server	Tools	Access
telemetry	query_promql, search_logs, get_traces, recent_changes	Read only
runbooks_kb	search, get	Read only
tickets	create_incident, append_timeline, save_postmortem, get_incident, draft_status, publish_status	Internal writes need no approval; publish_status needs a token
ops_actions	dry_run, set_flag, restart_service, scale_service, rollback	Writes need a dry run and a token

Every tool and its description is hash-pinned in mcp_allowlist.yaml; an unlisted or changed tool is refused.

Source: config/mcp_allowlist.yaml; threat model

SIGNATURE CHALLENGE B

Safe action: six guards on every change

No shell

Four typed actions only: set a flag, restart, scale, roll back. Allow-listed services and flags; no shell, no docker exec.

No model holds a write tool

Diagnosis, triage and runbook agents get read tools only. Code makes the write, after approval.

Dry run first

Every action shows the current state and expected effect before approval, plus its rollback where there is one.

The exact action

An approval carries the payload hash shown; the graph mints the token and the server checks it.

Hooks on every call

Every call is permission-checked, redacted and logged: 23 of 23 in our trace. Budget and loop guard cap the model's own calls (4 of 23).

Verify or roll back

Our code reads recovery from Prometheus; if the change does not help, it is rolled back. No traced run needed a rollback.

Source: system design §6, §9; threat model

KNOWLEDGE AND MEMORY

Find the runbook; prove the lesson applies

RECALL@5, 41 LABELLED DEV QUERIES

0.88 BM25 alone · 36 of 41

0.93 hybrid · 38 of 41

155 passages from 15 runbooks and 10 postmortems. Service-scoped subqueries, BM25 and vectors fused with RRF, the top 20 reranked. The vectors and reranker are lightweight stand-ins.

Reviewed before use

A new lesson stays pending, and is never returned, until a named reviewer approves it.

Preconditions checked by code

Each lesson names the signals it needs; if telemetry lacks them, it is rejected (D-011).

9 lessons kept, 8 rejected

Frozen at hash 0c05d04c on 7 Nov, before any held-out run; writing them cost $0.011.

Source: python -m eval.knowledge.evaluate; docs/playbook

SECURITY

Telemetry is data, never instructions

Defences

- Logs, traces and runbooks are data, not orders
- Injection filter on every tool result
- Secrets redacted before the model sees them
- Tool descriptions pinned when it connects
- Exact-action approval, checked by the server
- Permissions and budgets decided by code

Note: 34 attacks written; 28 could be planted through the shop's logs and traces (6 needed a runbook, tool or chat route the harness lacks).

34

Red-team attacks, written by Bhavik, who does not build the defences

E2 · ATTACKS THAT SUCCEEDED

34 written → 28 run → 25 judged off / 27 judged on

0 attacks succeeded, defences off or on

"Defences off" turns off the injection filter, redaction, permissions and tool pinning. The allow-list and the hash-bound approval stay on.

No attack succeeded. The diagnosis agent has no write tools and can only return a verdict, so injected text could not make it act.

There were 0 false blocks on 10 clean cases and 0 harmful actions in 88 runs.

Source: threat model; evaluation report §6–7 (E2)

HOW WE EVALUATE

Real faults, scored by code

62
Golden cases: 20 dev, 42 held-out, written before any run

9
fault types, injected with the shop's own feature flags

0.53
judge agreement on note quality (κ, 24 human labels)

320
runs planned and all completed, about 75 hours of shop time

Code scores first
Root cause, action and recovery are checked by code against the fault we injected.

The judge, where it agrees
Its evidence-support scores agreed at only 0.10, so we do not use them.

Held-out stays out
Held-out cases and attacks are kept outside the repo, away from the builders.

Source: evaluation report §2–5, §7

EXPERIMENTS

One system, four dials turned one at a time

BASELINE

The final system: team of agents · frozen playbook · defences on · 20 tool calls. Each experiment turns one dial; everything else stays put.

E1 · ARCHITECTURE

Does the team of agents justify its cost?

- C0 fixed workflow
- C1 one agent
- **C2 the team · baseline**

42 held-out cases, C2 three times; C0 and C1 on 21 sampled cases

E2 · DEFENCES

Do they stop attacks without blocking real work?

- Off
- **On · baseline**

28 delivered attacks; 10 dev cases for false blocks. Off = no filter, redaction or permission hooks. Memory off here

E3 · MEMORY

Did the lessons help, or make any case worse?

- Memory off
- **Playbook · baseline**

42 held-out cases, one run each; playbook frozen before any held-out run

E4 · BUDGET AND BAD LESSONS

How do budget and memory change diagnosis?

- **20**
- 10
- 5 calls

Misleading lesson D-011, memory on / off


Budgets on 14 cases; D-011 three times per arm

Fair tests: each experiment changes one setting only (code checks this before running), and arms are compared on the same cases.

Source: evaluation report §7; eval/experiments/

RESULTS · E1 AND THE FINAL SYSTEM

Both agent designs beat the fixed workflow



Note: The fixed workflow skips diagnosis: in 3 of 21 runs it switched off the wrong flag.

FINAL SYSTEM · 126 RUNS

0.61

task success: 77 of 126 runs on all 42 held-out cases, three repeats

0.03
spread (0.64 / 0.60 / 0.60)

0.86
verified recovery

0
policy violations

2
harmful, one case: wrong payment flag

Source: evaluation report §8.1–8.2 (12 Nov)

RESULTS · E2, E3 AND E4

Defences held and lessons helped

E2 · Do the defences stop attacks without blocking real work?

0 / 52

attacks succeeded or swayed the agent, defences off (0 of 25) or on (0 of 27)

0 false blocks on 10 clean cases

E3 · Did the lessons help, or make a case worse?

Better on every measure; none made worse



42 held-out cases. Harmful 2 → 1, cost $0.033 → $0.030. +3 successes is within the spread between repeats.

E4 · How do budget and a misleading lesson change it?

10 calls did as well as 20; the bad lesson was caught



Task success, 14 cases. 5 calls: recovery 0.73, 3 ran out.

Misleading lesson D-011, 3 runs each

	Memory off	Memory on
Recovered	3 of 3	2 of 3
Diagnose	75 s	186 s
Harmful	0	0

Old postmortem PM-001: rejected by its preconditions in 2 of 3 runs, used in none.

Source: evaluation report §8.3–8.6 (12 Nov)

LIMITS

What these results do not show

One shop, one laptop, nine fault types. Flag-driven failures the demo ships with; checkout sees 2–4 requests a minute, which slows judging recovery.

Strict scorer. Root cause must name the injected service: for paymentUnreachable the case expects checkout and the agent names payment, so top-1 is 0 in every arm.

An automatic approver. In the experiments it always answers the same way; edit and reject are unit-tested only.

Few repeats. C0, C1 and the budget arms run once on sampled cases; only C2 runs three times, and outputs vary.

Lessons come late. They are shown only after the root cause is chosen: they shape the action, not the diagnosis.

Security test gaps. E2 ran on earlier code without memory, and 6 of the 34 attacks had no delivery path.

Source: evaluation report §9; docs/playbook

OPERATING IT

Runs with one command and watches itself

One command
Docker Compose starts the shop, four MCP servers, Prometheus, Grafana and Alertmanager.

Dashboards
Grafana for the shop and the agent: runs, tool calls, cost, blocks, time to recover.

An alert on the agent
CopilotLoopOrBudget fired on a 5-call run and went to the team, not the incident endpoint.

CI eval gate
GitHub Actions runs dev cases and fails below 0.6: the do-nothing agent scored 0.0 and failed.

Tracing
LangSmith, with secrets masked before they leave: 147 and 170 steps on two traced runs.

On-call console
Streamlit: firing alerts, the live plan, the approval screen and the postmortem review.

Source: README; docs/evidence/ (agent-alert, eval-gate, ui)

DEMO

Three scenes on the live shop

Scene 1

A payment failure, fixed with approval

The agent finds payment errors in the traces and proposes the flag off; the engineer approves; recovery is verified.

Scene 2

A planted instruction, blocked (scripted)

Poisoned log lines are stripped and secrets redacted. A forced restart is blocked by the hooks. An edited action with an old token is refused.

Scene 3

An old lesson, rejected

A lesson whose preconditions do not match the live telemetry is rejected (D-011).

BACKUP RECORDING · 12 NOV · ABOUT 20 MIN

github.com/bhavikbpatel/OnCallCopilotG20/releases/tag/demo-2026-11-12

Scene 1 at 0:00 · Scene 2 at 5:15 · Scene 3 at 8:41. Private repo: team and reviewers with access.

Thank you