

# Logical Database Design

## Mapping ER Models to Relational Models


Also called “transformation” of conceptual models to logical models.

Entity-relationship model -> relational model

# Objectives

- Understand how to transform an ER model into a relational model
- Constructs of an entity-relationship model
  - Entity types
    - attributes (key, non-key)
  - Relationship types
    - 1:N
    - M:N
    - 1:1
- Construct of relational model
  - Relation

# Data modeling is part of database design methodology



# The Relational Model

- Collection of tables, called relations, stored in a database
  - Codd 1970
  - Simplicity
- Key concepts:
  - A **table** (relation) refers to a list of data arranged in columns (fields) and rows (records)
    - Structured to minimize redundancy
  - A database is either a single table or a collection of related tables
  - A column (**field**) defines the data that a table can hold
  - A row (**record**) represents a single instance of whatever the table keeps track of
  - A **key** is the field(s) used to uniquely identify each record in a table and to relate tables in a database
- SQL (Structured Query Language) – for creating and querying a database

## Simple Database (Revisited)

### Customers of sales representatives

Sales Representative (i.e. Employee)

RepNum	LastName	FirstName	Street	City	State	Zip	Commission	Rate
20	Kaiser	Valerie	624 Randall	Grove	FL	33321	\$20,542.50	0.05
35	Hull	Richard	532 Jackson	Sheldon	FL	33553	\$39,216.00	0.07
65	Perez	Juan	1626 Taylor	Fillmore	FL	33336	\$23,487.00	0.05

Customer

CustomerNum	CustomerName	Street	City	State	Zip	Balance	CreditLimit	RepNum
148	Al's Appliance	2837 Greenway	Filmore	FL	33336	\$6,550.00	\$7,500.00	20
282	Brookings Direct	3827 Devon	Grove	FL	33321	\$431.50	\$10,000.00	35
356	Ferguson's	382 Wildwood	Northfield	FL	33141	\$5,785.00	\$7,500.00	65
408	Everything Shop	1828 Raven	Crystal	FL	33503	\$5,285.24	\$5,000	35

---

What queries might you ask of this database? Note: minimize redundancy.

# Logical design:

## Transform conceptual model into a logical model to be implemented in a relational database

- Relational model has one construct (relation/table)
- Conceptual ER models are very descriptive (semantics rich)
- ER modeling concepts must be converted to relational concepts
  - Entities -> relations
  - Relationships -> foreign key in existing relation; or new relation
  - Depends on min/max cardinalities

Conceptual ER Model	Relational Model
Entity types	Relation (table)
Single valued attributes	Single-valued attributes
Relationships (1-to-1, 1-to-N)	Foreign keys
Many-to-many (N:M) relationships (w/ relationship attributes possible)	Relation (table)

# Translation to Logical Model

Transformation / Conversion / Mapping Rules – Entity

[Note: Do not confuse  
*mapping rules* with *mapping ratios*]


Each entity becomes a relation (table) with same key

Transformation / Conversion / Mapping Rules -- Relationship

- 1:N – Foreign key
  - (0,1) and (0/1,N) – foreign key (can have null value)
  - (1,1) and (0/1,N) – foreign key (cannot have null value)
- N:M – New relation
  - (0/1,N) and (0/1,M)
  - Key is concatenation (joining together) of keys of the two entities
  - Relationship attributes become non-keys
- 1:1 – foreign key
  - (1,1) and (1,1) – foreign key in either relation (decide based upon usage)
  - (0,1) and (1,1) [or (1,1) and (0,1)] – use foreign key such that there are no null values allowed.

# Binary (1-to-N) relationship represented as foreign keys

- (1) Map entity types and attributes
- (2) 1-to-N relationship: insert the PK of the entity with the many max cardinality into another entity's table as a FK



Note: 1:N relationship does not have relationship attributes




# Binary (1-to-N) relationship represented by foreign keys

Relations:


Advisor: [AdvisorID, location, ...]

Student: [StudentID, dob, .... advisorID]



# Binary N:M relationship represented as new relation

- (1) Map entity types and attributes
- (2) Map the N:M relationship and its attributes (if any) into a new relation
- (3) The concatenation of the PKs of the involved entities become the PK key of the new relation.




# Binary N:M relationship represented as new relation

Relations:

Department: [DeptName, address, ...]


Instructor: [EmpID, location, ....]

Work: [EmpID, DeptName]



# Binary N:M relationship with relationship attributes

- (1) Map entity types and attributes
- (2) Map the N:M relationship and its attributes into a new relationship table
- (3) The concatenation of the PKs of the involved entities become the PK key of the new relation
- (4) The relationship attribute(s) become the non-key(s).



Work (EmpID, DeptName, date-of-hire)


# Binary N:M relationship with relationship attributes

## Relations:

Department: [Name, address, ...]

Instructor: [EmpID, location, ....]

Work: [EmpID, DeptName, date-of-hire]




# 1:1 Relationship

Every dept must have one (and only one) department head.

Options:

-- foreign key in either relation



Department: [DeptName, location, ... EmpID]


Or:

Dept-Head: [EmpID, name, ....., DeptName]

How would you decide?

# Optional 1:1 Relationship

Business rule: department can have at most one department head




Head: [EmpID, name, ....., DeptName]

Where “DeptName” is not allowed to have a null value.

# Optional 1:1 Relationship in both directions

What if both optional?



Dept-Head: [EmpID, DeptName]

-or- Head: [EmpID, name, ....., DeptName]

(null FK allowed)


-or- Dept: [DeptName, ... EmpID]

(null FK allowed)



# Ternary relationships mapped to separate relation

- (1) Map entity types and attributes
- (2) Map the ternary relationship and its attributes (if any) into a new relation



Class: [Student\_Id, Course\_Id, Instructor\_Id, term, grade]

Assumptions inherent in this example?

# Summary

- Mapping rules
  - Conceptual data model  $\hookrightarrow$  relational data model
- Most common
  - 1:1, 1:N, M:N
  - Others – unary, ternary
- Special cases, exceptions
  - Understand application being modelled
- More examples coming