

```
1. #include <stdio.h>

#include <sys/types.h>

#include <sys/stat.h>
```

```
int main()
{
    if (mkfifo("myfifo", 0666) == -1)
    {
        perror("mkfifo");
        return 1;
    }

    printf("FIFO created\n");

    return 0;
}
```

```
bhavitha@SAIBHAVITHA:~$ gcc fifo_create.c -o fifo_create
bhavitha@SAIBHAVITHA:~$ ./fifo_create
FIFO created
bhavitha@SAIBHAVITHA:~$ ls -l myfifo
prw-r--r-- 1 root root 0 Sep 29 02:50 myfifo
bhavitha@SAIBHAVITHA:~$ ./fifo_create
mkfifo: File exists
bhavitha@SAIBHAVITHA:~$
```

```
2. #include <stdio.h>

#include <fcntl.h>

#include <unistd.h>
```

```
int main()
{
    int fd;

    char buffer[100];

    fd = open("myfifo", O_RDONLY);

    read(fd, buffer, sizeof(buffer));

    printf("Received: %s\n", buffer);
```

```
close(fd);

return 0;

}
```

```
bhavitha@SAIBHAVITHA:~$ gcc fifo_read.c -o fifo_read
bhavitha@SAIBHAVITHA:~$ ./fifo_read
Received: Hello from Writer
bhavitha@SAIBHAVITHA:~$
```

3. #include <stdio.h>

```
#include <fcntl.h>
```

```
#include <unistd.h>
```

```
#include <string.h>
```

```
int main()
```

```
{
```

```
int fd;
```

```
char message[] = "Hello from Writer";
```

```
fd = open("myfifo", O_WRONLY);
```

```
write(fd, message, strlen(message) + 1);
```

```
close(fd);
```

```
printf("Message sent\n");
```

```
return 0;
```

```
}
```

```
bhavitha@SAIBHAVITHA:~$ gcc fifo_write.c -o fifo_write
bhavitha@SAIBHAVITHA:~$ ./fifo_write
Message sent
bhavitha@SAIBHAVITHA:~$
```