

4) Select all the courier whose cost is greater than Rs 100 and less than Rs 500 & mode of payment is online.

Relational Algebra:

$$\Pi_{\langle c_id, p_amount, p_mode \rangle} (p, (\sigma_{\langle p_amount > 100 \text{ AND } p_amount < 500 \text{ AND } p_mode = \text{"online"} \rangle} \text{payment})) \bowtie_{\langle c_p_id = p_id \rangle} (c, \text{courier}))$$

SQL Code:

```
SELECT C_ID, P.P_AMOUNT, P.P_Mode FROM COURIER AS C JOIN  
PAYMENT AS P ON(C.P_ID=P.P_ID) WHERE P.P_AMOUNT < '500' AND  
P.P_AMOUNT > '100' AND P.P_MODE='ONLINE';
```

Output:

Data Output	Explain	Notifications	Messages																				
<table><thead><tr><th></th><th>c_id</th><th>p_amount</th><th>p_mode</th></tr><tr><td></td><td>character varying (10)</td><td>integer</td><td>character varying (10)</td></tr></thead><tbody><tr><td>1</td><td>C001</td><td>120</td><td>ONLINE</td></tr><tr><td>2</td><td>C005</td><td>140</td><td>ONLINE</td></tr><tr><td>3</td><td>C006</td><td>200</td><td>ONLINE</td></tr></tbody></table>		c_id	p_amount	p_mode		character varying (10)	integer	character varying (10)	1	C001	120	ONLINE	2	C005	140	ONLINE	3	C006	200	ONLINE			
	c_id	p_amount	p_mode																				
	character varying (10)	integer	character varying (10)																				
1	C001	120	ONLINE																				
2	C005	140	ONLINE																				
3	C006	200	ONLINE																				