DATA SCIENCE - 22DS102006

6. Time Series Analysis
   a. Create time series using datetime object in pandas indexed by timestamps.
   b. Use pandas.date_range to generate a DatetimeIndex with an indicated length.
   c. Generate data ranges by setting time zone, localize time zone and convert to particular time zone using tz_convert and combine two different time zones.
   d. Perform period arithmetic such as adding and subtracting integers from periods and construct range of periods using period_range function.
   e. Convert Periods and PeriodIndex objects to another frequency with asfreq method.
   f. Convert Series and DataFrame objects indexed by timestamps to periods with the to_period method.
   g. Perform resampling, downsampling and upsampling for the time series.

Create time series using datetime object in pandas indexed by timestamps.

Aim

To create a **time series in Pandas using `datetime` objects** and use the timestamps as the index of the time series.

Syntax

```
pd.to_datetime(date_values)
pd.Series(data, index=datetime_index)
```

General syntax:

```
import pandas as pd

dates = pd.to_datetime([...])
series = pd.Series(data, index=dates)
```

Program Solution

```
import pandas as pd

# Create datetime objects
dates = pd.to_datetime([
    '2026-01-01',
    '2026-01-02',
    '2026-01-03',
    '2026-01-04',
    '2026-01-05'
])

# Create data
temperature = [28, 30, 29, 31, 32]
```

```
# Create time series with timestamps as index
time_series = pd.Series(
    temperature,
    index=dates
)

# Display the time series
print("Time Series:")
print(time_series)
```

Output

```
Time Series:
2026-01-01    28
2026-01-02    30
2026-01-03    29
2026-01-04    31
2026-01-05    32
dtype: int64
```

The index of the Series consists of **timestamps**, while the corresponding values represent the temperature recorded on each date.

Use pandas.date_range to generate a DatetimeIndex with an indicated length.

Aim

To generate a **`DatetimeIndex` of a specified length** using the `pandas.date_range()` function.

Syntax

```
pd.date_range(start=None, end=None, periods=None, freq='D')
```

Important Parameters

- `start` – Starting date/time.
- `end` – Ending date/time.
- `periods` – Number of timestamps to generate.
- `freq` – Frequency of timestamps, such as `D` (daily), `h` (hourly), `M` (monthly).

For a specified length, the commonly used syntax is:

```
pd.date_range(start='YYYY-MM-DD', periods=n, freq='D')
```

Program Solution

```
import pandas as pd

# Generate a DatetimeIndex with 7 dates
date_index = pd.date_range(
    start='2026-01-01',
    periods=7,
    freq='D'
)

# Display the DatetimeIndex
print("Generated DatetimeIndex:")
print(date_index)
```

Output

```
Generated DatetimeIndex:

DatetimeIndex(['2026-01-01', '2026-01-02', '2026-01-03',
               '2026-01-04', '2026-01-05', '2026-01-06',
               '2026-01-07'],
              dtype='datetime64[ns]', freq='D')
```

Explanation

The `pd.date_range()` function is used to generate a sequence of dates at regular intervals.

In the program:

```
pd.date_range(
    start='2026-01-01',
    periods=7,
    freq='D'
)
```

Step-by-step

1. **`start='2026-01-01'`**
   Specifies the starting date.
2. **`periods=7`**
   Specifies that exactly **7 timestamps** should be generated.
3. **`freq='D'`**
   Specifies a **daily frequency**, so each timestamp is one day apart.

The resulting object is a `DatetimeIndex`.

Use pandas.date_range to generate a DatetimeIndex with an indicated length.

Aim

To generate date ranges by **setting a time zone, localizing a time zone, converting timestamps to another time zone using `tz_convert()`, and combining time-series data from two different time zones** using Pandas.

Syntax

1. Generate date range with a time zone

```
pd.date_range(start, periods=n, freq='h', tz='Asia/Kolkata')
```

2. Localize a time zone

```
datetime_index.tz_localize('Asia/Kolkata')
```

3. Convert to another time zone

```
datetime_index.tz_convert('America/New_York')
```

4. Combine time series

```
pd.concat([series1, series2])
```

Program Solution

```
import pandas as pd

--------------------------------------------------
1. Generate date range by setting a time zone
--------------------------------------------------

india_dates = pd.date_range(
    start='2026-01-01 09:00',
    periods=3,
    freq='h',
    tz='Asia/Kolkata'
)

print("1. Date Range with Asia/Kolkata Time Zone:")
print(india_dates)


--------------------------------------------------
2. Create a timezone-naive DatetimeIndex
--------------------------------------------------

dates = pd.date_range(
    start='2026-01-01 09:00',
    periods=3,
    freq='h'
)

print("\n2. Timezone-naive Date Range:")
```

```
print(dates)


--------------------------------------------------
3. Localize the timezone
--------------------------------------------------

localized_dates = dates.tz_localize('Asia/Kolkata')

print("\n3. After Localizing to Asia/Kolkata:")
print(localized_dates)


--------------------------------------------------
4. Convert to another timezone using tz_convert()
--------------------------------------------------

new_york_dates = localized_dates.tz_convert(
    'America/New_York'
)

print("\n4. Converted to America/New_York:")
print(new_york_dates)


--------------------------------------------------
5. Create another time series in a different
   timezone
--------------------------------------------------

india_series = pd.Series(
    [100, 200, 300],
    index=localized_dates
)

new_york_series = pd.Series(
    [400, 500, 600],
    index=new_york_dates
)

print("\n5. India Time Series:")
print(india_series)

print("\nNew York Time Series:")
print(new_york_series)


--------------------------------------------------
6. Combine two different timezone series
--------------------------------------------------

combined_series = pd.concat([
    india_series,
    new_york_series
])

print("\n6. Combined Time Series:")
```

```
print(combined_series)
```

Sample Output

1. Date Range with Time Zone

```
1. Date Range with Asia/Kolkata Time Zone:

DatetimeIndex(['2026-01-01 09:00:00+05:30',
               '2026-01-01 10:00:00+05:30',
               '2026-01-01 11:00:00+05:30'],
              dtype='datetime64[ns, Asia/Kolkata]', freq='h')
```

2. Timezone-Naive Date Range

```
2. Timezone-naive Date Range:

DatetimeIndex(['2026-01-01 09:00:00',
               '2026-01-01 10:00:00',
               '2026-01-01 11:00:00'],
              dtype='datetime64[ns]', freq='h')
```

3. Localized Time Zone

```
3. After Localizing to Asia/Kolkata:

DatetimeIndex(['2026-01-01 09:00:00+05:30',
               '2026-01-01 10:00:00+05:30',
               '2026-01-01 11:00:00+05:30'],
              dtype='datetime64[ns, Asia/Kolkata]', freq='h')
```

4. Converted to New York Time

```
4. Converted to America/New_York:

DatetimeIndex(['2025-12-31 22:30:00-05:00',
               '2025-12-31 23:30:00-05:00',
               '2026-01-01 00:30:00-05:00'],
              dtype='datetime64[ns, America/New_York]', freq='h')
```

5. Time Series

```
5. India Time Series:

2026-01-01 09:00:00+05:30    100
2026-01-01 10:00:00+05:30    200
2026-01-01 11:00:00+05:30    300
dtype: int64
New York Time Series:

2025-12-31 22:30:00-05:00    400
2025-12-31 23:30:00-05:00    500
2026-01-01 00:30:00-05:00    600
dtype: int64
```

6. Combined Time Series

```
6. Combined Time Series:
```

```
2025-12-31 22:30:00-05:00    400
2025-12-31 23:30:00-05:00    500
2026-01-01 00:30:00-05:00    600
2026-01-01 09:00:00+05:30    100
2026-01-01 10:00:00+05:30    200
2026-01-01 11:00:00+05:30    300
dtype: int64
```

Perform period arithmetic such as adding and subtracting integers from periods and construct range of periods using period_range function.

Aim

To perform **period arithmetic** by adding and subtracting integers from Pandas `Period` objects and to construct a range of periods using the `period_range()` function.

Syntax

1. Create a Period

```
pd.Period('2026-01', freq='M')
```

2. Add an integer to a Period

```
period + integer
```

3. Subtract an integer from a Period

```
period - integer
```

4. Construct a range of periods

```
pd.period_range(start, periods=n, freq='M')
```

Program Solution

```
import pandas as pd

# Create a monthly Period
p = pd.Period('2026-01', freq='M')

print("Original Period:")
print(p)

# Add integers to the period
print("\nAfter adding 2:")
print(p + 2)

print("\nAfter adding 5:")
print(p + 5)

# Subtract integers from the period
print("\nAfter subtracting 1:")
print(p - 1)

print("\nAfter subtracting 3:")
print(p - 3)

# Create a range of monthly periods
periods = pd.period_range(
    start='2026-01',
    periods=6,
    freq='M'
```

```
)

print("\nRange of Periods:")
print(periods)
```

Sample Output

```
Original Period:
2026-01

After adding 2:
2026-03

After adding 5:
2026-06

After subtracting 1:
2025-12

After subtracting 3:
2025-10

Range of Periods:
PeriodIndex(['2026-01', '2026-02', '2026-03',
             '2026-04', '2026-05', '2026-06'],
            dtype='period[M]')
```

Convert Periods and PeriodIndex objects to another frequency with asfreq method.

Aim

To convert **Pandas `Period` and `PeriodIndex` objects from one frequency to another** using the `asfreq()` method.

Syntax

1. Convert a Period to another frequency

```
period.asfreq(freq, how='start')
```

2. Convert a PeriodIndex to another frequency

```
period_index.asfreq(freq, how='start')
```

Parameters

- `freq` – The target frequency, such as `'D'`, `'M'`, `'Q'`, or `'Y'`.
- `how` – Specifies whether to use the **start** or **end** of the period.
  - `'start'` – Beginning of the period.
  - `'end'` – End of the period.

Program Solution

```
import pandas as pd

--------------------------------------------------
1. Create a monthly Period
--------------------------------------------------

p = pd.Period('2026-01', freq='M')

print("Original Period:")
print(p)


--------------------------------------------------
2. Convert monthly Period to daily frequency
--------------------------------------------------

daily_start = p.asfreq('D', how='start')

print("\nMonthly Period converted to Daily (Start):")
print(daily_start)


daily_end = p.asfreq('D', how='end')
```

```
print("\nMonthly Period converted to Daily (End):")
print(daily_end)


--------------------------------------------------
 3. Create a PeriodIndex
 --------------------------------------------------

period_index = pd.period_range(
    start='2026-01',
    periods=3,
    freq='M'
)

print("\nOriginal PeriodIndex:")
print(period_index)


 --------------------------------------------------
 4. Convert PeriodIndex to daily frequency
 --------------------------------------------------

daily_period_index = period_index.asfreq(
    'D',
    how='start'
)

print("\nPeriodIndex converted to Daily Frequency:")
print(daily_period_index)


 --------------------------------------------------
 5. Convert PeriodIndex to daily frequency at end
 --------------------------------------------------

daily_period_index_end = period_index.asfreq(
    'D',
    how='end'
)

print("\nPeriodIndex converted to Daily Frequency (End):")
print(daily_period_index_end)
```

Sample Output

```
Original Period:
2026-01

Monthly Period converted to Daily (Start):
2026-01-01

Monthly Period converted to Daily (End):
2026-01-31
```

```
Original PeriodIndex:
PeriodIndex(['2026-01', '2026-02', '2026-03'],
            dtype='period[M]')

PeriodIndex converted to Daily Frequency:
PeriodIndex(['2026-01-01', '2026-02-01', '2026-03-01'],
            dtype='period[D]')

PeriodIndex converted to Daily Frequency (End):
PeriodIndex(['2026-01-31', '2026-02-28', '2026-03-31'],
            dtype='period[D]')
```

Convert Series and DataFrame objects indexed by timestamps to periods with the to_period method.

Aim

To convert **Series and DataFrame objects indexed by timestamps into Period and PeriodIndex objects** using the Pandas `to_period()` method.

Syntax

1. Convert a Series to a PeriodIndex

```
series.to_period(freq)
```

2. Convert a DataFrame to a PeriodIndex

```
dataframe.to_period(freq)
```

Where:

- `freq` specifies the desired frequency.
- `'D'` – Daily
- `'M'` – Monthly
- `'Q'` – Quarterly
- `'Y'` – Yearly

Program Solution

```
import pandas as pd

--------------------------------------------------
 1. Create a Series with timestamp index
--------------------------------------------------

dates = pd.to_datetime([
    '2026-01-10',
    '2026-02-15',
    '2026-03-20',
    '2026-04-25'
])

sales = pd.Series(
    [1000, 1500, 1800, 2200],
    index=dates
)

print("Original Series:")
print(sales)


--------------------------------------------------
 2. Convert Series from timestamps to monthly periods
```

```
------------------------------------------------

period_series = sales.to_period('M')

print("\nSeries converted to Monthly Periods:")
print(period_series)


------------------------------------------------
3. Create a DataFrame with timestamp index
------------------------------------------------

df = pd.DataFrame(
    {
        'Sales': [1000, 1500, 1800, 2200],
        'Profit': [200, 300, 400, 500]
    },
    index=dates
)

print("\nOriginal DataFrame:")
print(df)


 ------------------------------------------------
 4. Convert DataFrame to monthly periods
 ------------------------------------------------

period_df = df.to_period('M')

print("\nDataFrame converted to Monthly Periods:")
print(period_df)
```

Sample Output

1. Original Series

```
Original Series:
2026-01-10    1000
2026-02-15    1500
2026-03-20    1800
2026-04-25    2200
dtype: int64
```

2. Series Converted to Monthly Periods

```
Series converted to Monthly Periods:
2026-01    1000
2026-02    1500
2026-03    1800
2026-04    2200
Freq: M, dtype: int64
```

3. Original DataFrame

```
Original DataFrame:
```

```
            Sales  Profit
2026-01-10   1000     200
2026-02-15   1500     300
2026-03-20   1800     400
2026-04-25   2200     500
```

4. DataFrame Converted to Monthly Periods

```
DataFrame converted to Monthly Periods:
         Sales  Profit
2026-01   1000     200
2026-02   1500     300
2026-03   1800     400
2026-04   2200     500

Freq: M
```

Perform resampling, downsampling and upsampling for the time series.

Aim

To perform **resampling, downsampling, and upsampling** operations on a time series using Pandas.

Syntax

1. Resampling

```
series.resample('frequency').aggregation_function()
```

Example:

```
series.resample('D').mean()
```

2. Downsampling

```
series.resample('larger_frequency').sum()
```

Example:

```
series.resample('6h').sum()
```

3. Upsampling

```
series.resample('smaller_frequency').asfreq()
```

or

```
series.resample('smaller_frequency').ffill()
```

Program Solution

```
import pandas as pd

 ------------------------------------------------
 1. Create an hourly time series
 ------------------------------------------------

dates = pd.date_range(
    start='2026-01-01 00:00',
    periods=12,
    freq='h'
)

values = [10, 12, 15, 14, 18, 20,
          22, 21, 25, 28, 30, 32]

time_series = pd.Series(
    values,
    index=dates
```

```
)

print("Original Hourly Time Series:")
print(time_series)


 ------------------------------------------------
 2. Resampling - calculate 3-hourly mean
 ------------------------------------------------

resampled = time_series.resample('3h').mean()

print("\nResampled Time Series - 3 Hour Mean:")
print(resampled)


 ------------------------------------------------
 3. Downsampling - Hourly to 4-hourly
 ------------------------------------------------

downsampled = time_series.resample('4h').sum()

print("\nDownsampled Time Series - 4 Hour Sum:")
print(downsampled)


 ------------------------------------------------
 4. Upsampling - Hourly to 30-minute intervals
 ------------------------------------------------

upsampled = time_series.resample('30min').asfreq()

print("\nUpsampled Time Series - 30 Minute:")
print(upsampled)


 ------------------------------------------------
 5. Upsampling with Forward Fill
 ------------------------------------------------

upsampled_ffill = time_series.resample('30min').ffill()

print("\nUpsampled Time Series using Forward Fill:")
print(upsampled_ffill)
```

Sample Output

1. Original Time Series

```
Original Hourly Time Series:

2026-01-01 00:00:00    10
2026-01-01 01:00:00    12
2026-01-01 02:00:00    15
```

```
2026-01-01 03:00:00    14
2026-01-01 04:00:00    18
2026-01-01 05:00:00    20
2026-01-01 06:00:00    22
2026-01-01 07:00:00    21
2026-01-01 08:00:00    25
2026-01-01 09:00:00    28
2026-01-01 10:00:00    30
2026-01-01 11:00:00    32
Freq: h, dtype: int64
```

2. Resampling

The hourly data is resampled into **3-hour intervals** and the mean is calculated.

```
Resampled Time Series - 3 Hour Mean:

2026-01-01 00:00:00    12.333333
2026-01-01 03:00:00    17.333333
2026-01-01 06:00:00    22.666667
2026-01-01 09:00:00    30.000000
Freq: 3h, dtype: float64
```

For example:

```
(10 + 12 + 15) / 3 = 12.33
```

3. Downsampling

Hourly data is reduced to **4-hour intervals** and the values are summed.

```
Downsampled Time Series - 4 Hour Sum:

2026-01-01 00:00:00    51
2026-01-01 04:00:00    81
2026-01-01 08:00:00    115
Freq: 4h, dtype: int64
```

For example:

```
10 + 12 + 15 + 14 = 51
```

4. Upsampling

Hourly data is increased to **30-minute intervals**.

```
Upsampled Time Series - 30 Minute:
```

```
2026-01-01 00:00:00    10.0
2026-01-01 00:30:00     NaN
2026-01-01 01:00:00    12.0
2026-01-01 01:30:00     NaN
2026-01-01 02:00:00    15.0
2026-01-01 02:30:00     NaN
2026-01-01 03:00:00    14.0
...
Freq: 30min, dtype: float64
```

The newly created 30-minute timestamps contain `NaN` because no original observation exists at those times.

5. Upsampling Using Forward Fill

The missing values can be filled using `ffill()`:

```
Upsampled Time Series using Forward Fill:

2026-01-01 00:00:00    10
2026-01-01 00:30:00    10
2026-01-01 01:00:00    12
2026-01-01 01:30:00    12
2026-01-01 02:00:00    15
2026-01-01 02:30:00    15
2026-01-01 03:00:00    14
...
Freq: 30min, dtype: int64
```

My Programs :

Time Series Analysis

a. Create Time Series

```
rng = pd.date_range('2023-01-01', periods=6, freq='D')
ts = pd.Series(np.random.randn(len(rng)), index=rng)
print(ts)
```

b. Time Zone Conversion

```
ts_utc = ts.tz_localize('UTC')
ts_ind = ts_utc.tz_convert('Asia/Kolkata')
print(ts_ind)
```

c. Period Arithmetic and Conversion

```
p = pd.Period('2024Q1')
print(p + 1)
print(p.asfreq('M', 'end'))
```

d. Resampling

```
ts = pd.Series(np.random.randn(100),
               index=pd.date_range('2024-01-01', periods=100))
ts_monthly = ts.resample('M').mean()
print(ts_monthly)
```