

[← Practice Programming Problems / K-Distribution](#)

K-Distribution

👁 Submissions Attempted by: 211 | Solved by: 73 | Partially Solved by: 122 | ★★★★★☆

[Combinatorics](#)[Dynamic Programming](#)[Hard](#)[Math](#)[Number Theory](#)[Edit](#)[Problem](#) [Editorial](#) [My Submissions](#) [Analytics](#)[🏆 June Clash '15](#)

In order to get at least some points you can try **all possible distributions** and for every of them check if requirements are satisfied. From *Constraints* section it is obvious that given solution should score at least **28 points**. But to get full score you need a different, faster approach.

In problem *K-distribution* you are asked about number of **valid partitions**. However, as it often happens in such tasks, it is easier to approach it from an opposite side. Let's count **bad partitions** – answer to original problem will be equal to total number of possible partitions minus number of bad partitions.

Counting bad partitions turns out to be a **standard DP problem** – it's one of modifications of **knapsack problem**. State of DP : $dp[sum]$ – number of ways to pick numbers which sum up to S . Add numbers one by one and recalculate values of DP (read about knapsack problem first if you are not familiar with it). When calculating final answer, don't forget that two symmetric ways of distribution are counted as different.

Also you have to handle cases when both groups will have sum **less than K**. Depending on implementation, you may count them twice or not count at all. Look at solutions below to see how it can be handled (again, with some sort of **inclusion-exclusion idea**). However, it turns out that things are much simpler. When both groups have sum **less than K** – it means that total sum of all numbers is **less than $2 \cdot K$** . But in this case answer will be simply 0, and you don't even need to calculate values of DP table.

[Edit Editorial](#)

IS THIS EDITORIAL HELPFUL?



Yes, it's helpful



No, it's not helpful

14 developer(s) found this editorial helpful.

[Author Solution](#) by [Pavel Sheftelevich](#)

```
1. #include <stdio>
2. #include <algorithm>
3. #include <vector>
4. #include <iostream>
5. #include <set>
6. #include <map>
7. #include <iomanip>
8. #include <string>
9. #include <string.h>
10. #include <stdlib>
11. #include <bitset>
12. #include <cmath>
13.
14. #define X first
15. #define Y second
16. #define mp make_pair
17. #define pb push_back
18.
19. typedef long long ll;
20.
21. using namespace std;
22.
23. const int MAXN = 110, MOD = 1E9 + 7, MAXK = 100100;
24. int n, a[MAXN], k;
25. int dp[MAXK];
26. ll totSum ;
27. int main() {
28.     cin>>n>>k;
29.     for (int i = 0; i < n; i++) {
30.         cin>>a[i];
31.         totSum += a[i];
32.     }
33.     dp[0] = 1;
34.     for (int i = 0; i < n; i++) {
35.         if (a[i] >= k) {
36.             continue;
37.         }
38.         for (int j = k - a[i]; j >= 0; j--) {
39.             dp[j + a[i]] += dp[j];
40.             if (dp[j + a[i]] >= MOD) {
41.                 dp[j + a[i]] -= MOD;
42.             }
43.         }
44.     }
45.     int sum = 0;
46.     for (int i = 0; i < k; i++) {
47.         //cerr<<i<<" : "<<dp[i]<<endl;
48.         sum += dp[i];
49.         if (sum >= MOD) {
50.             sum -= MOD;
51.         }
52.
53.         if (i != totSum - i) {
```

```

54.         //cerr<<"fklfl"<<endl;
55.         sum += dp[i];
56.         if (sum >= MOD) {
57.             sum -= MOD;
58.         }
59.     }
60. }
61. //cerr<<sum<<endl;
62. int tot = 1;
63. for (int i = 0; i < n; i++) {
64.     tot *= 2;
65.     if (tot >= MOD) {
66.         tot -= MOD;
67.     }
68. }
69. tot -= sum;
70. if (tot < 0) {
71.     tot += MOD;
72. }
73. cout<<tot<<endl;
74. return 0;
75. }

```

Tester Solution by Bohdan Pryshchenko

```

1. #include<bits/stdc++.h>
2. #define bs 1000000007
3.
4. using namespace std;
5.
6. int n,a[1<<20],ans,T;
7. int answ;
8. int dp[1<<20];
9. long long S;
10. long long rem;
11.
12. void add(int &a,int b)
13. {
14.     a+=b;
15.     if (a>=bs)
16.         a-=bs;
17. }
18.
19. int main(){
20.
21.     cin>>n;
22.     cin>>T;
23.     --T;
24.
25.     for (int i=1;i<=n;i++)
26.         cin>>a[i];
27.
28.     ans=1;

```

```

29. for (int i=1;i<=n;i++)
30.     ans*=2,
31.     ans%=bs;
32.
33. S=0;
34. for (int i=1;i<=n;i++)
35.     S+=a[i];
36.
37. dp[0]=1;
38. for (int i=1;i<=n;i++)
39.     for (int j=T-a[i];j>=0;--j)
40.         if (dp[j]>0)
41.             add(dp[j+a[i]],dp[j]);
42.
43. answ=0;
44. for (int i=0;i<=T;i++)
45. {
46.     rem=S-i;
47.     if (rem<=T)
48.         add(answ,dp[i]);
49.     else
50.         add(answ,2*dp[i]%bs);
51. }
52.
53. ans=(ans-answ+bs)%bs;
54. cout<<ans<<endl;
55.
56. return 0;}

```

COMMENTS (4)

[Refresh](#)

Join Discussion...

Cancel

Post

**nagasiva sudhakarreddykovvuri** 4 months ago

whyad add (answ,2*dp[i]%s);

[Reply](#) • [Message](#) • [Permalink](#)**Bohdan Pryshchenko** 4 months ago

You need to count every distribution twice, because if you have some way to pick items with cost X from set with total cost S, it gives you 2 distributions: (X,S-X) and (S-X,X) - you may choose to put your items in either first or second part.

[Reply](#) • [Message](#) • [Permalink](#)**nagasiva sudhakarreddykovvuri** 4 months ago

what abt add(answ,dp[i]);

[Reply](#) • [Message](#) • [Permalink](#)

**Bohdan Pryshchenko** 4 months ago

These are cases which will be counted only once, so you don't need *2 for them.

[Reply](#) ● [Message](#) ● [Permalink](#)

PROFILE IMPACT

[Complete Profile](#)

*Excellent profile will increase your profile discoverability and keep you on top among others.

PROBLEMS SUGGESTED FOR YOU

[The function problem](#)

Solved by 249

[Game Of Strengths](#)

Solved by 497

[Putting matrix](#)

Solved by 17

[more...](#)

RECENT SUBMISSIONS

User	Result	Time	Lang
Swapnil ...		2.7472	C++
Roman Bi...		1.7096	C
Himadri ...		13.4437	C++
Himadri ...		13.4778	C++
Parag Go...		1.7106	C++
Parag Go...		1.71	C++
Parag Go...		2.2292	C++

[View All](#)

TRENDING NOTES

Number Theory - III

written by Boris Sokolov

Exact String Matching Algorithms

written by Alei Reyes

Binary Indexed Tree or Fenwick Tree

written by Chandan Mittal

Small tricks in for loop

written by Rangeesh

Strings And String Functions

written by Vinay Singh

[more ...](#)

DEVELOPERS TO FOLLOW



সায়ান চৌধুরী

2160 followers



Hemesh Singh

6 followers



Sachin Gupta

6361 followers

COMPANIES TO FOLLOW

Gigstart

1717 followers

Zoomcar

552 followers

HARMAN

1971 followers

RECOMMENDED CHALLENGES

[Horlicks Hack 4 Fun](#)

03 Sep 2015, 09:00 PM IST

[Register](#)[CODE-HUNT-2F](#)

21 Oct 2015, 05:00 PM IST

[Register](#)[Zoomcar Ruby Challenge](#)

23 Oct 2015, 06:00 PM IST

[Register](#)[Zomato Hiring Challenge](#)

23 Oct 2015, 06:00 PM IST

[Register](#)[Diona iOS Developer Hiring Challenge](#)

24 Oct 2015, 12:00 PM IST

[Register](#)[Tipstat Android Developer Hiring Challenge](#)

24 Oct 2015, 12:00 PM IST

[Register](#)[D'code](#)**SUBSCRIBE TO HACKEREARTH NEWS**[Subscribe](#)**JOIN PROGRAMMING CLUB ON FACEBOOK**[Join now](#)**ABOUT US**[Blog](#)[Engineering Blog](#)**HACKEREARTH**[API](#)[Chrome Extension](#)**DEVELOPERS**[AMA](#)[Code Monk](#)

[Updates & Releases](#)[CodeTable](#)[Judge Environment](#)[Team](#)[HackerEarth Academy](#)[Solution Guide](#)[Careers](#)[Developer Profile](#)[Problem Setter Guide](#)[In the Press](#)[Resume](#)[Practice Problems](#)[Campus Ambassadors](#)[HackerEarth Challenges](#)[Get Me Hired](#)[College Challenges](#)[Privacy](#)[Terms of Service](#)

RECRUIT

[Developer Sourcing](#)[Lateral Hiring](#)[Campus Hiring](#)[FAQs](#)[Customers](#)[Annual Report](#)

REACH US



IIIrd Floor, Salarpuria Business Center,
4th B Cross Road, 5th A Block,
Koramangala Industrial Layout,
Bangalore, Karnataka 560095, India.

✉ contact@hackerearth.com

☎ +91-80-4155-4695

☎ +1-650-461-4192



© 2015 HackerEarth