

← Practice Programming Problems / Roy and Little Mario

# Roy and Little Mario

● Submissions Attempted by: 375 | Solved by: 203 | Partially Solved by: 39 | ★★★☆☆

Ad-Hoc Algorithms Combinatorics Dynamic Programming Medium & Edit

Problem Editorial My Submissions Analytics

**▼** Sokrati Hiring Challenge

Hi,

This problem is a representation of summing the values of the nth row of a Pascals triangle. So it can be calculated as 2 to the power of N. Where N is the number of bricks available.

Explanation is as:

1 brick can be arranged in 1 way. 2 bricks can be arranged in 1+1 way (coring 1 place at a time and covering two places at a time) 3 bricks can be arranged in 1+2+1 dray (covering 1, 2 and three places at a time respectively).

Going on this way we see that a **Pascal's triangle** is formed. The total number of ways in which the bricks can be arranged is the sum of the Nth row of the triangle.

It can be easily calculated using JAVA's Math.pow(2, N)...:-)

Edit Editorial

# IS THIS EDITORIAL HELPFUL?



Yes, it's helpful



No, it's not helpful

2 developer(s) found this editorial helpful.

# Author Solution by Ravi Ojha

- 1. """
- 2. This is O(1) solution for each test case
- 3. If one can't figure that its a Tribonacci Series,
- 4. then he will use bruteforce over  $((n-2)^2)/12$  possibilities
- 5. which shall get him AC in one or two Test Files.
- 6.
- 7. Note that I've used Dynamic-Programming Tag for O(1) solution and
- 8. Multiplicative-Inverse Tag for O(n^2) solution

```
9.
10. This question is inspired from integer partition problem, where ea
11. For each possible partition we find number of permutations and sum
12. Initially I actually restricted each partition to be just 1 or 2,
13. So to make things tough, I introduced 3 also and hence Tribonacci
14. """
15.
16. \text{ MOD} = 1000000007
17. trib = []
18. def calc_trib():
19.
        trib.append(0)
20.
        trib.append(1)
21.
        trib.append(2)
22.
        trib.append(4)
23.
        for i in xrange(4,100010):
             temp = (trib[i-1] + trib[i-2] + trib[i-3])%MOD
24.
25.
            trib.append(temp)
26. def roy_and_mario():
        calc trib() #we figured that it is nothing but a tribonacci se
27.
        for t in xrange(input()):
28.
             n = input()
29.
            print trib[n]
30.
31. roy_and_mario()
```

#### **Tester Solution**

```
1. #include <iostream>
2. #include<stdio.h>
using namespace std;
4. #define MOD 1000000007
5. #define LL long long int
6. int main() {
7.
        int t,N,i;
            LL tribonacci[100010];
8.
9.
            tribonacci[0]=0,tribonacci[1]=0,tribonacci[2]=1;
10.
            for(i=3;i<100010;i++) tribonacci[i]=(tribonacci[i-1]+tribon</pre>
11.
            scanf("%d",&t);
12.
            while(t--)
13.
            {
                    scanf("%d",&N);
14.
                    printf("%lld\n",tribonacci[N+2]);
15.
16.
17.
            return 0;
18. }
```

### COMMENTS (5)

**2** Refresh



loin Discussion...

Cancel

Post



Lavesh Gupta a year ago

Please Ravi can you explain how it is a Tribonacci series

Reply • Message • Permalink



Puneet Jain a year ago

How can it be a pascal triangle...as for n=4 pascal traingle gives a solution of 8...but the correct answer is 7

Reply • Message • Permalink



Puneet Jain a year ago

How can it be a pascal triangle...as for n=4 pascal triangle gives a solution of 8...but the correct answer is 7

Reply • Message • Permalink



Shivam Mishra 10 months ago

wrong explanation

Reply • Message • Permalink



rit2013060 7 days ago

whoever have written editorial for this problem -- is wrong - that is actually solution when there is no limit on bricks height.

Unfortunately that here is 3.

Reply • Message • Permalink

# **PROFILE IMPACT**

# Complete Profile

\*Excellent profile will increase your profile discoverability and keep you on top among others.

#### PROBLEMS SUGGESTED FOR YOU

Kriti and her Birthday Gift

Solved by 71

Apple Picking 2

Solved by 27

Swap and Sort

Solved by 34

more...

RECENT SUBMISSIONS				
User	Result	Time	Lang	
Meetu Ag		1.0062	C++	
Rajan Ka		1.0059	C++	
Rajan Ka		1.0058	C++	
Rajan Ka		1.0062	C++	
rit20130		1.0059	С	
rit20130		1.0058	С	
rit20130		1.0058	С	
View All				

# TRENDING NOTES

Number Theory - III

written by Boris Sokolov

**Exact String Matching Algorithms** 

written by Alei Reyes

Binary Indexed Tree or Fenwick Tree

written by Chandan Mittal

Small tricks in for loop

written by Rangeesh

**Strings And String Functions** 

written by Vinay Singh

more ...

### **DEVELOPERS TO FOLLOW**



Neeraj Lajpal 0 followers



dablu kumar 1425 followers



Vishal Goel 5 followers

# **COMPANIES TO FOLLOW**

AT&T

2713 followers

foodpanda

2340 followers

CommonFloor

3749 followers

# **RECOMMENDED CHALLENGES**

Horlicks Hack 4 Fun 03 Sep 2015, 09:00 PM IST  Register	
CODE-HUNT-2F 21 Oct 2015, 05:00 PM IST  Register	
Zoomcar Ruby Challenge 23 Oct 2015, 06:00 PM IST Register	
Zomato Hiring Challenge 23 Oct 2015, 06:00 PM IST  Register	
Diona iOS Developer Hiring Challenge 24 Oct 2015, 12:00 PM IST Register	
Tipstat Android Developer Hiring Challenge 24 Oct 2015, 12:00 PM IST  Register	
D'code  SUBSCRIBE TO HACKEREARTH NEWS	•
bhawnesh.dipu@gmail.com  Subscribe	
JOIN PROGRAMMING CLUB ON FACEBOOK	
Join now	

ABOUT US	HACKEREARTH	DEVELOPERS	
Blog	API	AMA	
Engineering Blog	Chrome Extension	Code Monk	

Updates & Releases

Team

Careers

In the Press

CodeTable

HackerEarth Academy

Developer Profile

Resume

Campus Ambassadors

Get Me Hired

Privacy

Terms of Service

Judge Environment

Solution Guide

Problem Setter Guide

Practice Problems

HackerEarth Challenges

College Challenges

# **RECRUIT**

**Developer Sourcing** 

Lateral Hiring

Campus Hiring

**FAQs** 

Customers

Annual Report

# **REACH US**



Illrd Floor, Salarpuria Business Center, 4th B Cross Road, 5th A Block, Koramangala Industrial Layout, Bangalore, Karnataka 560095, India.

contact@hackerearth.com

+91-80-4155-4695

**+1-650-461-4192** 









 $g_{\dagger}$ 



© 2015 HackerEarth