

1

# Function and Class Templates

CSC 340

March 30, 2016

2

## Overview

- ❖ **Generic Programming**
- ❖ Function Templates
- ❖ Class Templates
- ❖ Standard Template Library

2

3

## Generic Programming (Java pre 5.0)

- ❖ Use inheritance to implement generic programming - for example, all of the Collections API classes are written in terms of the Object class
- ❖ Limitations:
  - ❖ Primitive types cannot be directly added into a standard Java collection. Wrapper classes must be used
  - ❖ Excessive use of downcasting - time consuming and delaying typing errors until runtime

3

Using a Collection in Java, one would have to explicitly cast an object stored in the collection back to the appropriate type

4

## Generic Programming (C++, Java)

---

- ❖ Java now uses Generics
- ❖ C++ uses templates: a blueprint or pattern for creating functions or classes
- ❖ Two types:
  - ❖ Function templates
  - ❖ Class templates (parameterized classes)

4

5

## Purpose

---

- ❖ Relieve the programmer of the burden of having to write multiple versions of the same function just to carry out the same operation on different types

5

6

## Example

---

- ❖ Consider a function, swap

```
void swap(int& X, int& Y) {
    int temp = X;
    X = Y;
    Y = temp;
}
```

- ❖ Drawbacks?

6

We might have implemented swap for one of our sort methods

It only works on one type - integers. What happens if we want this to work for an array of doubles? floats? Envelopes?

7

## Overview

---

- ❖ Generic Programming
- ❖ **Function Templates**
- ❖ Class Templates
- ❖ Standard Template Library

7

8

## Function Templates

---

- ❖ A function template has one or more template parameters

```
template<class T>
return_type function_name(T param)
```

- ❖ T is a template parameter - it refers to a data type that will be supplied when the function is called

8

9

## Swap, revisited

---

- ❖ Multiple swaps for multiple types:

```
void swap(int& X, int& Y) {
    int temp = X;
    X = Y;
    Y = temp;
}

void swap(string& X, string& Y) {
    string temp = X;
    X = Y;
    Y = temp;
}
```

9

10

## Swap Function Template

---

- ✦ Works with any data type that supports the assignment operator

```
template <class TParam>
void swap(TParam & X, TParam & Y) {
    TParam temp = X;
    X = Y;
    Y = temp;
}
```

10

11

## Specific Swap Function

---

- ✦ This version can co-exist with the template function

```
void swap(string * X, string * Y) {
    string temp = *X;
    *X = *Y;
    *Y = temp;
}
```

11

12

## Calling swap

---

- ✦ When calling swap, the only requirement is that both parameters are the same data type, and that they are modifiable via the = operator

```
int A = 5;
int B = 6;
swap(A, B);

string P("string one");
string Q("other string");
swap(P, Q);

string * R = new string("John");
string * S = new string("Blarg");
swap(R, S);
```

12

13

## Illegal Template Calls

---

- ❖ Some combinations won't work - you can't pass constants, and you can't pass incompatible types

```
int B = 6;
// illegal
swap(10, B);

// illegal
swap("Harry", "Sally");

bool E = true;
// illegal
swap(B, E);
```

13

14

## Another example

---

- ❖ The display function can display any data type that overloads the stream insertion operator

```
template <class T>
void display(const T & val) {
    cout << val;
}
```

14

15

## Additional Parameters

---

- ❖ A function template can have additional parameters which are not template parameters

```
template <class T>
void display(const T & val, ostream & os) {
    os << val;
}
```

```
display("Hello", cout);
display(22, outfile);
```

15

16

## Additional Parameters

---

- ❖ There can be additional template parameters, as long as each is used at least once in the function's parameter list
- ❖ T1 is any container that support the begin() operation  
T2 is the data type stored in the container

```
template <class T1, class T2>
T2 & getFirst( const T1 & container, T2 & value )
{
    value = *container.begin();
    return value;
}
```

16

17

This will make more sense after we talk about STL

## Calling getFirst

---

```
vector<int> vec;
vec.push_back( 32 );
int n;
cout << getFirst( vec, n );

list<double> testList;
testList.push_back( 42.24 );
double x;
getFirst( testList, x );
```

17

18

## Tips for Defining Templates

---

- ❖ Start with an ordinary function that accomplishes the task with one type - it's often easier to deal with a concrete case rather than the general case
- ❖ Then, debug the ordinary function
- ❖ Next, convert the function to a template by replacing type names with a type parameter

18

## Overview

---

- ❖ Generic Programming
- ❖ Function Templates
- ❖ **Class Templates**
- ❖ Standard Template Library

19

## Class Templates

---

- ❖ Let you create new classes at runtime
- ❖ Use a class template when you would otherwise be forced to create multiple classes with the same attributes and operations
- ❖ STL (Standard Template Library) Container classes - vector, list, set - are good examples

20

## Defining a Class Template

---

- ❖ General format for declaring a class template. The parameter T represents a data type:

```
template <typename T>
class className
{};
```

```
// OR
template <class T>
class className
{};
```

21

## Defining a Class Template

---

- ❖ Class templates are defined ONLY IN THE .h FILE
- ❖ Read that again - class templates are not defined in separate compilation units (they're not really classes, they are patterns that the compiler uses to define classes when needed)

22

## Array Example

---

- ❖ Typed arrays: <https://gist.github.com/jrob8577/30a29237e05f77bcd6c>
- ❖ Array class template: <https://gist.github.com/jrob8577/dca3b3149d4cb78f0a7b>
- ❖ A client can create any type of array using our template, as long as it permits the use of the assignment operator =: <https://gist.github.com/jrob8577/d31a99928f57bbad16d2>

23

## Next Assignment

---

- ❖ Make Queue and Node template classes
- ❖ One gotcha - we can no longer return -1 in the event that the queue is empty. We will return the default type, as created using the default constructor for the specified type

```
template <typename T>
T Queue<T>::front() {
    // example of default constructor for type T
    return T();
}
```

24

This leads to some edge cases in code we've written - we can no longer test for -1, and should instead ensure the queue is not empty...



25

## Overview

---

- ❖ Generic Programming
- ❖ Function Templates
- ❖ Class Templates
- ❖ **Standard Template Library**

25

26

## STL

---

- ❖ Standard Template Library
  - ❖ Reference: <http://www.sgi.com/tech/stl/>
- ❖ Created by Alexander Stepanov and Meng Lee at Hewlett Packard
- ❖ Helps programmers avoid having to reinvent standard container implementation code
- ❖ Not part of the C++ core, but part of the C++ standard
- ❖ Key components: containers, iterators, algorithms

26

27

## Container Types

---

- ❖ Sequence
  - ❖ vector, deque, list
- ❖ Container Adapters
  - ❖ stack, queue, priority\_queue
- ❖ Associative Containers
  - ❖ set, multiset, map, multi map

27

## Including the STL

---

- ✦ The class name is the same as the header to require  
`<vector>`, `<list>`, `<deque>`, `<stack>`,  
`<bitset>`
- ✦ Also  
`<queue>` // queue and priority\_queue  
`<set>` // set and multiset  
`<map>` // map and multimap

28

## Common Member Functions

---

- ✦ default constructor, copy constructor, destructor
- ✦ empty
- ✦ max\_size (max number of elements for a container)
- ✦ size (number of elements currently in the container)
- ✦ operator = (assign one container to another)
- ✦ overloaded `<`, `<=`, `>`, `>=`, `==`, `!=`
- ✦ swap

29

reverse iterators iterate backwards

## Common Member Functions

---

- ✦ `begin()` returns an iterator pointing at the first element
- ✦ `end()` returns an iterator pointing after the last element
- ✦ `erase()` erases one or more elements
- ✦ `clear()` erases all elements
- ✦ `rbegin()` returns reverse\_iterator
- ✦ `rend()` return reverse\_iterator

30

31

## list Sequence Container

---

- ✦ Efficient insertion and deletion at any location
  - ✦ `deque` is more efficient if insertions and deletions are at the ends of the container
- ✦ Implemented as a doubly linked list
  - ✦ supports bidirectional iterators
- ✦ Does not support `at()` or `operator []`

31

32

## deque Sequence Container

---

- ✦ Provides benefits of `vector` and `list` in the same container
  - ✦ Rapid indexed access (like `vector`)
  - ✦ Efficient insertion and deletion at its end (like `list`)
  - ✦ Supports random access iterators
  - ✦ Often used for FIFO queue
  - ✦ Noncontiguous memory layout

32

33

## Common deque Operations

---

- ✦ `push_back()`
- ✦ `push_front()`
- ✦ `pop_back()`
- ✦ `pop_front()`
- ✦ `size()`
- ✦ `operator[]`
- ✦ `at()`

33

34

## Common `stack` Operations

---

- ✦ Constructor can take a reference to a `Container` (or create an empty stack)
- ✦ `empty()`
- ✦ `size()`
- ✦ `top()`
- ✦ `pop()`
- ✦ `push()`

34

35

## Common `queue` Operations

---

- ✦ Constructor can take a reference to a `Container` (or create an empty queue)
- ✦ `empty()`
- ✦ `size()`
- ✦ `front()`
- ✦ `back()`
- ✦ `pop()`
- ✦ `push()`

35

36

## Associative Containers

---

- ✦ Keys are always kept in sorted order
  - ✦ iterator always traverses in sort order
- ✦ `Set` - Single key values
- ✦ `Multiset` - Duplicate keys allowed
- ✦ `Map` - Contains pairs of (key, value)
  - ✦ key is unique
- ✦ `Multimap`
  - ✦ keys do not need to be unique

36

## Error Handling

---

- ❖ Exceptions are never thrown by STL classes
- ❖ Very little error checking exists in the STL classes
  - ❖ Read the docs!

37

## Iterator Basics

---

- ❖ An iterator is a generalization of pointers
- ❖ Facilitates cycling through the data in a container
- ❖ Although an iterator is not a pointer, you can think of it and use it as if it were
  - ❖ Supports the ++, --, ==, !=, and \* operators

38

## Iterator Example

---

- ❖ Declare a vector of integers, and an iterator to iterate over the vector

```
vector<int> container;
vector<int>::iterator p;
for( p = container.begin(); p !=
container.end(); p++ )
    cout << *p;
```

39

40

## Types of Iterators

---

- ✦ Input Iterator (InIt)
  - ✦ Used to read an element from a container
  - ✦ Moves only in the forward direction, one element at a time
  - ✦ Cannot pass through a sequence twice
- ✦ Output Iterator (OutIt)
  - ✦ Used to write an element to a container
  - ✦ Moves only in the forward direction, one element at a time
  - ✦ Cannot pass through a sequence twice

40

41

Note that each iterator's capabilities are a superset of the previously listed iterators

## Types of Iterators

---

- ✦ Forward Iterator (FwdIt)
  - ✦ Reads and writes in forward direction only
  - ✦ Retains its position in the container
- ✦ Bidirectional Iterator (BidIt)
  - ✦ Reads and writes in both directions
  - ✦ Retains its position in the container
- ✦ Random-Access Iterator (RadIt)
  - ✦ Reads and writes in randomly accessed positions
  - ✦ permits pointer arithmetic

41

42

## Iterator Support by Container

---

Containers	Supported Iterators
stack, queue, priority queue	no iterators
list, set, multiset, map, multimap	bidirectional
vector, deque	random

42

## Invalidating Iterators

---

- ✦ Some operations on a container may invalidate iterators
  - ✦ Results in a stale iterator
- ✦ Example:
  - ✦ `list.push_back()` does not invalidate iterators
  - ✦ `vector.push_back()` invalidates all iterators
  - ✦ `list.erase()` invalidates iterators that pointed to the delete elements
- ✦ Check the documentation for each method!

43

## Generic Algorithms

---

- ✦ Includes over 60 function templates
  - ✦ Sorting
  - ✦ Searching
  - ✦ Copying
  - ✦ accumulate
  - ✦ Inner\_product
  - ✦ Partial sum
  - ✦ Many More
- ✦ [http://www.sgi.com/tech/stl/table\\_of\\_contents.html](http://www.sgi.com/tech/stl/table_of_contents.html)

44

## Generic Algorithms for Sorting

---

- ✦ Syntax
 

```
void sort( Iterator begin, Iterator end );
void sort( Iterator begin, Iterator end, Comparator comp );
```
- ✦ Example
 

```
vector<int> vector;
sort( v.begin(), v.end(), less<int>() );
```
- ✦ `less<int>()` is called a function object

45

46

## Function Object Example

---

- ✦ Default comparison of STL container objects when sorting uses the < operator:

```
template<typename T>
class less {
public:
    bool operator() ( const T & x, const T & y) const
    {
        return x < y;
    }
};
```

46

47

## Predefined Function Objects

---

- ✦ Template class that contains a function
- ✦ Makes the STL more flexible - permits sorting on your own criteria
- ✦ Predefined objects in the STL:

```
divides<T>
equal_to<T>
greater<T>
greater_equal<T>
less<T>
...
```

47

48

## Searching

---

- ✦ Syntax
 

```
Iterator find( Iterator begin, Iterator end, const Object& x );
Iterator find_if( Iterator begin, Iterator end, Predicate pred );
```
- ✦ Example
 

```
template<int len>
class StringLength {
public:
    bool operator() (const string & s ) const {
        return s.length() == len;
    }
};

// Returns first string of length 9
find_if( v.begin(), v.end(), StringLength<9>() );
```

48

Predicate is a boolean function object

Many other searches, see docs!



## Copying

---

✦ Including - copy, copy\_backwards, remove, remove\_copy, remove\_if, replace, and many others

✦ Example

```
vector<int> source(10, 37);  
vector<int> target( 10 );  
copy( source.begin(), source.end(), target.begin() );
```