Chennai Mathematical Institute

Masters Thesis

Random Spanning Trees

Author:
Bhishmaraj S

Supervisor:
Dr. Samir Datta

A thesis submitted in fulfillment of the requirements
for the degree of Master of Science

in the

Computer Science at CMI

May 26, 2020

Declaration of Authorship

I, Bhishmaraj S, declare that this thesis titled, "Random Spanning Trees" and the work presented in it are my own. I confirm that:

- This work was done wholly or mainly while in candidature for a research degree at this University.
- Where any part of this thesis has previously been submitted for a degree or any other qualification at this University or any other institution, this has been clearly stated.
- Where I have consulted the published work of others, this is always clearly attributed.
- Where I have quoted from the work of others, the source is always given. With the exception of such quotations, this thesis is entirely my own work.
- I have acknowledged all main sources of help.
- Where the thesis is based on work done by myself jointly with others, I have made clear exactly what was done by others and what I have contributed myself .

Signed:

Date:

CHENNAI MATHEMATICAL INSTITUTE

Abstract

Faculty Name
Computer Science at CMI

Master of Science

Random Spanning Trees

by Bhishmaraj S

The Thesis Abstract is written here (and usually kept to just this page). The page is kept centered vertically so can expand into the blank space above the title too. . . .
I see

Acknowledgements

The acknowledgments and the people to thank go here, don't forget to include your project advisor…

Contents

List of Figures

List of Tables

List of Abbreviations

LAH	**L**ist **A**bbreviations **H**ere
WSF	**W**hat (it) **S**tands **F**or

1 Introduction

2 Background

2.1 Markov Chains

2.1.1 Fundamental theorem of Markov chain

2.1.2 Markov chain tree theorem

2.2 Results from Spectral Graph Theory

2.2.1 Kirchoff Matrix Tree Theorem

2.2.2 Some properties of Laplacian

2.3 Electric Networks

3 Random Walk Approach

3.1 Aldous, Broder

3.2 Wilson

4 Matrix Approach

4.1 Colbourn, Day, Nel

4.2 Harvey, Xu

4.2.1 Techniques used

Naive chain rule algorithm

Input: $G = (V, E)$ and L_G^+
Output: Set of edges corresponding to a random spanning tree

for $e = (u, v) \in E$ **do**
  $R_e^{\text{eff}} = (\chi_u - \chi_v)^T \ L_G^+ \ (\chi_u - \chi_v)$;
  if $(X \sim \mathit{Bernoulli}(R_e^{\text{eff}})) = 1$ **then**
    Add edge e to the spanning tree;
    $G = G/e$;
  else
    $G = G \setminus e$;
  end
  Update L_G^+ ;
end

Algorithm 1: Sampling uniform spanning tree using chain rule

4.2.2 Recursive Algorithm with lazy updates

Lemma 1 (Formulas in **Theorem 1** are well defined)**.** *Let $G = (V, E)$ be a connected graph and $D \subseteq E$ then*
$\left(I - L_D L_G^+\right)$ *is invertible* $\iff$ $G \setminus D$ *is connected*

Proof. TODO ■

Theorem 1 (Update identity for Deletion)**.** *Let $G = (V, E)$ be a connected graph and $D \subseteq E$. If $G \setminus D$ is connected then*

$$(L_G - L_D)^+ = L_G^+ - \left(L_G^+ \cdot (L_D L_G^+ - I)^{-1} \cdot L_D \cdot L_G^+\right)$$

Proof. TODO ■

Corollary 1 (Improved **Theorem 1** for submatrix)**.** *Let $G = (V, E)$ be a connected graph and $D \subseteq G$. For $S \subseteq V$ define $E[S]$ as $(S \times S) \cap E$. Suppose $E_D \subseteq E[S]$ and $G \setminus D$ is connected then*

$$(L_G - L_D)^+_{S,S} = (L_G^+)_{S,S} - \left((L_G^+)_{S,S} \cdot ((L_D)_{S,S} \ (L_G^+)_{S,S} \ - \ I)^{-1} \cdot (L_D)_{S,S} \cdot (L_G^+)_{S,S}\right)$$

Proof. TODO ■

5 Laplacian Paradigm

5.1 Kelner, Madry

6 Conclusion