

AI Agent Platform Database Schema Documentation

Users & Authentication

Table: users

Column	Type	Constraints
id	UUID	PRIMARY KEY
username	VARCHAR(50)	NOT NULL, UNIQUE
email	VARCHAR(100)	NOT NULL, UNIQUE
password_hash	VARCHAR(255)	NOT NULL
created_at	TIMESTAMP	NOT NULL, DEFAULT NOW()
updated_at	TIMESTAMP	NOT NULL, DEFAULT NOW()
is_active	BOOLEAN	NOT NULL, DEFAULT TRUE
is_admin	BOOLEAN	NOT NULL, DEFAULT FALSE

Table: refresh_tokens

Column	Type	Constraints
id	UUID	PRIMARY KEY
user_id	UUID	FOREIGN KEY (users.id)
token_hash	VARCHAR(255)	NOT NULL, UNIQUE
expires_at	TIMESTAMP	NOT NULL
created_at	TIMESTAMP	NOT NULL, DEFAULT NOW()
is_revoked	BOOLEAN	NOT NULL, DEFAULT FALSE

INDEX: idx_refresh_tokens_user_id (user_id)

Table: user_preferences

Column	Type	Constraints
user_id	UUID	PRIMARY KEY, FOREIGN KEY (users.id)
theme	VARCHAR(20)	DEFAULT 'light'
language	VARCHAR(10)	DEFAULT 'en'
default_agent_id	UUID	NULL, FOREIGN KEY (agents.id)
notification_enabled	BOOLEAN	DEFAULT TRUE
created_at	TIMESTAMP	NOT NULL, DEFAULT NOW()
updated_at	TIMESTAMP	NOT NULL, DEFAULT NOW()

Conversations & Messages

Table: conversations

Column	Type	Constraints
id	UUID	PRIMARY KEY
user_id	UUID	FOREIGN KEY (users.id)
title	VARCHAR(255)	NULL
created_at	TIMESTAMP	NOT NULL, DEFAULT NOW()
updated_at	TIMESTAMP	NOT NULL, DEFAULT NOW()
is_archived	BOOLEAN	NOT NULL, DEFAULT FALSE

INDEX: idx_conversations_user_id (user_id)

Table: messages

Column	Type	Constraints
id	UUID	PRIMARY KEY
conversation_id	UUID	FOREIGN KEY (conversations.id)
sender_type	VARCHAR(20)	NOT NULL
sender_id	UUID	NOT NULL
content	TEXT	NOT NULL
metadata	JSONB	NULL
created_at	TIMESTAMP	NOT NULL, DEFAULT NOW()

INDEX: idx_messages_conversation_id (conversation_id)

INDEX: idx_messages_created_at (created_at)

Analytics & System

Table: api_requests

Column	Type	Constraints
id	UUID	PRIMARY KEY
user_id	UUID	NULL, FOREIGN KEY (users.id)
endpoint	VARCHAR(255)	NOT NULL
method	VARCHAR(10)	NOT NULL
status_code	INTEGER	NOT NULL
request_time	TIMESTAMP	NOT NULL, DEFAULT NOW()
response_time	INTEGER	NOT NULL
ip_address	VARCHAR(45)	NULL
user_agent	VARCHAR(255)	NULL

INDEX: idx_api_requests_user_id (user_id)

INDEX: idx_api_requests_request_time (request_time)

Relationships

- 1. users 1
refresh_tokens
- 2. users 1:1 user_preferences
- 3. users 1
conversations
- 4. conversations 1
messages
- 5. users 1
api_requests

Note: Additional relationships will be added as other tables (agents, models, documents, etc.) are implemented in future iterations.