

How Bubble Sort Works?

We take an unsorted array for our example. Bubble sort takes $O(n^2)$ time so we're keeping it short and precise.




Bubble sort starts with very first two elements, comparing them to check which one is greater.



In this case, value 33 is greater than 14, so it is already in sorted locations. Next, we compare 33 with 27.



We find that 27 is smaller than 33 and these two values must be swapped.



The new array should look like this –



Next we compare 33 and 35. We find that both are in already sorted positions.



Then we move to the next two values, 35 and 10.



We know then that 10 is smaller 35. Hence they are not sorted.




We swap these values. We find that we have reached the end of the array. After one iteration, the array should look like this –




To be precise, we are now showing how an array should look like after each iteration. After the second iteration, it should look like this –



Notice that after each iteration, at least one value moves at the end.



And when there's no swap required, bubble sort learns that an array is completely sorted.



Now we should look into some practical aspects of bubble sort.

How Insertion Sort Works?

We take an unsorted array for our example.



Insertion sort compares the first two elements.



It finds that both 14 and 33 are already in ascending order. For now, 14 is in sorted sub-list.



Insertion sort moves ahead and compares 33 with 27.



And finds that 33 is not in the correct position.



It swaps 33 with 27. It also checks with all the elements of sorted sub-list. Here we see that the sorted sub-list has only one element 14, and 27 is greater than 14. Hence, the sorted sub-list remains sorted after swapping.



By now we have 14 and 27 in the sorted sub-list. Next, it compares 33 with 10.



These values are not in a sorted order.



So we swap them.



However, swapping makes 27 and 10 unsorted.



Hence, we swap them too.



Again we find 14 and 10 in an unsorted order.



We swap them again. By the end of third iteration, we have a sorted sub-list of 4 items.



This process goes on until all the unsorted values are covered in a sorted sub-list. Now we shall see some programming aspects of insertion sort.

How Insertion Sort Works?

We take an unsorted array for our example.



Insertion sort compares the first two elements.



It finds that both 14 and 33 are already in ascending order. For now, 14 is in sorted sub-list.



Insertion sort moves ahead and compares 33 with 27.



And finds that 33 is not in the correct position.



It swaps 33 with 27. It also checks with all the elements of sorted sub-list. Here we see that the sorted sub-list has only one element 14, and 27 is greater than 14. Hence, the sorted sub-list remains sorted after swapping.



By now we have 14 and 27 in the sorted sub-list. Next, it compares 33 with 10.



These values are not in a sorted order.



So we swap them.



However, swapping makes 27 and 10 unsorted.



Hence, we swap them too.



Again we find 14 and 10 in an unsorted order.



We swap them again. By the end of third iteration, we have a sorted sub-list of 4 items.



This process goes on until all the unsorted values are covered in a sorted sub-list. Now we shall see some programming aspects of insertion sort.

How Selection Sort Works?

Consider the following depicted array as an example.



For the first position in the sorted list, the whole list is scanned sequentially. The first position where 14 is stored presently, we search the whole list and find that 10 is the lowest value.




So we replace 14 with 10. After one iteration 10, which happens to be the minimum value in the list, appears in the first position of the sorted list.



For the second position, where 33 is residing, we start scanning the rest of the list in a linear manner.



We find that 14 is the second lowest value in the list and it should appear at the second place. We swap these values.



After two iterations, two least values are positioned at the beginning in a sorted manner.



The same process is applied to the rest of the items in the array.

Following is a pictorial depiction of the entire sorting process –

10	14	27	33	35	19	42	44
----	----	----	----	----	----	----	----

10	14	27	33	35	19	42	44
----	----	----	----	----	----	----	----

10	14	19	33	35	27	42	44
----	----	----	----	----	----	----	----

10	14	19	33	35	27	42	44
----	----	----	----	----	----	----	----

10	14	19	27	35	33	42	44
----	----	----	----	----	----	----	----

10	14	19	27	35	33	42	44
----	----	----	----	----	----	----	----

10	14	19	27	35	33	42	44
----	----	----	----	----	----	----	----

10	14	19	27	33	35	42	44
----	----	----	----	----	----	----	----

10	14	19	27	33	35	42	44
----	----	----	----	----	----	----	----

How Merge Sort Works?

To understand merge sort, we take an unsorted array as the following –



We know that merge sort first divides the whole array iteratively into equal halves unless the atomic values are achieved. We see here that an array of 8 items is divided into two arrays of size 4.



This does not change the sequence of appearance of items in the original. Now we divide these two arrays into halves.



We further divide these arrays and we achieve atomic value which can no more be divided.



Now, we combine them in exactly the same manner as they were broken down. Please note the color codes given to these lists.

We first compare the element for each list and then combine them into another list in a sorted manner. We see that 14 and 33 are in sorted positions. We compare 27 and 10 and in the target list of 2 values we put 10 first, followed by 27. We change the order of 19 and 35 whereas 42 and 44 are placed sequentially.



In the next iteration of the combining phase, we compare lists of two data values, and merge them into a list of found data values placing all in a sorted order.




After the final merging, the list should look like this –




Now we should learn some programming aspects of merge sorting.

How Shell Sort Works?


Let us consider the following example to have an idea of how shell sort works. We take the same array we have used in our previous examples. For our example and ease of understanding, we take the interval of 4. Make a virtual sub-list of all values located at the interval of 4 positions. Here these values are {35, 14}, {33, 19}, {42, 27} and {10, 44}




We compare values in each sub-list and swap them (if necessary) in the original array. After this step, the new array should look like this –



Then, we take interval of 1 and this gap generates two sub-lists - {14, 27, 35, 42}, {19, 10, 33, 44}



We compare and swap the values, if required, in the original array. After this step, the array should look like this –



Finally, we sort the rest of the array using interval of value 1. Shell sort uses insertion sort to sort the array.

Following is the step-by-step depiction –

