

Contents

- [2.b](#)
- [2.c](#)
- [Actuator](#)
- [Ideal model from 2\(a\)](#)
- [Summing junctions](#)
- [Generalized plant](#)
- [2.d](#)
- [bode plot of controller](#)
- [2.e with modified \$W_u\$](#)
- [Re-design controller with new \$W_u\$](#)
- [Bode plot of new controller](#)
- [New closed-loop system](#)
- [2.f Modified performance weight \$W_p\$](#)
- [Plot new performance weight](#)
- [Reset control penalty \$W_u\$ to original constant value](#)
- [H-infinity synthesis](#)
- [Closed-loop systems](#)
- [Simulate](#)
- [Plot response](#)
- [Plot elevator command](#)

```
A = [-2.4714 0.9514;  
     -43.9070 -3.4738];  
  
B = [-0.2501;  
     -44.9478];  
  
C = [0 1];  
D = 0;  
  
G = ss(A,B,C,D);  
  
p = eig(A);  
disp('Open-loop eigenvalues:')  
disp(p);  
  
sigma = real(p(1));  
wd     = imag(p(1));  
  
wn = sqrt(sigma^2 + wd^2)  
  
zeta_des = 0.8;  
  
pd1 = -zeta_des*wn + 1j*wn*sqrt(1-zeta_des^2);  
pd2 = conj(pd1);  
disp('Desired closed-loop poles:')  
disp(pd2);  
  
s = tf('s');
```

```

Aact = 31.42/(s + 31.42);

pdes = [pd1, pd2];

den_damp = poly(pdes);

% Choose gain to match original DC gain
G_tf = tf(G);

Kdc = dcgain(G_tf) * den_damp(end);

Gdamp = tf(Kdc, den_damp)

Gideal = minreal(Gdamp * Aact)

```

Open-loop eigenvalues:

```

-2.9726 + 6.4438i
-2.9726 - 6.4438i

```

wn =

```

7.0964

```

Desired closed-loop poles:

```

-5.6771 - 4.2578i

```

Gdamp =

```

      -100.1
-----
s^2 + 11.35 s + 50.36

```

Continuous-time transfer function.

Gideal =

```

      -3145
-----
s^3 + 42.77 s^2 + 407.1 s + 1582

```

Continuous-time transfer function.

2.b

```

pilot_cmd = 0.2618;
W_cmd = 1/pilot_cmd;

actuator_lim = 0.349;
d_max = actuator_lim * 0.15
W_dist = 1/d_max;

gyro_noise = 0.0067; %rad/s
W_noise = 1/gyro_noise;

model_err = 0.01; % <=0.01 rad/s
W_model = 1/model_err;

```

```
W_u = 1/actuator_lim;
```

```
d_max =  
  
0.0523
```

2.c

```
G.InputName = 'delta_actual';  
G.OutputName = 'q';
```

Actuator

```
Aact.InputName = 'delta_total';  
Aact.OutputName = 'delta_actual';
```

Ideal model from 2(a)

```
Gideal.InputName = 'pilot_actual';  
Gideal.OutputName = 'q_ideal';  
  
Wcmd_blk = tf(pilot_cmd);  
Wcmd_blk.InputName = 'Pilot';  
Wcmd_blk.OutputName = 'pilot_actual';  
  
Wd_blk = tf(d_max);  
Wd_blk.InputName = 'Dist';  
Wd_blk.OutputName = 'dist_actual';  
  
Wn_blk = tf(gyro_noise);  
Wn_blk.InputName = 'Noise';  
Wn_blk.OutputName = 'noise_actual';  
  
Wp_blk = tf(W_model);  
Wp_blk.InputName = 'e';  
Wp_blk.OutputName = 'z1';  
  
Wu_blk = tf(W_u);  
Wu_blk.InputName = 'delta_elev';  
Wu_blk.OutputName = 'z2';  
  
Wcmd_out = tf(W_cmd);  
Wcmd_out.InputName = 'pilot_actual';  
Wcmd_out.OutputName = 'z3';
```

Summing junctions

```
sum_delta = sumblk('delta_total = delta_elev + dist_actual');  
sum_error = sumblk('e = q - q_ideal');  
sum_meas = sumblk('q_meas = q + noise_actual');
```

Generalized plant

```
P = connect(G, Aact, Gideal, ...
    Wcmd_blk, Wd_blk, Wn_blk, Wp_blk, Wu_blk, ...
    sum_delta, sum_error, sum_meas, ...
    {'Pilot','Dist','Noise','delta_elev'}, ...
    {'z1','z2','pilot_actual','q_meas'});
```

2.d

```
nmeas = 2; % number of measurements
ncont = 1; % number of control inputs
[K,CL,gamma] = hinfsyn(P,nmeas,ncont);
disp('H-infinity optimal controller:')
disp(K)
disp('Closed-loop H-infinity norm:')
disp(gamma)
```

H-infinity optimal controller:
1x2 ss array with properties:

```
      A: [6x6 double]
      B: [6x2 double]
      C: [-9.8151 34.5776 -71.5020 0.5639 11.1905 217.4006]
      D: [0 0]
      E: []
  Offsets: []
    Scaled: 0
  StateName: {6x1 cell}
  StatePath: {6x1 cell}
  StateUnit: {6x1 cell}
InternalDelay: [0x1 double]
  InputDelay: [2x1 double]
OutputDelay: 0
   InputName: {2x1 cell}
   InputUnit: {2x1 cell}
InputGroup: [1x1 struct]
   OutputName: {' '}
   OutputUnit: {' '}
OutputGroup: [1x1 struct]
      Notes: [0x1 string]
   UserData: []
      Name: ''
        Ts: 0
   TimeUnit: 'seconds'
SamplingGrid: [1x1 struct]
```

Closed-loop H-infinity norm:
0.9026

code plot of controller

```
figure;
bode(K);
grid on;
title('H-infinity Controller Bode Plot');
saveCurrentFigure('1d_hinf_controller_bode');
```

```

K.InputName = {'pilot_actual','q'};
K.OutputName = 'delta_elev';

G.InputName = 'delta_actual';
G.OutputName = 'q';

Aact.InputName = 'delta_elev';
Aact.OutputName = 'delta_actual';

CL_q = connect(G,Aact,K, ...
    'pilot_actual', ...
    'q');

CL_u = connect(G,Aact,K, ...
    'pilot_actual', ...
    'delta_elev');

t = 0:0.01:20;
r = 0.2618*ones(size(t));

[y_cl,t] = lsim(CL_q,r,t);
[u_cmd,t] = lsim(CL_u,r,t);

[y_open,~] = lsim(minreal(G*Aact),r,t);
[y_ideal,~] = lsim(Gideal,r,t);

figure;
plot(t,y_open,'b','LineWidth',2); hold on;
plot(t,y_ideal,'k--','LineWidth',2);
plot(t,y_cl,'r','LineWidth',2);
grid on;
legend('Open-loop GA','Ideal','Closed-loop H_\infty');
xlabel('Time (sec)');
ylabel('Pitch rate q (rad/sec)');
title('Pitch Rate Response');
saveCurrentFigure('2d_pitch_rate_response');

figure;
plot(t,u_cmd,'LineWidth',2);
grid on;
xlabel('Time (sec)');
ylabel('Elevator command (rad)');
title('Elevator Command');
saveCurrentFigure('2d_elevator_command');


max(abs(u_cmd))

```


ans =


0.2622

H-infinity Controller Bode Plot




Pitch Rate Response





2.e with modified W_u

```
s = tf('s');  
  
Wu_bar = 1/0.349;  
Wu_new = Wu_bar*(s+20)/(0.01*s+20);  
  
Wu_new.InputName = 'delta_elev';  
Wu_new.OutputName = 'z2';  
  
figure;  
bodemag(Wu_new);  
grid on;  
title('Frequency-Dependent Control Weight W_u');  
saveCurrentFigure('2e_frequency_dependent_control_weight');
```



Re-design controller with new W_u

```
P_new = connect(G, Aact, Gideal, ...
    Wcmd_blk, Wd_blk, Wn_blk, Wp_blk, Wu_new, ...
    sum_delta, sum_error, sum_meas, ...
    {'Pilot','Dist','Noise','delta_elev'}, ...
    {'z1','z2','pilot_actual','q_meas'});

[K_new,CL_new,gamma_new] = hinfsyn(P_new,nmeas,ncont);

disp('H-infinity optimal controller with frequency-dependent W_u:')
disp(K_new)

disp('Closed-loop H-infinity norm with frequency-dependent W_u:')
disp(gamma_new)
```

Warning: The following block outputs are not used: delta_total.

H-infinity optimal controller with frequency-dependent W_u :

1x2 ss array with properties:

```

    A: [7x7 double]
    B: [7x2 double]
    C: [-0.2884 0.3247 -1.7280 0.0437 0.3369 2.1529 1.7941]
    D: [0 0]
    E: []
    Offsets: []
    Scaled: 0
    StateName: {7x1 cell}
    StatePath: {7x1 cell}
    StateUnit: {7x1 cell}
    InternalDelay: [0x1 double]
    InputDelay: [2x1 double]
    OutputDelay: 0
    InputName: {2x1 cell}
```



```

InputUnit: {2x1 cell}
InputGroup: [1x1 struct]
OutputName: {''}
OutputUnit: {''}
OutputGroup: [1x1 struct]
Notes: [0x1 string]
UserData: []
Name: ''
Ts: 0
TimeUnit: 'seconds'
SamplingGrid: [1x1 struct]

```


Closed-loop H-infinity norm with frequency-dependent W_u :
0.7501

Bode plot of new controller

```

figure;
bode(K_new);
grid on;
title("H-infinity Controller Bode Plot with Modified  $W_u$ ")
saveCurrentFigure('2e_hinf_controller_bode_modified_Wu');

```



New closed-loop system

```

Plant = minreal(Aact * G);

K_new.InputName = {'pilot_actual', 'q'};
K_new.OutputName = 'delta_elev';

G.InputName = 'delta_actual';
G.OutputName = 'q';

```

```

Aact.InputName = 'delta_elev';
Aact.OutputName = 'delta_actual';

CL_q = connect(G,Aact,K_new, ...
    'pilot_actual', ...
    'q');

CL_u = connect(G,Aact,K_new, ...
    'pilot_actual', ...
    'delta_elev');

t = 0:0.01:20;
r = 0.2618*ones(size(t));

[y_cl,t] = lsim(CL_q,r,t);
[u_cmd,t] = lsim(CL_u,r,t);

[y_open,~] = lsim(minreal(G*Aact),r,t);
[y_ideal,~] = lsim(Gideal,r,t);

figure;
plot(t,y_open,'b','LineWidth',2); hold on;
plot(t,y_ideal,'k--','LineWidth',2);
plot(t,y_cl,'r','LineWidth',2);
grid on;
legend('Open-loop GA','Ideal','Closed-loop H_\infty');
xlabel('Time (sec)');
ylabel('Pitch rate q (rad/sec)');
title('Pitch Rate Response');
saveCurrentFigure('2e_pitch_rate_response_modified_Wu');



figure;
plot(t,u_cmd,'LineWidth',2);
grid on;
xlabel('Time (sec)');
ylabel('Elevator command (rad)');
title('Elevator Command');
saveCurrentFigure('2e_elevator_command_modified_Wu');

max(abs(u_cmd))

```

ans =

0.2617



2.f Modified performance weight W_p

```
s = tf('s');


Wp_bar = W_model;           % from 2(b), e.g. 100 if error limit = 0.01
wc = 30;                    % crossover frequency rad/s

Wp_new = (0.01*s + Wp_bar*wc)/(s + wc);
```

```
Wp_new.InputName = 'e';
Wp_new.OutputName = 'z1';
```

Plot new performance weight

```
figure;
bodemag(Wp_new, Wp_blk);
grid on;
legend('Modified W_p','Constant W_p');
title('Performance Weight W_p: Constant vs Roll-off');
saveCurrentFigure('2f_performance_weight_Wp');
```



Reset control penalty Wu to original constant value

```
Wu_blk = tf(W_u);
Wu_blk.InputName = 'delta_elev';
Wu_blk.OutputName = 'z2';

P_f = connect(G, Aact, Gideal, ...
    Wcmd_blk, Wd_blk, Wn_blk, Wp_new, Wu_blk, ...
    sum_delta, sum_error, sum_meas, ...
    {'Pilot','Dist','Noise','delta_elev'}, ...
    {'z1','z2','pilot_actual','q_meas'});
```

Warning: The following block outputs are not used: delta_total.

H-infinity synthesis

```
nmeas = 2;
ncont = 1;
```

```

[K_f,CL_f,gamma_f] = hinfsyn(P_f,nmeas,ncont);

disp('H-infinity controller with modified W_p:')
disp(K_f)

disp('Closed-loop H-infinity norm with modified W_p:')
disp(gamma_f)

K_f.InputName = {'pilot_actual','q'};
K_f.OutputName = 'delta_elev';

G.InputName = 'delta_actual';
G.OutputName = 'q';

Aact.InputName = 'delta_elev';
Aact.OutputName = 'delta_actual';

```

H-infinity controller with modified W_p:
1x2 ss array with properties:

```

      A: [7x7 double]
      B: [7x2 double]
      C: [-6.1209 13.7674 -42.0086 0.5469 7.0477 87.7599 9.6615]
      D: [0 0]
      E: []
Offsets: []
Scaled: 0
StateName: {7x1 cell}
StatePath: {7x1 cell}
StateUnit: {7x1 cell}
InternalDelay: [0x1 double]
InputDelay: [2x1 double]
OutputDelay: 0
InputName: {2x1 cell}
InputUnit: {2x1 cell}
InputGroup: [1x1 struct]
OutputName: {''}
OutputUnit: {''}
OutputGroup: [1x1 struct]
Notes: [0x1 string]
UserData: []
Name: ''
Ts: 0
TimeUnit: 'seconds'
SamplingGrid: [1x1 struct]

```

Closed-loop H-infinity norm with modified W_p:
0.7501

Closed-loop systems

```

CL_q_f = connect(G,Aact,K_f, ...
    'pilot_actual', ...
    'q');

CL_u_f = connect(G,Aact,K_f, ...

```


```
'pilot_actual', ...  
'delta_elev');
```

Simulate

```
t = 0:0.01:20;  
r = 0.2618*ones(size(t));  
  
[y_cl_f,t] = lsim(CL_q_f,r,t);  
[u_cmd_f,t] = lsim(CL_u_f,r,t);  
  
[y_open,~] = lsim(minreal(G*Aact),r,t);  
[y_ideal,~] = lsim(Gideal,r,t);
```

Plot response

```
figure;  
plot(t,y_open,'b','LineWidth',2); hold on;  
plot(t,y_ideal,'k--','LineWidth',2);  
plot(t,y_cl_f,'r','LineWidth',2);  
grid on;  
legend('Open-loop GA','Ideal','Closed-loop  $H_{\infty}$  with modified  $W_p$ ');  
xlabel('Time (sec)');  
ylabel('Pitch rate q (rad/sec)');  
title('Pitch Rate Response with Modified  $W_p$ ');  
saveCurrentFigure('2f_pitch_rate_response_modified_Wp');
```



Plot elevator command

```
figure;  
plot(t,u_cmd_f,'LineWidth',2);  
grid on;
```

```
xlabel('Time (sec)');  
ylabel('Elevator command (rad)');  
title('Elevator Command with Modified W_p');  
saveCurrentFigure('2f_elevator_command_modified_Wp');  
  
disp("max actuator value with modified W_p:")  
max(abs(u_cmd_f))
```

max actuator value with modified W_p:

ans =

0.2617

