Softwarica
COLLEGE OF IT & E-COMMERCE

in collaboration with

Coventry University

ST7072CEM MACHINE LEARNING · COURSEWORK

Analysis and Prediction of Monsoon Hazards in Nepal Using Machine Learning Approaches

Will the monsoon hurt someone in this district in the next three days?

Bhimraj Yadav

Softwarica ID 260177 · Coventry ID 17624402

November 2026

BACKGROUND

Every monsoon costs lives and homes

2,561
deaths from 2017 to 2025

8,586
houses destroyed

56,379
families affected

AND IN 2026

The Bhotekoshi flood in Rasuwa (26 August) killed **more than 1,300** people, with thousands missing: more than 2021 to 2025 combined.

Deaths per year from floods, landslides, heavy rain and lightning




Chart: BIPAD disaster record, 2017 to 2025. 2026 flood: NDRRMA figures, 6 September 2026 (1,341 dead, 5,083 missing)

PROBLEM STATEMENT

Acting early needs a forecast of harm

THE POLICY

Release relief **before** a hazard strikes, on forecast triggers

WHAT IT NEEDS

A forecast of **which district** will be hurt, and **when**

WHAT EXISTS

Maps of **where** hazards can happen, not when

The gap: existing work does not forecast, district by district and day by day, whether the monsoon will cause a death, injury, missing person or destroyed house in Nepal.

Policy: NDRRMA, National Anticipatory Action Framework 2026, Government of Nepal

AIM AND OBJECTIVES


Can machine learning tell when and where monsoon harm will happen?

1. **Cluster** the 77 districts into risk regions with similar harm history and rain climate
2. **Classify** whether a district will suffer a damaging incident in the next three days
3. **Test** whether the regions improve the forecast, and explain what drives the risk

> If the forecast works, it can serve as a trigger for early relief.

DATASET

Built from open records and rain



Share of days followed by harm, by district

16,790

flood, landslide, heavy-rain and lightning records from BIPAD

146,223

district-days, April to October 2017 to 2025, with ERA5 rain

6.8%

followed by harm, so the classes are very unbalanced

> Harm rises with rain, from 3.3% of days in the driest tenth to 14.7% in the wettest. Features only use what was known on the day.

METHODS AND EXPERIMENTAL SETUP

Two stages, tested on unseen seasons

STAGE 1

Group districts

K-means, Ward and a Gaussian mixture find 6 risk regions

STAGE 2

Forecast harm

Logistic regression, random forest, gradient boosting, two SVMs

TEST


Beat the usual

Against climatology: each district’s normal rate for that month



RESULTS: RISK REGIONS


Six regions, each with its own pattern of harm



- **Eastern and inner Terai**
  Most lightning harm · 9 districts
- **Central and western Terai**
  Floods and heavy rain · 12 districts
- **Landslide-prone hills**
  Highest damage rate · 7 districts
- **Wet eastern hills and mountains**
  July landslide peak · 6 districts
- **Central hill belt**
  Includes Kathmandu valley · 23 districts
- **Dry far west and north-west**
  20 districts

RESULTS: FORECAST

A real gain, but only in one season



+0.026

mean PR-AUC gain over climatology in 2024 and 2025

Logistic regression, gradient boosting and linear SVM

DISCUSSION AND CONCLUSIONS

What each objective found

1 · Risk regions	Six regions, moderately stable, each with its own pattern of harm
2 · Forecast	Beats climatology by about 0.026 PR-AUC, but only in 2024
3 · Do regions help?	No. Knowing the next three days of rain would lift PR-AUC to about 0.21

A harm forecast for Nepal is possible, but its value depends on **better rain forecasts** and on testing it season by season.

CODE WALKTHROUGH

Now, the code

Python and Jupyter notebooks, from raw records to the results in the paper.

GITHUB REPOSITORY
bhimrazy/st7072cem-ml-assignment

01 **Set up and check**
Install the environment, run the leakage checks

02 **Build the data**
District-day panel, exploration, risk regions

03 **Train and evaluate**
Five classifiers, calibration, explanations

04 **See the results**
The season-by-season table and main figure

LIMITATIONS

BIPAD records reported harm, so reporting bias shapes the label

Lightning is the hardest hazard to forecast from daily rain

A live system would need rain forecasts, not observed rain

Thank you

github.com/bhimrazy/st7072cem-ml-assignment

Softwarica COLLEGE OF IT & E-COMMERCE | in collaboration with Coventry University

Bhimraj Yadav