Bhoomi Ramrakhiani
Batch: T23, Roll no: 2301095
Subject: ASD & D

Experiment 3: Deploying a Multi-Service Application

Using Docker Compose

1. Aim

To design, containerize, and deploy a multi-service web application consisting of a Frontend, a Backend, and a Database using Docker Compose, and to study service orchestration, intercontainer networking, and volume-based data persistence.

2. Theory

Docker is a platform that allows applications to be packaged with all their dependencies into standardized units called containers. A real-world application rarely consists of a single component - it typically has a presentation layer (frontend), a business logic layer (backend/API), and a data layer (database). Running each of these as a separate container and managing them individually using docker run commands is tedious and error-prone.

Docker Compose solves this problem by allowing all services of an application to be defined declaratively in a single YAML file (docker-compose.yml). With one command, docker compose up, Compose builds images, creates a private network, starts all containers in the correct order, and connects them together.

Key concepts used in this experiment:

- Service: A container definition (built from a Dockerfile or a base image) representing one component of the application.
- Image vs Build: 'image' pulls a ready-made image (e.g. mysql:8) from Docker Hub; 'build' compiles a custom image from a local Dockerfile.
- Networking: Compose automatically creates a bridge network. Containers can reach each other using the service name as the hostname (Docker's internal DNS), instead of IP addresses.
- Port Mapping: 'host_port:container_port' exposes a container's port to the host machine so it can be accessed from a browser.

- Volumes: Persistent storage that exists outside the container's lifecycle, so data (like database files) survives container restarts and recreation.
- depends_on: Controls the startup order of services, though it does not wait for the application inside the container to be fully ready.

3. Software / Tools Required


- Docker Engine (v20 or above)
- Docker Compose plugin (v2)
- A code editor (VS Code / nano)
- Web browser

4. System Architecture

The application follows a standard 3-tier architecture, with each tier running in its own container on a shared Docker bridge network defined in docker-compose.yml:


- Frontend: Nginx container serving a static HTML page (port 8080 on host).
- Backend: Node.js/Express REST API container that handles requests from the frontend and executes queries on the database (port 4000 on host).
- Database: MySQL 8 container that stores application data persistently using a named Docker volume (port 3306 on host).


5. Project Directory Structure



6. docker-compose.yml


This file defines all three services, their build context, exposed ports, environment variables, network, and the persistent volume for the database.



File Edit Selection View Go Run Terminal Help
Search [Administrator]
docker-compose.yml
C: > Users > 15L > multi-service-app > docker-compose.yml
Run All Services
Run Service
Run Service
Run Service
version: "3.9"
services:
frontend:
build: ./frontend
container_name: lab_frontend
ports:
- "8080:80"
depends_on:
- backend
networks:
- lab-network
backend:
build: ./backend
container_name: lab_backend
ports:
- "4000:4000"
environment:
DB_HOST: database
DB_USER: root
DB_PASSWORD: root123
DB_NAME: labdb
depends_on:
- database
networks:
- lab-network
database:
image: mysql:8
container_name: lab_database
restart: always
environment:
MYSQL_ROOT_PASSWORD: root123
MYSQL_DATABASE: labdb


File Edit Selection View Go Run Terminal Help
Search
docker-compose.yml
C: > Users > 15L > multi-service-app > docker-compose.yml
3 services:
15 backend:
27 networks:
28 - lab-network
29
Run Service
30 database:
31 image: mysql:8
32 container_name: lab_database
33 restart: always
34 environment:
35 MYSQL_ROOT_PASSWORD: root123
36 MYSQL_DATABASE: labdb
37 ports:
38 - "3306:3306"
39 volumes:
40 - db-data:/var/lib/mysql
41 networks:
42 - lab-network
43
44 networks:
45 lab-network:
46 driver: bridge
47
48 volumes:
49 db-data:
50
51

7. Backend Code (server.js)


The backend is a Node.js/Express application that connects to the database container using the hostname 'database' (the Compose service name), not 'localhost'. This demonstrates Docker's internal DNS-based service discovery.





8. Frontend Code (index.html)


The frontend is a static HTML page served by Nginx. It calls the backend's REST API from the browser to fetch data recorded in the database.



9. Steps Performed

Step 1: Verify Docker installation

```
docker --version docker
compose version
```



Step 2: Create the project folder structure

```
mkdir multi-service-app && cd multi-service-app mkdir frontend
backend
```

Step 3: Write Dockerfiles and application code


Created frontend/Dockerfile (Nginx base image), backend/Dockerfile (Node base image), and the application source files shown in Sections 7 and 8.

Step 4: Write docker-compose.yml

Defined the three services - frontend, backend, and database - along with a custom bridge network (lab-network) and a named volume (db-data) as shown in Section 6.

Step 5: Build and start all services

```
docker compose up –build
```




This command reads docker-compose.yml, builds the frontend and backend images from their Dockerfiles, pulls the mysql:8 image, creates the lab-network bridge network, creates the db-data volume, and starts all three containers.


Step 6: Verify all containers are running

```
docker compose ps
```

```
C:\Users\15L\Desktop\multi-service-app>docker compose ps
NAME            IMAGE                       COMMAND                  SERVICE    CREATED          STATUS          PORTS
lab_backend     multi-service-app-backend   "docker-entrypoint.s…"   backend    28 seconds ago   Up 27 seconds   0.0.0.0
:4000->4000/tcp
lab_database    mysql:8                     "docker-entrypoint.s…"   database   29 seconds ago   Up 27 seconds   33060/t
cp, 0.0.0.0:3307->3306/tcp
lab_frontend    multi-service-app-frontend  "/docker-entrypoint.…"   frontend   28 seconds ago   Up 27 seconds   0.0.0.0
:8081->80/tcp
```

Step 7: Test the application

- Opened http://localhost:8080 in a browser to view the frontend page.
- Clicked the 'Ping Backend + Database' button, which sent a request to http://localhost:4000/api/visits.
- The backend inserted a row into MySQL and returned the total visit count, confirming all three tiers were communicating correctly.
- 

- 

Step 8: Inspect logs and network

```
docker compose logs -f backend docker network
ls
docker network inspect multi-service-app_lab-network
```

Step 9: Stop and clean up

```
docker compose down        # stop and remove containers + network docker compose down -v     #
also remove the database volume
```

10. Observations

- All three containers (frontend, backend, database) started successfully with a single 'docker compose up' command.
- The backend was able to reach the database container using the service name 'database' as the hostname, confirming Docker Compose's built-in DNS-based service discovery.
- Data written to MySQL persisted across container restarts because it was stored in a named volume (db-data) rather than inside the container's writable layer.
- Running 'docker compose down -v' removed the volume and reset the visit counter to zero on the next run, confirming the role of volumes in data persistence.
- Port mapping allowed the host machine's browser to access services running inside isolated containers.

12. Docker Commands

COMMAND DESCRIPTION

DOCKER COMPOSE UP --BUILD	Builds images and starts all 3 services (frontend, backend, database)
DOCKER COMPOSE UP -D --BUILD	Same, but runs in the background (detached mode)
DOCKER COMPOSE DOWN	Stops and removes containers + network
DOCKER COMPOSE DOWN -V	Also deletes the volume (wipes MySQL data — fresh start)
DOCKER COMPOSE DOWN --REMOVE-ORPHANS	Cleans up leftover containers from old runs (we needed this once)
DOCKER COMPOSE PS	Lists our containers and their status (Up/Down, ports)
DOCKER COMPOSE LOGS -F	Streams logs from all services live

DOCKER COMPOSE LOGS -F BACKEND	Streams logs from just the backend (useful for debugging DB connection)
DOCKER COMPOSE BUILD	Rebuilds images without starting containers
DOCKER COMPOSE STOP / DOCKER COMPOSE START	Stops/starts existing containers without deleting them
DOCKER COMPOSE EXEC BACKEND SH	Opens a shell inside the running backend container (for debugging)
DOCKER NETWORK LS	Lists Docker networks, including the one Compose created
DOCKER NETWORK INSPECT MULTI-SERVICE-APP_LABNETWORK	Shows which containers are on our custom network
DOCKER COMPOSE VERSION	Confirms Compose is installed and shows the version

11. Conclusion

A multi-service application with a Frontend, Backend, and Database was successfully containerized and deployed using Docker Compose. The experiment demonstrated how Compose simplifies multi-container orchestration through a single declarative YAML file, how containers communicate over a custom bridge network using service names, and how named volumes provide persistent storage independent of container lifecycles. This confirms Docker Compose as an effective tool for developing, testing, and deploying multi-tier applications in a consistent and reproducible manner.