LAB-2

LAB:02 09/10/2024

EXPERIMENT:02



Aim: TO connect 2 PC's with 2 different routes using a router.

Topology: Connect 2 PC's to a router using 2 copper cross-over wires.

Procedure:
- Add 2 PC's and one generic router on the workspace
- Wire the PC's and IP address and default gateway.
- Let 1 PC be connected to the router through a copper cross over each.
- Click on the router, desktop and CLI commands and proceed with the following commands:

```
Router>enable
Router# config terminal
Router(config)# interface fastethernet 0/0
Router(config)# ip address 10.0.0.1 255.0.0.0
Router(config)# no shutdown
exit.
```

- Click on the PC → Desktop → Command Prompt.

```
ping 20.0.0.10
```

Observation:
- The buttons on the copper cross-over turned green.
- Packets were sent from one PC to the other
- PC received all packets.

Output:

Router# show ip route

C 10.0.0.0/8 is directly connected, FastEthernet 0/0

C 20.0.0.0/8 is directly connected, Fast Ethernet 1/0.

TOPOLOGY



```
PC>ping 30.0.0.1

Pinging 30.0.0.1 with 32 bytes of data:

Reply from 30.0.0.1: bytes=32 time=0ms TTL=255
Reply from 30.0.0.1: bytes=32 time=0ms TTL=255
Reply from 30.0.0.1: bytes=32 time=0ms TTL=255
Reply from 30.0.0.1: bytes=32 time=0ms TTL=255

Ping statistics for 30.0.0.1:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
Approximate round trip times in milli-seconds:
    Minimum = 0ms, Maximum = 0ms, Average = 0ms

PC>ping 30.0.0.2

Pinging 30.0.0.2 with 32 bytes of data:

Request timed out.
Request timed out.
Request timed out.
Request timed out.

Ping statistics for 30.0.0.2:
    Packets: Sent = 4, Received = 0, Lost = 4 (100% loss),

PC>ping 10.0.0.2
```

```
Packet Tracer PC Command Line 1.0
PC>ping 20.0.0.1

Pinging 20.0.0.1 with 32 bytes of data:

Reply from 10.0.0.2: Destination host unreachable.
Reply from 10.0.0.2: Destination host unreachable.
Reply from 10.0.0.2: Destination host unreachable.
Reply from 10.0.0.2: Destination host unreachable.

Ping statistics for 20.0.0.1:
    Packets: Sent = 4, Received = 0, Lost = 4 (100% loss),

PC>ping 10.0.0.2

Pinging 10.0.0.2 with 32 bytes of data:

Reply from 10.0.0.2: bytes=32 time=0ms TTL=255
Reply from 10.0.0.2: bytes=32 time=0ms TTL=255
Reply from 10.0.0.2: bytes=32 time=0ms TTL=255
Reply from 10.0.0.2: bytes=32 time=0ms TTL=255

Ping statistics for 10.0.0.2:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
Approximate round trip times in milli-seconds:
    Minimum = 0ms, Maximum = 0ms, Average = 0ms
```


Router1
Physical
Config
CLI
IOS Command Line Interface
%LINEPROTO-5-UPDOWN: Line protocol on Interface FastEthernet0/0, changed state to up
exit
Router(config)#interface serial 2/0
Router(config-if)#ip address 30.0.0.1 255.0.0.0
Router(config-if)#no shutdown
%LINK-5-CHANGED: Interface Serial2/0, changed state to down
Router(config-if)#exit
Router(config)#
%LINK-5-CHANGED: Interface Serial2/0, changed state to up
%LINEPROTO-5-UPDOWN: Line protocol on Interface Serial2/0, changed state to up
Router(config)#exit
Router#show ip route
Codes: C - connected, S - static, I - IGRP, R - RIP, M - mobile, B - BGP
D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area
N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
E1 - OSPF external type 1, E2 - OSPF external type 2, E - EGP
i - IS-IS, L1 - IS-IS level-1, L2 - IS-IS level-2, ia - IS-IS inter area
* - candidate default, U - per-user static route, o - ODR
P - periodic downloaded static route
Gateway of last resort is not set
C 10.0.0.0/8 is directly connected, FastEthernet0/0
C 30.0.0.0/8 is directly connected, Serial2/0
Router#

```
Pinging 20.0.0.1 with 32 bytes of data:

Request timed out.
Reply from 20.0.0.1: bytes=32 time=3ms TTL=126
Reply from 20.0.0.1: bytes=32 time=4ms TTL=126
Reply from 20.0.0.1: bytes=32 time=5ms TTL=126

Ping statistics for 20.0.0.1:
    Packets: Sent = 4, Received = 3, Lost = 1 (25% loss),
Approximate round trip times in milli-seconds:
    Minimum = 3ms, Maximum = 5ms, Average = 4ms

PC>ping 20.0.0.1

Pinging 20.0.0.1 with 32 bytes of data:

Reply from 20.0.0.1: bytes=32 time=5ms TTL=126
Reply from 20.0.0.1: bytes=32 time=1ms TTL=126
Reply from 20.0.0.1: bytes=32 time=1ms TTL=126
Reply from 20.0.0.1: bytes=32 time=1ms TTL=126

Ping statistics for 20.0.0.1:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
Approximate round trip times in milli-seconds:
    Minimum = 1ms, Maximum = 5ms, Average = 2ms
```