



DFM Rule Book

Every rule the engine judges a part against, by commodity

224 RULES · 35 PROCESS FAMILIES · 6 COMMODITY GROUPS

GENERATED 2026-08-10 · READ DIRECTLY FROM dfm-rule-catalogue.mjs

This book is generated from the catalogue the engine actually runs. Nothing on these pages was typed by hand, which means it cannot disagree with the tool: every threshold, comparison, citation and per-material override below is the value the analysis will use on your part.

Two figures travel with each rule that a checklist would leave out. The first is what the threshold rests on - a named standard, an industry consensus, or this tool's own cost model. The second is whether anyone has since gone and checked it. Where the answer is "not yet", the page says so.

118

HIGH SEVERITY

94

MEDIUM

12

LOW

137MATERIAL-SPECIFIC
THRESHOLDS**5**AUDITED TO A PRIMARY
SOURCE

WHAT THIS BOOK IS NOT

It is not a design standard. Most of these thresholds are widely-published practice rather than a clause anyone here has read in the original document, and 3 are actively contested - those are named in Appendix B. Where your plant has its own number, it outranks everything in this book, and the tool lets you set it. It is also not a complete list of what matters: Appendix A sets out 15 things the engine deliberately does not claim to check.

THE SIX COMMODITY GROUPS

Castings

89 RULES 10 PROCESSES

High-pressure die casting (Al / Mg) - High-pressure die casting (Zinc) - Low-pressure die casting - Gravity die casting - Squeeze casting - Semi-solid casting (thixo / rheo) - Sand casting - Shell mould casting - Investment casting - Centrifugal casting

Sheet metal and forming

42 RULES 7 PROCESSES

Sheet metal / stamping - Deep drawing (multi-stage) - Fine blanking - Hot stamping / press hardening - Roll forming - Hydroforming - Metal spinning

Forging and bulk forming

25 RULES 5 PROCESSES

Forging (hot) - Forging (cold) - Open-die forging - Cold heading / upsetting - Extrusion

Machining and material removal

24 RULES 5 PROCESSES

Machining (CNC mill/turn) - Turning (CNC lathe) - Deep-hole / gun drilling - Broaching - Wire EDM

Polymers, rubber and composites

29 RULES 5 PROCESSES

Injection moulding - Rubber moulding - Thermoforming (vacuum / pressure) - Rotational moulding - Composite layup / RTM

Powder and additive

15 RULES 3 PROCESSES

Powder metallurgy (press & sinter) - Metal injection moulding (MIM) - Laser powder bed fusion (DMLS / SLM)

How to read this book

A rule has three outcomes, not two

PASS	the measurement was taken and it is inside the limit.
FAIL	the measurement was taken and it is outside the limit. This is a finding.
NOT EVALUATED	the geometry needed for the measurement was not present or could not be read. The rule is reported with the reason, and it is NOT counted as a pass. A report that lists only failures invites you to assume everything else was checked.

Anatomy of an entry

```

wallP50Mm in 1 to 3 mm
im-wall-thickness-range

```

The grey line is the test itself, in the engine's own terms: the name of the measurement taken from your CAD, the comparison, the threshold and its unit. Below it is the rule id, which is what appears in the analysis output and in the Excel export - quote it if you want to challenge a result. Everything after that is prose: why the limit exists, what to do about it, and where the number came from.

Which threshold applies to your part

The number printed at the head of an entry is the process-generic one. Many rules carry a stricter or looser value for a specific alloy or material family, and those are listed underneath. The engine resolves them in this order, and stops at the first match:

- 1 Your company standard** a value set in your workspace. It outranks every published guideline, and the report credits it to you rather than to a handbook.
- 2 The exact material grade** e.g. the row for DP980 rather than for steel generally.
- 3 The material family** e.g. aluminium, titanium, thermoplastic.
- 4 The process-generic value** the headline number in this book.

How "best first" was decided

Rules are ordered within every commodity by the composite below, and the leaderboard in Chapter 1 uses the same figure across the whole catalogue. It is printed here in full because a ranking with a hidden formula is an opinion in a lab coat - every term is something you can check from the entry itself.

```

3 x severity          high 3   medium 2   low 1
2 x source strength  named standard 3   industry consensus 2   own cost model 1
+ 2                  carries per-GRADE thresholds (a number tuned to your alloy)
+ 1                  carries per-FAMILY thresholds
+ 2                  the cost engine can put a currency figure on the finding
+ 2                  blocking (the part cannot be made by this route at all)
- 3                  the threshold is contested in the audit register

```

A high score means the rule is severe, well-sourced, tuned to your material and priced. It does not mean it will fire on your part - that depends on whether the geometry carries the feature it measures.

By commodity

Chapter 1 - The highest-ranked rules across the whole catalogue		04
Castings	89 rules	05
High-pressure die casting (Al / Mg)	12	05
High-pressure die casting (Zinc)	13	08
Low-pressure die casting	11	11
Gravity die casting	13	13
Squeeze casting	6	16
Semi-solid casting (thixo / rheo)	6	18
Sand casting	10	19
Shell mould casting	5	21
Investment casting	10	23
Centrifugal casting	3	25
Sheet metal and forming	42 rules	27
Sheet metal / stamping	12	27
Deep drawing (multi-stage)	5	30
Fine blanking	6	31
Hot stamping / press hardening	5	33
Roll forming	6	34
Hydroforming	5	35
Metal spinning	3	37
Forging and bulk forming	25 rules	38
Forging (hot)	6	38
Forging (cold)	5	39
Open-die forging	5	40
Cold heading / upsetting	3	42
Extrusion	6	43
Machining and material removal	24 rules	45
Machining (CNC mill/turn)	7	45
Turning (CNC lathe)	5	47
Deep-hole / gun drilling	4	48
Broaching	4	49
Wire EDM	4	50
Polymers, rubber and composites	29 rules	52
Injection moulding	9	52
Rubber moulding	6	54
Thermoforming (vacuum / pressure)	4	55
Rotational moulding	4	56
Composite layup / RTM	6	57
Powder and additive	15 rules	59
Powder metallurgy (press & sinter)	6	59
Metal injection moulding (MIM)	5	60
Laser powder bed fusion (DMLS / SLM)	4	61
Appendix A - What this book does not check		63
Appendix B - Threshold audit register		65

The 40 highest-ranked rules

Across all 35 process families, by the composite on the previous page. If you read nothing else, read these: they are the severe, well-sourced, material-aware checks. Each is repeated in full in its own commodity chapter.

#	RULE	COMMODITY / PROCESS	TEST	SCORE
01	Wall thickness outside the practical moulding range	Injection moulding	1-3 mm	17
02	Too deep to draw in one operation	Deep drawing (multi-stage)	≤ 0.75 depth/width	15
03	Cup too deep for the drawing-ratio table	Deep drawing (multi-stage)	≤ 0 beyond the table (1...	15
04	Tolerance tighter than injection moulding holds	Injection moulding	≥ 0.2 mm total band	15
05	Tolerance tighter than roll forming holds	Roll forming	≥ 0.6 mm total band	15
06	Strip utilisation below the industry target	Sheet metal / stamping	≥ 70 % of strip area	15
07	Tolerance tighter than sheet metal / stamping holds	Sheet metal / stamping	≥ 0.4 mm total band	15
08	Wall thinner than the die can hold	Extrusion	≥ 1 mm	14
09	Section is not uniform enough for the die to run b...	Extrusion	≤ 0.35 (p95-p5)/p50	14
10	Web too thin for the forming load available	Forging (cold)	≥ 1.5 mm	14
11	Wall area below the minimum hot-forging draft	Forging (hot)	≤ 5 % of wall area	14
12	Web too thin to forge	Forging (hot)	≥ 3 mm	14
13	Tolerance tighter than forging holds	Forging (hot)	≥ 1 mm total band	14
14	Wall area below the minimum gravity die-casting...	Gravity die casting	≤ 5 % of wall area	14
15	Local section below the process minimum	Gravity die casting	≥ 2.5 mm	14
16	Wall thickness outside the gravity die-casting range	Gravity die casting	3-8 mm	14
17	Non-uniform wall thickness	Gravity die casting	≤ 0.7 (p95-p5)/p50	14
18	Cored hole beyond the core-pin slenderness limit	High-pressure die casting (Al / M...	≤ 10 core L/D	14
19	Corner radius too tight for the forming pressure a...	Hydroforming	≥ 3 r/t	14
20	Rib too thick at its base for the wall it stands on	Injection moulding	≤ 0.6 rib t / wall t	14
21	Local section below the process minimum	Investment casting	≥ 1.2 mm	14
22	Wall thickness outside the investment-casting ra...	Investment casting	1.5-6 mm	14
23	Thin web will chatter or deflect under the cutter	Machining (CNC mill/turn)	≥ 1.5 mm	14
24	Tolerance tighter than machining holds	Machining (CNC mill/turn)	≥ 0.05 mm total band	14
25	Wall area below the minimum sand-casting draft	Sand casting	≤ 5 % of wall area	14
26	Local section below the process minimum	Sand casting	≥ 3.5 mm	14
27	Tolerance tighter than sand casting holds	Sand casting	≥ 1.2 mm total band	14
28	Wall thickness outside the sand-casting range	Sand casting	4-12 mm	14
29	Inside bend radius below one material thickness	Sheet metal / stamping	≥ 1 r/t	14
30	Hole too deep to broach	Broaching	≤ 5 depth/dia	13
31	Blind features cannot be broached	Broaching	≤ 0 blind features	13
32	Part is not a body of revolution	Centrifugal casting	≥ 90 % of surface area	13
33	Tolerance tighter than centrifugal casting holds	Centrifugal casting	≥ 0.5 mm total band	13
34	Tolerance tighter than cold heading holds	Cold heading / upsetting	≥ 0.2 mm total band	13
35	Undercuts cannot be ejected from a heading die	Cold heading / upsetting	≤ 0 regions	13
36	Head too tall to upset in one blow	Cold heading / upsetting	≤ 2.5 upset L/D	13
37	Tolerance tighter than deep drawing holds	Deep drawing (multi-stage)	≥ 0.5 mm total band	13
38	Undercuts cannot be drawn off the punch	Deep drawing (multi-stage)	≤ 0 regions	13
39	Profile too large for a general-purpose press	Extrusion	≤ 203 mm CCD	13
40	Tolerance tighter than extrusion holds	Extrusion	≥ 0.5 mm total band	13

Metal poured or injected into a mould. The shared enemies are draft, wall uniformity, section transitions and anything that traps the pattern or the core.

89 RULES · 10 PROCESSES · 37 HIGH / 44 MEDIUM / 8 LOW · 17 CARRY MATERIAL-SPECIFIC THRESHOLDS

High-pressure die casting (Al / Mg)

12 RULES

01 Cored hole beyond the core-pin slenderness limit

HIGH

```
maxHoleDepthToDia <= 10 core L/D
hpdc-core-ld
```

A cored hole is a steel pin standing in the die with molten aluminium injected around it at speed. Beyond about 10:1 the pin deflects under that pressure, the hole drifts, and the pin becomes a consumable that breaks mid-run and stops the cell.

FIX Shorten the cored depth and drill the rest, open the diameter, or core from both ends so each pin is half the length.

SOURCE Die-casting design guidance (core pin L/D <= 10:1 for aluminium).

INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · CORROBORATED BY SEARCH

BY MATERIAL FAMILY

<= 12 magnesium

02 Wall area below the minimum die-casting draft

HIGH

```
wallAreaBelowDraftPct <= 5 % of wall area
hpdc-draft-minimum · measured only on faces below 1 deg
```

Aluminium shrinks onto the die steel as it solidifies, so a die casting needs more draft than a moulding. Insufficient draft galls the die surface and shortens die life as well as risking ejector distortion.

FIX Allow 1 to 2 degrees on external walls and 2 to 3 degrees on internal walls and cores; use 3 to 5 degrees on deep features.

SOURCE NADCA Product Specification Standards, S-4A-7 (Draft Constants). NADCA standard tolerances give 1 deg minimum on outside surfaces and 2 deg on inside; the 1 deg threshold used here is the outside-wall figure. Designation and values corroborated from secondary summaries – the standard itself is paywalled and has NOT been read.

NAMED STANDARD, NOT READ FIRST-HAND · CONTESTED - SEE APPENDIX B

BY MATERIAL FAMILY

<= 8 magnesium

03 Tolerance tighter than high-pressure die casting holds

HIGH

```
tightestToleranceMm >= 0.2 mm total band
hpdc-tolerance-capability
```

As-cast linear tolerance is about +/-0.1 mm on a small dimension and grows with size. Anything tighter is machined after casting, which means a fixture, a datum scheme and a second cost centre.

FIX Open the as-cast tolerance and machine only the features that need to be accurate, with the datums declared.

SOURCE NADCA Product Specification Standards, linear dimensional tolerances (as-cast).

INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED

04 Undercuts require slides or lifters in the die

HIGH

```
undercutFaceCount <= 0 regions  
hpdc-undercuts
```

A die-cast undercut needs a slide or a loose core. Both add die cost and maintenance, and a loose core adds a manual handling step to every shot.

FIX Reorient the part to the draw, move the parting line, or price the slide explicitly.

SOURCE Die casting tool design: the die opens along one axis, so a re-entrant feature needs a slide or a lifter – a cam mechanism, its wear parts and the cycle time to move it. Derived from the process, not quoted from a design guide.

INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED

05 Wall thickness outside the die-casting range

HIGH

```
wallP50Mm in 1 to 3.5 mm  
hpdc-wall-thickness-range · PRICED BY THE COST ENGINE
```

Below about 1 mm the die will not fill reliably and cold shuts appear; above about 3.5 mm the section traps porosity as it solidifies and holds the cycle open.

FIX Hold a uniform nominal wall in the 2.0–3.5 mm band and core out heavy sections.

SOURCE Aluminium HPDC design guidance (1.0 mm minimum, 2.0–3.5 mm recommended). Widely published and mutually consistent across die-casting suppliers; NOT audited against NADCA or a foundry standard.

INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · CONTESTED - SEE APPENDIX B

BY MATERIAL FAMILY

1.5-4 aluminium

1.3-3.5 magnesium

06 Cored holes below the core-pin draft

MEDIUM

```
coredHoleDraftPerSideDeg >= 2 deg per side  
hpdc-cored-hole-draft
```

A casting shrinks ONTO a core pin rather than away from it, so a cored hole needs more draft than an outside wall, not the same. A pin that binds galls, deflects and puts the hole off position; a bound pin in a deep hole can pull the casting off the ejector side.

FIX Take cored holes to 2 degrees per side. Where the hole must be parallel, drill it after casting and cost the secondary operation rather than fighting the pin.

SOURCE NADCA Product Specification Standards, S-4A-7 (Draft Constants): cored holes take roughly 2 deg per side against 1 deg on outside walls. Corroborated from secondary summaries – the standard itself is paywalled and has NOT been read first-hand.

NAMED STANDARD, NOT READ FIRST-HAND · CORROBORATED BY SEARCH

07 Hole too small to be cast — it will be drilled

MEDIUM

```
minHoleDiaMm >= 2.5 mm dia  
hpdc-min-cored-hole
```

The hole is made by a steel pin standing in the die, taking the full shot pressure on every cycle. Below roughly 2.5 mm in aluminium the pin is too slender to survive production — it soldiers, bends and eventually snaps — and unsupported pins under about 1.5 mm are not run at all. The feature does not disappear from the part; it moves to the drill, and a drilling operation nobody costed is a piece price nobody predicted.

FIX Open the hole to at least 2.5 mm to cast it, or delete it from the casting and quote it as a drilled feature so the secondary operation is in the price from the start.

SOURCE Die casting core-pin design guidance: unsupported core pins below about 1.5 mm are avoided or reinforced; the practical as-cast aluminium hole floor sits above that at roughly 2.5 mm. Consistent across supplier design guides; no primary standard audited.

INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED

BY MATERIAL GRADE

>= 2 Magnesium AZ91D (die-cast)

08 Rib heavier than the wall it stands on

MEDIUM

```
maxRibThicknessToWall <= 0.8 rib t / wall t  
hpdc-rib-thickness-max · PRICED BY THE COST ENGINE
```

A rib approaching the full wall thickness makes the junction the thickest section in the casting. That is where shrinkage porosity collects, and it holds the die open while it solidifies.

FIX Bring the rib base to roughly 60–80% of the adjoining wall and fillet the root rather than thickening it.

SOURCE Die-casting design guidance (rib base ~60–80% of the adjoining wall).

INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED

09 Rib taller than three wall thicknesses

MEDIUM

```
maxRibHeightToWall <= 3 rib h / wall t  
hpdc-rib-height
```

A deep rib is a deep, narrow blade of die steel. It runs hotter than the rest of the die, heat-checks first, and is the feature most likely to break out in service; the casting also grips it hard on ejection.

FIX Limit rib height to about 3x the wall, or split one deep rib into several shallower ones and increase the draft on what remains.

SOURCE Die-casting design guidance (rib height $\leq 3 \times$ wall; deep ribs need 3–5 deg draft).

INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED

BY MATERIAL FAMILY

≤ 4 magnesium

10 Rib too thin to fill before it freezes

MEDIUM

```
minRibThicknessToWall >= 0.6 rib t / wall t  
hpdc-rib-thickness-min
```

Aluminium loses superheat fast in a thin section. A rib much below 60% of the wall chills before the cavity is full and leaves a cold shut at the rib tip — a crack starter, not just a cosmetic defect.

FIX Thicken the rib toward 60–80% of the wall, or shorten it so the flow path to its tip is shorter.

SOURCE Die-casting design guidance (rib base ~60–80% of the adjoining wall).

INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED

BY MATERIAL FAMILY

≥ 0.5 magnesium

11 Sharp internal corners concentrate stress and restrict flow

MEDIUM

```
minInternalCornerRadiusMm >= 1.6 mm  
hpdc-internal-radius
```

A sharp internal corner is a hot spot in the casting and a stress raiser in the die, where it becomes the first place a heat-check crack starts.

FIX Fillet internal corners to at least 1.5 times the adjacent wall thickness, and never below about 1.6 mm.

SOURCE Die-casting design guidance (minimum ~1.6 mm fillet; 1.5x wall preferred). Industry consensus, no primary source audited.

INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED



12 Non-uniform wall thickness

MEDIUM

```
wallSpreadRatio <= 0.6 (p95-p5)/p50  
hpdc-wall-uniformity
```

A heavy section next to a thin one is the last place to freeze and has no feed path once the gate has solidified, so it draws shrinkage porosity. It also distorts the casting as the two sections contract at different times.

FIX Core out the heavy sections to a uniform nominal wall and blend the transitions rather than stepping them.

SOURCE Die-casting design guidance (uniform section thickness; heavy sections trap shrinkage porosity).

INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED

High-pressure die casting (Zinc)

13 RULES

01 Local section below the process minimum

HIGH

```
wallP5Mm >= 0.5 mm  
hpdc-zinc-min-section
```

Zinc fills thinner than any other die-cast alloy, and 0.5 mm is roughly where even zinc stops. A local web thinner than the nominal wall is where a short shot starts.

FIX Thicken the thinnest region, or move the feature to where the section is already full.

SOURCE Process minimum-section guidance. Checked on the 5th-percentile wall, which is the thinnest measured place rather than the nominal.

INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED

02 Tolerance tighter than high-pressure die casting holds

HIGH

```
tightestToleranceMm >= 0.15 mm total band  
hpdc-zinc-tolerance-capability
```

Zinc holds tighter as-cast tolerances than aluminium because it runs cooler and shrinks less onto the die — about +/-0.075 mm on a small dimension. That accuracy is one of the reasons to choose the alloy.

FIX Take advantage of the alloy: hold the tolerance as-cast rather than adding a machining operation.

SOURCE Zinc die-casting dimensional tolerance guidance (tighter than aluminium by roughly a third).

INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED

03 Wall thickness outside the zinc die-casting range

HIGH

```
wallP50Mm in 0.6 to 3 mm  
hpdc-zinc-wall-thickness-range
```

Zinc runs at a far lower melting point than aluminium in a hot-chamber machine, so it fills sections aluminium cannot — 0.6 mm is routine and 0.4 mm is achievable on small parts. That thinness is the reason to choose zinc at all. Above about 3 mm the section is heavy, slow to freeze and porous, and the material cost of a dense alloy starts to dominate.

FIX Take advantage of the alloy: thin the nominal wall towards 1.0-1.5 mm and add ribs for stiffness. A zinc part left at an aluminium wall is paying for metal it does not need.

SOURCE Zinc hot-chamber die-casting design guidance (ZAMAK): 0.6 mm practical minimum, 1.0-2.0 mm typical nominal.

INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED

04 Boss taller than the core pin can hold

MEDIUM

```
maxBossHeightToDia <= 4 height/dia  
hpdc-zinc-boss-height
```

A tall boss is cored by a pin standing in the flow, and the taller it is the more it deflects and the sooner it erodes. Zinc is kinder to pins than aluminium but the geometry still governs.

FIX Shorten the boss, widen it, or support it with ribs to its base.

SOURCE Die casting boss guidance: a boss is cored by a pin standing in the die and the same slenderness argument applies as to a cored hole, with zinc holding the finest pins of the die-casting alloys. The 4:1 figure sits above the aluminium core-pin limit used elsewhere in this catalogue because a boss pin is supported by the surrounding cavity where a through-core pin is not. DERIVED from that ordering; no primary standard audited.

INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED

05 Cored hole beyond the core-pin slenderness limit

MEDIUM

```
maxHoleDepthToDia <= 12 core L/D  
hpdc-zinc-core-ld
```

A cast hole is made by a steel pin standing in the flow. Zinc enters cooler than aluminium, so the pin survives a longer reach before it bends or erodes, but a slender pin is still the first thing in the die to fail.

FIX Shorten the cored hole, open its diameter, or cast it partly and drill the rest.

SOURCE Zinc die-casting design guidance (core-pin length-to-diameter limits).

INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED

06 Cored holes below the core-pin draft

MEDIUM

```
coredHoleDraftPerSideDeg >= 1 deg per side  
hpdc-zinc-cored-hole-draft
```

Zinc shrinks onto the pin less than aluminium and releases more readily, so the cored-hole figure is about half the aluminium one — but it is still larger than the wall figure for the same reason.

FIX Take cored holes to 1 degree per side in zinc.

SOURCE Zinc die-casting design guidance: draft constants roughly half the aluminium values, cored holes drafted more than walls. Same family of secondary sources as the zinc wall rule.

INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED

07 Wall area below the minimum zinc die-casting draft

MEDIUM

```
wallAreaBelowDraftPct <= 5 % of wall area  
hpdc-zinc-draft-minimum · cutoff 0.5 deg
```

Zinc shrinks onto the die much less than aluminium and runs cooler, so it strips with about half the draft. Half a degree on an external wall is normal practice and holding an aluminium part's 1-2 degrees on a zinc part gives away dimensional accuracy for nothing.

FIX Allow 0.5 degrees on external walls and 1 degree on internal walls and cores.

SOURCE Zinc die-casting design guidance (draft constants roughly half the aluminium values).

INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED

08 Hole too small to be cast — it will be drilled

MEDIUM

```
minHoleDiaMm >= 1.5 mm dia  
hpdc-zinc-min-cored-hole
```

Zinc runs cooler and thinner than aluminium and is the least aggressive of the die-casting alloys on tooling, so a hot-chamber die will hold a finer core pin than an aluminium die will. It will not hold an arbitrarily fine one: below about 1.5 mm the pin is unsupported steel in a pressurised cavity and breaks.

FIX Open the hole to at least 1.5 mm, or move it to a drilling operation and cost that operation.

SOURCE Die casting core-pin design guidance: avoid unsupported cores below about 1.5 mm diameter, or reinforce them. Zinc is the alloy this floor is most nearly achievable in. No primary standard audited.

INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED

09 Rib heavier than the wall it stands on

MEDIUM

```
maxRibThicknessToWall <= 1 rib/wall  
hpdc-zinc-rib-thickness-max
```

Zinc fills thin ribs readily, which is why zinc parts are ribbed rather than thick. A rib heavier than the wall wastes that advantage and slows the cycle.

FIX Thin the rib, or add two thinner ribs instead of one heavy one.

SOURCE Casting rib-proportion guidance (rib thickness against nominal wall).

INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED

10 Rib too thin to fill before it freezes

MEDIUM

```
minRibThicknessToWall >= 0.5 rib/wall  
hpdc-zinc-rib-thickness-min
```

A rib is the last thing to fill and the first thing to freeze, because it presents the most surface for its volume. Below this fraction of the nominal wall it will not fill reliably.

FIX Thicken the rib towards the process minimum, or shorten it so the metal has less distance to travel.

SOURCE Casting rib-proportion guidance (fill limit against nominal wall).

INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED

11 Undercuts require slides or lifters in the die

MEDIUM

```
undercutFaceCount <= 0 regions  
hpdc-zinc-undercuts
```

An undercut needs a slide or a loose core, which adds die cost and maintenance. Zinc dies carry slides more readily than aluminium dies because the alloy is far kinder to the tooling, so this is a cost question rather than a feasibility one.

FIX Re-orient the part on the parting line, or split the feature so it forms between the two die halves.

SOURCE Die-casting design guidance (side actions and loose cores).

INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED

12 Non-uniform wall thickness

MEDIUM

```
wallSpreadRatio <= 0.6 (p95-p5)/p50  
hpdc-zinc-wall-uniformity
```

A heavy section beside a thin one is the last place to freeze and has no feed path once the gate solidifies, so it draws shrinkage porosity and distorts as the two sections contract at different times.

FIX Core out the heavy sections to a uniform nominal wall and blend the transitions rather than stepping them.

SOURCE Die-casting design guidance (uniform section thickness).

INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED

13 Rib taller than the wall can support

LOW

```
maxRibHeightToWall <= 5 rib height/wall  
hpdc-zinc-rib-height
```

A tall rib must fill against die chilling along its whole length, and it also concentrates stress at its base where the section changes.

FIX Reduce the rib height, or use more shorter ribs and generous base fillets.

SOURCE Casting rib-proportion guidance (height against nominal wall).

INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED

Low-pressure die casting

11 RULES

01 Wall area below the minimum permanent-mould draft

HIGH

```
wallAreaBelowDraftPct <= 5 % of wall area  
lpdc-draft-minimum · cutoff 1 deg
```

The part shrinks onto a steel mould as it solidifies under pressure. Without taper it grips, and the ejectors either mark the face or tear it.

FIX Add at least 1° of draft to every drawn wall, 2-3° on deep or cosmetic faces.

SOURCE Permanent-mould design guidance: minimum draft about 1°, with 2-3° generally recommended and 2° specified on box-section walls perpendicular to the parting plane. No primary standard audited.

INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED

02 Local section below what a low-pressure fill reaches

HIGH

```
wallP5Mm >= 2 mm  
lpdc-min-section
```

Low-pressure filling is slow and bottom-fed, which is what makes it clean — and also what limits it. Below about 2 mm the front freezes before the section is full and the result is a misrun or a cold shut, the two defects the process is otherwise chosen to avoid.

FIX Thicken the section to at least 2 mm, or move the part to high-pressure die casting, which fills a 1.0-1.5 mm wall.

SOURCE Low-pressure die casting is quoted at 2.0-3.0 mm thin-wall capability, against gravity die casting requiring 3 mm and up, where cold shuts and misruns appear at 4 mm. Consistent across process-comparison guides; no primary standard audited.

INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED

03 Tolerance tighter than low-pressure die casting holds

HIGH

```
tightestToleranceMm >= 0.6 mm total band  
lpdc-tolerance-capability
```

Low-pressure die casting is the most accurate of the permanent-mould routes — ISO 8062 CT6-CT7 against gravity's CT7-CT9 — but it is still a casting. A band tighter than about 0.6 mm total is a machining requirement, and the stock for it has to be on the part.

FIX Open the tolerance, or add machining stock on that feature and quote the operation.

SOURCE Low-pressure die casting quoted at ISO 8062 CT6-CT7 and ± 0.3 mm, against gravity die casting at CT7-CT9. Consistent across process-comparison guides; no primary standard audited.

INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED

04 Non-uniform wall thickness

HIGH

```
wallSpreadRatio <= 0.7 (p95-p5)/p50  
lpdc-wall-uniformity
```

The held pressure feeds shrinkage from the fill tube upward, so a heavy section ABOVE a thin one is cut off from its own feed path and shrinks into porosity. Uniformity matters more here than in gravity casting, not less, because the feed direction is fixed by the process.

FIX Even out the section, or re-orient the part so heavy sections sit low, nearest the fill tube.

SOURCE Casting design guidance on uniform wall thickness and gradual transitions, applied to a bottom-fed directional-solidification process. No primary standard audited.

INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED

05 Hole too small to be cast — it will be drilled

MEDIUM

```
minHoleDiaMm >= 6 mm dia  
lpdc-min-cored-hole
```

The core hardware is the same steel-in-a-permanent-mould as gravity die casting, and 0.3-1.5 bar is not the 500-1000 bar that lets high-pressure die casting run a finer pin. The permanent-mould floor applies unchanged: 6 mm, parallel to the draw.

FIX Open the hole to at least 6 mm and align it with the draw, or quote it as drilled.

SOURCE Permanent-mould (gravity and low-pressure die) design guidance, citing NADCA: minimum cored hole diameter 6.0 mm, parallel to the direction of draw. The standard is NAMED by the design guide; the NADCA document itself has not been read first-hand.

NAMED STANDARD, NOT READ FIRST-HAND · NOT YET AUDITED

06 Cored hole beyond the core slenderness limit

MEDIUM

```
maxHoleDepthToDia <= 6 core L/D  
lpdc-core-ld
```

Past about six diameters a core pin deflects under the metal front and the hole walks off position, taking the wall around it eccentric with it.

FIX Open the diameter, shorten the hole, or support the pin at both ends by taking it through.

SOURCE Die casting core-pin guidance: past an L/D of 6:1 deflection risk rises sharply and additional support, a larger diameter or reduced local pressure is needed. No primary standard audited.

INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED

07 Cored holes below the core draft

MEDIUM

```
coredHoleDraftPerSideDeg >= 2 deg per side  
lpdc-cored-hole-draft
```

Low-pressure filling is gentler than HPDC but the casting still shrinks onto a steel core, and the pin sees the same binding risk over a longer cycle.

FIX Take cored holes to 2 degrees per side.

SOURCE Permanent-mould and low-pressure die design guidance: cored holes drafted roughly twice the wall figure. Secondary sources, consistent with the wall rule for this family.

INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED

08 Rib heavier than the wall it stands on

MEDIUM

```
maxRibThicknessToWall <= 1 rib/wall  
lpdc-rib-thickness-max
```

A rib thicker than its wall is a heavy section hanging off a thin one. It solidifies last, draws metal it cannot get, and leaves a sink on the show face opposite.

FIX Bring the rib base to 0.6-1.0 times the wall.

SOURCE Die casting rib guidance: rib base thickness $0.6-1.0 \times \text{wall}$, height $\leq 5 \times \text{rib thickness}$, fillet $1.0-1.25 \times \text{rib thickness}$, draft $1-3^\circ$. No primary standard audited.

INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED

09 Undercuts need a slide or a sand core

MEDIUM

```
undercutFaceCount <= 0 regions  
lpdc-undercuts
```

A permanent mould opens along one axis. An undercut buys either a slide — mechanism, maintenance and cycle time — or a sand core, which reintroduces the sand handling the permanent mould was chosen to escape.

FIX Re-orient the part, or move the undercut feature to a machined operation.

SOURCE Permanent-mould design guidance on parting-line selection and slide cost. No primary standard audited.

INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED

10 Rib taller than it can be filled and drawn

LOW

```
maxRibHeightToWall <= 5 rib height/wall  
lpdc-rib-height
```

A tall thin rib is a deep narrow slot in the mould: hard to fill, hard to vent, and hard to draw without tearing.

FIX Keep rib height within five times the wall, or split one tall rib into two shorter ones.

SOURCE Die casting rib guidance: rib height $\leq 5 \times \text{rib thickness}$. No primary standard audited.

INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED

11 Rib too thin to fill

LOW

```
minRibThicknessToWall >= 0.6 rib/wall  
lpdc-rib-thickness-min
```

A rib much thinner than the wall freezes off before the slow low-pressure front reaches its tip, and the stiffness it was drawn for is not there.

FIX Bring the rib base to at least 0.6 of the wall.

SOURCE Die casting rib guidance: rib base thickness $0.6-1.0 \times \text{wall}$. No primary standard audited.

INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED

Gravity die casting

13 RULES

HIGH

HIGH

HIGH

HIGH

- 05

Tolerance tighter than gravity die casting holds

HIGH
- ```
tightestToleranceMm >= 0.6 mm total band
gdc-tolerance-capability
```
- A gravity casting cools slowly against a steel mould and moves as it does. About ISO 8062 CT8-10 is normal, which is roughly +/-0.3 mm on a 50 mm dimension.
- FIX** Open the as-cast tolerance and machine the functional faces.
- SOURCE** ISO 8062 casting tolerance grades CT8-CT10 (permanent mould).
- INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED**
- 06

**Hole too small to be cast — it will be drilled**

MEDIUM
- ```
minHoleDiaMm >= 6 mm dia  
gdc-min-cored-hole
```
- A gravity-poured permanent mould has no shot pressure to force metal down a fine pin, and the pin itself sits in a hot die for a long, slow fill. The published permanent-mould floor is 6 mm, and the hole must run parallel to the draw. Anything finer is a drilled feature wearing a cast feature's drawing callout.
- FIX** Open the hole to at least 6 mm and align it with the draw direction, or delete it from the casting and quote the drilling.
- SOURCE** Permanent-mould (gravity die) design guidance, citing NADCA: minimum cored hole diameter 6.0 mm, parallel to the direction of draw. The standard is NAMED by the design guide; the NADCA document itself has not been read first-hand.
- NAMED STANDARD, NOT READ FIRST-HAND · NOT YET AUDITED**
- 07

Boss taller than the core can hold

MEDIUM
- ```
maxBossHeightToDia <= 3 height/dia
gdc-boss-height
```
- A gravity-cast boss is cored by steel or bonded sand and neither is injected against, but a slender core still floats and distorts as the metal rises around it.
- FIX** Shorten the boss, widen it, or cast it solid and drill afterwards.
- SOURCE** Permanent-mould boss-proportion guidance.
- INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED**
- 08

**Cored hole beyond the core slenderness limit**

MEDIUM
- ```
maxHoleDepthToDia <= 6 core L/D  
gdc-core-ld
```
- Gravity die cores are steel or bonded sand and are not injected against, but a slender core still floats, distorts or breaks on extraction, and a sand core has no strength to spare.
- FIX** Shorten the cored hole, open its diameter, or drill it after casting.
- SOURCE** Permanent-mould casting design guidance (core slenderness limits).
- INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED**
- 09

Cored holes below the core draft

MEDIUM
- ```
coredHoleDraftPerSideDeg >= 3 deg per side
gdc-cored-hole-draft
```
- Permanent-mould cores are steel and the casting shrinks onto them through a longer, slower solidification than die casting, so cored holes need more draft than the 1.5 deg the walls take.
- FIX** Take cored holes to 3 degrees per side, or use a sand core where the hole must stay parallel.
- SOURCE** Permanent-mould (gravity die) design guidance: cored holes drafted roughly twice the wall figure. Secondary sources, consistent with the same guidance the wall rule cites.
- INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED**

## 10 Rib heavier than the wall it stands on

MEDIUM

```
maxRibThicknessToWall <= 0.8 rib/wall
gdc-rib-thickness-max
```

A gravity casting freezes slowly, so a rib fuller than about 80% of the wall becomes a hot spot with no feed path and draws shrinkage into the junction.

**FIX** Thin the rib, or add two thinner ribs instead of one heavy one.

**SOURCE** Casting rib-proportion guidance (rib thickness against nominal wall).

**INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED**

## 11 Rib too thin to fill before it freezes

MEDIUM

```
minRibThicknessToWall >= 0.5 rib/wall
gdc-rib-thickness-min
```

A rib is the last thing to fill and the first thing to freeze, because it presents the most surface for its volume. Below this fraction of the nominal wall it will not fill reliably.

**FIX** Thicken the rib towards the process minimum, or shorten it so the metal has less distance to travel.

**SOURCE** Casting rib-proportion guidance (fill limit against nominal wall).

**INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED**

## 12 Undercuts complicate the tool

MEDIUM

```
undercutFaceCount <= 0 regions
gdc-undercuts
```

A permanent mould opens on a fixed axis. An undercut needs a loose piece or a sand core set into the steel die, which adds a core-making operation and a setting step to every cycle.

**FIX** Re-orient the part on the mould split, or design the feature to be formed by the sand core that is already there.

**SOURCE** Process tooling guidance (split lines, loose pieces and cores).

**INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED**

## 13 Rib taller than the wall can support

LOW

```
maxRibHeightToWall <= 4 rib height/wall
gdc-rib-height
```

A tall rib must fill against die chilling along its whole length, and it also concentrates stress at its base where the section changes.

**FIX** Reduce the rib height, or use more shorter ribs and generous base fillets.

**SOURCE** Casting rib-proportion guidance (height against nominal wall).

**INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED**

## Squeeze casting

6 RULES

### 01 Wall area below the minimum squeeze-casting draft

HIGH

```
wallAreaBelowDraftPct <= 5 % of wall area
squeeze-draft-minimum · cutoff 1.5 deg
```

The part is held against the die under load while it solidifies, so it grips harder than a free-shrinking casting. Zero-draft walls that a die caster would accept will not release here.

**FIX** Add at least 1.5° of draft to every drawn wall, 2-3° on deep pockets.

**SOURCE** Die casting draft guidance of 1-3°, with 2-3° minimum on deep pockets, applied to a process that solidifies under applied load. No primary standard audited.

**INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED**





## 02 Local section below what squeeze casting fills HIGH

```
wallP5Mm >= 2 mm
squeeze-min-section
```

Squeeze casting fills slowly and relies on pressure rather than velocity, so it does not chase a thin section the way a high-pressure shot does. Below about 2 mm the section is short-filled before the press closes on it.

**FIX** Thicken the section to at least 2 mm, or move the part to high-pressure die casting.

**SOURCE** Squeeze casting is quoted as producing walls of 2.0-2.5 mm at 800-1200 mm length, and 2.5-3.5 mm at 900-2000 mm. No primary standard audited.

**INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED**

## 03 Tolerance tighter than squeeze casting holds HIGH

```
tightestToleranceMm >= 0.6 mm total band
squeeze-tolerance-capability
```

Squeeze casting works in a steel die and holds a permanent-mould class of tolerance. A band tighter than about 0.6 mm total is a machining requirement.

**FIX** Open the tolerance, or leave machining stock and quote the operation.

**SOURCE** Permanent-mould tolerance class (ISO 8062 CT6-CT8) applied to a steel-die process. No primary standard audited.

**INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED**

## 04 Cored hole beyond the core slenderness limit MEDIUM

```
maxHoleDepthToDia <= 5 core L/D
squeeze-core-ld
```

A core pin in a squeeze die is loaded by the ram for the whole solidification, not by a shot for milliseconds. The slenderness it survives is below the die-casting figure, not above it.

**FIX** Open the diameter, shorten the hole, or drill it afterwards.

**SOURCE** Die casting core-pin guidance (deflection risk rising sharply past L/D 6:1), tightened for a core loaded through solidification rather than during fill. Derived, not quoted – treat as a screening value.

**INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED**

## 05 Undercuts need a slide in a pressurised die MEDIUM

```
undercutFaceCount <= 0 regions
squeeze-undercuts
```

A slide in a squeeze die carries the full press load, not just a shot pressure spike. It is a more expensive mechanism than the same slide in a gravity mould and it is the first thing to wear.

**FIX** Re-orient the part, or machine the undercut afterwards.

**SOURCE** Permanent-mould design guidance on parting-line selection and slide cost, applied to a load-bearing die. No primary standard audited.

**INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED**

## 06 Non-uniform wall thickness MEDIUM

```
wallSpreadRatio <= 0.9 (p95-p5)/p50
squeeze-wall-uniformity
```

Applied pressure feeds shrinkage, which is precisely why squeeze casting tolerates a heavier section than gravity does — but the pressure has to reach it. A heavy pocket isolated behind a thin wall freezes off from the feed path and shrinks anyway.

**FIX** Even out the section, or place the heavy section where the ram pressure acts directly on it.

**SOURCE** Casting design guidance on uniform wall thickness, relaxed for a process whose applied pressure feeds solidification shrinkage. No primary standard audited.

**INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED**

**01 Local section below what a semi-solid slurry fills****HIGH**

```
wallP5Mm >= 0.5 mm
ssm-min-section
```

A semi-solid slurry fills thinner than liquid metal because it does not spray and freeze off at the front. Walls down to 0.5 mm over palm-sized areas are documented — but 0.5 mm is the floor, not the target.

**FIX** Thicken the section to at least 0.5 mm; anything below that is not a casting feature.

**SOURCE** Thixomolding design guidance: wall thickness as low as 0.5 mm over 150 × 100 mm areas, with parts up to 18-19 mm thick also moulded. No primary standard audited.

**INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED**

**02 Tolerance tighter than semi-solid casting holds****HIGH**

```
tightestToleranceMm >= 0.4 mm total band
ssm-tolerance-capability
```

Low shrinkage and a laminar fill make semi-solid the most repeatable of the die routes, so it holds a tighter band than plain HPDC. It is still a die process with thermal growth in the tool, and a band under about 0.4 mm total belongs to machining.

**FIX** Open the tolerance, or leave stock and machine the feature.

**SOURCE** Semi-solid processing is quoted as holding tighter dimensional repeatability than conventional die casting on account of reduced solidification shrinkage. Positioned tighter than the HPDC band used elsewhere in this catalogue; no primary standard audited.

**INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED**

**03 Wall area below the minimum semi-solid draft****MEDIUM**

```
wallAreaBelowDraftPct <= 10 % of wall area
ssm-draft-minimum · cutoff 0.5 deg
```

This is the one die process that draws with almost no taper — zero draft has been used in production. The rule is here to catch a wall with NO taper across a large area, not to demand the 1-2° a die caster would ask for. A part flagged by the HPDC draft rule is very often fine here, and that difference is the reason to choose the route.

**FIX** Add half a degree where the drawn area is large, or confirm zero-draft ejection with the moulder before committing.

**SOURCE** Thixomolding design guidance: parts can be moulded with minimum draft angles or none at all, and zero draft has been used. The threshold here is deliberately permissive against the 1-3° die-casting norm. No primary standard audited.

**INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED**

**04 Rib heavier than the wall it stands on****MEDIUM**

```
maxRibThicknessToWall <= 1 rib/wall
ssm-rib-thickness-max
```

A rib heavier than its wall is a late-freezing section on an early-freezing one, and it sinks the show face opposite whatever the fill physics.

**FIX** Match the rib base to the wall or bring it below it.

**SOURCE** Thixomolding design guidance: match bosses and studs to wall thickness. No primary standard audited.

**INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED**

## 05 Undercuts need a slide

MEDIUM

```
undercutFaceCount <= 0 regions
ssm-undercuts
```

Low draft does not mean no draw. The die still opens along one axis, and an undercut still buys a slide or a lifter.

**FIX** Re-orient the part on the parting line, or machine the undercut afterwards.

**SOURCE** Thixomolding design guidance on gating, ejection and tool opening. No primary standard audited.

**INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED**

## 06 Non-uniform wall thickness

MEDIUM

```
wallSpreadRatio <= 0.9 (p95-p5)/p50
ssm-wall-uniformity
```

Laminar filling and a low superheat mean less solidification shrinkage than a fully liquid shot, so the section change this process tolerates is wider than HPDC's. It is not unlimited: a heavy boss on a thin wall still sinks.

**FIX** Even out the section, or core out the heavy region.

**SOURCE** Thixomolding design guidance: concentrate on uniform wall thickness and cavity filling; match bosses and studs to wall thickness. No primary standard audited.

**INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED**

## Sand casting

10 RULES

### 01 Wall area below the minimum sand-casting draft

HIGH

```
wallAreaBelowDraftPct <= 5 % of wall area
sand-draft-minimum · cutoff 1.5 deg
```

The pattern is drawn out of rammed sand. Without taper it tears the mould wall on the way out, and the casting carries the damage. Sand needs the most draft of any casting process.

**FIX** Allow 1.5-3 degrees on all drawn surfaces, and more on deep pockets.

**SOURCE** Sand-casting design guidance (pattern draw taper, typically 1.5-3 degrees).

**INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED**

**BY MATERIAL FAMILY**

**<= 3** ferrous **<= 7** castiron

### 02 Local section below the process minimum

HIGH

```
wallP5Mm >= 3.5 mm
sand-min-section
```

A sand mould is weak and the metal must carry itself through it. One thin web below about 3.5 mm in aluminium misruns or erodes the sand into the casting, whatever the median section says.

**FIX** Thicken the thinnest region, or move the feature to where the section is already full.

**SOURCE** Process minimum-section guidance. Checked on the 5th-percentile wall, which is the thinnest measured place rather than the nominal.

**INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED**

**BY MATERIAL FAMILY**

**>= 5** ferrous **>= 4** castiron **>= 4** copper



### 03 Tolerance tighter than sand casting holds

HIGH

```
tightestToleranceMm >= 1.2 mm total band
sand-tolerance-capability
```

Sand moves. The mould is rammed, the cores are set by hand and the casting contracts against a yielding medium, so ISO 8062 CT11-13 is the realistic band — roughly  $\pm 0.6$  mm on a 50 mm dimension.

**FIX** Machine every functional surface and open everything else. A tight as-cast tolerance on a sand casting is a scrap rate, not a specification.

**SOURCE** ISO 8062 casting tolerance grades CT11-CT13 (sand, hand-moulded).

**INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED**

**BY MATERIAL FAMILY**

**$\geq 1.6$**  ferrous

**$\geq 1$**  castiron

### 04 Wall thickness outside the sand-casting range

HIGH

```
wallP50Mm in 4 to 12 mm
sand-wall-thickness-range
```

Sand insulates, so the metal stays liquid longer and fills a long path — but the mould is weak and the section must carry itself, and below about 4 mm in aluminium (5 mm in iron) the casting misruns or the sand erodes. Because cooling is slow, sand tolerates far heavier sections than any die process.

**FIX** Hold 5-8 mm as the nominal wall. A part needing a 2 mm wall is not a sand casting.

**SOURCE** Sand-casting design guidance: about 4 mm minimum in aluminium and 5 mm in grey iron; 5-10 mm typical nominal.

**INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED**

**BY MATERIAL FAMILY**

**5-15** castiron

**6-18** ferrous

**4-12** aluminium

**5-12** copper

### 05 Cored hole beyond the sand-core slenderness limit

MEDIUM

```
maxHoleDepthToDia <= 4 core L/D
sand-core-ld
```

A bonded sand core has almost no strength in bending and is buoyant in liquid metal. A slender core floats, sags or washes away, and the hole ends up bent or absent.

**FIX** Open the hole, support the core on prints at both ends, or drill after casting.

**SOURCE** Sand-casting design guidance (core strength and buoyancy).

**INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED**

### 06 Rib heavier than the wall it stands on

MEDIUM

```
maxRibThicknessToWall <= 1 rib/wall
sand-rib-thickness-max
```

Sand cools slowest of all, so it tolerates the fullest ribs — but a rib heavier than the wall it stands on inverts the freezing order and pulls a shrinkage cavity into the joint.

**FIX** Thin the rib, or add two thinner ribs instead of one heavy one.

**SOURCE** Casting rib-proportion guidance (rib thickness against nominal wall).

**INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED**



## 07 Rib too thin to fill before it freezes MEDIUM

```
minRibThicknessToWall >= 0.6 rib/wall
sand-rib-thickness-min
```

A rib is the last thing to fill and the first thing to freeze, because it presents the most surface for its volume. Below this fraction of the nominal wall it will not fill reliably.

**FIX** Thicken the rib towards the process minimum, or shorten it so the metal has less distance to travel.

**SOURCE** Casting rib-proportion guidance (fill limit against nominal wall).

**INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED**

## 08 Non-uniform wall thickness MEDIUM

```
wallSpreadRatio <= 0.9 (p95-p5)/p50
sand-wall-uniformity
```

Slow cooling in sand gives a heavy section time to feed from a riser, so sand tolerates more section change than any die process — but an isolated hot spot with no feed path still draws shrinkage.

**FIX** Taper sections towards the risers and avoid isolated heavy bosses far from a feed path.

**SOURCE** Sand-casting design guidance (feeding distance and hot spots).

**INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED**

## 09 Rib taller than the wall can support LOW

```
maxRibHeightToWall <= 4 rib height/wall
sand-rib-height
```

A tall rib must fill against die chilling along its whole length, and it also concentrates stress at its base where the section changes.

**FIX** Reduce the rib height, or use more shorter ribs and generous base fillets.

**SOURCE** Casting rib-proportion guidance (height against nominal wall).

**INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED**

## 10 Undercuts require a core or a loose pattern piece LOW

```
undercutFaceCount <= 0 regions
sand-undercuts
```

Sand casting handles undercuts more cheaply than any die process — a core box or a loose pattern piece, not a hydraulic slide in hardened steel. Each one still adds a core to make, set and remove, so the count is a cost driver rather than a feasibility limit.

**FIX** Where a core is unavoidable, design it to be set on prints at both ends so it cannot float.

**SOURCE** Sand-casting design guidance (cores and loose pieces).

**INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED**

## Shell mould casting

5 RULES

## 01 Wall area below the minimum shell-mould draft HIGH

```
wallAreaBelowDraftPct <= 5 % of wall area
shell-draft-minimum · cutoff 1 deg
```

The pattern is drawn from a cured resin shell, which is rigid — so it needs less taper than green sand, where the mould crumbles if the pattern rubs, but more than nothing.

**FIX** Add at least 1° of draft to every drawn wall.

**SOURCE** Casting draft allowance guidance of 1-3° per vertical face, taken at the lower end because the cured shell is rigid where green sand is not. No primary standard audited.

**INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED**

## 02 Local section below what a shell mould fills

HIGH

```
wallP5Mm >= 2.5 mm
shell-min-section
```

A resin shell chills faster than rammed green sand, so it fills a thinner section than green sand does — but it is still a gravity pour into a sand-class mould, not a pressurised one.

**FIX** Thicken the section, or move the part to a permanent-mould or pressurised route.

**SOURCE** Shell moulding is quoted as reaching thinner sections and a better finish (Ra 1.6-3.2 µm) than green sand casting. The figure here sits between the sand-casting minimum used elsewhere in this catalogue and the permanent-mould minimum; it is DERIVED from that ordering, not quoted, and should be the first threshold a foundry review corrects.

INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED

## 03 Tolerance tighter than shell moulding holds

HIGH

```
tightestToleranceMm >= 0.8 mm total band
shell-tolerance-capability
```

A rigid cured shell holds a tighter band than rammed green sand — that accuracy, with the finish, is the whole reason to pay for the heated pattern — but it does not approach a steel die.

**FIX** Open the tolerance, or leave machining stock and quote the operation.

**SOURCE** Shell moulding sits between green sand and permanent mould on the ISO 8062 CT scale. The value here is positioned between the sand-casting and gravity-die bands used elsewhere in this catalogue; DERIVED from that ordering, not quoted.

INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED

## 04 Non-uniform wall thickness

HIGH

```
wallSpreadRatio <= 1 (p95-p5)/p50
shell-wall-uniformity
```

A gravity pour feeds shrinkage through risers, and a riser only feeds a section it can still reach through liquid metal. Isolated heavy sections shrink whatever the mould is made of.

**FIX** Even out the section, or add a feeder path to the heavy region.

**SOURCE** Casting design guidance on uniform wall thickness and gradual transitions. No primary standard audited.

INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED

## 05 Cored hole beyond the sand-core slenderness limit

MEDIUM

```
maxHoleDepthToDia <= 10 core L/D
shell-core-ld
```

A resin-bonded core is far stronger than a green-sand one, but it is still bonded sand. Past roughly ten diameters unsupported it is too brittle to handle without damage, let alone to survive the pour.

**FIX** Support the core at both ends, open the diameter, or drill the hole after casting.

**SOURCE** Foundry core guidance: an unsupported core length-to-diameter ratio beyond about 10-15 forces alternatives to conventional sand cores. The lower end of that band is used here. No primary standard audited.

INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED

**01 Local section below the process minimum****HIGH**

```
wallP5Mm >= 1.2 mm
inv-min-section
```

The preheated shell keeps metal fluid a long way, but below about 1.2 mm even investment casting misruns. This is the process floor, not the design target.

**FIX** Thicken the thinnest region, or move the feature to where the section is already full.

**SOURCE** Process minimum-section guidance. Checked on the 5th-percentile wall, which is the thinnest measured place rather than the nominal.

**INDUSTRY CONSENSUS**, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED

**BY MATERIAL FAMILY**

**>= 1.6** ferrous **>= 2** titanium

**02 Wall thickness outside the investment-casting range****HIGH**

```
wallP50Mm in 1.5 to 6 mm
inv-wall-thickness-range
```

The ceramic shell is preheated before pouring, so the metal stays fluid and fills thinner than sand allows — about 1.5 mm routinely and under 1 mm on small parts. Heavy sections are limited by feeding, as in any gravity process.

**FIX** Hold 2-4 mm as the nominal wall; investment casting is chosen for thin, complex sections, so leaving a heavy wall wastes the process.

**SOURCE** Investment-casting design guidance: about 1.5 mm general minimum, 2-4 mm typical.

**INDUSTRY CONSENSUS**, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED

**BY MATERIAL FAMILY**

**2-6** ferrous **2.5-8** titanium **1.5-5** aluminium

**03 Blind cored hole too deep for an unsupported ceramic core****HIGH**

```
maxBlindHoleDepthToDia <= 2 blind core L/D
inv-blind-core-ld
```

A blind hole is formed by a ceramic core held at one end only. Past about two diameters the cantilever cannot survive wax injection and shell build, and it snaps off inside the pattern where nobody sees it until the casting is sectioned.

**FIX** Reduce the depth to twice the diameter, open the diameter, or take the hole through so the core can be supported at both ends.

**SOURCE** Investment casting design guidance: depth/diameter ratio for BLIND holes should be under 2, and for THROUGH holes under 5. Consistent across several foundry design guides; no primary standard audited.

**INDUSTRY CONSENSUS**, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED

**04 Cored hole beyond the ceramic-core slenderness limit****HIGH**

```
maxHoleDepthToDia <= 4 core L/D
inv-core-ld
```

An investment-cast internal passage is made by a ceramic core that has to survive wax injection, shell building, burnout and pouring, and then be leached out. Ceramic cores are the most fragile of any casting process.

**FIX** Open the passage, shorten it, or accept a drilled hole after casting.

**SOURCE** Investment-casting design guidance (ceramic core fragility).

**INDUSTRY CONSENSUS**, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED

## 05 Tolerance tighter than investment casting holds

HIGH

```
tightestToleranceMm >= 0.3 mm total band
inv-tolerance-capability
```

The wax pattern is moulded to a machined die and the ceramic shell is rigid, so investment casting holds ISO 8062 CT5-7 — roughly  $\pm 0.15$  mm. This is the accuracy the process is bought for.

**FIX** Hold the tolerance as-cast where you can; if it must be tighter, machine only that feature.

**SOURCE** ISO 8062 casting tolerance grades CT5-CT7 (investment).

**INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED**

## 06 Non-uniform wall thickness

MEDIUM

```
wallSpreadRatio <= 0.7 (p95-p5)/p50
inv-wall-uniformity
```

The shell is a poor conductor, so an isolated heavy section stays liquid after its feed path has frozen and draws a shrinkage cavity.

**FIX** Blend section changes and place heavy masses where a feeder can reach them.

**SOURCE** Investment-casting design guidance (feeding and hot spots).

**INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED**

**BY MATERIAL FAMILY**

**<= 0.6** ferrous

## 07 Hole too small for a ceramic core

MEDIUM

```
minHoleDiaMm >= 1.5 mm dia
inv-min-cored-hole
```

Investment casting makes a hole with a ceramic core inside a wax pattern, not with a steel pin. Ceramic is brittle but it is also formed, not machined, so it goes finer than any die pin — down to about 1.5 mm. Below that the core breaks during wax injection or dewax and the hole closes.

**FIX** Open the hole to at least 1.5 mm, or drill it after casting — investment castings machine easily and the stock is already there.

**SOURCE** Investment casting design guidance: minimum hole diameter approximately 1.5 mm (some houses quote 2.0 mm for through holes), with tolerances of the order of  $\pm 0.13$  mm up to 25 mm. Consistent across several foundry design guides; no primary standard audited.

**INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED**

## 08 Through cored hole too deep for a ceramic core

MEDIUM

```
maxThroughHoleDepthToDia <= 5 through core L/D
inv-through-core-ld
```

A through hole lets the ceramic core be anchored at both ends, which roughly doubles the slenderness it survives against a blind one. It is still ceramic: past about five diameters it bows during shell build and the bore goes out of straightness.

**FIX** Open the diameter, shorten the hole, or accept a drilled bore and leave machining stock.

**SOURCE** Investment casting design guidance: depth/diameter ratio for THROUGH holes should be under 5, against under 2 for blind holes. Consistent across several foundry design guides; no primary standard audited.

**INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED**





## 09 Wall area below the minimum investment-casting draft

LOW

```
wallAreaBelowDraftPct <= 10 % of wall area
inv-draft-minimum · cutoff 0.5 deg
```

Nothing is drawn out of the ceramic shell — it is broken away. Draft is needed only to release the wax pattern from its own die, and zero-draft walls are routinely cast. This is the reason to choose investment casting for a part that cannot carry draft.

**FIX** Allow a nominal 0.5 degrees where it costs nothing; genuinely zero-draft walls are acceptable and should be discussed with the founder rather than redesigned.

**SOURCE** Investment-casting design guidance (draft needed only for wax-pattern release).

**INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED**

## 10 Undercuts complicate the tool

LOW

```
undercutFaceCount <= 0 regions
inv-undercuts
```

The ceramic shell is broken away, so the CASTING has no undercut problem — but the wax pattern still has to leave its own die, and that die is a two-part tool. An undercut moves the cost into the wax tooling rather than removing it.

**FIX** Re-orient the pattern on its die split, or accept a loose piece in the wax tool.

**SOURCE** Process tooling guidance (split lines, loose pieces and cores).

**INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED**

# Centrifugal casting

3 RULES

## 01 Part is not a body of revolution

HIGH

```
axisymmetricAreaPct >= 90 % of surface area
cent-body-of-revolution · BLOCKING
```

Centrifugal casting forms the part by spinning the mould: the outer surface is the mould bore and the inner surface is a free liquid surface held by rotation. A feature that is not axisymmetric — a lug, a flat, a bolt boss — cannot be produced by that motion at all. This is not a tolerance to negotiate; it is whether the route exists for this part.

**FIX** Cast an axisymmetric blank and machine the non-axisymmetric features, or choose a route with a static mould.

**SOURCE** Derived from the process kinematics rather than from a design guide: a spinning mould can only generate surfaces of revolution about its own axis. The 90% threshold allows for small machined-in features on an otherwise round part; it is this tool's own screening value, not a published one.

**THIS TOOL'S OWN COST MODEL · NOT YET AUDITED**

## 02 Tolerance tighter than centrifugal casting holds

HIGH

```
tightestToleranceMm >= 0.5 mm total band
cent-tolerance-capability
```

Rotation gives a dense, well-controlled OUTER diameter — the tightest as-cast surface of any sand-class process. The bore is a free liquid surface and is not controlled at all; it is machined.

**FIX** Open the tolerance, or apply the tight band to the outer diameter only and machine the bore.

**SOURCE** Centrifugal casting is quoted at radial tolerance CT3-CT8 ( $\pm 0.1$ -0.5%) with a surface finish of Ra 3-8  $\mu\text{m}$ . The value here takes the loose end of that band as a screening figure; no primary standard audited.

**INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED**

03 Local section below what a spun pour fills

MEDIUM

```
wallP5Mm >= 5 mm
cent-min-section
```

Centrifugal castings are liners, rings and bushings: the wall is set by the mould bore and the pour volume, and the inner surface carries the dross that has to be machined off. A thin as-cast wall leaves nothing to remove it from.

**FIX** Thicken the as-cast wall, or choose a route that casts closer to net shape.

**SOURCE** Centrifugal casting practice: the bore is machined to remove the dross layer that collects on the inside diameter, so the as-cast wall must carry that allowance on top of the finished wall. Machining allowances of 1-3 mm are quoted for casting processes generally. DERIVED from that practice, not quoted as a wall minimum.

**INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED**

## Sheet metal and forming

Flat stock cut and bent. Nearly every limit here is a ratio to material thickness, and most are material-dependent because the alloy decides how far it will stretch before it splits.

42 RULES · 7 PROCESSES · 23 HIGH / 19 MEDIUM / 0 LOW · 12 CARRY MATERIAL-SPECIFIC THRESHOLDS

### Sheet metal / stamping

12 RULES

#### 01 Strip utilisation below the industry target

HIGH

```
blankUtilisationPct >= 70 % of strip area
sm-blank-utilisation
```

The book opens its material-economy chapter with 'the major portion of the cost of producing a stamped component is the material' and sets the target at 70 to 80 percent of the strip. On a stamping this is usually the largest single cost lever on the part, and it is invisible on a report that quotes only a piece price.

**FIX** Re-lay the blank: rotate it, nest it two-up or interlocked, or alter the outline where function allows. The book devotes Sec. 4.4.2 to changing the workpiece design for exactly this.

**SOURCE** Boljanovic, Sec. 4.4 with Eq. 4.7 and Table 4.3 for the webs; the 70-80% target is stated in the text. READ FIRST-HAND.

NAMED STANDARD, NOT READ FIRST-HAND · PRIMARY SOURCE READ

#### 02 Tolerance tighter than sheet metal / stamping holds

HIGH

```
tightestToleranceMm >= 0.4 mm total band
sm-tolerance-capability
```

A formed feature carries springback, and springback varies with the coil, not just the tool. About +/-0.2 mm on a formed dimension is normal; a pierced hole in the flat is far better than a formed feature and should be toleranced separately.

**FIX** Tolerance pierced features tightly and formed features loosely, and datum from the pierced ones.

**SOURCE** Sheet-metal forming tolerance guidance (springback-dominated, formed vs pierced features).

INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED

##### BY MATERIAL GRADE

|                                 |                                      |                               |
|---------------------------------|--------------------------------------|-------------------------------|
| >= 0.8 Steel DP980 (dual-phase) | >= 0.3 Steel 22MnB5 (press-hardened) | >= 0.4 Aluminium 5052 (sheet) |
| >= 0.6 Steel (high-strength)    | >= 0.6 Aluminium 6061                |                               |

#### 03 Inside bend radius below one material thickness

MEDIUM

```
minBendRadiusToThickness >= 1 r/t
sm-bend-radius · PRICED BY THE COST ENGINE
```

Bending tighter than about one thickness works the outer fibre beyond its uniform elongation and cracks it. Less ductile alloys need considerably more.

**FIX** Open the inside radius to at least 1x thickness; allow 1.5–2x for stainless or 6061-T6.

**SOURCE** Sheet-metal design guidance (1x t typical, 1.5–2x for stainless and 6061-T6).

INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · PRIMARY SOURCE READ

##### BY MATERIAL GRADE

|                                 |                               |                                    |
|---------------------------------|-------------------------------|------------------------------------|
| >= 2.5 Steel DP600 (dual-phase) | >= 4 Steel DP980 (dual-phase) | >= 6 Steel 22MnB5 (press-hardened) |
| >= 1 Stainless Steel 316L       | >= 1.5 Stainless Steel 430    | >= 1 Aluminium 5052 (sheet)        |
| >= 3 Aluminium 6082             | >= 3 Aluminium 6061           | >= 4 Aluminium 7075                |
| >= 2 Steel (high-strength)      | >= 1 Stainless Steel 304      | >= 1 Steel (mild)                  |

#### 04 Hole too close to a bend line

HIGH

```
holeToBendClearanceMm >= 0 mm clear of 2t+r
sm-hole-to-bend
```

A hole inside the bend deformation zone is pulled oval as the bend forms, and no amount of press setup recovers the shape.

**FIX** Move the hole clear of the bend zone (at least 2 thicknesses plus the bend radius), or pierce it after forming.

**SOURCE** Sheet-metal design guidance (hole-to-bend  $\geq 2T + R$ ).

**INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED**

#### 05 Bend radius too LARGE to take a permanent set

MEDIUM

```
bendRadiusMaxRatio <= 1 x the maximum that will yield
sm-bend-radius-max
```

Every DFM tool checks that a bend is not too tight. A bend that is too GENTLE never strains the outer fibre past yield, so on unloading the part springs back to flat and the feature does not exist. The limit is  $T^*E/(2*YS)$ , which on thin high-yield sheet is reached at surprisingly modest radii.

**FIX** Tighten the radius below  $T^*E/(2*YS)$ , or form the feature by another means — a large-radius contour is a stretch-forming or roll-forming job, not a brake bend.

**SOURCE** Boljanovic, 'Sheet Metal Forming Processes and Die Design', Eq. 5.15:  $R_i(\max) \leq T^*E/(2*YS)$ . READ FIRST-HAND.

**NAMED STANDARD, NOT READ FIRST-HAND · PRIMARY SOURCE READ**

#### 06 Parallel bends too close to form

MEDIUM

```
minBendToBendToThickness >= 4 flat/t
sm-bend-to-bend
```

A press brake needs flat material to clamp between two bends. When the land between parallel bends falls below roughly four thicknesses there is nothing for the tooling to hold, and the second bend pulls the first out of angle.

**FIX** Open the land between the bends to at least 4t, or form them in one operation with a dedicated tool.

**SOURCE** Sheet-metal design guidance (minimum flat between parallel bends).

**INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED**

**BY MATERIAL GRADE**

**$\geq 6$  Aluminium 6061  $\geq 5$  Steel (high-strength)**

#### 07 Flange too short to form

MEDIUM

```
minFlangeToThickness >= 3 flange/t
sm-flange-length
```

A flange shorter than about three thicknesses gives the press-brake tooling nothing to hold, so the bend wanders and the angle is not repeatable.

**FIX** Lengthen the flange to at least 3x thickness, or form it as part of a larger feature and trim after.

**SOURCE** Sheet-metal design guidance (minimum flange  $\sim 3\times$  thickness).

**INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED**

**BY MATERIAL GRADE**

**$\geq 4$  Aluminium 6061  $\geq 4$  Steel (high-strength)**

## 08 Hole too close to the part edge

MEDIUM

```
minHoleToEdgeToThickness >= 2 gap/t
sm-hole-to-edge
```

A hole pierced near a trimmed edge pushes material sideways with nothing to react against, so the edge bulges and the hole goes oval. Below about two thicknesses the web can shear away entirely.

**FIX** Move the hole inboard to at least  $2t$  from the edge, or pierce it before the blank is trimmed.

**SOURCE** Sheet-metal design guidance (minimum edge distance for a pierced hole, typically  $2t$ ).

**INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED**

**BY MATERIAL GRADE**

**>= 2.5** Steel DP600 (dual-phase)      **>= 3** Steel DP980 (dual-phase)      **>= 2.5** Steel (high-strength)

## 09 Holes too close together

MEDIUM

```
minHoleToHoleToThickness >= 2 gap/t
sm-hole-to-hole
```

The web of material between two punched holes is pulled in both directions as each is pierced. Below about two material thicknesses it distorts, tears, or wears the punch and die out of tolerance early.

**FIX** Move the holes apart to at least  $2t$  edge-to-edge, or pierce them in separate stations so the web is not loaded twice at once.

**SOURCE** Sheet-metal design guidance (minimum web between pierced holes, typically  $2t$ ).

**INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED**

**BY MATERIAL GRADE**

**>= 2.5** Steel DP980 (dual-phase)      **>= 2.5** Steel (high-strength)      **>= 2.5** Stainless Steel 304

## 10 Cut-out smaller than the material thickness

MEDIUM

```
minApertureToThickness >= 1 size/t
sm-min-aperture
```

A punch narrower than the sheet is thick buckles under the piercing load, and the shape of the aperture does not change that — a 3 mm slot in 4 mm plate breaks the same punch a 3 mm hole would. This is the same limit `sm-hole-diameter` applies to round holes, extended to the slots, obrounds and shaped cut-outs that make up most of a real stamping.

**FIX** Open the smallest cut-out to at least one material thickness across, or laser it rather than piercing it and price the slower operation.

**SOURCE** Sheet-metal piercing guidance (punch slenderness), applied to the aperture's size rather than to a diameter it may not have.

**INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED**

**BY MATERIAL GRADE**

**>= 1.5** Steel DP980 (dual-phase)      **>= 1.2** Stainless Steel 304

## 11 Springback beyond what overbend alone can compensate

MEDIUM

```
springbackOverbendPct <= 8 % overbend required
sm-springback
```

Springback scales with  $YS/E$ , which is why high-strength steel recovers far more than mild steel at identical geometry. The book gives 2 to 8 percent added bend angle as the practical overbend allowance; past that the die has to bottom or stretch-bend the part, and the tooling is a different design at a different price.

**FIX** Tighten the bend radius, choose a lower-yield grade, or budget for bottoming or stretch bending rather than overbend alone.

**SOURCE** Boljanovic, Sec. 5.7, Eq. 5.22 for the springback factor and the 2-8% practical overbend allowance. READ FIRST-HAND.

**NAMED STANDARD, NOT READ FIRST-HAND · PRIMARY SOURCE READ**

## 12 Punched hole smaller than the material thickness

MEDIUM

```
minHoleDiaToThickness >= 1 d/t
sm-hole-diameter
```

A punch narrower than the sheet is thick is loaded in buckling and breaks often. It becomes a consumable rather than a tool.

**FIX** Increase the hole diameter to at least one thickness, or drill rather than punch.

**SOURCE** Sheet-metal design guidance (minimum punched hole diameter ~1x thickness).

**INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · CONTESTED - SEE APPENDIX B**

**BY MATERIAL GRADE**

|                                           |                                                |                                       |
|-------------------------------------------|------------------------------------------------|---------------------------------------|
| <b>&gt;= 1.5</b> Steel DP980 (dual-phase) | <b>&gt;= 2.5</b> Steel 22MnB5 (press-hardened) | <b>&gt;= 1.2</b> Stainless Steel 316L |
| <b>&gt;= 1.2</b> Stainless Steel 304      | <b>&gt;= 1.5</b> Steel (high-strength)         | <b>&gt;= 1</b> Aluminium 6061         |

## Deep drawing (multi-stage)

5 RULES

### 01 Too deep to draw in one operation

HIGH

```
drawDepthToWidth <= 0.75 depth/width
dd-draw-depth
```

A cup deeper than about three quarters of its width cannot be drawn in one hit: the wall thins until it splits at the punch nose. Past that limit the part needs redraws, and every redraw is another die, another station and an anneal if the alloy work-hardens.

**FIX** Reduce the depth, widen the part, or plan for redraws — the first draw takes the most, and each redraw after it takes 1.3-1.5:1, not 2:1.

**SOURCE** Deep drawing design guidance: maximum depth-to-diameter in a SINGLE operation is 0.5-0.75 for most metals, approaching or slightly exceeding 1.0 for highly ductile low-carbon steel and aluminium; limiting draw ratio 1.8-2.3 for most steels, redraw ratios 1.3-1.5:1 per stage. MEASURED HERE AS A PROXY: this rule reads bounding-box depth over the narrower box width, not blank diameter over punch diameter — the blank and the punch are not in a finished solid. See UNWRITTEN\_RULES for what that proxy cannot see. No primary standard audited.

**INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED**

**BY MATERIAL GRADE**

|                             |                                         |                                        |
|-----------------------------|-----------------------------------------|----------------------------------------|
| <b>&lt;= 1</b> Steel (mild) | <b>&lt;= 0.6</b> Aluminium 5052 (sheet) | <b>&lt;= 0.5</b> Steel (high-strength) |
|-----------------------------|-----------------------------------------|----------------------------------------|

### 02 Cup too deep for the drawing-ratio table

HIGH

```
drawStagesBeyondTable <= 0 beyond the table (1 = yes)
dd-draw-stages
```

Each draw can only reduce the diameter to m times the previous one, and Table 6.2 runs to five successive draws. A cup still larger than target after five is not simply expensive — it needs interstage annealing the table never contemplated, and the process plan is no longer a stamping plan.

**FIX** Reduce the draw depth, increase the starting blank thickness, or plan the part as a drawn-and-ironed or spun component.

**SOURCE** Boljanovic, Sec. 6.2.1 and Table 6.2: optimal drawing ratio m per operation against relative thickness  $100 \cdot T/D$ . READ FIRST-HAND.

**NAMED STANDARD, NOT READ FIRST-HAND · PRIMARY SOURCE READ**



### 03 Tolerance tighter than deep drawing holds

HIGH

```
tightestToleranceMm >= 0.5 mm total band
dd-tolerance-capability
```

A drawn wall is formed between a punch and a die with clearance in between and it springs back when the punch withdraws. It is looser than a blanked edge, not tighter.

**FIX** Open the tolerance, or add an ironing or sizing station on the feature that needs it.

**SOURCE** Positioned above the 0.4 mm flat-stamping band used elsewhere in this catalogue, because a drawn wall adds springback the blanked edge does not have. DERIVED from that ordering, not quoted.

INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED

### 04 Undercuts cannot be drawn off the punch

HIGH

```
undercutFaceCount <= 0 regions
dd-undercuts
```

The cup is stripped off the punch along the draw axis. A re-entrant feature holds it there, and the strip either tears the wall or leaves the part on the tool.

**FIX** Re-orient the part on the draw axis, or form the feature in a separate cam operation after the draw.

**SOURCE** Drawing tool design: the part is stripped along the draw axis, so a re-entrant feature cannot be produced by the draw itself. Derived from the process, not quoted from a design guide.

INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED

### 05 Wall variation beyond what drawing produces

MEDIUM

```
wallSpreadRatio <= 0.4 (p95-p5)/p50
dd-wall-uniformity
```

Drawing THINS the cup wall and thickens the flange, so a drawn part legitimately varies where a blanked one does not — but the variation comes from the draw, not from the drawing office. A section change the sheet never had is a machining feature on a pressing.

**FIX** Check whether the thick or thin region is a drawn consequence or a designed one; a designed section change on a drawn part is not a pressing.

**SOURCE** Deep drawing thins the wall progressively toward the punch nose while the flange thickens. The band here is positioned above the flat-sheet families in this catalogue and below the casting families; DERIVED from that ordering, not quoted.

INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED

## Fine blanking

6 RULES

### 01 Tolerance tighter than fine blanking holds

HIGH

```
tightestToleranceMm >= 0.06 mm total band
fb-tolerance-capability
```

This is where fine blanking earns its tooling cost: a clean sheared face over the full thickness and a band an order of magnitude tighter than conventional stamping. It is not machining, and a band under about 0.06 mm total still belongs to a grinder.

**FIX** Open the tolerance, or grind that feature after blanking.

**SOURCE** Fine blanking is quoted as repeatably holding +/-0.01 to 0.03 mm depending on sheet type and thickness. The LOOSE end of that band (0.03 either way = 0.06 total) is used, so the rule flags only what is clearly outside the process. No primary standard audited.

INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED

## 02 Internal corner sharper than the sheet can be cut to

MEDIUM

```
minBendRadiusToThickness >= 0.5 r/t
fb-corner-radius
```

A sharp internal corner concentrates the cutting stress into a point on the tool. The tool cracks there first, and the part carries a tear-out where a clean sheared face was specified.

**FIX** Put a radius of at least half the sheet thickness in every internal corner; an obtuse corner can go smaller, an acute one needs more.

**SOURCE** Fine blanking design guidance: minimum inside radius 0.5 x sheet thickness to spread stress evenly and avoid cracks; corner radius by angle – obtuse 5-10% of thickness, right angle 10-15%, acute 25-30%. The single 0.5t figure is used because the corner ANGLE is not measured by this engine (see UNWRITTEN\_RULES). No primary standard audited.

INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED

## 03 Pierced hole below the fine-blanking minimum

MEDIUM

```
minHoleDiaToThickness >= 0.65 d/t
fb-hole-diameter
```

The V-ring grips the sheet and the counter-punch supports it, so the material does not flow away from the punch the way it does in conventional blanking. That is what lets a fine-blanked hole go below one thickness — but the punch is still a slender column under load and it breaks below about 0.65 of the sheet.

**FIX** Open the hole to at least 0.65 of the sheet thickness, or drill it as a secondary operation.

**SOURCE** Fine blanking design guidance: hole diameter approximately 60-65% of material thickness. NOTE – a second guide quotes minimum hole diameter  $\geq 1.2 \times$  thickness, which is nearly twice this figure and closer to the conventional-blanking rule. The two are in genuine conflict; the more permissive figure is used because going finer than conventional blanking is the capability fine blanking is bought for, and the finding should be treated as a screening result to put to your press shop. No primary standard audited.

INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED

## 04 Hole too close to the blanked edge

MEDIUM

```
minHoleToEdgeToThickness >= 1.5 gap/t
fb-hole-to-edge
```

The V-ring clamps just outside the cut line, so the material between a hole and the edge is held far better than in conventional blanking — but it is still the narrowest section on the part and it is where the blank will bow if it goes too thin.

**FIX** Move the hole inboard to at least 1.5 thicknesses from the edge.

**SOURCE** Fine blanking design guidance: keep holes at least 1.5-2 x sheet thickness from the nearest edge, against 2t for conventional blanking. No primary standard audited.

INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED

## 05 Web between features narrower than the sheet is thick

MEDIUM

```
minHoleToHoleToThickness >= 1 gap/t
fb-hole-to-hole
```

The web between two pierced features is unsupported on both sides while both punches are in the sheet. Below one thickness it collapses, and the two holes break through into one.

**FIX** Open the web to at least one sheet thickness, or combine the two features into one aperture.

**SOURCE** Fine blanking design guidance: maintain webs  $\geq$  material thickness between adjacent features. Against 2t for conventional blanking. No primary standard audited.

INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED





## 06 Cut-out smaller than the fine-blanking minimum

MEDIUM

```
minApertureToThickness >= 0.65 size/t
fb-min-aperture
```

A non-round aperture is cut by a shaped punch, and a slender punch snaps whatever its outline. The same floor applies as to a round hole.

**FIX** Open the aperture to at least 0.65 of the sheet thickness across its narrowest span.

**SOURCE** Fine blanking design guidance on minimum feature size, applied to non-circular apertures on the same basis as pierced holes. No primary standard audited.

INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED

## Hot stamping / press hardening

5 RULES

### 01 Bend radius below what press-hardened steel tolerates

HIGH

```
minBendRadiusToThickness >= 6 r/t
hs-bend-radius
```

The radius is formed hot and soft, but it is quenched to martensite in the same die and lives its life at 1500 MPa. A tight radius carries the residual stress of the quench on top of the forming strain, and it is where a hydrogen-assisted crack starts.

**FIX** Open the radius to at least six thicknesses, or move the bend to a region that stays soft (a tailored or partially-quenched blank).

**SOURCE** The 22MnB5 (press-hardened) figure carried by the sheet-metal bend rule in this same catalogue: 6 r/t. It is the base threshold here because hot stamping IS that alloy, so the two families cannot disagree about it. No primary standard audited.

INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED

### 02 Hole too small to pierce in press-hardened steel

HIGH

```
minHoleDiaToThickness >= 2.5 d/t
hs-hole-diameter
```

A hole in a press-hardened part is either pierced hot before quench, when its position moves with the shrinkage, or cut by laser afterwards at a cost per hole. Neither route makes a small hole cheap, and a punch driven through martensite chips.

**FIX** Open the hole to at least 2.5 thicknesses, or accept laser trimming and cost it per hole.

**SOURCE** The 22MnB5 (press-hardened) figure carried by the sheet-metal hole rule in this same catalogue: 2.5 d/t. No primary standard audited.

INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED

### 03 Tolerance tighter than hot stamping holds

HIGH

```
tightestToleranceMm >= 0.3 mm total band
hs-tolerance-capability
```

Quenching in the die is what makes hot stamping DIMENSIONALLY good — the part is held while it transforms, so there is almost no springback and very little warping. It is still a phase transformation inside a closing tool, and a band under about 0.3 mm total is a machining or laser requirement.

**FIX** Open the tolerance, or laser-cut that feature after quench.

**SOURCE** The 22MnB5 (press-hardened) figure carried by the sheet-metal tolerance rule in this same catalogue: 0.3 mm total band — TIGHTER than the 0.4 mm mild-steel stamping band, because quenching in the die removes the springback that drives cold-stamped variation. No primary standard audited.

INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED

#### 04 Undercuts cannot be drawn from a quenching die

HIGH

```
undercutFaceCount <= 0 regions
hs-undercuts
```

The die must stay closed on the part until the quench is complete and then open cleanly. An undercut needs a slide that has to be water-cooled like the rest of the tool and has to move against a part that is gripping it as it shrinks.

**FIX** Re-orient the part on the die axis, or cut the undercut feature by laser afterwards.

**SOURCE** Press-hardening tool design: the part is quenched in the closed die and then drawn, so the tool geometry must release a shrinking, hardening part. Derived from the process, not quoted from a design guide.

INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED

#### 05 Pierced holes too close for a hot-formed part

MEDIUM

```
minHoleToHoleToThickness >= 1.5 gap/t
hs-hole-to-hole
```

Holes closer than about 1.5 thicknesses distort each other as they are pierced, and on a part that then shrinks through a quench the position error and the distortion add.

**FIX** Open the gap to at least 1.5 thicknesses, or loosen the position tolerance between them to cover springback and bend variation.

**SOURCE** Stamping design guidance: hole spacing of at least 1.5 x material thickness to avoid distortion; same-plane piercing holds close position, and holes closer than that or on different planes need a loosened band. No primary standard audited.

INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED

### Roll forming

6 RULES

#### 01 Tolerance tighter than roll forming holds

HIGH

```
tightestToleranceMm >= 0.6 mm total band
roll-tolerance-capability
```

A roll-formed profile is worked gradually through many stations and springs back at every one, so cross-section tolerance is looser than a press brake and length tolerance depends on the flying cut.

**FIX** Open the profile tolerance and add a secondary operation for anything that must locate.

**SOURCE** Roll-forming dimensional tolerance guidance.

INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED

BY MATERIAL GRADE

>= 0.8 Aluminium 6061

#### 02 Hole too close to a formed corner

HIGH

```
holeToBendClearanceMm >= 0 mm clear of 2t+r
roll-hole-to-bend
```

A hole pre-punched in the strip distorts as the corner is worked up over successive stations. Roll forming spreads the deformation over more stations than a press brake, which helps, but the hole still pulls oval if it sits inside the bend allowance.

**FIX** Move the hole clear of the forming zone, or pierce it after forming in a secondary station.

**SOURCE** Roll-forming design guidance (pre-punched features and the forming zone).

INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED



## 01 Corner radius too tight for the forming pressure available

HIGH

```
minBendRadiusToThickness >= 3 r/t
hydro-corner-radius
```

A hydroformed corner is filled by internal pressure pushing the wall into the die, and the pressure needed rises as the radius falls. Below about 3 r/t the tube thins and splits at the corner before the die is filled.

**FIX** Open the corner radii, or accept a two-stage form with an intermediate anneal.

**SOURCE** Tube hydroforming design guidance (corner radius against forming pressure and wall thinning).

**INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED**

**BY MATERIAL FAMILY**

**>= 3** ferrous **>= 4** aluminium

## 02 Local section below the process minimum

HIGH

```
wallP5Mm >= 0.8 mm
hydro-min-section
```

The tube thins where it expands, and the thinnest surviving section is what bursts. It is the measure that predicts the failure, not the average.

**FIX** Thicken the thinnest region, or move the feature to where the section is already full.

**SOURCE** Process minimum-section guidance. Checked on the 5th-percentile wall, which is the thinnest measured place rather than the nominal.

**INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED**

## 03 Section varies more than the expansion limit allows

HIGH

```
wallSpreadRatio <= 0.3 (p95-p5)/p50
hydro-section-uniformity
```

A hydroformed part starts as a tube of one wall thickness and thins wherever it expands. A large variation in the finished section means a large expansion ratio somewhere, and past roughly 30-40% expansion the wall splits.

**FIX** Reduce the largest expansion, start from a pre-bent tube closer to the final shape, or use a thicker starting gauge.

**SOURCE** Tube hydroforming design guidance (expansion ratio and wall thinning limits).

**INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED**

## 04 Tolerance tighter than hydroforming holds

HIGH

```
tightestToleranceMm >= 0.5 mm total band
hydro-tolerance-capability
```

The tube conforms to the die under pressure, so the formed shape is repeatable, but the wall thins unevenly and the ends move as the tube is fed. About +/-0.25 mm is realistic.

**FIX** Tolerance from the die-formed faces, not from the tube ends.

**SOURCE** Tube hydroforming holds a permanent-die class of tolerance on the formed section because the tube is pressed against a steel die, but the tube diameter, wall and length going in all vary, and that variation carries through. The band sits between the stamping and casting families used elsewhere in this catalogue. DERIVED from that ordering; no primary standard audited.

**INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED**

## 05 Undercuts prevent the die from opening

HIGH

```
undercutFaceCount <= 0 regions
hydro-undercuts
```

The formed tube is trapped in a two-part die that must open along one axis. An undercut locks the part in the tool.

**FIX** Re-orient the part relative to the die parting line, or split the feature so it forms between the halves.

**SOURCE** Hydroforming design guidance (die opening and part extraction).

**INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED**

**01 Part is not a body of revolution****HIGH**

```
axisymmetricAreaPct >= 90 % of surface area
spin-body-of-revolution · BLOCKING
```

Spinning forms the part by pressing a roller against a blank rotating on a mandrel. Every surface it can make is a surface of revolution about the mandrel axis. A flat, a lug or a bolt boss is not reachable by that motion — not expensively, but at all.

**FIX** Spin an axisymmetric shell and add the non-axisymmetric features as a secondary operation, or press the part instead.

**SOURCE** Derived from the process kinematics rather than from a design guide: a rotating mandrel and a following roller generate only surfaces of revolution about the mandrel axis. The 90% threshold allows small secondary features on an otherwise round part; it is this tool's own screening value, shared with the centrifugal-casting rule for the same reason.

**THIS TOOL'S OWN COST MODEL · NOT YET AUDITED**

**02 Tolerance tighter than spinning holds****HIGH**

```
tightestToleranceMm >= 0.8 mm total band
spin-tolerance-capability
```

The roller follows a path against a blank whose thickness is changing under it. CNC spinning is repeatable on round shapes, but the wall thins by a quarter to a third as it forms and the band reflects that.

**FIX** Open the tolerance, or machine the feature that needs it after spinning — the stock is there, because the blank was specified thicker.

**SOURCE** Metal spinning is quoted at tolerances of about 1/32 inch (0.79 mm), with material specified 25-30% thicker than the finished wall to allow for thinning. No primary standard audited.

**INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED**

**03 Undercuts cannot be drawn off the mandrel****HIGH**

```
undercutFaceCount <= 0 regions
spin-undercuts
```

The finished shell is pulled off the mandrel along its axis. A re-entrant profile locks it on, and the only ways out are a collapsible mandrel — an expensive, wearing assembly — or scrapping the part.

**FIX** Remove the re-entrant profile, or budget for a collapsible or segmented mandrel.

**SOURCE** Metal spinning tool practice: the shell is drawn off the mandrel along the spin axis, so a re-entrant profile needs a collapsible mandrel. Derived from the process, not quoted from a design guide.

**INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED**

## Forging and bulk forming

Solid metal moved under load. Draft is far heavier than in casting, webs and ribs have hard minimums, and the die closes in one direction only.

25 RULES · 5 PROCESSES · 20 HIGH / 4 MEDIUM / 1 LOW · 6 CARRY MATERIAL-SPECIFIC THRESHOLDS

### Forging (hot)

6 RULES

#### 01 Wall area below the minimum hot-forging draft

HIGH

```
wallAreaBelowDraftPct <= 5 % of wall area
forge-hot-draft-minimum · cutoff 5 deg
```

A hot forging shrinks onto the die as it cools and is knocked out mechanically, so it needs far more draft than any casting — 3 degrees on external surfaces and 5-7 on internal ones is normal. This is the single largest difference between forging and casting geometry.

**FIX** Allow 3 degrees on external walls and 5-7 degrees on internal walls and pockets.

**SOURCE** Closed-die hot forging design guidance (draft typically 3 degrees external, 5-7 degrees internal).

**INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED**

**BY MATERIAL FAMILY**

<= 10 aluminium <= 3 titanium

#### 02 Web too thin to forge

HIGH

```
wallP5Mm >= 3 mm
forge-hot-min-web
```

Metal must flow to fill a thin web, and a thin web chills against the die before it fills. It also drives forging load up sharply, because the thinner the web the higher the pressure needed to make the material move.

**FIX** Thicken the web to at least 3 mm, or machine the thin region after forging.

**SOURCE** Closed-die forging design guidance (minimum web thickness and forging load).

**INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED**

**BY MATERIAL FAMILY**

>= 2.5 aluminium >= 3.5 ferrous >= 5 titanium

#### 03 Tolerance tighter than forging holds

HIGH

```
tightestToleranceMm >= 1 mm total band
forge-hot-tolerance-capability
```

A hot forging shrinks as it cools, the dies wear, and the flash line moves with die closure. About +/-0.5 mm is the realistic as-forged band, and it grows across the parting line.

**FIX** Machine every functional surface. As-forged tolerances belong on the non-functional envelope only.

**SOURCE** Closed-die hot forging tolerance guidance (die wear and thermal contraction).

**INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED**

**BY MATERIAL FAMILY**

>= 0.6 aluminium >= 1.4 titanium

#### 04 Undercuts cannot be forged

HIGH

```
undercutFaceCount <= 0 regions
forge-hot-undercuts
```

A forging die has two halves and no slides. There is no forging equivalent of a side action: an undercut simply cannot be forged and must be machined afterwards.

**FIX** Remove the undercut from the forged shape and machine it as a secondary operation, or re-orient the part on the parting line.

**SOURCE** Closed-die forging design guidance (two-part dies, no side actions).

**INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED**

#### 05 Rib too tall for the metal to fill

MEDIUM

```
maxRibHeightToWall <= 4 rib height / wall
forge-hot-rib-height
```

A tall, thin rib is the hardest thing to fill in a forging: the metal must flow furthest against the most die chilling, and an unfilled rib is scrap.

**FIX** Reduce the rib height, thicken it, or add generous fillets at its base so metal reaches the top.

**SOURCE** Closed-die forging design guidance (rib height-to-width and die filling).

**INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED**

#### 06 Section varies more than the process tolerates

MEDIUM

```
wallSpreadRatio <= 0.9 (p95-p5)/p50
forge-hot-uniformity
```

Metal flows from thick to thin under the die, and a large section change means the thin region fills last, against the most die chilling. It is also where the die cracks, because the pressure needed to fill it is highest.

**FIX** Even out the section and add generous fillets so metal reaches the thin regions.

**SOURCE** Casting and forging design guidance on gradual section change. A hot forging fills by displacing metal between closing dies rather than by flowing into a cavity, so it tolerates MORE section variation than a die casting and less than a machined part – this band sits between the two used elsewhere in this catalogue. DERIVED from that ordering, not quoted.

**INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED**

### Forging (cold)

5 RULES

#### 01 Web too thin for the forming load available

HIGH

```
wallP5Mm >= 1.5 mm
forge-cold-min-web
```

Cold forging works the material below its recrystallisation temperature, so it work-hardens as it flows. A thin web needs very high pressure to fill and is where the tool cracks.

**FIX** Thicken the web, add an intermediate anneal, or machine the thin region afterwards.

**SOURCE** Cold forging design guidance (forming pressure and tool life against web thickness).

**INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED**

**BY MATERIAL FAMILY**

**>= 2** ferrous **>= 1.2** aluminium



## 02 Tolerance tighter than forging holds

HIGH

```
tightestToleranceMm >= 0.2 mm total band
forge-cold-tolerance-capability
```

Cold forging holds far tighter than hot because nothing shrinks on cooling — about +/-0.1 mm — and that accuracy is most of the reason to pay for the tooling.

**FIX** Hold the tolerance as-forged; adding a machining operation gives away the advantage that justified the process.

**SOURCE** Cold forging / cold heading tolerance guidance.

**INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED**

## 03 Undercuts cannot be cold forged

HIGH

```
undercutFaceCount <= 0 regions
forge-cold-undercuts
```

The part is ejected from a closed die by a knock-out pin along one axis. An undercut locks it in the tool.

**FIX** Machine the undercut as a secondary operation, or re-orient the part on the die axis.

**SOURCE** Cold forging design guidance (axial ejection).

**INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED**

## 04 Section varies more than the process tolerates

MEDIUM

```
wallSpreadRatio <= 0.7 (p95-p5)/p50
forge-cold-uniformity
```

Cold forging work-hardens as it flows, so a large section change means the last region to fill is also the hardest to fill. Tool life is set by that region.

**FIX** Even out the section, or split the shape across two blows with an intermediate anneal.

**SOURCE** The same section-change guidance as hot forging, tightened because cold metal work-hardens as it moves: the load needed to fill a section change rises with every millimetre the metal travels, and the press has a limit the furnace removes in hot work. DERIVED from the hot-forging band in this catalogue, not quoted.

**INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED**

## 05 Wall area below the minimum cold-forging draft

LOW

```
wallAreaBelowDraftPct <= 10 % of wall area
forge-cold-draft-minimum · cutoff 0.5 deg
```

A cold forging does not shrink onto the die the way a hot one does, and it is ejected by a knock-out pin rather than being drawn. Near-zero draft is normal, which is a large part of why cold forging holds tolerances that hot forging cannot.

**FIX** Allow 0.5 degrees where the function permits; zero-draft walls are usually acceptable here.

**SOURCE** Cold forging / cold heading design guidance (draft near zero because there is no thermal shrink onto the die).

**INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED**

## Open-die forging

5 RULES





## 01 Wall area below the minimum open-die forging draft

HIGH

```
wallAreaBelowDraftPct <= 5 % of wall area
odf-draft-minimum · cutoff 7 deg
```

The workpiece is turned and repositioned between blows against tools that are flat or barely contoured. Nothing about that process produces a near-vertical wall, and asking for one means the wall is machined afterwards out of stock that has to be there.

**FIX** Open the taper to at least 7°, or accept that the face is a machined face and leave stock for it.

**SOURCE** Forging draft guidance, taken at the top of the hot-forging band (the closed-die family in this catalogue reads the 5° point). Open-die work is manipulated between simple tools and takes more taper than closed-die, so the 7° point is read instead. DERIVED from that ordering, not quoted.

**INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED**

## 02 Section thinner than open-die forging reaches

HIGH

```
wallP5Mm >= 6 mm
odf-min-web
```

Between flat tools there is no cavity to fill and no die wall to hold the metal, so a thin web simply is not formed — it is machined out of a thicker one.

**FIX** Thicken the section, or move to closed-die forging where a cavity can hold a thinner web.

**SOURCE** Positioned at twice the closed-die hot-forging minimum used elsewhere in this catalogue (3 mm), because open-die work has no cavity to fill a thin section into. DERIVED from that ordering, not quoted.

**INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED**

## 03 Tolerance tighter than open-die forging holds

HIGH

```
tightestToleranceMm >= 3 mm total band
odf-tolerance-capability
```

There is no die cavity setting the shape — the operator and the manipulator set it, blow by blow. Every dimension that matters on an open-die forging is machined afterwards, and the forging exists to put grain flow and mass roughly where they are needed.

**FIX** Treat the forging as a blank: put the tolerance on the machined feature and leave stock for it.

**SOURCE** Positioned at three times the closed-die hot-forging band used elsewhere in this catalogue (1.0 mm), because open-die work has no cavity setting the dimension. DERIVED from that ordering, not quoted — and it is the threshold in this family most in need of a forge-shop review.

**INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED**

## 04 Undercuts cannot be forged between open tools

HIGH

```
undercutFaceCount <= 0 regions
odf-undercuts
```

Flat or simply-contoured tools approach along one axis and separate along it. There is no mechanism in an open-die press to form or release a re-entrant feature.

**FIX** Machine the undercut afterwards.

**SOURCE** Open-die forging tool practice: flat tools approach and separate along one axis. Derived from the process, not quoted from a design guide.

**INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED**

## 05 Section change beyond what open-die work produces

MEDIUM

```
wallSpreadRatio <= 1.2 (p95-p5)/p50
odf-uniformity
```

Open-die forging makes simple shapes: shafts, discs, rings, blocks. A part whose section varies more than the process can work into it is a machined part with a forged blank, and it should be quoted that way.

**FIX** Simplify the forged shape and machine the detail, or move to closed-die forging.

**SOURCE** Positioned above the closed-die hot-forging band used elsewhere in this catalogue (0.9), because open-die work is deliberately a simpler shape carrying more machining stock. DERIVED from that ordering, not quoted.

INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED

## Cold heading / upsetting

3 RULES

### 01 Tolerance tighter than cold heading holds

HIGH

```
tightestToleranceMm >= 0.2 mm total band
ch-tolerance-capability
```

Cold forming in a closed die is accurate and repeatable — that is why fasteners are made this way and not machined. Below about 0.2 mm total the feature is being ground or rolled, not headed.

**FIX** Open the tolerance, or grind the feature after heading.

**SOURCE** The cold-forging tolerance band used elsewhere in this catalogue (0.2 mm total), applied to cold heading as the same class of closed-die cold forming. DERIVED from that neighbour, not quoted.

INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED

### 02 Undercuts cannot be ejected from a heading die

HIGH

```
undercutFaceCount <= 0 regions
ch-undercuts
```

A headed part is knocked out of the die along the wire axis by a pin. A re-entrant feature holds it in the cavity, and heading machines run too fast to unload one part at a time.

**FIX** Remove the re-entrant feature, or machine it in afterwards — a cold-headed blank machines easily.

**SOURCE** Cold heading tool practice: the part is ejected along the die axis by a knock-out pin. Derived from the process, not quoted from a design guide.

INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED

### 03 Head too tall to upset in one blow

HIGH

```
maxBossHeightToDia <= 2.5 upset L/D
ch-upset-ratio
```

Cold heading forms the head by upsetting an unsupported length of wire. Past about two and a half wire diameters that free length buckles sideways instead of spreading, and the head folds over rather than filling.

**FIX** Reduce the head volume, or plan a two-blow sequence — a second blow reaches roughly four and a half diameters, and enclosing the blank in a die cavity extends the first.

**SOURCE** Cold heading practice: unsupported lengths of up to 2 to 2.5 x blank diameter can be upset in one blow in steel; enclosing the blank in a cavity of 1.5 x diameter allows more, and a two-blow sequence reaches about 4.5 diameters. MEASURED HERE AS A PROXY: the engine reads the recognised BOSS height over its diameter on the finished part, which is not the same thing as the free wire length before upsetting. No primary standard audited.

INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED



## 01 Wall thinner than the die can hold

HIGH

```
wallP5Mm >= 1 mm
extr-min-wall
```

The die tongue that forms a thin wall is unsupported and deflects under extrusion pressure. Below about 1 mm in a solid aluminium profile the tongue chatters or breaks, and a hollow profile needs more again.

**FIX** Thicken the thinnest wall to 1.5-2 mm, especially on any hollow section.

**SOURCE** Aluminium extrusion design guidance: about 1.0 mm minimum for a solid profile, 1.5-2.0 mm for a hollow.

**INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED**

**BY MATERIAL FAMILY**

**>= 1.5** copper

## 02 Section is not uniform enough for the die to run balanced

HIGH

```
wallSpreadRatio <= 0.35 (p95-p5)/p50
extr-section-uniformity
```

Metal flows faster through a thick part of the die than a thin one. A profile whose wall varies sharply comes out twisted or bowed, and the die has to be corrected by trial — which is why extruders charge more for an unbalanced section and reject the worst of them outright.

**FIX** Even out the wall across the profile, and where a thick region is structurally necessary, blend into it rather than stepping.

**SOURCE** Aluminium extrusion design guidance (balanced metal flow and die correction).

**INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED**

**BY MATERIAL FAMILY**

**<= 0.25** copper

## 03 Profile too large for a general-purpose press

HIGH

```
circumscribingCircleMm <= 203 mm CCD
extr-circumscribing-circle
```

The circumscribing circle is the smallest circle the section fits inside, and it is what decides which press can run the job at all. Past about 203 mm (8 in) the profile leaves the general-purpose press population: it needs a bigger container, more tonnage and a specific supplier, and the quote changes shape rather than degrading gently.

**FIX** Bring the section inside a 203 mm circle, or split the profile into two extrusions and join them.

**SOURCE** Aluminium extrusion design guidance: extrusions are most economical within a circumscribing circle of roughly 1-10 in; general-purpose presses prefer CCD at or below 203 mm (8 in), with some plants reaching ~457 mm given tonnage and tooling. No primary standard audited.

**INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED**

## 04 Tolerance tighter than extrusion holds

HIGH

```
tightestToleranceMm >= 0.5 mm total band
extr-tolerance-capability
```

An extruded profile is pulled through a die that wears and deflects, and it twists and bows as it cools on the run-out table. Straightness and twist usually bind before the section tolerance does.

**FIX** Tolerance the section loosely and specify straightness and twist separately; machine any locating feature.

**SOURCE** Aluminium extrusion tolerance guidance (EN 12020 / supplier standard practice).

**INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED**

## 05 Channel too deep for its width — the die tongue will fail

HIGH

```
maxPocketDepthToWidth <= 3 depth/width
extr-tongue-ratio
```

A channel in the profile is a TONGUE in the die: a cantilevered finger of tool steel with metal flowing round it at hundreds of bar. It is the classic way an extrusion die breaks. Past about three times its own width the tongue deflects, the channel opens out along the run, and eventually the tongue snaps.

**FIX** Open the channel, shorten it, or put a large radius at its mouth and a full radius at its root — that buys roughly a 2:1 improvement.

**SOURCE** Aluminium extrusion design guidance: the ratio of channel height to width should be about 3:1 to keep die strength; with large radii at the opening and a full radius at the base a 2:1 improvement is available. No primary standard audited.

**INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED**

## 06 Feature blocks the profile leaving the die

HIGH

```
undercutFaceCount <= 0 regions
extr-undercuts
```

An extrusion is a constant profile pushed through a fixed opening. Any feature that is not open along the extrusion axis cannot exist in the extruded shape and must be machined afterwards.

**FIX** Remove the feature from the profile and machine it after extrusion, or reconsider the extrusion axis.

**SOURCE** Extrusion design guidance (constant profile along the extrusion axis).

**INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED**

## Machining and material removal

Material taken away by a tool. Cost follows access, setups and slenderness — how many directions the features are approached from, and how deep a tool has to reach.

24 RULES · 5 PROCESSES · 12 HIGH / 12 MEDIUM / 0 LOW · 4 CARRY MATERIAL-SPECIFIC THRESHOLDS

### Machining (CNC mill/turn)

7 RULES

#### 01 Thin web will chatter or deflect under the cutter

HIGH

```
wallP5Mm >= 1.5 mm
mach-thin-web
```

A thin unsupported web deflects away from the tool, so the cut is inaccurate and the surface chatters. It usually forces a finishing pass at reduced depth of cut, or a support fixture.

**FIX** Thicken the web, add a rib, or leave sacrificial support material to be removed last.

**SOURCE** General machining design guidance (workpiece rigidity).

**INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED**

**BY MATERIAL FAMILY**

|                          |                            |                           |
|--------------------------|----------------------------|---------------------------|
| <b>&gt;= 0.8</b> ferrous | <b>&gt;= 1</b> castiron    | <b>&gt;= 1.2</b> titanium |
| <b>&gt;= 1</b> aluminium | <b>&gt;= 1.2</b> magnesium | <b>&gt;= 2</b> plastic    |

#### 02 Tolerance tighter than machining holds

HIGH

```
tightestToleranceMm >= 0.05 mm total band
mach-tolerance-capability
```

A general machining tolerance of +/-0.025 mm (0.05 total) is routine on a rigid part. Tighter than that needs grinding, temperature control or in-process gauging, and each is a different cost base — not a tighter setting on the same machine.

**FIX** Open the tolerance to +/-0.025 mm or tighter only where the function needs it, and say WHICH feature needs it rather than applying a blanket tolerance to the drawing.

**SOURCE** General machining tolerance guidance (ISO 2768 fine class and shop practice).

**INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED**

**BY MATERIAL FAMILY**

|                            |                          |                             |
|----------------------------|--------------------------|-----------------------------|
| <b>&gt;= 0.08</b> titanium | <b>&gt;= 0.2</b> plastic | <b>&gt;= 0.05</b> aluminium |
|----------------------------|--------------------------|-----------------------------|

#### 03 Deep pocket relative to its width

HIGH

```
maxPocketDepthToWidth <= 4 depth/width
mach-pocket-depth-ratio
```

Beyond about 4:1 the cutter must be stepped down in a long, slender tool with reduced feed, and chip evacuation becomes the limiting factor. Cycle time rises faster than depth.

**FIX** Open the pocket out, split it across two setups, or accept a larger corner radius so a shorter, stiffer tool reaches the floor.

**SOURCE** General machining design guidance (tool L/D and chip-evacuation limits).

**INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED**

## 04 Surface a standard cutter cannot reach

HIGH

```
unreachableAreaPct <= 2 % of surface area
mach-tool-access
```

A face a cutter cannot physically get to is not a machining problem to be priced — it is a feature that has to be made another way. The usual answers are EDM, a long-reach or custom tool, an extra setup, or a redesign, and all four cost more than the feature looks like it should.

**FIX** Open the pocket or slot so a standard cutter fits, increase the internal corner radii, or split the feature so it can be approached from a face that is already being machined.

**SOURCE** General machining design guidance (tool reach and shank clearance). Measured by sweeping a cylinder of the tool diameter along each approach direction — the HOLDER and machine envelope are not modelled, so this is a lower bound on the access problem, not an upper one.

**INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED**

## 05 Hole deeper than five diameters

MEDIUM

```
maxHoleDepthToDia <= 5 depth/dia
mach-hole-depth-ratio
```

Past about 5x diameter a standard jobber drill stops clearing its own chips, so the cycle becomes a peck cycle — retract, clear, re-enter — and the tool wanders off centre. Past roughly 10x it is a gun-drilling or coolant-through operation on different equipment.

**FIX** Open the hole diameter, drill from both ends where the tolerance allows, or accept the deep-hole process and price it as one.

**SOURCE** General machining design guidance (chip evacuation and drill L/D limits).

**INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED**

**BY MATERIAL FAMILY**

<= 6 aluminium

<= 4 ferrous

<= 5 castiron

<= 3 titanium

<= 6 plastic

## 06 Features approached from many directions

MEDIUM

```
setupCount <= 3 setups
mach-setup-count · PRICED BY THE COST ENGINE
```

Each additional setup adds fixturing, re-datuming and its own tolerance stack. Setup time is charged whether the batch is 10 parts or 1000.

**FIX** Group features onto fewer faces, or design a fixture that presents several faces in one clamping.

**SOURCE** Setup-driven cost is modelled directly in machining-feature-cost.mjs.

**THIS TOOL'S OWN COST MODEL · NOT YET AUDITED**

**BY MATERIAL FAMILY**

<= 2 titanium

## 07 Internal corner radius forces a small cutter

MEDIUM

```
minInternalCornerRadiusMm >= 3 mm
mach-internal-corner-radius
```

An internal corner cannot be smaller than the cutter that makes it. A sharp internal corner on a drawing is either impossible or forces a very small, slow, fragile tool for the whole pocket.

**FIX** Specify the largest corner radius the function allows — often a third of the pocket depth — so a rigid cutter can be used.

**SOURCE** General machining design guidance (an internal corner radius equals the tool radius).

**INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED**



**01 Shaft too slender to turn without extra support****HIGH**

```
slendernessLtoD <= 8 length/dia
turn-slenderness
```

A bar held in the chuck at one end deflects away from the tool and chatters. Past about three diameters it needs a tailstock, and past roughly eight it needs a steady rest — another setup, another fixture and a cycle that is no longer a simple turn.

**FIX** Shorten the part, increase the diameter, or accept the steady rest and cost the extra setup.

**SOURCE** Turning practice: a slender workpiece whips without support; a tailstock extends the workable ratio and a steady rest extends it further. The 8:1 figure is the commonly-quoted tailstock-supported limit. Reported from practitioner discussion rather than a design standard, and it is the threshold in this family most worth checking against your own machines.

INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED

**02 Tolerance tighter than turning holds****HIGH**

```
tightestToleranceMm >= 0.02 mm total band
turn-tolerance-capability
```

A lathe holds a diameter better than a mill holds a position: the part spins on one axis and the tool moves on two. Below about 0.02 mm total the feature is ground or honed, not turned.

**FIX** Open the tolerance, or add a grinding operation and leave stock for it.

**SOURCE** Turning is quoted as holding tighter diametral tolerances than general milling. Positioned below the 0.05 mm general-machining band used elsewhere in this catalogue. DERIVED from that ordering; no primary standard audited.

INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED

**03 Bore too deep for a boring bar****MEDIUM**

```
maxHoleDepthToDia <= 4 depth/dia
turn-hole-depth-ratio
```

A bore on a lathe is opened by a boring bar cantilevered from the turret. The bar has to fit inside the hole, so its own slenderness is set by the feature it is cutting, and past about four diameters it chatters and leaves a tapered bore.

**FIX** Open the diameter, shorten the bore, or use a damped or carbide bar and accept the tooling cost.

**SOURCE** Boring-bar practice: a steel bar is used to about 4:1 overhang and a carbide or damped bar beyond that. Positioned just below the general machining hole limit used elsewhere in this catalogue (5:1), because a boring bar is more constrained than a drill. DERIVED from that ordering, not quoted.

INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED

**04 Internal corner sharper than a standard insert nose****MEDIUM**

```
minInternalCornerRadiusMm >= 0.4 mm
turn-internal-corner-radius
```

A turned internal corner is the radius of the insert nose that cut it. Standard ISO turning inserts come at 0.2, 0.4, 0.8 and 1.2 mm, and the smaller the nose the weaker the edge and the poorer the finish. Below 0.4 mm the corner is a grinding or EDM feature, not a turned one — and this is where turning beats milling by an order of magnitude, because a milled corner starts at the cutter radius.

**FIX** Open the corner to at least 0.4 mm, or accept a 0.2 mm nose and the reduced feed and edge life that come with it.

**SOURCE** Standard ISO turning insert nose radii (0.2 / 0.4 / 0.8 / 1.2 mm); the corner a turned feature carries is the nose radius of the insert that produced it. Widely published across insert catalogues; no primary standard audited.

INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED

## 05 Wall too thin to hold in a chuck

MEDIUM

```
wallP5Mm >= 1.5 mm
turn-thin-web
```

A thin-walled turned part distorts in the chuck jaws before the tool touches it, and springs back out of round when it is released. The bore that measured perfectly in the machine is oval on the bench.

**FIX** Thicken the wall, or use soft jaws or an expanding mandrel and cost the fixture.

**SOURCE** The same thin-web limit the general machining family uses (1.5 mm), which is a cutting-force argument that applies equally to a lathe. Shared deliberately rather than restated with a different number.

INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED

## Deep-hole / gun drilling

4 RULES

### 01 Hole deeper than a gun drill reaches

HIGH

```
maxHoleDepthToDia <= 100 depth/dia
gundrill-hole-ld
```

A gun drill is a single-flute tool with coolant fed down its centre and chips carried out along an external vee. That is what lets it run to a hundred diameters where a twist drill is finished at five to ten. Past a hundred the tool wanders and the bore runs off, and the job needs BTA or a counter-bored approach from both ends.

**FIX** Shorten the hole, open the diameter, or drill from both ends and accept the step where they meet.

**SOURCE** Deep-hole drilling guidance: gun drills reach depth-to-diameter ratios of 100:1 and beyond, against roughly 5-10:1 for a conventional twist drill; past about 40:1 a dedicated deep-hole machine gives markedly better accuracy. Consistent across deep-hole machine builders; no primary standard audited.

INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED

### 02 Tolerance tighter than a gun-drilled bore holds

HIGH

```
tightestToleranceMm >= 0.05 mm total band
gundrill-tolerance-capability
```

A gun-drilled bore is straight and round to a degree no twist drill approaches, but it is still a drilled hole a long way from its entry. A tighter band than the general machining limit means honing or reaming after it.

**FIX** Open the tolerance, or hone the bore and leave stock for it.

**SOURCE** The general machining band used elsewhere in this catalogue (0.05 mm total), applied unchanged because a gun-drilled bore is a drilled feature. Shared deliberately rather than restated with a different number.

INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED

### 03 Hole above the gun-drill diameter range

MEDIUM

```
maxHoleDiaMm <= 30 mm dia
gundrill-max-dia
```

Above about 30 mm the chip volume outgrows the vee flute and the process changes: BTA takes the chips back through the middle of the tool instead. It is a different machine and a different quotation, not a bigger gun drill.

**FIX** Quote the large bore as BTA or trepanning; the small ones can stay on the gun drill.

**SOURCE** Gun drilling is quoted for diameters of about 1-30 mm; larger deep holes move to BTA or ejector drilling. Consistent across deep-hole machine builders; no primary standard audited.

INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED





#### 04 Hole below the gun-drill diameter range

MEDIUM

```
minHoleDiaMm >= 1 mm dia
gundrill-min-dia
```

A gun drill has to carry a coolant passage down its own centre, so there is a diameter below which there is no tool. Under about 1 mm the hole is EDM-drilled, not gun-drilled.

**FIX** Open the hole to at least 1 mm, or quote it as a fast-hole EDM feature.

**SOURCE** Gun drilling is quoted for diameters of about 1-30 mm, most commonly 2-20 mm. Consistent across deep-hole tooling suppliers; no primary standard audited.

**INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED**

### Broaching

4 RULES

#### 01 Hole too deep to broach

HIGH

```
maxHoleDepthToDia <= 5 depth/dia
broach-hole-ld
```

The broach has to be longer than the feature by its whole cutting length, and it carries every chip it has cut along with it. Past about five diameters the tool is unwieldy, the chip packing is unmanageable and the pull load rises past what the machine will give.

**FIX** Shorten the feature, open it, or broach from both ends.

**SOURCE** Broaching process guidance: the depth-to-diameter ratio of a broached hole is generally not more than 5. No primary standard audited.

**INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED**

#### 02 Blind features cannot be broached

HIGH

```
blindHoleCount <= 0 blind features
broach-no-blind
```

A broach is pulled or pushed straight through the workpiece, each tooth taking a little more than the last. There is nowhere for it to stop and nowhere for the chips to go if it does. A blind feature is a milling, EDM or rotary-broaching job.

**FIX** Take the feature through, or use rotary broaching, which can form a blind profile to a shallow depth.

**SOURCE** Broaching process guidance: blind holes, deep holes, stepped holes and obstructed outer surfaces cannot be processed by broaching. No primary standard audited.

**INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED**

#### 03 Feature above the broachable size range

MEDIUM

```
maxHoleDiaMm <= 100 mm dia
broach-max-dia
```

Above about 100 mm the broach and the load needed to pull it both outgrow the standard machine, and the feature is bored or milled instead.

**FIX** Bore or mill the large feature; broaching stays worthwhile on the small ones.

**SOURCE** Broaching process guidance: broached hole diameters run generally from 10 to 100 mm. No primary standard audited.

**INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED**

#### 04 Feature below the broachable size range

MEDIUM

```
minHoleDiaMm >= 10 mm dia
broach-min-dia
```

A broach small enough for a fine hole has no cross-section left to carry the pull load, and it snaps inside the part.

**FIX** Open the feature, or produce it by wire EDM — which is what most small internal splines and keyways actually are.

**SOURCE** Broaching process guidance: broached hole diameters run generally from 10 to 100 mm. No primary standard audited.

INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED

### Wire EDM

4 RULES

#### 01 Blind features cannot be wire-cut

HIGH

```
blindHoleCount <= 0 blind features
wedm-no-blind-features
```

Wire EDM threads a wire through a start hole and cuts a profile straight through the part. There is no way to stop part-way and leave a floor. A blind feature on a wire-cut part is a separate milling or sinker-EDM operation, and it is usually the one nobody quoted.

**FIX** Take the feature through, or quote the blind feature as a separate operation — sinker EDM if the corner needs to stay sharp, milling if it does not.

**SOURCE** Wire EDM process guidance: the wire cuts a through profile and cannot produce a blind pocket or hole. Derived from the process, not quoted from a design guide.

INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED

#### 02 Tolerance tighter than wire EDM holds

HIGH

```
tightestToleranceMm >= 0.01 mm total band
wedm-tolerance-capability
```

Wire EDM is the most accurate route in this catalogue and this is where it earns its cycle time — but it is not unlimited, and below about 0.01 mm total the part is being jig-ground or lapped.

**FIX** Open the tolerance, or move that feature to grinding.

**SOURCE** Wire EDM is quoted as holding beyond +/-0.005 mm with multi-pass skim cutting. The total band used here is twice that single-sided figure. No primary standard audited.

INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED

#### 03 Internal corner sharper than the wire can turn

MEDIUM

```
minInternalCornerRadiusMm >= 0.15 mm
wedm-internal-corner-radius
```

The smallest inside corner a wire can leave is its own radius plus the spark gap — about 0.15 mm on a standard 0.25 mm wire. This is the number that decides whether a die plate is wire-cut or milled: an end mill cannot go below its own radius, and that is twenty times coarser.

**FIX** Open the corner to at least 0.15 mm, or specify a finer wire (0.10 mm reaches about 0.06 mm) and accept the slower cut.

**SOURCE** Wire EDM design guidance: minimum internal corner radius is approximately the wire RADIUS plus the spark gap — a 0.25 mm wire gives roughly 0.13-0.15 mm, and a 0.10 mm wire about 0.06 mm at reduced cutting speed. Consistent across several EDM suppliers; no primary standard audited.

INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED



## 04 Web too thin even for a no-force process

MEDIUM

```
wallP5Mm >= 0.2 mm
wedm-thin-web
```

The wire exerts no cutting force, which is exactly why wire EDM leaves webs a milling cutter would tear off — the general machining limit of 1.5 mm does not apply here and applying it would reject a part the process handles easily. What does still apply is the flushing pressure and the part's own handling: below about 0.2 mm the web bends when the part is taken out of the tank.

**FIX** Thicken the web, or leave tabs and remove them after the part is out of the machine.

**SOURCE** Wire EDM removes material by spark erosion with no mechanical cutting force, so its thin-web limit is set by flushing and handling rather than by deflection. The value is positioned an order of magnitude below the 1.5 mm milling limit used elsewhere in this catalogue. DERIVED from that ordering, not quoted.

**INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED**

## Polymers, rubber and composites

Melt or resin into a tool. Wall thickness governs both fill and cycle time, so it drives piece price twice over.

29 RULES · 5 PROCESSES · 15 HIGH / 11 MEDIUM / 3 LOW · 6 CARRY MATERIAL-SPECIFIC THRESHOLDS

### Injection moulding

9 RULES

#### 01 Wall thickness outside the practical moulding range

HIGH

wallP50Mm in 1 to 3 mm

im-wall-thickness-range · PRICED BY THE COST ENGINE

Below about 1 mm the cavity is hard to fill before the melt freezes; above about 3 mm the part is cooling-limited, so cycle time climbs roughly with the square of the wall and sink marks appear over thick sections.

**FIX** Core out thick sections to a uniform nominal wall and add ribs for stiffness instead of solid mass.

**SOURCE** Injection-moulding design guidance; practical range for engineering thermoplastics.

**INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED**

##### BY MATERIAL GRADE

|                                   |                               |                                       |
|-----------------------------------|-------------------------------|---------------------------------------|
| <b>1.2-3.5</b> PC/ABS blend       | <b>0.8-3</b> PBT              | <b>1.2-4</b> PP-T20 (talc-filled)     |
| <b>1-3.5</b> PET                  | <b>0.8-3</b> PPS              | <b>1-4</b> PEEK                       |
| <b>1-4</b> TPU (thermoplastic PU) | <b>1-5</b> HDPE               | <b>0.8-3</b> Polypropylene (PP)       |
| <b>1.2-3.5</b> ABS                | <b>0.8-3</b> PA6 (Nylon)      | <b>1.5-4</b> PA66-GF30 (glass-filled) |
| <b>0.8-3</b> POM (Acetal)         | <b>1-4</b> Polycarbonate (PC) |                                       |

#### 02 Tolerance tighter than injection moulding holds

HIGH

tightestToleranceMm >= 0.2 mm total band

im-tolerance-capability

Moulding tolerance is dominated by shrinkage, which varies with fill, pack and the batch of resin. About 0.2 mm total on a 50 mm dimension is normal for an engineering thermoplastic; a filled or semi-crystalline grade is worse, not better.

**FIX** Open the tolerance, or machine the feature after moulding and price the secondary operation.

**SOURCE** Injection-moulding dimensional tolerance guidance (DIN 16901 / SPI commercial class).

**INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED**

##### BY MATERIAL GRADE

|                             |                                  |                                        |
|-----------------------------|----------------------------------|----------------------------------------|
| >= <b>0.22</b> PC/ABS blend | >= <b>0.35</b> PBT               | >= <b>0.3</b> PP-T20 (talc-filled)     |
| >= <b>0.5</b> HDPE          | >= <b>0.25</b> PEEK              | >= <b>0.25</b> PPS                     |
| >= <b>0.35</b> POM (Acetal) | >= <b>0.35</b> PA6 (Nylon)       | >= <b>0.3</b> PA66-GF30 (glass-filled) |
| >= <b>0.2</b> ABS           | >= <b>0.2</b> Polycarbonate (PC) |                                        |

#### 03 Rib too thick at its base for the wall it stands on

MEDIUM

maxRibThicknessToWall <= 0.6 rib t / wall t

im-rib-thickness-max · PRICED BY THE COST ENGINE

A rib meeting the wall at more than about 60% of the wall thickness makes a heavy junction that is the last place to solidify. It shows as a sink mark on the opposite — usually visible — surface, and as a void inside the section.

**FIX** Thin the rib to 40–60% of the nominal wall and add more ribs, or gusset it, if stiffness is lost.

**SOURCE** Injection-moulding design guidance (rib base 40-60% of nominal wall). Widely published, and actively DISPUTED by practising moulders — Mack Molding publish "Why 60% Rib-to-Wall Ratio is NOT Sacred", arguing the limit depends on resin, texture and whether the opposite face is cosmetic. Treat as a screening threshold, not a specification.

**INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED**

##### BY MATERIAL GRADE

|                            |                                  |                                        |
|----------------------------|----------------------------------|----------------------------------------|
| <= <b>0.5</b> PBT          | <= <b>0.5</b> HDPE               | <= <b>0.6</b> PP-T20 (talc-filled)     |
| <= <b>0.5</b> POM (Acetal) | <= <b>0.5</b> PA6 (Nylon)        | <= <b>0.6</b> PA66-GF30 (glass-filled) |
| <= <b>0.6</b> ABS          | <= <b>0.6</b> Polycarbonate (PC) |                                        |

04

Wall area below the minimum draft angle

HIGH

```
wallAreaBelowDraftPct <= 5 % of wall area
im-draft-minimum · measured only on faces below 1 deg
```

A wall with no draft drags on the core as the part ejects, scuffing the surface and raising ejection force. Textured surfaces need considerably more draft than smooth ones.

**FIX** Add at least 0.5 to 1 degree per side on smooth walls; allow 2 to 5 degrees where the surface is textured.

**SOURCE** Injection-moulding design guidance (0.5–1 deg/side smooth, 2–5 deg textured).

**INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED**

05

Undercuts require side actions

HIGH

```
undercutFaceCount <= 0 regions
im-undercuts
```

Any feature the two mould halves cannot form in a straight pull needs a slide, lifter or collapsible core. Each mechanism adds tooling cost, adds a moving part that can wear, and lengthens the cycle.

**FIX** Redesign the feature so it forms in the draw direction, relocate the parting line, or accept the side action with its tooling cost priced in.

**SOURCE** Injection-moulding design guidance (side actions add roughly \$500–\$5,000 of tooling per feature).

**INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED**

06

Boss taller than three times its diameter

MEDIUM

```
maxBossHeightToDia <= 3 height/dia
im-boss-height
```

A tall boss is formed by a long, slender core pin standing alone in the cavity. The melt front pushes it sideways, so the hole drifts off position and the pin fatigues; the boss itself is also a thick section that sinks on the show surface behind it.

**FIX** Shorten the boss, or support it with gussets and blend it into a nearby wall so the core pin is not standing free.

**SOURCE** Injection-moulding design guidance (boss height  $\leq 3 \times$  outside diameter; support tall bosses with ribs or gussets).

**INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED**

**BY MATERIAL GRADE**

$\leq 2.5$  PA66-GF30 (glass-filled)  $\leq 3$  Polycarbonate (PC)

07

Rib taller than three wall thicknesses

MEDIUM

```
maxRibHeightToWall <= 3 rib h / wall t
im-rib-height
```

A tall thin rib is a long dead-end for the melt and a deep, narrow slot in the tool steel that is hard to vent and hard to cool. It also grips the core on ejection, so it needs more draft than the rest of the part.

**FIX** Cap the rib at about 3x the nominal wall and use two or three shorter ribs, or a cross-rib, to recover the section modulus.

**SOURCE** Injection-moulding design guidance (rib height  $\leq 3 \times$  nominal wall).

**INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED**

**BY MATERIAL GRADE**

$\leq 2.5$  POM (Acetal)  $\leq 2.5$  PA6 (Nylon)

## 08 Non-uniform wall thickness

MEDIUM

```
wallSpreadRatio <= 0.6 (p95-p5)/p50
im-wall-uniformity
```

Uneven walls cool at different rates, which drives differential shrinkage — the usual root cause of warp, sink and locked-in stress. Transitions should be tapered rather than stepped.

**FIX** Even out the nominal wall; where a change is unavoidable, blend it over about a 3:1 taper.

**SOURCE** Injection-moulding design guidance (3:1 transition rule).

**INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED**

## 09 Rib too thin to fill reliably

LOW

```
minRibThicknessToWall >= 0.4 rib t / wall t
im-rib-thickness-min
```

A rib much below 40% of the wall is a narrow, high-resistance flow path off the main cavity. It fills late or not at all, and a short-shot rib contributes none of the stiffness it was drawn for.

**FIX** Take the rib back up to 40% of the wall, or delete it and thicken the wall locally instead.

**SOURCE** Injection-moulding design guidance (rib base 40-60% of nominal wall). See the rib-thickness-max note: the 60% figure is disputed by practising moulders and depends on resin and cosmetics.

**INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED**

**BY MATERIAL GRADE**

**>= 0.5** PA66-GF30 (glass-filled)      **>= 0.3** Polypropylene (PP)

## Rubber moulding

6 RULES

### 01 Local section below the process minimum

HIGH

```
wallP5Mm >= 0.8 mm
rubber-min-section
```

Uncured rubber is stiff and slow-flowing. A local section below about 0.8 mm will not fill before the compound scorches.

**FIX** Thicken the thinnest region, or move the feature to where the section is already full.

**SOURCE** Process minimum-section guidance. Checked on the 5th-percentile wall, which is the thinnest measured place rather than the nominal.

**INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED**

### 02 Tolerance tighter than rubber moulding holds

HIGH

```
tightestToleranceMm >= 0.5 mm total band
rubber-tolerance-capability
```

Rubber shrinks heavily on cure and keeps moving afterwards, and it deforms under its own measurement. Tolerances are graded (RMA A/B/C) and even the closest is loose against a rigid part.

**FIX** Use a graded rubber tolerance class rather than a machined-part tolerance, and dimension in the free state.

**SOURCE** RMA rubber dimensional tolerance classes.

**INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED**

### 03 Wall thickness outside the practical rubber-moulding range MEDIUM

```
wallP50Mm in 1 to 6 mm
rubber-wall-thickness-range
```

Rubber cures from the outside in, and cure time rises with the square of the section — a thick part is a slow part and risks an under-cured core. Below about 1 mm the uncured compound will not fill reliably.

**FIX** Hold 2-4 mm as the nominal section and hollow out heavy masses.

**SOURCE** Rubber moulding design guidance (cure time against section thickness).

**INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED**

### 04 Non-uniform section cures unevenly MEDIUM

```
wallSpreadRatio <= 0.8 (p95-p5)/p50
rubber-wall-uniformity
```

The cure is set by the thickest section, so a part with one heavy region holds the whole press open while the thin regions over-cure and lose elongation.

**FIX** Even out the section, or hollow the heavy region.

**SOURCE** Rubber moulding design guidance (cure uniformity).

**INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED**

### 05 Wall area below the minimum rubber-moulding draft LOW

```
wallAreaBelowDraftPct <= 15 % of wall area
rubber-draft-minimum · cutoff 0.5 deg
```

Rubber is elastic and strips off modest undercuts and zero-draft walls that would lock a rigid part in the tool. Draft helps but is rarely the constraint.

**FIX** Allow 0.5-1 degree where it is free; a zero-draft rubber wall is usually acceptable.

**SOURCE** Rubber moulding design guidance (elastic recovery permits low draft).

**INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED**

### 06 Undercuts complicate the tool LOW

```
undercutFaceCount <= 0 regions
rubber-undercuts
```

Rubber strips off undercuts that would lock a rigid part in the tool — that elasticity is a genuine design freedom. Each one still slows demoulding and eventually tears the part, so the count is a cycle-time driver.

**FIX** Keep undercuts shallow enough to strip, or split the tool where they are deep.

**SOURCE** Process tooling guidance (split lines, loose pieces and cores).

**INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED**

## Thermoforming (vacuum / pressure)

4 RULES

### 01 Wall area below the minimum thermoforming draft HIGH

```
wallAreaBelowDraftPct <= 5 % of wall area
tf-draft-minimum · cutoff 2 deg
```

The sheet shrinks onto the tool as it cools. On a male tool it grips hard and needs 4-6 degrees; on a female tool it pulls away and 1.5-2 will do. Two degrees is the floor either way, and a vertical wall on a male tool will not come off at all.

**FIX** Add at least 2° to every drawn wall — and 4-6° if the part forms over a male tool rather than into a cavity.

**SOURCE** Thermoforming design guidance: 1.5-2° on vertical female features (part formed into the mould) and 4-6° on male features (part formed over the mould). The lower figure is used as the floor because this engine cannot tell male tooling from female. No primary standard audited.

**INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED**

## 02 Draw deeper than the sheet will stretch evenly

HIGH

```
drawDepthToWidth <= 1 depth/width
tf-draw-ratio
```

The sheet is one thickness before forming and it has to cover the whole tool. Everything drawn deep is drawn thin, and past a depth equal to the width the corners of the part carry a fraction of the wall the flange still has. Beyond this the part needs plug assist — a second tool that pre-stretches the sheet — and that is a different quotation.

**FIX** Reduce the depth, widen the part, or accept plug-assisted forming and cost the plug.

**SOURCE** Thermoforming design guidance: for depth-to-width ratios exceeding 1:1, plug-assisted female forming is normally needed to keep material distribution acceptable; 3:1 is quoted as the outer limit. The 1:1 point is used because it is where the PROCESS changes rather than where it fails. No primary standard audited.

INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED

## 03 Tolerance tighter than thermoforming holds

HIGH

```
tightestToleranceMm >= 1 mm total band
tf-tolerance-capability
```

Only one face of a thermoformed part touches the tool; the other is free and its position depends on how the sheet happened to thin. Anything tight is trimmed or machined afterwards, not formed.

**FIX** Put the tight dimension on the tool side, or trim it after forming.

**SOURCE** Thermoforming is the loosest of the plastic-forming routes in this catalogue: the sheet contacts one tool face only and the wall thins unevenly. Positioned above the rotational-moulding and injection-moulding bands used elsewhere here. DERIVED from that ordering, not quoted.

INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED

## 04 Undercuts trap the sheet on the tool

HIGH

```
undercutFaceCount <= 0 regions
tf-undercuts
```

A formed sheet is stripped off the tool along the draw axis while it is still warm. A re-entrant feature holds it, and the part tears or stays on the tool.

**FIX** Remove the re-entrant feature, or use a split or collapsible tool and cost it.

**SOURCE** Thermoforming tool practice: the part is stripped along the draw axis. Derived from the process, not quoted from a design guide.

INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED

# Rotational moulding

4 RULES

## 01 Wall thinner than rotational moulding can build

HIGH

```
wallP5Mm >= 3 mm
rm-min-wall
```

The wall is built by powder sticking to a hot mould, tumble after tumble. There is no pressure to push it anywhere. Below about 3 mm the coverage is a matter of luck, and the risk is not a thin wall but a hole.

**FIX** Thicken the wall to at least 3 mm, or blow-mould the part instead.

**SOURCE** Rotational moulding design guidance: use a minimum wall of 3 mm and a maximum of 10 mm; below roughly 1.9 mm (0.075 in) areas of the part risk inadequate or zero thickness. No primary standard audited.

INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED





## 02 Undercuts cannot be pulled from a rotational mould

HIGH

```
undercutFaceCount <= 0 regions
rm-undercuts
```

A rotational mould is a shell that splits and is opened by hand. There is no ejection mechanism and no slide, so a re-entrant feature has to come off by flexing the part — which works on a thin flexible wall and not on anything else.

**FIX** Remove the re-entrant feature, or design it shallow enough that the part flexes off.

**SOURCE** Rotational moulding tool practice: split shell moulds opened manually, with no ejection system. Derived from the process, not quoted from a design guide.

INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED

## 03 Wall area below the minimum rotational-moulding draft

MEDIUM

```
wallAreaBelowDraftPct <= 5 % of wall area
rm-draft-minimum · cutoff 1 deg
```

The part shrinks onto the mould as it cools and has to be pulled off by hand. A degree or two of taper is what makes that possible without a puller.

**FIX** Add 1-2° of draft to every vertical wall; more on a textured surface.

**SOURCE** Rotational moulding design guidance: draft angles of generally 1-2°, varying with the shrinkage of the polymer. No primary standard audited.

INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED

## 04 Wall thicker than the cycle will fuse

MEDIUM

```
wallP50Mm <= 10 mm
rm-max-wall
```

Heat reaches the powder through the mould, so a thick wall means a long cycle and an inner surface that is still fusing while the outer one degrades. This is one of the few processes with a MAXIMUM wall as well as a minimum.

**FIX** Thin the wall and add ribs or a kiss-off, or move to a pressure process.

**SOURCE** Rotational moulding design guidance: minimum 3 mm, maximum 10 mm nominal wall. No primary standard audited.

INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED

## Composite layup / RTM

6 RULES

## 01 Local section below the process minimum

HIGH

```
wallP5Mm >= 1 mm
rtm-min-section
```

A laminate cannot be thinner than the plies it is built from. Below about 1 mm there are too few plies to lay up repeatably and the resin flow front stalls.

**FIX** Thicken the thinnest region, or move the feature to where the section is already full.

**SOURCE** Process minimum-section guidance. Checked on the 5th-percentile wall, which is the thinnest measured place rather than the nominal.

INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED



## 02 Tolerance tighter than composite layup / rtm holds

HIGH

```
tightestToleranceMm >= 0.5 mm total band
rtm-tolerance-capability
```

A laminate takes the tool surface accurately on the tool side and the bag or second tool side less so, and it springs in as it cures off a corner. Thickness varies with fibre volume fraction.

**FIX** Tolerance from the tool face, and allow for spring-in at every corner.

**SOURCE** Composite moulding tolerance guidance (tool-side vs bag-side, cure spring-in).

**INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED**

## 03 Undercuts trap the cured part in the tool

HIGH

```
undercutFaceCount <= 0 regions
rtm-undercuts
```

A cured laminate has no give. An undercut needs a split or collapsible tool, which multiplies tooling cost and cycle time.

**FIX** Re-orient the part on the tool split line, or bond the undercut feature on as a secondary part.

**SOURCE** Composite tooling design guidance (split tools and collapsible cores).

**INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED**

## 04 Wall area below the minimum RTM draft

MEDIUM

```
wallAreaBelowDraftPct <= 5 % of wall area
rtm-draft-minimum · cutoff 1 deg
```

A cured laminate is stiff and grips a matched tool hard. Without draft it cannot be released without damaging the part or the tool surface.

**FIX** Allow 1-3 degrees on all tool-contact surfaces.

**SOURCE** Composite tooling design guidance (part release from matched moulds).

**INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED**

## 05 Section varies more than the process tolerates

MEDIUM

```
wallSpreadRatio <= 0.8 (p95-p5)/p50
rtm-uniformity
```

Resin flows fastest through the thickest part of the preform, so an uneven laminate traps dry spots at the flow-front convergence. Thickness change is also where a laminate delaminates.

**FIX** Even out the ply count, and taper thickness changes over at least 20:1 rather than stepping them.

**SOURCE** Composite design guidance on uniform laminate thickness. A resin-transfer laminate is built from plies of a fixed thickness, so a section change is a ply drop – a stress raiser and a resin-rich pocket. The band sits with the bulk-forming families in this catalogue rather than the casting ones. DERIVED from that ordering, not quoted.

**INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED**

## 06 Laminate thickness outside the practical RTM range

MEDIUM

```
wallP50Mm in 1.5 to 10 mm
rtm-wall-thickness-range
```

A laminate is built from plies of finite thickness, so a very thin wall has too few plies to be laid up repeatably, and a very thick one is slow to wet out and exotherms as it cures.

**FIX** Hold 2-5 mm and vary stiffness through the lay-up and ply orientation rather than through thickness.

**SOURCE** RTM / resin-transfer moulding design guidance (ply count and cure exotherm).

**INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED**

## Powder and additive

Built up rather than cut down. Density, aspect ratio and — for additive — build orientation replace the usual mould-opening constraints.

15 RULES · 3 PROCESSES · 11 HIGH / 4 MEDIUM / 0 LOW · 0 CARRY MATERIAL-SPECIFIC THRESHOLDS

### Powder metallurgy (press & sinter)

6 RULES

#### 01 Wall thinner than the tooling will survive

HIGH

```
wallP5Mm >= 1.52 mm
pm-min-wall
```

A thin wall in the part is a thin blade in the die, and that blade takes the full compaction pressure on every stroke. The limit is set by tool life, not by the powder.

**FIX** Thicken the wall to at least 1.5 mm; a long thin wall is worse than a short one at the same thickness.

**SOURCE** Powder metallurgy design guidance: wall thickness should not be less than 1.52 mm (0.060 in), and long thin walls make the tooling fragile and shorten its service life. No primary standard audited.

INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED

#### 02 Powder column too deep for its wall — density will vary

HIGH

```
pressDepthToWallRatio <= 8 depth/wall
pm-press-depth-ratio
```

Powder does not flow. It is compacted along one axis and friction against the die wall means the density falls away from the punch face, so a deep column in a thin wall comes out dense at the top and soft at the bottom. That gradient is not visible, it does not sinter out, and it is measured as a strength difference in the finished part.

**FIX** Reduce the depth, thicken the wall, or split the part — a double-action press buys some depth but does not remove the gradient.

**SOURCE** Powder metallurgy design guidance: density variations become unavoidable once the length-to-wall-thickness ratio passes about 8:1. Related figures in circulation are an overall aspect ratio limit of 3:1 even with double-ended compaction, and L/D limits of 2 for a single-action press and 4 for a double-action one. The 8:1 wall figure is used because it is the one stated against WALL thickness, which is what this measure reads. No primary standard audited.

INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED

#### 03 Features approached from more than the press axis

HIGH

```
setupCount <= 1 directions
pm-single-press-axis
```

Compaction and ejection both happen along one vertical axis. A feature that needs a second approach direction — a cross hole, a side pocket, a transverse slot — cannot be pressed at all. It is a machining operation on a sintered blank, and it is usually the one missing from the quotation.

**FIX** Move the feature onto the press axis, or quote the cross-feature as secondary machining.

**SOURCE** Powder metallurgy design guidance: because powder compaction and ejection both occur along a vertical axis, there can be no obstructions in the press direction; undercuts and transverse holes cannot be formed directly and must be produced by secondary machining. No primary standard audited.

INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED

#### 04 Tolerance tighter than pressing and sintering holds

HIGH

```
tightestToleranceMm >= 0.1 mm total band
pm-tolerance-capability
```

In the press plane the die sets the dimension and PM is very repeatable — that is why it competes with machining at all. Along the press axis the fill and the sintering shrinkage both move it. A band under about 0.1 mm total is sized or machined afterwards.

**FIX** Open the tolerance, or add a sizing operation and cost it.

**SOURCE** Powder metallurgy is dimensionally repeatable in the press plane and less so along the press axis, where fill variation and sintering shrinkage act. Positioned between the cold-forging and general-machining bands used elsewhere in this catalogue. DERIVED from that ordering, not quoted.

**INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED**

#### 05 Undercuts cannot be pressed

HIGH

```
undercutFaceCount <= 0 regions
pm-undercuts
```

The same single-axis argument, in the other direction: the compact is ejected by the punch that formed it and nothing can be re-entrant to that motion.

**FIX** Remove the undercut, or machine it into the sintered part.

**SOURCE** Powder metallurgy design guidance: no obstructions in the press direction; undercuts must be produced by secondary machining. No primary standard audited.

**INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED**

#### 06 Hole too small to press

MEDIUM

```
minHoleDiaMm >= 1.5 mm dia
pm-min-hole
```

A hole in a pressed part is a core rod standing in the die through the whole compaction stroke. Below about 1.5 mm the rod is too slender to survive the pressure cycle and it is drilled into the sintered blank instead — a secondary operation on a process bought for being net-shape.

**FIX** Open the hole to at least 1.5 mm, or quote the drilling as a secondary operation.

**SOURCE** Powder metallurgy design guidance: the minimum recommended hole diameter is 1.5 mm (0.060 in), alongside a minimum wall of 1.52 mm. No primary standard audited.

**INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED**

### Metal injection moulding (MIM)

5 RULES

#### 01 Section too thick to debind

HIGH

```
wallP50Mm <= 12.5 mm
mim-max-wall
```

Every gram of binder in the middle of the part has to travel out through the part to get away. Past about 12.5 mm the centre is still debinding when the outside has started to sinter, and the result is a part with a core defect nobody can see.

**FIX** Core out the heavy section, or split the part — 1.3 to 6.3 mm is where MIM is comfortable.

**SOURCE** MIM design guidance: wall thicknesses of 1.3-6.3 mm are preferred, and sections thicker than 12.5 mm should be avoided. No primary standard audited.

**INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED**



## 02 Wall thinner than a MIM feedstock will fill

HIGH

```
wallP5Mm >= 0.5 mm
mim-min-wall
```

A MIM feedstock is a metal powder in a binder — far more viscous than a neat polymer. Below about 0.5 mm it will not fill, and what does fill will not survive debinding.

**FIX** Thicken the section to at least 0.5 mm.

**SOURCE** MIM design guidance: minimum wall thickness 0.5 mm. No primary standard audited.

**INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED**

## 03 Tolerance tighter than MIM holds

HIGH

```
tightestToleranceMm >= 0.1 mm total band
mim-tolerance-capability
```

A MIM part shrinks by around a fifth on sintering, uniformly if everything went right. The tolerance is a percentage of the dimension, so a band that is generous on a 40 mm feature is impossible on a 4 mm one.

**FIX** Open the tolerance, or machine the one feature that needs it after sintering.

**SOURCE** MIM tolerances are quoted as a PERCENTAGE of dimension (of order +/-0.3%), which this engine cannot express — it reads one tightest band in millimetres. The flat value here is a screening figure only; see UNWRITTEN\_RULES for what a percentage-of-dimension rule would need. DERIVED, not quoted.

**INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED**

## 04 Internal corner sharper than a MIM part will survive

MEDIUM

```
minInternalCornerRadiusMm >= 0.2 mm
mim-corner-radius
```

A sharp internal corner is a stress raiser in the green part, which is chalk-fragile between moulding and sintering. It cracks there while it is being handled, long before anyone loads it.

**FIX** Put a radius of at least 0.2 mm in every internal corner.

**SOURCE** MIM design guidance: corner radius greater than 0.2 mm. No primary standard audited.

**INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED**

## 05 Undercuts need a slide or a collapsible core

MEDIUM

```
undercutFaceCount <= 0 regions
mim-undercuts
```

MIM CAN mould an undercut — with a slide, or a collapsible core — which is the one thing it does that press-and-sinter cannot. What it cannot do is make it cheap: the mechanism costs tooling and brings flash with it.

**FIX** Remove the undercut, or accept the slide and cost it — it is still likely cheaper than the machining press-and-sinter would need.

**SOURCE** MIM design guidance: undercuts can be moulded using slides or collapsible cores — an advantage over conventional powder metallurgy — but the added cost and potential flashing mean internal undercuts are avoided in most MIM designs. No primary standard audited.

**INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED**

# Laser powder bed fusion (DMLS / SLM)

4 RULES

## 01 Wall thinner than the melt pool can stand up

HIGH

```
wallP5Mm >= 0.4 mm
lpbf-min-wall
```

A wall a laser-track wide has nothing to conduct heat into but the track below it. It warps as it builds and it may not survive depowdering.

**FIX** Thicken the wall to at least 0.4 mm, and to 0.6 mm if it is tall or free-standing.

**SOURCE** Powder-bed fusion design guidance: a strut or thin-wall diameter of at least 0.4-0.6 mm should be chosen. No primary standard audited.

INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED

## 02 Downward surface too shallow to build without support

HIGH

```
overhangAreaBelowDeg <= 10 % of surface area
lpbf-overhang-45
```

A downward-facing surface is built onto loose powder, and loose powder does not conduct heat away. Below about 45 degrees from the plate the melt pool sinks in, the surface dross-forms and the geometry drifts — so the region needs a support, which has to be built, cut off, and the witness dressed. Support is not a small cost: it is often the largest single line in an AM quotation.

**FIX** Re-orient the part on the plate, add a self-supporting chamfer to shallow faces, or re-model horizontal holes as teardrops — a teardrop whose top angle stays at or above 45° builds at almost any diameter.

**SOURCE** Powder-bed fusion design guidance: 45° is the widely-used self-supporting threshold, and teardrop features with a 45° top angle show no significant material fall-in. Material and parameter dependent – some alloy and parameter sets self-support below this, and lattice struts want better than 25°. The rule reads the 45° point off a curve so a different angle can be asked for. No primary standard audited.

INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED

## 03 Tolerance tighter than an as-built surface holds

HIGH

```
tightestToleranceMm >= 0.2 mm total band
lpbf-tolerance-capability
```

An as-built powder-bed surface carries partly-melted powder and the part moves as residual stress relaxes on cutting from the plate. Every tight feature on an AM part is machined afterwards, and the stock for it has to be in the model.

**FIX** Open the tolerance, or add machining stock on that feature and quote the operation.

**SOURCE** As-built powder-bed fusion surfaces are quoted well looser than machined ones, with diameter deviation significant below 04 mm. Positioned above the general machining band used elsewhere in this catalogue. DERIVED from that ordering, not quoted.

INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED

## 04 Hole too small to build open

MEDIUM

```
minHoleDiaMm >= 1.5 mm dia
lpbf-min-hole
```

A hole below about 1.5 mm closes as the melt pool bridges it, and whatever does stay open is full of partly-sintered powder that has to be got out. Under 4 mm the diameter deviates enough that a fit is not safe to specify as-built.

**FIX** Open the hole to at least 1.5 mm — and to 4 mm if the diameter matters — or build it undersize and ream it.

**SOURCE** Powder-bed fusion study data: holes at 01.5 mm remained fully open, while holes below 04 mm showed high diameter deviation. Alloy dependent. No primary standard audited.

INDUSTRY CONSENSUS, NO PRIMARY SOURCE AUDITED · NOT YET AUDITED

## What this book does not check

Every entry above is something the engine measures. This appendix is the other half of the truth: limits that matter to a manufacturing engineer and that this tool cannot currently evaluate honestly. Each one names what would be needed to close it and what the tool does instead in the meantime. It is here because a rule book that lists only what it can do teaches the reader to assume the rest was covered.

### 01 Tolerance expressed as a PERCENTAGE of dimension (MIM, and casting CT grades)

A per-feature tolerance chain rather than one tightest band. MIM is quoted at roughly  $\pm 0.3\%$  of the dimension and ISO 8062 casting grades are the same idea — a band that is generous on a 40 mm feature is impossible on a 4 mm one. This engine reads ONE tightest callout in millimetres from the PMI, so it cannot ask "is this band achievable FOR THIS SIZE".

**MEANWHILE** ``mim-tolerance-capability`` and every ``*-tolerance-capability`` rule use a flat millimetre screening value and say so. A part whose tight band sits on a small feature will pass when it should fail.

### 02 Best BUILD ORIENTATION for an additive part

A sweep over candidate build directions, scoring support area, height and down-facing area for each — the additive equivalent of the draw-direction sweep this engine already does for moulding. ``overhang()`` measures the part AS DRAWN along +Z, and re-orienting on the plate is the first thing an AM engineer does.

**MEANWHILE** The overhang figure is a measure of the model in its modelled orientation, and the rule says so. A part that fails at  $45^\circ$  may be entirely self-supporting once tipped.

### 03 BLOW MOULDING as a family

Sourced numbers for the blow ratio and for pinch-off geometry. The research turned up neither, and blow moulding competes directly with rotational moulding — a family built from rotomoulding's numbers with a different name would make the comparison between them meaningless, which is exactly what the route table exists to support.

**MEANWHILE** None. Blow moulding is not offered; rotational moulding is, and carries the hollow-part question for now.

### 04 SINKER (ram) EDM as its own family

Sourced numbers for the two limits that would distinguish it: the smallest internal corner a shaped electrode can burn, and the deepest rib an electrode can carry without arcing. The research found neither. Sinker EDM is the exact inverse of wire EDM — it is the process that CAN make a blind pocket with a sharp corner — so a family that merely copied the wire-EDM thresholds would be worse than none.

**MEANWHILE** None. Sinker EDM is not offered. The two processes it competes with, wire EDM and milling, are both in the catalogue, and a blind sharp-cornered pocket now surfaces as a wire-EDM finding ("blind features cannot be wire-cut") that names sinker EDM in its fix.

### 05 Tube bending — bend radius against tube OD, and wall thinning round the bend

The part recognised AS a tube: a circular section swept along a centreline, so the outside diameter, the wall and the centreline radius can be read separately. The engine finds cylinders and it finds bends between planar flanges; it has no swept-section recogniser, and a bent tube is neither a body of revolution nor folded sheet.

**MEANWHILE** None. Tube Bending is the ONE shaping process in this tool priced and carbon-scored but not judged, and the picker prints that reason when it is selected rather than showing an empty report.

### 06 Corner ANGLE for the fine-blanking corner-radius rule

The included angle at each internal corner. The published guidance is angle-dependent — an obtuse corner needs 5-10% of thickness, a right angle 10-15%, an acute one 25-30% — and the catalogue applies the single 0.5t "minimum inside radius" figure to every corner because the angle is not measured.

**MEANWHILE** ``fb-corner-radius`` uses the flat 0.5t figure, which is stricter than the obtuse case and more permissive than the acute one. A sharp acute corner can therefore pass a rule it should fail.

### 07 True LIMITING DRAW RATIO (blank diameter / punch diameter)

The blank and the punch. Neither is in a finished solid model: the blank is the flat sheet before forming and the punch is tooling. Computing the real LDR would need the part unfolded to its developed blank, which is a forming simulation, not a measurement.

**MEANWHILE** ``dd-draw-depth`` reads bounding-box depth over the narrower box width, which is the depth-to-diameter figure design guides quote alongside the LDR. It cannot see a stepped or tapered cup, where the governing diameter is not the

box width, and it ABSTAINS when the draw direction is not a box axis.

---

#### 08 Minimum as-cast cored hole diameter for SAND casting

A published sand-foundry figure for the smallest hole worth coring. Every other casting family in this catalogue now carries one — HPDC 2.5 mm, zinc 1.5 mm, permanent mould 6.0 mm, investment 1.5 mm — and sand does not, because the research turned up a sand CORE cross-section floor (about 1.6 mm for stability against the melt) and an unsupported core L/D band (10-15), but no sand cored-HOLE minimum from any source. Interpolating one from the permanent-mould 6 mm would have looked identical on the page to the four that are sourced.

**MEANWHILE** ``sand-core-ld`` still catches a sand core that is too SLENDER. Nothing catches one that is simply too fine, so a small hole on a sand casting is currently unjudged rather than passed — it appears under NOT EVALUATED with this reason.

---

#### 09 Vacuum-assisted die casting as a distinct GEOMETRIC family

Nothing — and that is the point. Evacuating the cavity changes the gas in it, not the shape the die can make: wall, draft, core slenderness and undercut limits are the die-casting limits either way. What vacuum buys is porosity low enough to heat-treat and weld, which is a metallurgical property this tool does not measure. The process is offered in the picker and priced separately, and routed to the HPDC rule family on purpose.

**MEANWHILE** The ``hpdc`` family judges it, correctly. A near-copy family would have invented six thresholds to restate the same limits and inflated the catalogue count by six.

---

#### 10 Tool HOLDER and machine-envelope collision (machining)

The holder geometry, the spindle nose and the machine work envelope. The shank-clearance sweep behind ``mach-tool-access`` now measures whether a cutter of a given diameter can reach each face along each approach direction, which is the larger half of this — but a face it calls reachable can still be unreachable once the holder is on the tool.

**MEANWHILE** ``mach-tool-access`` measures shank clearance and reports it as a LOWER bound on the access problem.

---

#### 11 Tolerance STACK-UP along a dimensional chain

The datum reference frames and the chain of dimensions between them, so accumulated variation can be propagated feature to feature. Reading individual callouts is not the same problem: a part can pass every tolerance on the drawing and still fail at assembly because they add up.

**MEANWHILE** Individual dimensions, geometric tolerances and datums ARE read from semantic AP242 PMI, and the tightest callout is checked against each process's capability. What is missing is the accumulation, not the reading.

---

#### 12 Datum reference frames (AP242 PMI)

The link from each geometric tolerance to the datums it is measured from. The reader extracts datum labels, but on the round-trip fixture written by this repo none survived the write, so the datum path is IMPLEMENTED AND UNVERIFIED — it has never been proved against a file with datums in it.

**MEANWHILE** Datum COUNT is reported and is zero on every file tested so far, which is honest but untested. Treat a non-zero datum count from a vendor CAD export as unproven until a fixture confirms it.

---

#### 13 Sink and warp prediction (injection moulding)

A mould-flow simulation: fill pattern, cooling layout and differential shrinkage.

**MEANWHILE** Wall uniformity and rib proportions cover the two geometric causes the engine CAN see.

---

#### 14 Blank nesting utilisation (sheet metal)

A flat pattern and a strip layout. Unfolding a formed part is a solver in its own right and the recogniser does not do it.

**NO PROXY - THE ENGINE REPORTS NOTHING IN THIS AREA**

---

#### 15 Press tonnage and station count (sheet metal)

Cut perimeter from the flat pattern, plus a progressive-die strip layout. The same unfolding gap as nesting.

**MEANWHILE** `stampingFeatureCost` estimates forming cost from the recognised bend count, which is a cost output rather than a design rule.



## Threshold audit register

The catalogue grades its citations, but a grade is a claim about a source rather than a record that anybody opened it. This is that record. 13 of 224 thresholds have been through it so far; the rest are marked NOT YET AUDITED on their own entries, and that is the honest state of them. Run "node scripts/threshold-audit.mjs" for the live work list.

### CONTESTED

#### Wall area below the minimum die-casting draft

hpdc-draft-minimum · High-pressure die casting (Al / Mg)

The rule applied ONE draft figure to all wall area. Published summaries of the NADCA draft constants split the requirement: roughly 0.5-1 deg on outside walls, 1-2 deg on inside walls, and about 2 deg per side in cored holes. HALF of that split is now implemented — `hpdc-cored-hole-draft` judges bore walls on their own curve at 2 deg, measured from the faces the analytic cylinder pass identifies as bores. The inside-vs-outside WALL half is NOT implemented and is not planned without a reliable test: from a bore wall the outward normal escapes through the bore opening, so the obvious ray test classifies a through-hole as an outer surface.

**RECOMMENDATION** Remains contested. The wall rule keeps the conservative OUTSIDE figure (1 deg), so it under-reports on inside walls. Closing this needs either a solid-side test that survives through-features, or the mould-half assignment from a real parting line rather than a draw vector.

BLOCKED BY: NADCA.COM AND DIECASTING.ORG UNREACHABLE FROM THIS ENVIRONMENT (EGRESS\_BLOCKED)

### CONTESTED

#### Wall thickness outside the die-casting range

hpdc-wall-thickness-range · High-pressure die casting (Al / Mg)

Independent sources agree on the 2.0-3.5 mm practical band and on ~1.0 mm as a thin-wall floor, so the VALUE is sound. But published summaries of the NADCA standards state that NADCA sets no absolute minimum wall thickness — it specifies tolerance grades and calls for uniformity. The rule's citation therefore must not drift toward reading as a standard.

**RECOMMENDATION** Keep the value and the industry-consensus grade. Do NOT promote this rule to standard-named. Consider adding a uniformity rule, which is what the standards actually emphasise.

BLOCKED BY: DIECASTINGDESIGN.ORG UNREACHABLE FROM THIS ENVIRONMENT (EGRESS\_BLOCKED)

### CONTESTED

#### Punched hole smaller than the material thickness

sm-hole-diameter · Sheet metal / stamping

GENUINE CONFLICT on the high-strength grades. Sec. 9.3.3(a) sizes the punch so it does not crush: combined with the punch force of Eq. 4.3 this gives  $d_{\min}/T = 2.8 \cdot UTS / \sigma_{pd}$ , with  $\sigma_{pd} = 980\text{--}1560$  MPa for hardened tool steel. At the conservative end that is 2.80 d/t for DP980 against the 1.50 d/t the catalogue holds, 1.77 for 304 against 1.20, and 1.66 for 316L against 1.20 — the book is stricter on every high-strength grade. It is LOOSER on 22MnB5 (1.71 vs our 2.50), but our figure there is for the hardened condition, which the book does not cover. The book's number is first-principles; ours is unattributed prose.

**RECOMMENDATION** Do not switch silently. The engine now computes the book's limit alongside ours and publishes both (`punchedHoleMarginRatio` and `\_punchLimit`); a plant that pierces DP980 at 1.5 d/t successfully is evidence the 980 MPa punch-stress floor is too conservative for their tooling, and that is exactly the measurement needed to settle it. Resolve with one real part before changing either number.

### PRIMARY SOURCE READ

#### Inside bend radius below one material thickness

sm-bend-radius · Sheet metal / stamping

CORROBORATED, not superseded. The catalogue's twelve per-alloy values were checked row by row against Table 5.2 ( $R_{\min} = c \cdot T$ , c by material group and temper). Every steel and stainless value we hold sits INSIDE the book's soft-to-hard band, and 7075 at 4.0 r/t sits inside the 1.5-6.0 band for high-strength heat-treatable aluminium. The book does NOT supply our values — it has no row for 6000-series aluminium and predates dual-phase steel entirely — so the catalogue's figures stand and the book is the check on them, not the source.

**RECOMMENDATION** Keep the per-alloy table. The book adds a dimension we do not model at all — TEMPER — with c ranging 0.5 to 3.0 for the same low-carbon steel. Capturing temper as an input would let the rule tighten or relax correctly instead of holding one figure per alloy.

PRIMARY SOURCE READ

### Bend radius too LARGE to take a permanent set

sm-bend-radius-max · Sheet metal / stamping

$R_i(\max) \leq T \cdot E / (2 \cdot YS)$ . A bend gentler than this never yields and the part springs back flat. New capability — nothing in the catalogue tested for it.

RECOMMENDATION None outstanding. The source was read first-hand and the equation is implemented as printed.

PRIMARY SOURCE READ

### Springback beyond what overbend alone can compensate

sm-springback · Sheet metal / stamping

Springback factor from the material's own  $YS/E$ , with the 2-8% practical overbend allowance stated in the text. New capability — springback was entirely absent.

RECOMMENDATION None outstanding. The source was read first-hand and the equation is implemented as printed.

PRIMARY SOURCE READ

### Strip utilisation below the industry target

sm-blank-utilisation · Sheet metal / stamping

Webs  $m = T + 0.015 \cdot D$  and  $n$  from Table 4.3, against the text's own 70-80% utilisation target. The utilisation figure is a LOWER bound: it assumes a rectangular envelope in a single-pass layout (Fig. 4.7a) and real nesting does better.

RECOMMENDATION None outstanding. The source was read first-hand and the equation is implemented as printed.

PRIMARY SOURCE READ

### Cup too deep for the drawing-ratio table

dd-draw-stages · Deep drawing (multi-stage)

Successive drawing ratios  $m1..m5$  by relative thickness  $100 \cdot T/D$ . The blank diameter is estimated by area equivalence rather than the book's Guldinus method (Sec. 6.4.2), which needs a meridian profile the recogniser does not extract — so the STAGE COUNT is sound and the blank it starts from is an estimate.

RECOMMENDATION None outstanding. The source was read first-hand and the equation is implemented as printed.

CORROBORATED BY SEARCH

### Cored hole beyond the core-pin slenderness limit

hpdc-core-ld · High-pressure die casting (Al / Mg)

Widely published as a practical limit; the exact figure varies with alloy, pin cooling and whether the pin is supported at both ends. A single number across all cored holes is a simplification the report should keep stating.

RECOMMENDATION Where a customer standard exists it should override this, which the threshold resolver already supports.

BLOCKED BY: NO PRIMARY SOURCE REACHABLE FROM THIS ENVIRONMENT

CORROBORATED BY SEARCH

### Cored holes below the core-pin draft

hpdc-cored-hole-draft · High-pressure die casting (Al / Mg)

Cored holes at ~2 deg per side against ~1 deg on outside walls is consistent across every secondary summary found. The value is the one half of the draft split that could be measured, because the cylinder pass knows which faces are bore walls.

RECOMMENDATION Read S-4A-7 first-hand before this is promoted past search-corroborated. The grade on the rule is standard-named because the citation is a standard; the STATUS here is what says nobody has opened it.

BLOCKED BY: NADCA.COM AND DIECASTING.ORG UNREACHABLE FROM THIS ENVIRONMENT (EGRESS\_BLOCKED)

NOT YET AUDITED

### Cored holes below the core draft

gdc-cored-hole-draft · Gravity die casting

Derived by the same reasoning as the aluminium cored-hole rule — a cored hole needs more draft than a wall because the casting shrinks onto the core — at 3.0 deg for this family. NOT independently corroborated: it is consistent with the family's own wall rule and with the aluminium figure, which is an argument, not evidence.

RECOMMENDATION Corroborate against a permanent-mould foundry design guide before relying on it.



NOT YET AUDITED

### Cored holes below the core draft

lpdc-cored-hole-draft · Low-pressure die casting

Derived by the same reasoning as the aluminium cored-hole rule — a cored hole needs more draft than a wall because the casting shrinks onto the core — at 2.0 deg for this family. NOT independently corroborated: it is consistent with the family's own wall rule and with the aluminium figure, which is an argument, not evidence.

**RECOMMENDATION** Corroborate against a permanent-mould foundry design guide before relying on it.

---

NOT YET AUDITED

### Cored holes below the core-pin draft

hpdc-zinc-cored-hole-draft · High-pressure die casting (Zinc)

Derived by the same reasoning as the aluminium cored-hole rule — a cored hole needs more draft than a wall because the casting shrinks onto the core — at 1.0 deg for this family. NOT independently corroborated: it is consistent with the family's own wall rule and with the aluminium figure, which is an argument, not evidence.

**RECOMMENDATION** Corroborate against a permanent-mould foundry design guide before relying on it.

---