

SHOULD-COST ANALYSIS REPORT

Generated: 12 Aug 2026 · 14:59

Bottom-Up Manufacturing Cost Model · Fully Traceable Rate Data

Forged Steel Steering Knuckle / Stub Axle Assembly

Commodity: FORGING · Currency: CNY · FX Rate: 9.0498 to GBP · Operations: 2 · Region: CN

Total Should-Cost	Material	Process	Labour	Margin
¥399.52	27.7%	38.2%	10.2%	7.4%

Model Confidence: **Low** · 2 traced operations · 7 data points auditable

Engine Warnings (1)

rawMaterial.materialId: Material rate confidence: Medium

Geometry Provenance — MEASURED (OCCT B-rep kernel)

Volume, weight and every feature were measured from the CAD solid by the Open CASCADE kernel. Measured volume 1037.1 cm³; mass for the selected material family 8.141 kg.

Material cost and geometry-derived machining are grounded in the actual solid — not an estimate.

Key Assumptions

Annual volume: 200,000 · Region: CN · Commodity: forging

Alloy / material: 1020 / S20C · Net weight: 8.141 kg (measured)

Material utilisation: 68% · Overhead: 12% of factory base · Margin: 8% of subtotal · Operations: 2

§1 — 8-Bucket Cost Breakdown

Cost Bucket	Amount (CNY)	% of Total	Cost Mix Bar
1. Raw Material	¥110.65	27.7%	
2. Process (Machine)	¥152.67	38.2%	
3. Direct Labour	¥40.92	10.2%	
4. Tooling (amortised)	¥16.60	4.2%	
5. Packaging	¥3.53	0.9%	

Cost Bucket	Amount (CNY)	% of Total	Cost Mix Bar
6. Logistics	¥7.06	1.8%	
Factory Cost	¥331.42	83.0%	
7. Overhead (SG&A)	¥38.50	9.6%	
Subtotal	¥369.92	92.6%	
8. Supplier Margin	¥29.59	7.4%	
TOTAL SHOULD-COST	¥399.52	100.0%	

§2 — Commercial Parameters

Overhead Rate	12.0%	Supplier Margin	8.0%
Packaging / part	¥3.53	Logistics / part	¥7.06
Total Tooling Cost	¥3319873.30	Amortisation Volume	200,000 parts

§3 — Material Detail

Parameter	Value	Unit	Notes
Material ID	mat-steel1020	ID	
Grade / Specification	1020 / S20C		UK steel billet, Jun 2026. Index-anchored 2026-07 (see FORGING PRICING BASIS). Regional adj. ×0.880 (millSteel)
Region	China		
Net Finished Weight	8.1410 kg	kg	Weight in finished part
Gross Weight (stock)	12.0525 kg	kg	Net ÷ utilisation ratio
Scrap / Runner Weight	3.9115 kg	kg	Gross - Net
Material Utilisation	67.5%	%	Benchmark: forging 75–90 % (flash + bar drop)
Material Price	¥6.53	CNY /kg	UK steel billet, Jun 2026. Index-anchored 2026-07 (see FORGING PRICING BASIS). Regional adj. ×0.880 (millSteel)
Scrap Recovery Price	¥1.51	CNY /kg	
Gross Material Cost	¥78.71	CNY	Gross × price/kg
Scrap Credit	-¥5.92	CNY	Scrap × recovery price
Consumables (core / wax / shell)	¥37.86	CNY	Per-part recurring
NET RAW MATERIAL COST	¥110.65	CNY	Gross - scrap credit + consumables
Data Confidence	Medium		
Effective Date	2026-07		

§4 — Operations Detail

4A Machine Operations

Operation	Machine Class	Rate / hr	Cycle (min)	Parts / Cycle	OEE %	Machine Cost
Forging	1600T Mechanical Forge Press	¥416.21	1.33	1	80.0%	¥11.56
CNC Machining — 29 features (1×Ø3.1×3, 1×Ø6.3×4, 1×Ø10.0×23, 2×Ø14.0×8, 2×Ø14.0×40, 2×Ø14.0×59, 1×Ø16.0×3, 1×Ø24.0×18, 1×Ø37.0×45,	CNC VMC 3-axis	¥254.30	28.30	1	85.0%	¥141.10

Operation	Machine Class	Rate / hr	Cycle (min)	Parts / Cycle	OEE %	Machine Cost
1×Ø39.0×45, 2×Ø40.0×3, 2×Ø40.0×7, 2×Ø42.5×2, 1×Ø45.0×3, 1×Ø46.0×6, 1× face 10594mm², 1× face 4683mm², 1× face 3158mm², 1× face 2940mm², 1× face 2381mm², 1× face 2212mm², 1× face 1046mm², 1× face 910mm²) [geometry-measured]						
TOTAL						¥152.67

4B Labour Detail

Operation	Labour Grade	Rate / hr	Man ning	Lab. min	Eff %	Labour Cost	Op Total
Forging	Skilled Machinist	¥71.49	2	1.33	92.0 %	¥3.45	¥15.02
CNC Machining — 29 features (1×Ø3.1×3, 1×Ø6.3×4, 1×Ø10.0×23, 2×Ø14.0×8, 2×Ø14.0×40, 2×Ø14.0×59, 1×Ø16.0×3, 1×Ø24.0×18, 1×Ø37.0×45, 1×Ø39.0×45, 2×Ø40.0×3, 2×Ø40.0×7, 2×Ø42.5×2, 1×Ø45.0×3, 1×Ø46.0×6, 1× face 10594mm², 1× face 4683mm², 1× face 3158mm², 1× face 2940mm², 1× face 2381mm², 1× face 2212mm², 1× face 1046mm², 1× face 910mm²) [geometry-measured]	Skilled Machinist	¥71.49	1	28.30	90.0 %	¥37.47	¥178.57
TOTAL						¥40.92	¥193.58

4C Machined Features — Geometry Audit

Feature	Ø×depth / area	Qty	Operation	Min	Cost	Costed ?
Boss	Ø20.0 × 4	1	Turning (external Ø)	0.38	—	No
Boss	Ø24.0 × 25	1	Turning (external Ø)	0.79	—	No
Boss	Ø35.0 × 47	1	Turning (external Ø)	1.24	—	No
Boss	Ø55.0 × 32	1	Turning (external Ø)	0.93	—	No
Boss	Ø57.0 × 7	1	Turning (external Ø)	0.44	—	No
Boss	Ø77.0 × 2	1	Turning (external Ø)	0.34	—	No
Boss	Ø114.0 × 7	1	Turning (external Ø)	0.44	—	No
Hole / bore	Ø3.1 × 3 blind	1	Drilling (blind)	0.19	¥0.81	Yes
Hole / bore	Ø6.3 × 4 blind	1	Drilling (blind)	0.32	¥1.37	Yes
Hole / bore	Ø10.0 × 23 blind	1	Drilling (blind)	0.70	¥2.97	Yes
Hole / bore	Ø14.0 × 8 blind	2	Drill + bore (blind)	1.64	¥6.95	Yes

Feature	Ø×depth / area	Qty	Operation	Min	Cost	Costed ?
Hole / bore	Ø14.0 × 40 blind	2	Drill + bore (blind)	4.16	¥17.63	Yes
Hole / bore	Ø14.0 × 59 blind	2	Drill + bore (blind)	5.72	¥24.24	Yes
Hole / bore	Ø16.0 × 3 blind	1	Drill + bore (blind)	0.63	¥2.66	Yes
Hole / bore	Ø24.0 × 18 blind	1	Drill + bore (blind)	1.20	¥5.09	Yes
Hole / bore	Ø37.0 × 45 blind	1	Drill + bore (blind)	2.85	¥12.08	Yes
Hole / bore	Ø39.0 × 45 blind	1	Drill + bore (blind)	2.85	¥12.08	Yes
Hole / bore	Ø40.0 × 3 blind	2	Drill + bore (blind)	0.72	¥3.05	Yes
Hole / bore	Ø40.0 × 7 blind	2	Drill + bore (blind)	0.72	¥3.05	Yes
Hole / bore	Ø42.5 × 2 blind	2	Drill + bore (blind)	0.74	¥3.14	Yes
Hole / bore	Ø45.0 × 3 blind	1	Drill + bore (blind)	0.38	¥1.61	Yes
Hole / bore	Ø46.0 × 6 blind	1	Drill + bore (blind)	0.38	¥1.63	Yes
Face	10594 mm ²	1	Face milling (facing)	1.52	¥6.46	Yes
Face	4683 mm ²	1	Face milling (facing)	0.79	¥3.33	Yes
Face	3158 mm ²	1	Face milling (facing)	0.59	¥2.52	Yes
Face	2940 mm ²	1	Face milling (facing)	0.57	¥2.41	Yes
Face	2381 mm ²	1	Face milling (facing)	0.50	¥2.11	Yes
Face	2212 mm ²	1	Face milling (facing)	0.48	¥2.02	Yes
Face	1046 mm ²	1	Face milling (facing)	0.33	¥1.40	Yes
Face	910 mm ²	1	Face milling (facing)	0.31	¥1.33	Yes
TOTAL costed		29		28.30	¥119.94	Yes

7 detected feature(s) NOT costed

7 machinable feature instance(s) (4.6 min) were detected in the geometry but are NOT included in this cost — on a near-net part they may be as-cast. If they are machined, tick them in the Machined-Features panel and re-cost; this could add up to ¥19.36.

\$5 — Machine Rate Buildup

CNC VMC 3-axis [mach-vmc3] · Confidence: Low · UK Tier-2 3-axis VMC (HAAS VF/VM class). Target £55/hr. Jun 2026 | Regional: capex/overhead ×0.55, energy re-tariffed @£0.07/kWh

Cost Component	Annual Cost (CNY)	Rate/hr @80% util	Notes
Depreciation	¥273755.66	¥85.55	4,000 hr/yr available
Maintenance	¥149321.27	¥46.66	
Energy	¥77119.81	¥24.10	
Floor Space	¥59728.51	¥18.67	
Indirect Support	¥149321.27	¥46.66	
Finance Cost	¥104524.89	¥32.66	
TOTAL — CNC VMC 3-axis	¥813771.39	¥254.30	Effective hours: 3200/yr

1600T Mechanical Forge Press [forge-press-1600t] · Confidence: Low · UK forge shop benchmark (mid-size crank press), Jun 2026 | Regional: capex/overhead ×0.55, energy re-tariffed @£0.07/kWh

Cost Component	Annual Cost (CNY)	Rate/hr @78% util	Notes
Depreciation	¥447963.80	¥164.09	3,500 hr/yr available
Maintenance	¥209049.77	¥76.58	
Energy	¥234113.71	¥85.76	
Floor Space	¥99547.51	¥36.46	
Indirect Support	¥89592.76	¥32.82	
Finance Cost	¥55995.48	¥20.51	
TOTAL — 1600T Mechanical Forge Press	¥1136263.03	¥416.21	Effective hours: 2730/yr

How to read the machine rate

Rate/hr = (annual depreciation + maintenance + energy + floor + indirect + finance) ÷ effective hours, where effective hours = available hours × utilisation.

Effective hours encode the shift pattern: a lower hours-base raises £/hr and a higher one lowers it. A challenge from a supplier will target this divisor and whether depreciation is machine-only or full-cell (machine + dosing furnace + trim + robots/extraction) — state your basis when defending the number.

\$6 — Rate Traceability

Field	Value	Unit	Source / Reference	Rate ID	Conf.
material.pricePerKg	0.7216	£/kg	UK steel billet, Jun 2026. Index-anchored 2026-07 (see FORGING PRICING BASIS). Regional adj.	mat-steel1020	Medium

Field	Value	Unit	Source / Reference	Rate ID	Conf.
			×0.880 (millSteel)		
material.scrapRecoveryPricePerKg	0.1672	£/kg	UK steel billet, Jun 2026. Index-anchored 2026-07 (see FORGING PRICING BASIS). Regional adj. ×0.880 (millSteel)	mat-steel1020	Medium
rawMaterial.consumablesCostPerPart	4.1839	£	Per-part consumable (core/wax/shell)	mat-steel1020	Medium
Forging.machineRatePerHr	45.9916	£/hr	UK forge shop benchmark (mid-size crank press), Jun 2026 Regional: capex/overhead ×0.55, energy re-tariffed @£0.07/kWh	forge-press-1600t	Low
Forging.labourRatePerHr	7.9000	£/hr	Regional benchmark China — 2026 Q2	lab-uk-skilled	Low
CNC Machining — 29 features (1×Ø3.1×3, 1×Ø6.3×4, 1×Ø10.0×23, 2×Ø14.0×8, 2×Ø14.0×40, 2×Ø14.0×59, 1×Ø16.0×3, 1×Ø24.0×18, 1×Ø37.0×45, 1×Ø39.0×45, 2×Ø40.0×3, 2×Ø40.0×7, 2×Ø42.5×2, 1×Ø45.0×3, 1×Ø46.0×6, 1× face 10594mm², 1× face 4683mm², 1× face 3158mm², 1× face 2940mm², 1× face 2381mm², 1× face 2212mm², 1× face 1046mm², 1× face 910mm²) [geometry-measured].machineRatePerHr	28.1005	£/hr	UK Tier-2 3-axis VMC (HAAS VF/VM class). Target £55/hr. Jun 2026 Regional: capex/overhead ×0.55, energy re-tariffed @£0.07/kWh	mach-vmc3	Low
CNC Machining — 29 features (1×Ø3.1×3, 1×Ø6.3×4, 1×Ø10.0×23, 2×Ø14.0×8, 2×Ø14.0×40, 2×Ø14.0×59, 1×Ø16.0×3, 1×Ø24.0×18, 1×Ø37.0×45, 1×Ø39.0×45, 2×Ø40.0×3, 2×Ø40.0×7, 2×Ø42.5×2, 1×Ø45.0×3, 1×Ø46.0×6, 1× face 10594mm², 1× face 4683mm², 1× face 3158mm², 1× face 2940mm², 1× face 2381mm², 1× face 2212mm², 1× face 1046mm², 1× face 910mm²) [geometry-measured].labourRatePerHr	7.9000	£/hr	Regional benchmark China — 2026 Q2	lab-uk-skilled	Low

§7 — Should-Cost with Uncertainty

Monte-Carlo · Low confidence

Estimate (± band)	P10 · optimistic	P50 · median	P90 · conservative	Band	CV
¥399.52 ± 16.7%	¥334.75	¥395.93	¥468.42	moderate	13.2%

Range reflects how well each cost driver is known (High / Medium / Low confidence). Tighten it by attaching CAD, a BOM, or logging an actual quote.

Why confidence is Low

Main band drivers: 4 rate(s) at Low confidence; tooling amortisation carries the widest per-bucket spread; some detected features not costed (see §4C).

What's excluded from this unit cost

One-time NRE — tooling / die, fixtures and CNC programming — is amortised separately, not in this unit cost.
 Import duty and international freight (regional table is Ex-Works).
 Formal embodied-carbon reporting (figures are indicative cradle-to-gate — replace with supplier EPDs).

§8 — Sensitivity Analysis

± 10% driver swing · ranked by ¥ impact

Cost Driver	Base	-10% cost	+10% cost	Range ¥
CNC Machining — 29 features (1×Ø3.1×3, 1×Ø6.3×4, 1×Ø10.0×23, 2×Ø14.0×8, 2×Ø14.0×40, 2×Ø14.0×59, 1×Ø16.0×3, 1×Ø24.0×18, 1×Ø37.0×45, 1×Ø39.0×45, 2×Ø40.0×3, 2×Ø40.0×7, 2×Ø42.5×2, 1×Ø45.0×3, 1×Ø46.0×6, 1× face 10594mm², 1× face 4683mm², 1× face 3158mm², 1× face 2940mm², 1× face 2381mm², 1× face 2212mm², 1× face 1046mm², 1× face 910mm²) [geometry-measured]: Cycle Time	0.47hr	-5.4%	+5.4%	¥43.20
CNC Machining — 29 features (1×Ø3.1×3, 1×Ø6.3×4, 1×Ø10.0×23, 2×Ø14.0×8, 2×Ø14.0×40, 2×Ø14.0×59, 1×Ø16.0×3, 1×Ø24.0×18, 1×Ø37.0×45, 1×Ø39.0×45, 2×Ø40.0×3, 2×Ø40.0×7, 2×Ø42.5×2, 1×Ø45.0×3, 1×Ø46.0×6, 1× face 10594mm², 1× face 4683mm², 1× face 3158mm², 1× face 2940mm², 1× face 2381mm², 1× face 2212mm², 1× face 1046mm², 1× face 910mm²) [geometry-measured]: Machine Rate	¥254.30/hr	-4.3%	+4.3%	¥34.14
Material: 1020 / S20C	¥6.53/kg	-2.4%	+2.4%	¥19.04
Material utilisation	0.68	+2%	-1.7%	¥14.78
Forging: Labour Rate	¥71.49/hr	-1.2%	+1.2%	¥9.90
CNC Machining — 29 features (1×Ø3.1×3, 1×Ø6.3×4, 1×Ø10.0×23, 2×Ø14.0×8, 2×Ø14.0×40, 2×Ø14.0×59, 1×Ø16.0×3, 1×Ø24.0×18, 1×Ø37.0×45, 1×Ø39.0×45, 2×Ø40.0×3, 2×Ø40.0×7, 2×Ø42.5×2, 1×Ø45.0×3, 1×Ø46.0×6, 1× face 10594mm², 1× face 4683mm², 1× face 3158mm², 1× face 2940mm², 1× face 2381mm², 1× face 2212mm², 1× face 1046mm², 1× face 910mm²) [geometry-measured]: Labour Rate	¥71.49/hr	-1.2%	+1.2%	¥9.90
Overhead %	12%	-1%	+1%	¥8.32

Cost Driver	Base	-10% cost	+10% cost	Range ¥
Supplier Margin %	8%	-0.7%	+0.7%	¥5.92

§9 — Regional Cost Comparison

Ex-Works · per-region should-cost · vs China

Region	Material	Process	Labour	Tooling	Overhead	Ex-Works	Logistics	Total	vs China
United Kingdom (GBP)	¥125.74	¥277.57	¥147.31	¥30.18	¥51.33	¥632.13	¥4.87	¥671.64	+68%
Germany (EUR)	¥129.51	¥291.45	¥238.07	¥31.69	¥67.15	¥757.88	¥5.60	¥804.21	+101%
France (EUR)	¥128.25	¥255.37	¥171.12	¥27.77	¥54.06	¥636.56	¥5.60	¥677.30	+70%
Spain (EUR)	¥125.74	¥244.26	¥107.88	¥26.56	¥42.36	¥546.80	¥5.60	¥583.24	+46%
Poland (PLN)	¥121.97	¥199.85	¥66.96	¥21.73	¥30.84	¥441.35	¥5.84	¥472.55	+18%
Turkey (TRY)	¥113.17	¥166.54	¥37.20	¥18.11	¥23.10	¥358.11	¥6.33	¥385.46	-4%
China (CNY)	¥110.65	¥152.67	¥40.92	¥16.60	¥38.50	¥359.33	¥7.06	¥399.52	Base
India (INR)	¥113.17	¥144.34	¥26.04	¥15.69	¥19.04	¥318.28	¥7.30	¥344.02	-14%
Mexico (MXN)	¥119.45	¥166.54	¥43.15	¥18.11	¥23.94	¥371.20	¥6.57	¥399.14	-0%
United States (USD)	¥125.74	¥235.94	¥193.43	¥25.65	¥48.76	¥629.53	¥6.09	¥669.92	+68%

Per-region should-cost using regional labour, energy and rate benchmarks. Tooling held fixed. Ex-Works — excludes import duty + international freight. Indicative — confirm with RFQ.

§10 — Embodied Carbon

40.84 kgCO2e · 5.02 /kg · cradle-to-gate

Material	18.33 kgCO2e	Material factor	2.10 kg/kg (Steel)
Process	21.21 kgCO2e	Grid intensity	0.550 kg/kWh · 38.57 kWh
Logistics	1.30 kgCO2e	Total	40.84 kgCO2e

Indicative cradle-to-gate factors — replace with supplier EPDs for formal reporting.

[WARNING] Machining / process cost above benchmark

Finding	Process cost at 38.2% of total is above the benchmark range of 10–20%. Cycle time or machine rate is elevated.
Impact	High · up to 9% potential saving
Benchmark	Process %: yours 38.2% vs industry 10–20%
Action 1	Reduce cycle time via feeds/speeds optimisation and toolpath strategy review
Action 2	Combine multiple operations into one setup to eliminate re-fixture time

[WARNING] Low material utilisation — high scrap rate

Finding	Material utilisation at 68% is below the forging benchmark of 75%. You are paying for 48% more raw material than ends up in the part.
Impact	Medium · up to 1% potential saving
Action 1	Redesign blank/preform geometry to minimise offcuts
Action 2	Optimise nesting/layout for sheet or profile stock

[INFO] Material cost is below benchmark range

Finding	Material at 27.7% is below the typical 38–62% range. Conversion cost is the dominant driver.
Impact	Low
Benchmark	Material %: yours 27.7% vs industry 38–62%
Action 1	Focus optimisation efforts on process and labour efficiency

§12 — Cost-Reduction Opportunities (ranked by saving)

7 opportunities · combined ¥53.14/part (~13%)

Ranked on money per part against this costing. The combined figure is the root-sum-square of the top three, capped at 40% — overlapping actions do not save twice, so the column is deliberately not summed.

#	Category	Action	Why it is on the list	Save/p art	%	Timeframe	Risk
1	Material	Improve Material Utilisation via Near-Net-Shape	Current utilisation at 68%. Near-net-shape process or improved nesting targets 80–90%.	¥34.87	8.7%	Medium Term	Medium
2	Material	Consumables Rationalisation (Cores, Patterns, Shell)	Per-part consumables are 34% of the material line. Core count, pattern life and shell recipe are all design-controllable.	¥23.97	6.0%	Medium Term	Medium
3	Material	Scrap Revenue	32% of the bought material leaves as chips,	¥11.46	2.9%	Quick Win	Low

#	Category	Action	Why it is on the list	Save/p art	%	Timeframe	Risk
		Recovery at Index Prices	offcuts or skeleton. That scrap has an index price — the credit belongs in the piece price, not in the supplier's margin.				
4	Process & Automation	Attack the Bottleneck: "CNC Machining — 29 features (1×Ø3.1×3, 1×Ø6.3×4, 1×Ø10.0×23, 2×Ø14.0×8, 2×Ø14.0×40, 2×Ø14.0×59, 1×Ø16.0×3, 1×Ø24.0×18, 1×Ø37.0×45, 1×Ø39.0×45, 2×Ø40.0×3, 2×Ø40.0×7, 2×Ø42.5×2, 1×Ø45.0×3, 1×Ø46.0×6, 1× face 10594mm², 1× face 4683mm², 1× face 3158mm², 1× face 2940mm², 1× face 2381mm², 1× face 2212mm², 1× face 1046mm², 1× face 910mm²) [geometry-measured]"	One operation — CNC Machining — 29 features (1×Ø3.1×3, 1×Ø6.3×4, 1×Ø10.0×23, 2×Ø14.0×8, 2×Ø14.0×40, 2×Ø14.0×59, 1×Ø16.0×3, 1×Ø24.0×18, 1×Ø37.0×45, 1×Ø39.0×45, 2×Ø40.0×3, 2×Ø40.0×7, 2×Ø42.5×2, 1×Ø45.0×3, 1×Ø46.0×6, 1× face 10594mm², 1× face 4683mm², 1× face 3158mm², 1× face 2940mm², 1× face 2381mm², 1× face 2212mm², 1× face 1046mm², 1× face 910mm²) [geometry-measured] — carries 92% of the conversion cost. Improving anything else first is working on the wrong problem.	¥31.96	8.0%	Medium Term	Medium
5	Process & Automation	Line-balance or automate the multi-manned station first; check whether the second operator exists only to load/unload	High manning (2.0 operators on one operation) — At least one operation runs with 2.0 operators. Multi-manned stations are the strongest automation candidates on any part.	¥23.97	6.0%	Medium Term	Medium
6	Commercial & Sourcing	Annual Volume Re-Commitment for Better Pricing	Provide 12-month rolling volume forecast to supplier to secure better unit pricing and tooling amortisation.	¥11.99	3.0%	Quick Win	Low
7	Sustainability & Energy	Energy Productivity Programme	This process is energy-intensive (melt, cure, oven or heat-treat content). Energy sits inside the machine rate and overhead — and it is the fastest-moving input cost of the decade.	¥11.99	3.0%	Medium Term	Low

§13 — Opportunity by Category

4 categories with an actionable lever

Category	Opportunities	Best single action	Best save/part	Category total (indicative)
Material	3	Improve Material Utilisation via Near-Net-Shape	¥34.87	¥70.29
Process & Automation	2	Attack the Bottleneck: "CNC Machining — 29 features (1×Ø3.1×3, 1×Ø6.3×4, 1×Ø10.0×23, 2×Ø14.0×8, 2×Ø14.0×40, 2×Ø14.0×59, 1×Ø16.0×3, 1×Ø24.0×18, 1×Ø37.0×45, 1×Ø39.0×45, 2×Ø40.0×3, 2×Ø40.0×7, 2×Ø42.5×2, 1×Ø45.0×3, 1×Ø46.0×6, 1× face 10594mm², 1× face 4683mm², 1× face 3158mm², 1× face 2940mm², 1× face 2381mm², 1× face 2212mm², 1× face 1046mm², 1× face 910mm²) [geometry-measured]"	¥31.96	¥55.93
Commercial & Sourcing	1	Annual Volume Re-Commitment for Better Pricing	¥11.99	¥11.99
Sustainability & Energy	1	Energy Productivity Programme	¥11.99	¥11.99

§15 — Implementation Roadmap

Quick Wins — Implement Immediately

- Scrap Revenue Recovery at Index Prices
- Annual Volume Re-Commitment for Better Pricing