Software Requirements Specification

Context-aware AAC Board

B — The Outliers

· A context-aware communication assistant for everyday requests

Table 1. Project information

Document control	Value
Team	B – The Outliers
Authors	Veronika Surianinova · Jiahui Chen · Thibaut de Robien · Abid Ali
Course / institution	Software Engineering · Beihang University
Document edition	v0.5 (Markdown edition of review draft v0.3, with internal review fixes)
Date	29 October 2026
Scope	Web-first prototype · English only · café scenario first
Baseline	IEEE-inspired SRS template supplied by professor

Table of Contents

- Chapter 1 — Introduction
  - 1.1 Document Purpose
  - 1.2 Product Scope
  - 1.3 Definitions, Acronyms, and Abbreviations
  - 1.4 References
  - 1.5 Document Overview
- Chapter 2 — Product Overview
  - 2.1 Product Perspective
  - 2.2 Product Functions
  - 2.3 Product Constraints
  - 2.4 User Characteristics
  - 2.5 Assumptions and Dependencies
  - 2.6 Apportioning of Requirements
- Chapter 3 — Software Requirements
  - 3.1 External Interfaces
  - 3.2 Functional
  - 3.3 Quality of Service
  - 3.4 Compliance
  - 3.5 Design and Implementation
  - 3.6 AI/ML
- Chapter 4 — Verification
- Chapter 5 — Appendixes
  - Appendix A — Primary acceptance scenario
  - Appendix B — Open decisions to close before professor submission
  - Appendix C — Frontend progress screenshots
  - Appendix D — Architecture and records
  - Appendix E — Verified team contributions and development evidence
  - Appendix F — Scholarly literature and technical reference list
  - Appendix G — Sources and limitations

List of Figures

- Figure 1. Work Breakdown Structure (WBS)
- Figure 2. System use case diagram
- Figure 3. AAC request activity diagram
- Figure 4. Logical system architecture
- Figure 5. Login page — branding, email/password input and account entry
- Figure 6. Context page — café context, symbol tiles, optional photo and intention text
- Figure 7. Suggestions page — three sentence choices and confirm/reject/stop controls
- Figure 8. Project schedule with course milestones

List of Tables

- Table 1. Project information
- Table 2. Document sections
- Table 3. Revision history
- Table 4. 1.2 Product Scope
- Table 5. 1.3 Definitions, Acronyms, and Abbreviations
- Table 6. 1.4 References

- Table 7. 2.1 Product Perspective
- Table 8. 2.4 User Characteristics
- Table 9. 2.6 Apportioning of Requirements
- Table 10. Specification and acceptance criteria — REQ-INT-001
- Table 11. Specification and acceptance criteria — REQ-INT-002
- Table 12. Specification and acceptance criteria — REQ-INT-007
- Table 13. Specification and acceptance criteria — REQ-INT-003
- Table 14. Specification and acceptance criteria — REQ-INT-004
- Table 15. Specification and acceptance criteria — REQ-INT-005
- Table 16. Specification and acceptance criteria — REQ-INT-006
- Table 17. Specification and acceptance criteria — REQ-FUNC-001
- Table 18. Specification and acceptance criteria — REQ-FUNC-002
- Table 19. Specification and acceptance criteria — REQ-FUNC-003
- Table 20. Specification and acceptance criteria — REQ-FUNC-004
- Table 21. Specification and acceptance criteria — REQ-FUNC-005
- Table 22. Specification and acceptance criteria — REQ-FUNC-006
- Table 23. Specification and acceptance criteria — REQ-FUNC-007
- Table 24. Specification and acceptance criteria — REQ-FUNC-008
- Table 25. Specification and acceptance criteria — REQ-FUNC-009
- Table 26. Specification and acceptance criteria — REQ-FUNC-010
- Table 27. Specification and acceptance criteria — REQ-FUNC-011
- Table 28. Specification and acceptance criteria — REQ-FUNC-012
- Table 29. Specification and acceptance criteria — REQ-PERF-001
- Table 30. Specification and acceptance criteria — REQ-SEC-001
- Table 31. Specification and acceptance criteria — REQ-SEC-002
- Table 32. Specification and acceptance criteria — REQ-SEC-003
- Table 33. Specification and acceptance criteria — REQ-SEC-004
- Table 34. Specification and acceptance criteria — REQ-SEC-005
- Table 35. Specification and acceptance criteria — REQ-SEC-006
- Table 36. Specification and acceptance criteria — REQ-SEC-007
- Table 37. Specification and acceptance criteria — REQ-REL-001
- Table 38. Specification and acceptance criteria — REQ-REL-002
- Table 39. Specification and acceptance criteria — REQ-REL-003
- Table 40. Specification and acceptance criteria — REQ-AVAIL-001
- Table 41. Specification and acceptance criteria — REQ-OBS-001
- Table 42. Specification and acceptance criteria — REQ-COMP-001
- Table 43. Specification and acceptance criteria — REQ-COMP-002
- Table 44. Specification and acceptance criteria — REQ-INST-001
- Table 45. Specification and acceptance criteria — REQ-BUILD-001
- Table 46. Specification and acceptance criteria — REQ-DIST-001
- Table 47. Specification and acceptance criteria — REQ-MAINT-001
- Table 48. Specification and acceptance criteria — REQ-PORT-001
- Table 49. Course milestones
- Table 50. Specification and acceptance criteria — REQ-POC-001
- Table 51. Specification and acceptance criteria — REQ-CM-001
- Table 52. Specification and acceptance criteria — REQ-ML-001
- Table 53. Specification and acceptance criteria — REQ-ML-002
- Table 54. Specification and acceptance criteria — REQ-ML-008
- Table 55. Specification and acceptance criteria — REQ-ML-003
- Table 56. Specification and acceptance criteria — REQ-ML-004
- Table 57. Specification and acceptance criteria — REQ-ML-005
- Table 58. Specification and acceptance criteria — REQ-ML-006
- Table 59. Specification and acceptance criteria — REQ-ML-007
- Table 60. Requirement status on 29 October 2026

- Table 61. Requirement traceability
- Table 62. Primary acceptance scenario
- Table 63. Open decisions with owner and target week
- Table 64. Appendix D — Architecture and records
- Table 65. E.2 Group contributions and evidence
- Table 66. E.3 Implemented backend behavior (API v0.1)

Table 2. Document sections

Section	Contents
1	Introduction and terminology
2	Product overview, actors, scope, constraints and increments
3	External interfaces; 49 requirement identifiers across interfaces, functional, quality, compliance, design and AI/ML
4	Verification approach, traceability and current progress
5	Appendixes: end-to-end scenario, diagrams, frontend screenshots and outstanding decisions

Revision History

Table 3. Revision history

Version	Date	Change
0.1	13 Oct 2026	Initial team draft grounded in proposal/backend starter
0.2	13 Oct 2026	Standalone application; Cboard is inspiration only
0.3 review draft	27 Oct 2026	Presentation-ready layout; screenshots and current update incorporated; verification pending team review
0.4	29 Oct 2026	Markdown edition of v0.3 with the same structure and requirements. Figures 1–4 redrawn in Mermaid to match the real workflow (sign in → context → suggestions → confirm and speak or reject and regenerate). AI-related text (2.1, 3.6, REQ-INT-005, REQ-ML-001 … 006, AI evidence) corrected against the implementation. A specific rationale written for every requirement
0.5	29 Oct 2026	Internal review fixes (24 issues): reuse endpoint in REQ-INT-004; measurable acceptance criteria with the enforced limits; numbered criteria for bundled requirements; new REQ-INT-007 (accessibility), REQ-FUNC-012 (no suggestions), REQ-ML-007 (backup models and quotas) and REQ-ML-008 (reuse); evidence re-checked on 29 Oct 2026 with per-requirement traceability; milestones W7/W12/W16; Figures 2 and 3 corrected; scope, glossary, references, owners, verification methods and open decisions updated; duplicated text removed

Chapter 1 — Introduction

This SRS provides the agreed documentation baseline for Team B — The Outliers: Veronika, Jiahui, Thibaut and Abid Ali. The Context-aware AAC Board is a standalone English-language web application intended to help people with speech or language impairments communicate everyday requests by selecting meaningful symbols, giving context and choosing a complete English sentence. User-selected symbols or text communicate intent; optional scene information helps produce appropriate sentence options, and the user retains control over what is spoken. The document describes intended behavior, not a claim that every proposed feature has already been completed.

1.1 Document Purpose

This specification is written for the four team members, the course instructor, peer reviewers, testers and future maintainers. It defines the expected external behaviors, quality attributes, interfaces, constraints and acceptance criteria, sets boundaries for implementation, and connects uniquely numbered requirements to measurable acceptance checks. Readers should use it to review scope, manage changes and decide whether evidence from testing or demonstration meets each requirement. This document separates verified prototype behavior from future AI, deployment, authentication and accessibility work.

1.2 Product Scope

The initial release demonstrates an English-language café request: users select a scene and pictorial item, optionally add an intention and photo, receive up to three sentence options, then choose and explicitly confirm what is spoken. Inputs include symbols, free-text intent, scene hint and optional photo; requests, suggestions and feedback are recorded. Rejection and regeneration are part of the workflow. The backend currently answers with mock templates rather than genuine photo understanding; wider contexts, live AI and mobile support must not be treated as already delivered. A mobile app and public production deployment are not included in the first demonstrated increment.

Table 4. 1.2 Product Scope

In scope	Excluded or deferred
Standalone web frontend and API	Cboard fork or reuse of Cboard code/assets
English symbol/text and scene context; optional photo	Multilingual interface/speech
Up to three suggested English sentences	Autonomous speech without confirmation
Selection, acceptance, rejection, regeneration	Public user study without privacy and consent readiness
Initial café scenario; evaluation and feedback	Mobile packaging unless prioritized
Reuse of sentences the user accepted before (exact match in the backend; similarity in the AI prototype)	Embedding-based semantic search

1.3 Definitions, Acronyms, and Abbreviations

AAC denotes Augmentative and Alternative Communication, including tools that supplement or replace speech. A symbol tile is a selectable pictogram representing an item or action; a scene hint identifies the setting; intent text specifies what the user wants to communicate. The sentence provider is the replaceable component that returns candidate English phrases, whether it uses fixed templates or a language model. Verification evidence is a dated test record, inspection or demonstration supporting a requirement result.

Table 5. 1.3 Definitions, Acronyms, and Abbreviations

Term	Meaning
AAC	Augmentative and Alternative Communication
API	Application Programming Interface
Backup chain	Ordered list of AI models; when one cannot answer (quota, error or timeout) the next one is used
Cboard	An existing AAC product serving as design inspiration only
CI	Continuous Integration
EXIF	Image metadata that may include device or location information
Feedback	The user's current decision on a generation: accepted (with the chosen suggestion) or rejected
Free tier	No-cost use of a hosted AI service, limited in requests per minute and per day for each model
Generation chain	A request and its regenerations for the same unchanged inputs, linked by `parent_request_id`
HTTP 429 / 503	Status codes: 429 "Too Many Requests" (quota used up); 503 "Service Unavailable" (cannot answer now)
Intention (intent text)	Free text in which the user states what they want, e.g. "I do not want sugar"
LLM	Large Language Model
Mock provider	Rule/template-based generator, not a real AI model
Reuse	Showing a sentence the user accepted before for a matching request, without a model call
Scene hint	Text naming where the user is, e.g. "A café"; it is context, not the intention
Sentence provider	Replaceable component behind the `SentenceProvider` interface that returns candidate sentences
SRS	Software Requirements Specification
TBD	To Be Determined: a value the team has not decided yet
TTS	Text-to-Speech
VLM	Vision-Language Model
WCAG	Web Content Accessibility Guidelines (W3C)

1.4 References

GitHub IEEE-style SRS template determines this document's main organization. Internal source material consists of the original team presentation, the weekly report and the supplied interface screenshots. The earlier presentation proposed extending Cboard, while the newer weekly update defines a standalone system with Cboard only as design inspiration. The latest recorded scope is therefore used, and unresolved implementation choices remain identified as pending decisions.

Table 6. 1.4 References

Ref	Document / source
R1	Professor template: https://github.com/ovikrai/SRS-Template-IEEE
R2	Team SRS v0.2: https://github.com/bhsei/26B/blob/main/docs/requirements/SRS.md (Git history)
R3	Team proposal presentation (proposal-level background): weekly-reports/W02/Weekly_Report_W02.pptx
R4	Weekly progress reports (scope, task allocation and progress): weekly-reports/, latest W07
R5	Frontend screenshots supplied 27 Oct 2026 (login, context board, suggestion selection)
R6	Companion team files: docs/API.md, docs/ERRORS.md, docs/DATABASE.md, docs/REUSE.md, docs/TEAM_NEXT_STEPS.md; docs/VERIFICATION.md is historical (v0.1 starter)
R7	AI model plan: docs/design/AI_Model_Plan.md (model choice, hardware limits, failure handling)
R8	AI prototype and measured free-tier limits: src/ai/README.md
R9	Interest discovery proposal (for team decision): docs/design/Interest_Discovery_Proposal.md
R10	WCAG 2.1: https://www.w3.org/TR/WCAG21/

Academic research added to the bibliography in Appendix F includes Pereira et al. (2024) on Transformers for predictive AAC, Valencia et al. (2023) on AAC users' preferences and agency when using AI suggestions, and Pak et al. (2023) on speech-generating AAC interventions. The SRS draws on these for requirements justification; they are not validation results for the current prototype.

1.5 Document Overview

Section 2 introduces product context, expected users, main functions and project constraints.

Section 3 specifies external interfaces, functional behavior, quality of service, compliance, design and implementation, and AI/ML obligations.

Section 4 defines verification methods and traceability.

Section 5 holds example scenarios, illustrations and decisions awaiting team approval; these appendixes supplement but do not replace numbered requirements.

Chapter 2 — Product Overview

The intended product is a browser-based assistive communication tool rather than a general chatbot. It combines a small number of explicit selections with contextual phrasing so a user can express a request with less typing. Respecting the user's intention is fundamental: photographs or model outputs cannot independently authorize speech or introduce a request the person did not choose.

2.1 Product Perspective

The updated solution is a standalone React frontend communicating with a FastAPI backend over HTTP/JSON. The backend validates input, calls a replaceable sentence provider and maintains records for requests, suggestions and feedback. SQLite is the reported tested database in the backend starter; PostgreSQL is a planned deployment option requiring verification. Browser speech output belongs to the interaction path and must follow explicit user confirmation. The backend currently uses mock sentence templates. The real provider exists as a tested prototype (`src/ai/`): one multimodal call to a hosted Gemini model on the free tier, with a backup chain of further Gemini models and a planned local model; it is not yet connected to the backend. The browser/device supplies English speech output. The application is standalone, not a Cboard extension.

Table 7. 2.1 Product Perspective

Component	Responsibility / status
User and browser	Select context symbols/text; upload optional photo; review and speak
Frontend: React / JavaScript	New team UI; screenshots show login, context tile board and suggestion selection
Backend: Python / FastAPI	Input validation, generation orchestration, feedback endpoints
Sentence Provider	Mock in the backend; real provider prototyped in `src/ai/` (Gemini Flash-Lite and Flash backup chain on the free tier, local Ollama model planned), evaluation pending
Storage	SQLite in local starter; PostgreSQL server target not yet verified
Speech	Browser speech output planned / manual device verification outstanding
Deployment	Docker Compose and public security controls pending

2.2 Product Functions

The main user journey begins after sign-in with a scene such as a café, a chosen symbol such as Water and optional typed intentions or a photo. The user requests up to three complete English suggestions, then chooses one and explicitly confirms speech, or rejects them and gets new ones; audio can be stopped and the user can go back to change the context. The system checks submitted data, shows clear status and error messages, and records requests, suggestions and feedback while minimizing retained image data. Sentences accepted before can be reused for a matching request. Request identity, feedback storage and readiness checks support integration and evaluation. Login, live model inference and broader situation coverage require independent implementation and testing; authentication is depicted in updated screenshots, but secure account ownership must be verified separately.

2.3 Product Constraints

The first release is English-only, web-first and focused on a café demonstration; mobile adaptation is optional. Interfaces should emphasize legible text, understandable symbols and predictable controls suitable for people with differing communication and motor needs. The team must work within course milestones, licensing rules and practical hosting costs. Model, deployment and authentication details have not all been finalized, so they must be settled through change control before release. Initial English-only interface/output; web-first delivery; café-first test scenario; no copying of Cboard assets; explicit user confirmation before sound; user intent must never be inferred from image alone; zero AI budget, so only free tiers of hosted models are used, and the development laptop (7.3 GB RAM, no CUDA GPU) cannot

run local models above about 2 B parameters; avoid using real sensitive photos or users until consent, security and retention safeguards are approved.




Figure 1. Work Breakdown Structure (WBS).

2.4 User Characteristics

The main users may have difficulty speaking or composing long English phrases, so they need an interface where a few deliberate inputs can lead to a usable sentence. Some users may prefer symbols and others short text, and not every device will provide a camera. Caregivers or educators may assist during evaluation, while developers administer backend operations. Actual accessibility and usability with representative AAC users have not yet been established by the supplied screenshots.

Table 8. 2.4 User Characteristics

User group	Characteristics / needs
Primary AAC user	May have speech/language impairment, benefits from large selectable pictograms, plain language, predictable navigation, speech confirmation
Support person/caregiver	May help configure or demonstrate the system; no unapproved impersonation
Team tester	Runs café scenario and records performance, relevance, safety and usability feedback
System operator	Configures services, deployment, database, logging and secrets

2.5 Assumptions and Dependencies

The core workflow assumes a functioning browser; audible speech additionally depends on an accessible English voice and suitable device speakers. Photo input must remain optional. The quality, cost and latency of live contextual sentences will depend on the final AI provider, whereas the reported backend checkpoint uses fixed mock suggestions. Hosting, secrets, cross-platform support, database migration and data consent require further decisions and verified configuration. A device supports browser access and may provide a usable English voice; photos are optional and not sufficient alone to determine user intent; synthetic data can be used in development; the selected generation provider is reachable within available budget; free-tier limits and model names can change without notice, and free-tier inputs may be used by the provider to improve its products; third-party dependencies remain installable; frontend/backend can be integrated during the course schedule. A failed assumption must trigger fallback handling or a change request.

2.6 Apportioning of Requirements

The team prioritizes an end-to-end café scenario before extending the symbol vocabulary to other contexts. Thibaut leads frontend and symbol interaction, Veronika leads backend and data integration, Jiahui leads model selection and evaluation, and Abid Ali leads deployment, authentication and limits, as recorded in the weekly report. Public access requires deployment security and rate controls; work with real users additionally requires consent, data-retention and licence review. The group shares integration testing and documentation review.




Figure 2. System use case diagram. The AAC user signs in, gives context with symbols, text or a photo, requests suggestions, and then confirms and speaks one sentence or rejects them and regenerates.

Table 9. 2.6 Apportioning of Requirements

Owner	Responsibility	Near-term deliverable
Thibaut	Symbol board, accessible frontend and cross-page navigation	Water tile → suggestion-selection flow
Veronika	Backend/API, relational storage, frontend integration	Working provider API, errors, database checks
Jiahui	AI/provider selection, prompts and evaluation	Connect the tested backup chain to the backend; evaluated café outputs
Abid Ali	CI/deployment/security/operations	Compose deployment, PostgreSQL migration, auth and rate-limit plan
All	SRS validation, human evaluation, consent, licenses	Cross-review and repeatable acceptance demo

Chapter 3 — Software Requirements

Each requirement below defines an outcome that should be observable, inspectable or measurable. Existing requirement IDs and verification references are retained so the revised prose does not invalidate the team's traceability: the 45 IDs of v0.3 are kept, and v0.5 adds REQ-INT-007, REQ-FUNC-012, REQ-ML-007 and REQ-ML-008 (49 in total). Suggested performance or service targets that have not been approved are marked provisional or recorded as open decisions, not represented as tested results. Acceptance criteria with several parts are numbered (AC1, AC2, …) so that each part passes or fails on its own. Each Evidence/status field starts with one status — Passed, Partial, Prototype, Not run or Not started — and gives the state on 29 October 2026, checked against `main` (CI passing, 108 automated tests) unless stated otherwise. All quantitative TBD values require group approval before final acceptance.

3.1 External Interfaces

Interfaces specify how users, hardware and connected services exchange information. Inputs must be validated and outputs must communicate state clearly, including unsupported devices, provider failures and invalid requests. Separating UI, hardware and software contracts allows independent component tests followed by end-to-end browser demonstrations.

3.1.1 User Interfaces

The current screens (Appendix C) illustrate a welcome/login design, a context screen with café selection and pictogram tiles, and a suggestion screen with candidate sentences and confirm/reject/stop actions. The experience must support revising the selected context without retaining stale suggestions, readable feedback and user confirmation before speech. The pictures show frontend work but do not establish that sign-in, AI image analysis or audio output have passed functional testing.

REQ-INT-001 | English communication flow

Table 10. Specification and acceptance criteria — REQ-INT-001

Field	Specification
Statement	The UI shall support entering context, viewing up to three English suggestions, selecting one, confirming/speaking, rejecting/regenerating and stopping speech.
Rationale	AAC users need a short, predictable path from context to a spoken sentence. Every control must work with pointer and keyboard because motor abilities differ, and confirmation before speech keeps the user in control.
Acceptance criteria	AC1: the context, suggestions and choose/speak stages can be completed with keyboard and with pointer or touch. AC2: "Confirm and speak" is disabled until a suggestion is selected. AC3: "Reject and try again", "Stop speaking" and "Back to context" are available on the suggestions page. Speech itself follows REQ-FUNC-007.
Verification method	Demonstration
Evidence/status	**Partial** (29 Oct 2026). Flow and controls implemented in the demo page; the team's frontend pages exist locally but are not yet connected to the API.
Owner	Thibaut

REQ-INT-002 | Text-only status and errors

Table 11. Specification and acceptance criteria — REQ-INT-002

Field	Specification
Statement	The UI shall display validation, generation and service messages as text and shall never speak these messages.
Rationale	A spoken error or status message would be heard by the listener as if the user had said it. Only a sentence the user selected and confirmed may be voiced.
Acceptance criteria	Simulated backend errors appear visibly with zero speech output.
Verification method	Demonstration
Evidence/status	**Partial** (29 Oct 2026). The demo page shows notices and errors as text; not yet checked in the team's frontend.
Owner	Thibaut

REQ-INT-007 | Accessible interface

Table 12. Specification and acceptance criteria — REQ-INT-007

Field	Specification
Statement	The three pages (login, context, suggestions) shall meet WCAG 2.1 level AA (proposed level, to be confirmed by the team).
Rationale	The primary users have speech and often motor or reading impairments; without keyboard, touch, contrast and screen-reader support the product would exclude the people it is built for.
Acceptance criteria	AC1: every action works with keyboard and touch, with a visible focus. AC2: text and controls reach a contrast ratio of at least 4.5:1. AC3: every tile, button and photo control has a text label read by a screen reader. AC4: touch targets are at least 44 × 44 CSS pixels.
Verification method	Inspection / Demonstration
Evidence/status	**Not started** (29 Oct 2026). New in v0.5; level to be confirmed (Appendix B).
Owner	Thibaut

3.1.2 Hardware Interfaces

The application is intended for ordinary web-capable devices with a display and pointer or touch input. Camera and photo-gallery access are optional input methods, and audio hardware supports audible sentence output. The interface should remain usable if a camera or speaker is unavailable, with an appropriate visible explanation rather than an unexplained failure. Physical-device and browser permission checks must be documented for each tested environment.

REQ-INT-003 | Optional photo and English audio

Table 13. Specification and acceptance criteria — REQ-INT-003

Field	Specification
Statement	The system shall accept supported browser photo/file inputs and shall produce speech with an available English voice, only as defined in REQ-FUNC-007.
Rationale	A photo adds context but many users or devices have no camera, so it must stay optional. Speech is the product's output, so it must use an English voice and start only after confirmation.
Acceptance criteria	AC1: JPEG, PNG and WebP can be selected from the camera, gallery or a file. AC2: a confirmed sentence is heard with an English voice. AC3: if no voice is available, a visible notice appears and the choice is still saved.
Verification method	Demonstration
Evidence/status	**Not run** (29 Oct 2026). Photo selection exists in the demo page and the frontend; speech audio not yet verified on a device.
Owner	Thibaut

3.1.3 Software Interfaces

The React client sends structured requests to the FastAPI service, which is responsible for validation, suggestions, feedback and service health. A stable sentence-provider abstraction permits switching from a deterministic mock to a live AI model without changing the user journey. Database migrations support consistent storage. Any selected external API must have recorded request/response formats, authentication, timeouts, error mapping and data-sharing rules.

REQ-INT-004 | REST API

Table 14. Specification and acceptance criteria — REQ-INT-004

Field	Specification
Statement	The server shall expose POST /api/suggestions, POST /api/suggestions/image, PUT /api/requests/{request_id}/feedback, POST /api/suggestions/reuse, GET /health, GET /ready and /openapi.json. Every error response shall contain `detail` and a stable `error_code`.
Rationale	A fixed, documented contract lets the frontend and backend be built and tested separately and lets reviewers check the behaviour against it.
Acceptance criteria	AC1: each endpoint returns its documented status codes (200, 201, 404, 409, 413, 415, 422, 502, 503). AC2: each of the 15 error codes in docs/ERRORS.md is returned for its case. AC3: all seven endpoints appear in /openapi.json and in docs/API.md.
Verification method	Test
Evidence/status	**Passed** (29 Oct 2026). All seven endpoints and the 15 error codes covered by automated tests; docs/API.md does not yet document the reuse endpoint (AC3 open).
Owner	Veronika

REQ-INT-005 | Replaceable provider

Table 15. Specification and acceptance criteria — REQ-INT-005

Field	Specification
Statement	The backend shall use a SentenceProvider abstraction accepting validated inputs, sanitized optional image bytes and excluded suggestions; response shall include sentences and an image_analyzed flag.
Rationale	The model is still being chosen and free-tier offers change often. A stable interface lets the team replace the mock or switch models without changing the API or the user journey, and lets tests inject a fake provider.
Acceptance criteria	Mock/test provider can be swapped without changing API contract.
Verification method	Test
Evidence/status	**Passed** (29 Oct 2026). Verified with the mock and injected test providers. The real adapters (Gemini, Ollama, OpenAI-compatible) follow the same interface in the `src/ai/` prototype but are not yet registered (`AI_PROVIDER` accepts only `mock`).
Owner	Jiahui / Veronika




Figure 3. AAC request activity diagram.

REQ-INT-006 | Symbol tile mapping

Table 16. Specification and acceptance criteria — REQ-INT-006

Field	Specification
Statement	The UI shall map chosen image tiles to stable, unambiguous text labels sent as symbols to the backend.
Rationale	The backend, the stored records and the reuse of accepted sentences match requests by these labels. Ambiguous or changing labels would produce wrong sentences or miss earlier choices.
Acceptance criteria	Selecting Water sends the agreed water symbol label and updates active-tile indication.

Field	Specification
Verification method	Demonstration
Evidence/status	**Not started** (29 Oct 2026). Tiles exist in the frontend; the API call is not yet connected.
Owner	Thibaut

3.2 Functional

Functional requirements describe externally visible steps: entering meaningful context; selecting a symbol; validating images and text; receiving a bounded set of appropriate alternatives; recording accepted or rejected suggestions; avoiding repeated rejected options; and speaking only after selecting and confirming a sentence. Tests must include unusual inputs, changes of context, failed providers and repeat clicks. An automated backend pass does not alone establish the same behavior in the real frontend.

REQ-FUNC-001 | Input validation

Table 17. Specification and acceptance criteria — REQ-FUNC-001

Field	Specification
Statement	The API shall validate allowed symbol labels, intent text, scene hint and English language field.
Rationale	Unchecked symbols and text could overload the provider, fill the database or carry instructions aimed at the model. Validation also gives the user a clear, early error.
Acceptance criteria	Valid input returns 201. Requests with neither a symbol nor a nonblank intention, more than 20 symbols, a symbol longer than 80 characters, an intention or scene hint longer than 500 characters, a language other than `en`, or unknown fields return 422 `VALIDATION_ERROR`.
Verification method	Test
Evidence/status	**Passed** (29 Oct 2026). Limits enforced in `app/schemas.py`.
Owner	Veronika

REQ-FUNC-002 | Image validation

Table 18. Specification and acceptance criteria — REQ-FUNC-002

Field	Specification
Statement	The API shall validate file format, file size and decodability before using images.
Rationale	Uploaded files can be huge, malformed or crafted as decompression bombs. Checking format, size and decodability protects the server before any image processing.
Acceptance criteria	A JPEG, PNG or WebP photo up to 5 MiB and 20 megapixels returns 201 with `image_supplied=true`; larger files return 413 `IMAGE_TOO_LARGE`; larger images return 413 `IMAGE_DIMENSIONS_TOO_LARGE`; other formats return 415 `UNSUPPORTED_IMAGE_FORMAT`; unreadable files return 415 `INVALID_IMAGE`.
Verification method	Test
Evidence/status	**Passed** (29 Oct 2026). Format, size and pixel limits enforced in `app/images.py`.
Owner	Veronika

REQ-FUNC-003 | Generate options

Table 19. Specification and acceptance criteria — REQ-FUNC-003

Field	Specification
Statement	The system shall produce no more than three complete English sentence suggestions from the provided input.
Rationale	Three complete sentences give a real choice without a long list to read, which matters for users with reading or motor difficulties.
Acceptance criteria	The café water scenario produces 1–3 readable English sentences, each with an ID, plus the request ID, provider name, `image_supplied`, `image_analyzed` and a notice. When nothing fits, REQ-FUNC-012 applies.
Verification method	Test
Evidence/status	**Passed** (29 Oct 2026). Verified with the mock provider.
Owner	Veronika

REQ-FUNC-004 | Stable request identity

Table 20. Specification and acceptance criteria — REQ-FUNC-004

Field	Specification
Statement	Each successful request shall return an identifier enabling downstream feedback and regeneration.
Rationale	Feedback and regeneration must refer to exactly the sentences the user saw. Without a stable identifier a choice could be stored against the wrong request.
Acceptance criteria	The ID resolves the correct request and suggestions.
Verification method	Test
Evidence/status	**Passed** (29 Oct 2026).
Owner	Veronika

REQ-FUNC-005 | Accept a suggestion

Table 21. Specification and acceptance criteria — REQ-FUNC-005

Field	Specification
Statement	The system shall persist acceptance only for a suggestion belonging to the indicated request.
Rationale	Storing a choice for a sentence that belongs to another request would record something the user never saw and corrupt the evaluation data and the reuse history.
Acceptance criteria	Valid acceptance succeeds; mismatched or unknown IDs fail.
Verification method	Test
Evidence/status	**Passed** (29 Oct 2026).
Owner	Veronika

REQ-FUNC-006 | Reject and regenerate

Table 22. Specification and acceptance criteria — REQ-FUNC-006

Field	Specification
Statement	The user shall reject options and regenerate without repeating earlier sentences in the same unchanged-input chain.
Rationale	Seeing a rejected sentence again wastes the user's effort. Allowing changed inputs inside a chain would mix two different wishes.
Acceptance criteria	Prior strings are excluded; changed chained inputs are rejected.
Verification method	Test
Evidence/status	**Passed** (29 Oct 2026).
Owner	Veronika

REQ-FUNC-007 | User-confirmed speech

Table 23. Specification and acceptance criteria — REQ-FUNC-007

Field	Specification
Statement	The frontend shall speak only after the chosen sentence is explicitly confirmed; stopping speech shall be possible.
Rationale	The sentence is spoken in the user's name. Speaking before confirmation could say something the user never chose, and a stop control limits the harm of a wrong choice.
Acceptance criteria	Loading/options alone produce no sound; stop button interrupts playback.
Verification method	Demonstration
Evidence/status	**Not run** (29 Oct 2026). Implemented in the demo page; buttons present in the frontend pages; audio not yet checked.
Owner	Thibaut / All

REQ-FUNC-008 | Clear stale options

Table 24. Specification and acceptance criteria — REQ-FUNC-008

Field	Specification
Statement	The UI shall invalidate previous suggestions when any context input changes.
Rationale	If old suggestions stay after the place, tile, text or photo changes, the user could confirm a sentence that belongs to the previous situation.
Acceptance criteria	Changing location, selected tile, text or photo clears previous selection.
Verification method	Demonstration
Evidence/status	**Not run** (29 Oct 2026). Implemented in the demo page; not yet in the frontend.
Owner	Thibaut / All




Figure 4. Logical system architecture.

REQ-FUNC-009 | Persist activity metadata

Table 25. Specification and acceptance criteria — REQ-FUNC-009

Field	Specification
Statement	The backend shall store generation inputs, suggestions, provider/latency, link to previous request and feedback, but not raw photos.
Rationale	Inputs, outputs, latency and decisions are needed to evaluate quality and to support regeneration and reuse. Raw photos are not needed and would add privacy risk.
Acceptance criteria	Data survives restart; feedback updates without duplicate records.
Verification method	Test
Evidence/status	**Passed** (29 Oct 2026). Raw photos are not stored.
Owner	Veronika

REQ-FUNC-010 | Integrated web flow

Table 26. Specification and acceptance criteria — REQ-FUNC-010

Field	Specification
Statement	The team web frontend shall complete the context → suggestions → choose → confirm/speak workflow via the actual backend.
Rationale	Backend tests and the demo page do not prove that the team's own interface works; the course product is the integrated web application.
Acceptance criteria	One repeatable café scenario passes from tile selection to saved acceptance.
Verification method	Demonstration
Evidence/status	**Not started** (29 Oct 2026). Frontend not yet connected to the backend.
Owner	Thibaut / All

REQ-FUNC-011 | Additional contexts

Table 27. Specification and acceptance criteria — REQ-FUNC-011

Field	Specification
Statement	After the café increment the product should support further approved everyday situations, e.g. bus or medical visit.
Rationale	AAC users communicate in many places. A single café scenario would not show that the approach works beyond one vocabulary.
Acceptance criteria	Team agrees scenario set and demonstrates at least one additional case.
Verification method	Demonstration
Evidence/status	**Partial** (29 Oct 2026). More places and tiles exist in the frontend; evaluation cases for new situations not yet defined.
Owner	Thibaut / All

REQ-FUNC-012 | Handle no suggestions

Table 28. Specification and acceptance criteria — REQ-FUNC-012

Field	Specification
Statement	When no suitable sentence can be produced, the system shall return an empty suggestion list with an explanatory notice, and the UI shall let the user edit the input.
Rationale	An honest empty answer with a way to edit the input is safer than a guessed sentence, which could be spoken in the user's name (REQ-ML-003).
Acceptance criteria	An unsupported or negated intention for the mock (e.g. "I do not want water") returns HTTP 201 with an empty list and a notice; nothing is spoken.
Verification method	Test
Evidence/status	**Passed** (29 Oct 2026). Verified with the mock provider.
Owner	Veronika

3.3 Quality of Service

The application must not merely generate plausible language; it must do so promptly, consistently, securely and with enough diagnostic information for maintenance. Quality claims should be supported with measured latency, fault-handling trials, security inspection and operational records in clearly identified environments. Numerical targets that are still open must be agreed before final acceptance.

3.3.1 Performance

Sentence suggestions need to arrive quickly enough for an ordinary real-time interaction. Measurements should separate interface delay, request validation, model computation and start of speech playback. Because a mock template provider may be much faster than a real vision-language service, the team must report provider version, test hardware and the percentile measured alongside any response-time result. The final performance threshold remains subject to agreement.

REQ-PERF-001 | Generation latency

Table 29. Specification and acceptance criteria — REQ-PERF-001

Field	Specification
Statement	The server shall record provider latency per generation. The end-to-end time from request to displayed suggestions shall be at most 10 s at the 95th percentile for single-user use on the demo network (provisional target, to be confirmed after the AI evaluation).
Rationale	A listener will not wait long for a reply. Hosted models are much slower than the mock (1.4–26 s measured on the free tier), so latency must be measured before a target can be agreed.
Acceptance criteria	AC1: `latency_ms` is stored for every generation. AC2: over the evaluation set, the p95 end-to-end time is ≤ 10 s, reported with provider, model and network.
Verification method	Analysis
Evidence/status	**Partial** (29 Oct 2026). Latency stored per request. Measured on synthetic inputs: Gemini 3.5 Flash 1.4–26 s per request (21 Oct); full generations with 3.5 and 3.1 Flash-Lite 1.7–6.2 s (28 Oct). p95 over the evaluation set not yet measured.
Owner	Veronika

3.3.2 Security

Security is especially important because users may enter personal intentions or upload scene photographs. Uploaded files should be checked and minimized, sensitive metadata should not be unnecessarily retained, and credentials or API secrets must remain outside browser code. Any public multi-user version needs authenticated ownership checks, request limits and clear consent and retention rules. The provided login mockup must not be taken as evidence that secure authentication is already implemented.

REQ-SEC-001 | Photo minimization

Table 30. Specification and acceptance criteria — REQ-SEC-001

Field	Specification
Statement	The system shall decode, resize to at most 1024×1024, and re-encode submitted photos without EXIF metadata; raw originals shall not be stored.
Rationale	Scene photos can show faces, homes or GPS metadata. Minimising them and never storing the originals limits the harm of a data leak.
Acceptance criteria	DB has no raw photo; output re-encoded JPEG has no EXIF.
Verification method	Test / Inspection
Evidence/status	**Partial** (29 Oct 2026). Resize, re-encoding and no raw storage implemented; EXIF removal checked by inspection only, no automated test.
Owner	Abid / Veronika

REQ-SEC-002 | Safe error responses

Table 31. Specification and acceptance criteria — REQ-SEC-002

Field	Specification
Statement	API shall not expose provider stack traces, secrets or internal exception content to users.
Rationale	Stack traces and provider messages can reveal keys, paths or internal structure to an attacker and mean nothing to the user.
Acceptance criteria	Failures return safe generic error responses.
Verification method	Test / Inspection
Evidence/status	**Passed** (29 Oct 2026).
Owner	Abid / Veronika

REQ-SEC-003 | Secrets configuration

Table 32. Specification and acceptance criteria — REQ-SEC-003

Field	Specification
Statement	Service credentials shall come from environment/secret configuration and never be committed to public source.
Rationale	The repository is public. A committed API key would be copied at once and could use up the free quota or create costs.
Acceptance criteria	Repository inspection confirms no exposed keys.
Verification method	Test / Inspection
Evidence/status	**Passed** (29 Oct 2026). Repository scanned before the 28 Oct push: no keys.
Owner	Abid / Veronika

REQ-SEC-004 | Input and output safety

Table 33. Specification and acceptance criteria — REQ-SEC-004

Field	Specification
Statement	The backend shall validate input and the frontend shall escape generated text when displaying it.
Rationale	Model output is untrusted text. Rendering it as HTML could run injected scripts in the user's browser.
Acceptance criteria	Injected HTML is displayed as text and cannot execute.
Verification method	Test / Inspection
Evidence/status	**Partial** (29 Oct 2026). Backend validation tested; escaping in the team's frontend not yet checked.
Owner	Abid / Veronika

REQ-SEC-005 | Authentication and ownership

Table 34. Specification and acceptance criteria — REQ-SEC-005

Field	Specification
Statement	Prior to public trial, all user-owned records and endpoints, including the history of accepted sentences used for reuse, shall enforce authenticated access and ownership.
Rationale	Request IDs are not authorization. Personal requests and accepted sentences must not be readable or changeable by other users, especially once they are reused.
Acceptance criteria	Cross-account read/write tests are denied; reuse never returns another user's sentences.
Verification method	Test / Inspection
Evidence/status	**Not started** (29 Oct 2026). The login page is interface only.
Owner	Abid / Veronika

REQ-SEC-006 | Abuse and budget limits

Table 35. Specification and acceptance criteria — REQ-SEC-006

Field	Specification
Statement	Public endpoints shall use approved rate limits, request/image limits and provider-spend safeguards.
Rationale	An open endpoint can be flooded, and every model call uses a scarce free quota (as low as 20 requests per day per model) or money on a paid tier.
Acceptance criteria	Load/abuse tests verify safe limits; thresholds TBD.
Verification method	Test / Inspection
Evidence/status	**Prototype** (29 Oct 2026). AI quota safeguards in the prototype: daily cap of 16 calls per model, no retry on 429, pause until the quota resets. Public rate and spending limits not started.
Owner	Abid / Veronika

REQ-SEC-007 | Consent and retention

Table 36. Specification and acceptance criteria — REQ-SEC-007

Field	Specification
Statement	Before testing with real users, the application shall present informed consent and implement a reviewed retention/deletion policy that also covers the stored requests, feedback and the reuse history.
Rationale	AAC users may be in a vulnerable position, and free-tier AI services may use inputs to improve their products. Consent and retention rules must exist before any real personal data is used.
Acceptance criteria	Written policy, consent record and erasure test available.
Verification method	Test / Inspection
Evidence/status	**Not started** (29 Oct 2026). Synthetic-only rule applied to all AI tests.
Owner	All

3.3.3 Reliability

A communication request must behave predictably during invalid input, provider timeout, network interruption or repeated button presses. Error messages should allow the person to retry or revise a request without unintentionally speaking an old sentence. Feedback processing should avoid accidental duplicate records, and the system must never treat a failed generation as a confirmed user choice. Failure injection and retry tests should document these properties.

REQ-REL-001 | Generation error mapping

Table 37. Specification and acceptance criteria — REQ-REL-001

Field	Specification
Statement	The system shall handle invalid or failing provider output with a controlled response rather than crash.
Rationale	A model can return malformed, overlong, empty or duplicated output. Showing or storing it unchecked would break the interface or the records.
Acceptance criteria	Provider error yields documented controlled status.
Verification method	Test
Evidence/status	**Passed** (29 Oct 2026).
Owner	Veronika

REQ-REL-002 | Unavailable provider

Table 38. Specification and acceptance criteria — REQ-REL-002

Field	Specification
Statement	The system shall return a controlled 503 when provider is unavailable and enforce configured network timeout for real services.
Rationale	Hosted models can be overloaded (HTTP 503) or hang. Without a timeout the user waits indefinitely; a clear 503 lets the frontend offer a retry instead of failing silently.
Acceptance criteria	ProviderUnavailable maps to 503; timeout target TBD.
Verification method	Test
Evidence/status	**Partial** (29 Oct 2026). 503 mapping passed in the backend; timeouts implemented in the prototype (hosted 15 s connect / 30 s read, local 3 s / 180 s), not yet in the backend.
Owner	Veronika

REQ-REL-003 | Idempotent feedback

Table 39. Specification and acceptance criteria — REQ-REL-003

Field	Specification
Statement	Repeated identical feedback submissions shall not create duplicate feedback rows.
Rationale	Double clicks and network retries are common on touch devices. Duplicate feedback rows would distort the evaluation and the reuse history.
Acceptance criteria	Two equivalent updates produce exactly one current record.
Verification method	Test
Evidence/status	**Passed** (29 Oct 2026).
Owner	Veronika

3.3.4 Availability

Service readiness means the application and its dependencies are reachable when needed. The backend starter includes health and readiness endpoints, but those checks do not establish an operational uptime guarantee. A service-level objective requires an approved hosting environment, monitoring period, defined outage criteria and recovery plan. Until these decisions are made and measured, any numerical availability claim should remain pending.

REQ-AVAIL-001 | Health and readiness

Table 40. Specification and acceptance criteria — REQ-AVAIL-001

Field	Specification
Statement	The backend shall expose a liveness check and a readiness check covering database reachability/migrations; a target service availability is TBD.
Rationale	Deployment and demonstrations need an automatic signal that the service and its database are really ready before users arrive.
Acceptance criteria	AC1: /health returns 200 with status, provider name and version. AC2: /ready returns 503 `DATABASE_UNAVAILABLE` or `MIGRATIONS_REQUIRED` before migration and 200 "ready" after `alembic upgrade head`. AC3: the availability target is set once hosting is chosen (Appendix B).
Verification method	Test
Evidence/status	**Passed** (29 Oct 2026). AC1 and AC2 pass; availability target open (AC3).
Owner	Abid

3.3.5 Observability

Logs, test outputs and metrics should make it possible to investigate validation errors, unavailable model providers, latency and service readiness. Diagnostic records should use stable request identifiers and avoid exposing raw private photographs or unnecessary personal text. Evidence such as CI results, health checks and measured timings must be tied to a dated build and environment so that reviewers can distinguish prototype observations from validated deployment behavior.

REQ-OBS-001 | Privacy-safe operations

Table 41. Specification and acceptance criteria — REQ-OBS-001

Field	Specification
Statement	Operational logs shall not record image bytes, full personal intentions, passwords or provider secrets.
Rationale	Logs are copied, shared and kept longer than the database. They must not become a store of photos, intentions or secrets.
Acceptance criteria	Inspection of normal and error logs reveals no prohibited sensitive content.
Verification method	Inspection
Evidence/status	**Partial** (29 Oct 2026). AI evaluation records tested (no key, no image); server log review not done.
Owner	Abid

3.4 Compliance

The team must review licences for software dependencies, symbols and other media, correctly attribute external inspirations, and follow course submission and repository rules. Data-protection and accessibility obligations depend partly on the final deployment location, participant group and handling of photographs or user records. Because those factors remain unresolved, the specification requires an explicit pre-release assessment rather than asserting compliance with unverified legal or clinical standards.

REQ-COMP-001 | Open-source licensing

Table 42. Specification and acceptance criteria — REQ-COMP-001

Field	Specification
Statement	The team shall document and respect all dependency and asset licenses and shall not copy Cboard code/assets without compatible permission.
Rationale	The repository is public and the product is inspired by Cboard. Using code, symbols or icons without a compatible licence would infringe copyright.
Acceptance criteria	Inventory and project LICENSE reviewed and available.
Verification method	Inspection
Evidence/status	**Not started** (29 Oct 2026). No repository licence yet; UI label "Select Cboard tiles" to be renamed.
Owner	All

REQ-COMP-002 | Course collaboration rules

Table 43. Specification and acceptance criteria — REQ-COMP-002

Field	Specification
Statement	The team shall use the mandated GitHub commit convention and peer review workflow, including issues for review actions.
Rationale	The course assesses the process as well as the product, and a consistent history makes peer review and auditing possible.
Acceptance criteria	Git history and issues show applied course conventions.
Verification method	Inspection
Evidence/status	**Partial** (29 Oct 2026). Course format used on main since W6; the backend branch commits merged on 28 Oct did not use it.
Owner	All

3.5 Design and Implementation

The implementation approach divides user interaction, API orchestration, storage and sentence generation into replaceable modules. Delivery processes must make builds reproducible, migrations reviewable and service configuration secure. The following constraints specify how the team intends to install, test, package and maintain its implementation without falsely suggesting that every planned production component has been finished.

3.5.1 Installation

A new developer should be able to reproduce the project from documented dependencies, environment variables, database migrations and startup commands. A mock provider should permit development without paid external AI credentials. Installation evidence should come from a clean environment and identify platform versions; successful Linux testing with SQLite does not automatically establish Windows or PostgreSQL support.

REQ-INST-001 | Reproducible local setup

Table 44. Specification and acceptance criteria — REQ-INST-001

Field	Specification
Statement	The backend shall install with Python 3.12 and pinned dependencies, migrate via Alembic and serve a ready state with documented configuration.
Rationale	A new teammate or reviewer must be able to run the system from the documentation alone, without paid AI credentials.
Acceptance criteria	A new teammate runs documented installation and /ready succeeds.
Verification method	Demonstration
Evidence/status	**Partial** (29 Oct 2026). Install, migrations and all tests run on Windows (28 Oct); the README quick start has not been re-run end to end.
Owner	Veronika

3.5.2 Build and Delivery

GitHub Actions runs pytest, Ruff and the migration checks on every push. On 28–29 October 2026 it passed on `main` with 108 automated tests (77 backend, 31 AI; the Week 6 report recorded 26). The AI tests use mock transports, so CI needs no key and spends no quota. Future release evidence should include a pinned revision, reproducible build steps, test outcomes, integration checks and documented exceptions so a reviewer can connect the delivered code to the SRS version.

REQ-BUILD-001 | Automated CI

Table 45. Specification and acceptance criteria — REQ-BUILD-001

Field	Specification
Statement	Each push/PR shall run Ruff lint, pytest and migration checks in CI.
Rationale	Four people commit in parallel. Automatic checks on every change keep main working and catch schema drift before it reaches others.
Acceptance criteria	A clean change passes all automated checks.
Verification method	Inspection
Evidence/status	**Passed** (29 Oct 2026). CI passed on main at commit 6b85dba (28 Oct).
Owner	Abid

3.5.3 Distribution

Docker Compose is the proposed means of deploying the coordinated services for demonstration and later hosting. The deployed stack must manage database initialization, configuration, secret injection, network exposure and readiness. A PostgreSQL-backed run and public-hosting security controls still require their own verification. The team should specify which services are locally hosted and which may transfer inputs to an external model endpoint before any outside use.

REQ-DIST-001 | Container deployment

Table 46. Specification and acceptance criteria — REQ-DIST-001

Field	Specification
Statement	The backend and database shall deploy with Docker Compose, persistent storage, ordered migrations and protected secrets.
Rationale	The demonstration and later hosting need the same reproducible stack, with the database initialised and secrets injected rather than set by hand.
Acceptance criteria	From fresh stack, migration succeeds and /ready is ready.
Verification method	Demonstration
Evidence/status	**Not started** (29 Oct 2026). Hosting not chosen.
Owner	Abid

3.5.4 Maintainability

Changes to a symbol board or model provider should not require rewriting unrelated components. Modular service interfaces, documented API contracts, database migrations and regression tests help preserve maintainability. Error mapping and provider adapters should remain independently testable, and the SRS revision history must be updated when accepted behavior changes. This reduces divergence between the submitted document and the evolving source code.

REQ-MAINT-001 | Modular provider and schema

Table 47. Specification and acceptance criteria — REQ-MAINT-001

Field	Specification
Statement	The model shall remain behind a replaceable interface, and database schema changes shall be handled through migrations.
Rationale	AI models and free-tier offers change often and the schema will grow. Replaceable components and migrations keep each change local and reversible.
Acceptance criteria	Alternate provider injects successfully; migration check passes.
Verification method	Inspection
Evidence/status	**Passed** (29 Oct 2026).
Owner	Veronika

3.5.5 Reusability

General input validation, the symbol-to-intent mapping, the sentence-provider interface and the API client are candidates for reuse when another setting is introduced. The goal is to adapt the existing workflow with new vocabulary rather than create a separate application for each context. Cboard is an inspiration in the revised scope, so any actual reused third-party code or icons must be recorded and licensed separately. No additional numbered requirement is established for reuse. The sentence provider and API are intended to be reusable modules; Cboard code and assets are not reused.

3.5.6 Portability

Browser and deployment portability should be supported through documented runtime versions and environment-driven configuration. Cross-platform claims must be justified with named operating systems, browsers, database engines and container environments. The current weekly checkpoint supports Linux/SQLite starter testing while identifying Windows and live PostgreSQL verification as outstanding work. These checks should be completed before expanding the declared supported-platform list.

REQ-PORT-001 | SQLite / PostgreSQL portability

Table 48. Specification and acceptance criteria — REQ-PORT-001

Field	Specification
Statement	The backend shall support SQLite in local development and PostgreSQL for deployment via configuration without altering business rules.
Rationale	The team develops on Windows laptops with SQLite while deployment targets Linux containers with PostgreSQL; business rules must not depend on the engine.
Acceptance criteria	Database migration and tests pass against both engines.
Verification method	Test
Evidence/status	**Partial** (29 Oct 2026). SQLite on Windows (local) and Linux (CI) verified; PostgreSQL not yet run.
Owner	Veronika / Abid

3.5.7 Cost

Model inference, image processing, storage and external hosting may generate recurring charges even for a small demonstration. The team should define a budget owner, usage monitoring, provider quotas and rate limits before enabling paid or publicly reachable endpoints. The supplied materials do not establish a final monetary ceiling, so a number should be approved through the open-decision process rather than invented for this report. Model API usage, compute and hosting costs shall be monitored before real-provider and public-trial deployment. Budget ceiling remains a project decision, not an established acceptance threshold. For the AI part the current budget is zero: the prototype uses only the Gemini free tier, whose measured limits are as low as 5 requests per minute and 20 per day per model, and stops each model at a local cap of 16 calls a day; one generation uses about 410 input tokens with a photo and 150 without.

3.5.8 Deadline

Feature increments follow the café proof of concept, protected deployment and then broader situations. Each milestone is tracked by both an agreed date and objective evidence, including specific tests or deliverables. The course milestones are fixed; the dates of the team's own work packages after week 7 are tentative and agreed in the weekly meetings (the weekly report holds the current chart).

Table 49. Course milestones

Week	Course milestone
7	Software Requirements Specification, with cross-team peer review
12	Software detailed design
16	Product launch and investment pitch




Figure 8. Project schedule with course milestones.

3.5.9 Proof of Concept

The first proof of concept demonstrates one complete café request using context, a selected Water symbol, alternative English sentences and user-confirmed speech. It must also show that rejection and changed inputs have predictable effects. Fixed mock templates are sufficient for preliminary wiring and UI flow testing, but they do not validate multimodal scene understanding or the final live-model quality targets.

REQ-POC-001 | Café end-to-end proof of concept

Table 50. Specification and acceptance criteria — REQ-POC-001

Field	Specification
Statement	The integrated product shall support the water-in-a-café scenario from context selection through reviewed suggestions to explicit English speech.
Rationale	One complete scenario is the smallest proof that interface, API, storage, sentence provider and speech work together.
Acceptance criteria	One tester completes scenario; acceptance saved; speech starts only after confirmation.
Verification method	Demonstration
Evidence/status	**Not started** (29 Oct 2026). Frontend not yet connected.
Owner	All

3.5.10 Change Management

Scope and implementation decisions should be recorded with an owner, rationale, affected requirement IDs and corresponding verification changes. The change from a Cboard extension to a standalone inspired product is an

important example. Each revision should receive team review before the document is considered the new baseline, and unresolved choices should remain visible instead of being silently embedded as assumptions.

REQ-CM-001 | Managed requirement changes

Table 51. Specification and acceptance criteria — REQ-CM-001

Field	Specification
Statement	Changes affecting external behavior, scope or acceptance criteria shall be recorded, reviewed and versioned before implementation.
Rationale	Requirements change during the project, as the move from a Cboard extension to a standalone product showed. Untracked changes would let the SRS and the code drift apart.
Acceptance criteria	Issue, reviewer decision and updated specification are traceable.
Verification method	Inspection
Evidence/status	**Partial** (29 Oct 2026). SRS changes recorded; docs/API.md not yet updated for the reuse endpoint.
Owner	All

3.6 AI/ML

The AI/ML requirements describe the transition from fixed sentence templates to genuinely context-aware suggestions. The model combines scene cues with the explicitly selected symbols and text while preserving user autonomy and understandable English phrasing. The backend still uses the mock provider. The real provider has been built and tested as a standalone prototype (`src/ai/`, 31 offline tests): adapters for Gemini, a local Ollama model and OpenAI-compatible services, a backup chain with quota handling, and reuse of sentences the user accepted before. Its quality criteria are therefore proposed acceptance obligations until the evaluation (REQ-ML-002) has been run and the provider is connected to the backend.

3.6.1 Model Specification

The chosen model is documented by version, provider, accepted input modalities, output format, timeout and evaluation approach (R7, R8). Because the laptop cannot run large local models and the budget is zero, the provider calls a hosted vision-capable model on the free tier. It makes **one** call per request: the photo (resized to at most 384 px and sent at low media resolution, about 266 tokens) and the user's input as named JSON fields go in, and a JSON object with at most three sentences comes out, with the lowest thinking level and at most 150 output tokens. Free-tier quotas are counted per model, so the provider tries an ordered list: `gemini-3.5-flash-lite`, `gemini-3.1-flash-lite`, `gemini-3.5-flash`, `gemini-3.8-flash`, and a small local model (`qwen3-vl:2b` through Ollama, about 1.9 GB) as an offline backup that is not yet installed. Model names are configuration, not code. The group compares candidates on a defined café evaluation set and approves minimum relevance and quality levels before real provider acceptance.

REQ-ML-001 | Model selection

Table 52. Specification and acceptance criteria — REQ-ML-001

Field	Specification
Statement	A real provider shall be selected and documented with input/output schema, version and English sentence quality evaluation. It shall make one multimodal call per request (optional photo plus the user's input as JSON fields in, at most three sentences as JSON out), with model names held in configuration.
Rationale	The product's value depends on the model, and it must run with zero budget and without a GPU. Documenting the choice, its input and output, and its evaluation makes it reviewable and replaceable.
Acceptance criteria	Provider identity, model order and a repeatable model evaluation report are present; one provider request per generation.
Verification method	Analysis / Demonstration
Evidence/status	**Prototype** (29 Oct 2026). Gemini free tier; order `gemini-3.5-flash-lite`, `gemini-3.1-flash-lite`, `gemini-3.5-flash`, `gemini-3.8-flash`, then local `qwen3-vl:2b` (Ollama, not yet installed). Measured 412 input tokens with a photo and 0 thinking tokens. Evaluation report pending; not yet connected to the backend.
Owner	Jiahui

3.6.2 Data Management

Evaluation data should record the selected scene, chosen symbols, optional intent and permitted imagery, together with reference intentions or quality ratings. Test examples should have traceable provenance and an agreed separation between development examples and final evaluation cases. Personal photos must not be introduced into external services without appropriate consent and a documented retention and disclosure policy; the Gemini free tier states that inputs may be used to improve Google's products, so only synthetic text and drawn photos are sent. Evaluation runs are saved with the model, the prompt version, inputs, outputs, latency and token use, but never the API key or the image. Accepted sentences may be reused for matching requests (backend endpoint `POST /api/suggestions/reuse`, exact match) or passed to the model as wording examples (prototype); this history has no user ownership yet and is limited to synthetic data. The final dataset size and composition remain open technical decisions.

REQ-ML-002 | Evaluation inputs

Table 53. Specification and acceptance criteria — REQ-ML-002

Field	Specification
Statement	The team shall maintain a documented, consent-safe set of synthetic café contexts and intended requests for evaluation.
Rationale	A provider can only be compared and accepted against a fixed set of cases with known intentions. Synthetic cases avoid sending personal material to free-tier services.
Acceptance criteria	Dataset provenance, cases and expected intentions documented.
Verification method	Analysis / Demonstration
Evidence/status	**Not started** (29 Oct 2026). Case categories defined in the AI model plan; three cases run live; the 30–40 case set is pending.
Owner	Jiahui

REQ-ML-008 | Reuse of accepted sentences

Table 54. Specification and acceptance criteria — REQ-ML-008

Field	Specification
Statement	For a text-only request whose place, intention and symbols match an earlier request, the system shall be able to return up to three sentences the user accepted before, newest first, without a model call and without changing any record. Similar but not matching requests may pass up to three accepted sentences to the model as wording examples. A negated wish shall never match a plain one, and requests with a photo shall not be answered from reuse.
Rationale	Reusing a sentence the user already accepted saves scarce free-tier requests and keeps the user's own wording; matching must not turn a negative wish into a positive one.
Acceptance criteria	AC1 (backend): an exact match returns the accepted sentence and its source IDs; after the feedback changes to rejected it is no longer returned. AC2 (backend): no provider call and no record change. AC3 (prototype): symbols match in any order or case; a score of at least 0.9 reuses, at least 0.4 gives examples. AC4: "no sugar" never matches "sugar".
Verification method	Test
Evidence/status	**Partial** (29 Oct 2026). AC1 and AC2 passed in the backend (exact, case-sensitive match; 40 tests; merged 28 Oct). AC3 and AC4 implemented in the prototype (7 tests). Not yet called automatically before generation.
Owner	Veronika / Jiahui

3.6.3 Guardrails

Generated language must be constrained by the user's explicit choices rather than guess what the user wants from a photo. The system should validate response shape and length, screen malformed or unsafe output and avoid presenting requests unrelated to the supplied intention. If generation fails or produces unsuitable results, the user must be able to reject, revise or stop; output must never automatically trigger speech. In the prototype the scene hint, intention and symbols travel as JSON data, never inside the instructions, and the model is told to ignore instructions found in them or in the photo. After each answer the provider drops sentences longer than 300 characters, repeats of earlier suggestions, and any sentence that loses a negation the user expressed ("I do not want sugar"). An unparseable or blocked answer becomes an empty list, never a guessed sentence.

REQ-ML-003 | Respect explicit intent

Table 55. Specification and acceptance criteria — REQ-ML-003

Field	Specification
Statement	Generated sentences shall reflect the user's symbols/text and must not invent an intent from the photograph alone. A negative intention shall stay negative, and scene text, intention text and photo content shall be treated as data, never as instructions to the model.
Rationale	A photo cannot reveal what the person wants, and the sentence is spoken in their name. An invented wish, or a lost negation such as "no sugar", is the most harmful error the product can make.
Acceptance criteria	AC1: contradictory scene tests preserve user intent and avoid unsafe assumptions. AC2: a negative intention never produces an affirmative sentence. AC3: an injection text in the scene hint or intention changes nothing beyond context.
Verification method	Test / Analysis
Evidence/status	**Partial** (29 Oct 2026). Mock: negative or unknown intent returns nothing (passed). Prototype: JSON input fields, prompt rules and a negation post-check (tested); the live negation case kept "no sugar" in all three sentences. AC3 injection case not yet run.
Owner	Jiahui

3.6.4 Ethics

An assistive communication tool should enhance the person's ability to express a preference, not override that preference. Its interface should make clear when suggestions are generated and avoid claiming human-level understanding or clinical effectiveness. Evaluation should examine respectful wording, intent preservation and accessibility for representative users. Real-user studies and collection of personal material require an ethical and privacy review appropriate to the study context. Suggesting options the user did not ask for (for example "juice" when the user selected "water") would conflict with REQ-ML-003; a proposal for doing this safely is open for team decision (R9, Appendix B).

REQ-ML-004 | Non-deceptive operation

Table 56. Specification and acceptance criteria — REQ-ML-004

Field	Specification
Statement	The UI shall accurately communicate when photos have not been analyzed and shall not misrepresent template outputs as AI understanding.
Rationale	Users and evaluators must not believe that fixed templates understood their photo. A false claim would mislead the user and invalidate the evaluation.
Acceptance criteria	Mock mode is labeled; image analyzed flag truthfully shown.
Verification method	Test
Evidence/status	**Passed** (29 Oct 2026). Mock returns `image_analyzed=false` and the suggestions page shows "Mock templates only. Photos are not analyzed."; the prototype sets the flag only after a successful call with a photo.
Owner	Jiahui

3.6.5 Human-in-the-Loop

The person using the AAC board is the final authority on any spoken request. They must be able to inspect available sentences, select one, confirm it for speech, reject alternatives and stop playback. Changing context must prevent stale outputs from being inadvertently used. Verification should exercise these actions from the actual browser interface and test repeated clicks and asynchronous provider responses.

REQ-ML-005 | User veto and confirmation

Table 57. Specification and acceptance criteria — REQ-ML-005

Field	Specification
Statement	Users shall be able to inspect, reject, regenerate and confirm the final sentence before any speech action, as defined in REQ-FUNC-007.
Rationale	The person using the board is the final authority on what is said in their name; research on AI-assisted AAC stresses this control (Valencia et al., 2023).
Acceptance criteria	No unconfirmed output is spoken; rejected options are not voiced.
Verification method	Demonstration
Evidence/status	**Not run** (29 Oct 2026). User oversight implemented in the demo page; integrated check pending.
Owner	Jiahui

3.6.6 Model Lifecycle and Operations

Model integration should preserve the provider identifier, version, evaluation dataset, chosen settings and dated release evidence. Updating prompts or switching services may change output quality or latency, so the same representative tests should be rerun before release; each evaluation record carries a prompt version (a hash of the system prompt). Free-tier models are renamed, retired or overloaded without notice: on a quota error (HTTP 429) the provider does not

retry the same model but cools it down for the delay the service returns, or until the next quota day, and moves to the next model; three failures in a row pause a model for five minutes; daily counts survive restarts. If no model can answer, the request ends with 503 "Generation unavailable"; mock templates are never shown as an AI answer. Monitoring for failed calls, unacceptable suggestions and cost spikes should inform rollback. Retraining is not planned; the local model is optional until the team formally selects and verifies it.

REQ-ML-006 | Model quality/version oversight

Table 58. Specification and acceptance criteria — REQ-ML-006

Field	Specification
Statement	Deployment shall record model/provider version and support rollback to an alternate provider if the live model fails. When no provider can answer, the system shall return a controlled 503 and shall never present mock templates as an AI answer.
Rationale	Free-tier models are renamed, retired or overloaded without notice. Recording the version and keeping a tested fallback lets the team compare results and recover quickly, without ever presenting templates as AI.
Acceptance criteria	Provider identity is logged without sensitive content; fallback order, quota cooldowns and the all-providers-down case are tested; rollback procedure tested.
Verification method	Test
Evidence/status	**Partial** (29 Oct 2026). Provider name stored per request in the backend; fallback and the all-down case tested in the prototype; rollback not yet tested in the backend.
Owner	Jiahui

REQ-ML-007 | Backup models and quota handling

Table 59. Specification and acceptance criteria — REQ-ML-007

Field	Specification
Statement	The provider shall try an ordered list of models. On HTTP 429 it shall not retry the same model but shall pause it for the delay returned by the service (or 60 s), or until the next quota day for a daily quota, and use the next model at once. After three failures in a row a model shall be paused for 5 minutes. Each model shall stop at a local daily cap (default 16). If every model fails, the request shall end with HTTP 503.
Rationale	The free tier allows as little as 5 requests per minute and 20 per day per model, and quotas are counted per model; without ordered fallback and quota handling the product would stop after a few requests.
Acceptance criteria	AC1: a per-minute 429 moves to the next model and pauses the first for the returned delay. AC2: a daily 429 pauses the model until the next quota day, also after a restart. AC3: the daily cap stops calls and counts failed calls. AC4: three failures pause a model for 5 minutes. AC5: when all models fail the result is 503, never a mock answer. AC6: an empty answer does not spend another model's quota.
Verification method	Test
Evidence/status	**Prototype** (29 Oct 2026). Implemented in `src/ai/chain.py`; limits measured for 20 models on 28 Oct; Flash-Lite daily limits still unknown.
Owner	Jiahui

Chapter 4 — Verification

Verification combines automated tests, manual demonstration, source and configuration inspection, and measured analysis. Each requirement must link to a test or review artifact with its environment, revision, date and observed status, so an assessor can distinguish a pass, partial implementation, pending manual check and not-started work. The status below was re-checked on 29 October 2026 against `main`, where CI passed with 108 automated tests. For comparison, the Week 6 checkpoint reported 45 requirements as 19 passed, 8 in progress, 6 awaiting manual checks and 12 not started, with 26 backend tests. Frontend speech, authentication, real AI in the backend and deployment must still be demonstrated before they are marked Passed.

Verification methods: Test = automated assertions; Demonstration = observed end-to-end interaction; Inspection = review of source/configuration and artifacts; Analysis = latency or quality measurements. Evidence status must come from a dated run, not screenshots alone.

Table 60. Requirement status on 29 October 2026

Status	Requirements
Passed	18
Partial	15
Prototype	3
Not run	4
Not started	9
Total	**49**

"Passed" means the behaviour is verified by the listed tests or inspection; when it was verified with the mock provider, it must be re-checked once the real provider is connected. "Prototype" means implemented and tested in the standalone AI prototype (`src/ai/`) but not yet in the backend.

Table 61. Requirement traceability

Requirement	Method	Test or artifact	Status
REQ-INT-001	Demonstration	Frontend pages (Appendix C); demo page `app/static/`	Partial
REQ-INT-002	Demonstration	Demo page status line	Partial
REQ-INT-007	Inspection / Demonstration	Accessibility review (TBD)	Not started
REQ-INT-003	Demonstration	Manual device check	Not run
REQ-INT-004	Test	`tests/test_api.py`, `tests/test_errors.py`, `test_reuse_contract_is_in_openapi`	Passed
REQ-INT-005	Test	`test_provider_failure_is_safe`, `test_invalid_provider_output_is_not_saved`	Passed
REQ-INT-006	Demonstration	REQ-POC-001 scenario	Not started
REQ-FUNC-001	Test	`test_invalid_inputs`, `test_validation_error_keeps_detail_list`	Passed
REQ-FUNC-002	Test	`test_photo_input`, `test_oversized_photo`, `test_image_error_codes`, `test_invalid_photo_and_payload`	Passed
REQ-FUNC-003	Test	`test_generation_persists_and_survives_restart`	Passed
REQ-FUNC-004	Test	`test_unknown_request`, `test_request_not_found`	Passed
REQ-FUNC-005	Test	`test_cannot_accept_another_requests_suggestion`, `test_invalid_feedback`	Passed
REQ-FUNC-006	Test	`test_regeneration_excludes_entire_chain`, `test_changed_intent_requires_new_chain`, `test_changed_inputs`	Passed
REQ-FUNC-007	Demonstration	Manual check on the demo page	Not run
REQ-FUNC-008	Demonstration	Manual check on the demo page	Not run
REQ-FUNC-009	Test	`test_generation_persists_and_survives_restart`, `test_feedback_is_idempotent_and_can_be_changed`	Passed
REQ-FUNC-010	Demonstration	REQ-POC-001 scenario	Not started
REQ-FUNC-011	Demonstration	Situation list (TBD)	Partial
REQ-FUNC-012	Test	`test_mock_does_not_misrepresent_free_text`	Passed
REQ-PERF-001	Analysis	`latency_ms`; `src/ai/README.md`	Partial
REQ-SEC-001	Test / Inspection	Inspection of `app/images.py`; `test_photo_input`	Partial
REQ-SEC-002	Test / Inspection	`test_provider_failure_is_safe`, `test_provider_errors_hide_internal_details`	Passed
REQ-SEC-003	Test / Inspection	Inspection of `.gitignore`, `.env.example`; `test_key_is_sent_in_header_not_url`	Passed
REQ-SEC-004	Test / Inspection	`test_invalid_inputs`, `test_invalid_photo_and_payload`	Partial
REQ-SEC-005	Test / Inspection	Cross-account tests (TBD)	Not started
REQ-SEC-006	Test / Inspection	`test_chain_local_cap_counts_failed_calls_and_resets_next_day`	Prototype
REQ-SEC-007	Test / Inspection	Policy document (TBD)	Not started

Requirement	Method	Test or artifact	Status
REQ-REL-001	Test	`test_invalid_provider_output_is_not_saved`, `test_sentences_from_text_tolerates_extra_text_and_bad_json`	Passed
REQ-REL-002	Test	`test_provider_failure_is_safe`, `test_gemini_timeout_becomes_unavailable_without_details`	Partial
REQ-REL-003	Test	`test_feedback_is_idempotent_and_can_be_changed`	Passed
REQ-AVAIL-001	Test	`test_health_ready_and_demo`, `test_readiness_requires_migration`	Passed
REQ-OBS-001	Inspection	`test_saved_generations_have_results_but_no_key_or_image`; log review (TBD)	Partial
REQ-COMP-001	Inspection	Licence file (TBD)	Not started
REQ-COMP-002	Inspection	Git history, Issues	Partial
REQ-INST-001	Demonstration	README quick start	Partial
REQ-BUILD-001	Inspection	`.github/workflows/tests.yml`	Passed
REQ-DIST-001	Demonstration	Compose stack (TBD)	Not started
REQ-MAINT-001	Inspection	`test_migration_roundtrip_and_schema_match`; `alembic check`	Passed
REQ-PORT-001	Test	`test_migration_roundtrip_and_schema_match`	Partial
REQ-POC-001	Demonstration	Appendix A scenario	Not started
REQ-CM-001	Inspection	Git history, docs/API.md, Revision History	Partial
REQ-ML-001	Analysis / Demonstration	`test_gemini_request_has_json_fields_low_resolution_and_examples`; live runs 21 and 28 Oct	Prototype
REQ-ML-002	Analysis / Demonstration	Evaluation set (TBD)	Not started
REQ-ML-008	Test	`tests/test_reuse.py`; `tests/test_ai_retrieval.py`	Partial
REQ-ML-003	Test / Analysis	`test_mock_does_not_misrepresent_free_text`, `test_clean_sentences_keeps_negation_and_drops_repeats`	Partial
REQ-ML-004	Test	`test_photo_input`; `test_gemini_request_has_json_fields_low_resolution_and_examples`	Passed
REQ-ML-005	Demonstration	Manual check on the demo page	Not run
REQ-ML-006	Test	`test_generation_persists_and_survives_restart`; `tests/test_ai_chain.py`	Partial
REQ-ML-007	Test	`tests/test_ai_chain.py` (chain tests)	Prototype

Recommended evidence set: pytest report, Ruff output, CI status, OpenAPI contract checks, image metadata inspection, cross-browser manual screen recording, real TTS playback check, PostgreSQL migration results, provider evaluation spreadsheet, and a signed usability/consent review before real-user testing. For the AI part, the offline tests in `tests/test_ai_chain.py`, `tests/test_ai_retrieval.py` and `tests/test_gemini_scripts.py` (31 cases, mock transports, no key or network) and the dated free-tier measurements in `src/ai/README.md` are the current evidence.

Chapter 5 — Appendixes

The appendixes preserve supporting, non-normative material: an illustrative café scenario, open decisions, architecture notes and screenshots of the current interface. The shared pictures show the login design, context and symbol selection, and the proposed sentence-selection and speech controls. These visual materials help the professor understand intended navigation and progression, but they are not substitutes for requirement-specific test results. If an appendix conflicts with a numbered requirement, the agreed requirements baseline should be reviewed and updated explicitly.

Appendix A — Primary acceptance scenario

Table 62. Primary acceptance scenario

Step	Action	Expected outcome
1	Open login or demo route and sign in	Landing UI displays; sign-in is interface only, account verification not assumed (REQ-SEC-005)
2	Choose "A café" and Water tile	Selected tile visibly active; intent = water
3	Optional: type "I want water" or attach photo	Context retained, image handling as defined
4	Request suggestions	Request and up to three full English sentence candidates stored and shown
5	Reject and try again	New suggestions do not repeat previous unchanged-input chain
6	Select "Could I have a glass of water, please?"	Confirm action becomes enabled
7	Press Confirm and speak	Acceptance saved (PUT feedback), then only the chosen text is spoken
8	Press Stop speaking	Playback stops; no error/status read aloud

Appendix B — Open decisions to close before professor submission

Table 63. Open decisions with owner and target week

#	Decision	Owner	Target week	Blocks W12 design
1	Confirm the UI accessibility target (proposed WCAG 2.1 AA) and keyboard/touch rules	Thibaut	W8	Yes
2	Confirm symbol/icon source and distribution license; rename the "Select Cboard tiles" label	Thibaut / All	W8	No
3	Confirm the provider order (Gemini Flash-Lite first, then Flash, then the local model) and its pass thresholds after running the evaluation dataset	Jiahui	W9	Yes
4	Confirm the provisional p95 ≤ 10 s response-time target and the provider timeout values	Jiahui / Veronika	W9	Yes
5	Select hosting approach and service availability target	Abid	W9	Yes
6	Specify account authentication and ownership behavior for the login screen, including the reuse history	Abid / Veronika	W9	Yes
7	Define request/rate and cost budgets for public trial	Abid	W10	No
8	Document informed consent, retention and deletion policy for real users	All	W12	No
9	Confirm browser/operating-system speech compatibility and test devices	Thibaut	W10	No
10	Agree scenario-expansion milestones and evidence owners	All	W9	No
11	Decide whether reuse runs automatically before generation, how a reused sentence is recorded when accepted, and whether matching ignores case	Veronika / Jiahui	W8	Yes
12	Decide whether to add interest discovery (open choice, alternatives) and change REQ-ML-003 (R9)	All	W8	Yes

Appendix C — Frontend progress screenshots

The following supplied screenshots are design/development evidence, not substitutes for independent verification. The current UI is more advanced than the backend-only state described in the earlier weekly presentation; it runs locally and is not yet connected to the API.




Figure 5. Login page — branding, email/password input and account entry.




Figure 6. Context page — café context, symbol tiles, optional photo and intention text.




Figure 7. Suggestions page — three sentence choices and confirm/reject/stop controls.

Appendix D — Architecture and records

High-level request path: AAC User → React web interface → FastAPI REST API → SentenceProvider (mock in the backend; the Gemini backup chain is prototyped in `src/ai/` and not yet connected). The API also writes metadata, suggestions and feedback to SQLite (development) or PostgreSQL (deployment target). Confirmed sentence → browser TTS engine → device speaker. Optional image undergoes format/size validation and metadata removal before provider use; raw photographs are not intended to be stored.

Table 64. Appendix D — Architecture and records

Logical record	Representative fields
Request	request ID, context hint, selected labels, intent, language, photo-present, parent ID
Suggestion	request ID, suggestion ID, text, provider version
Feedback	request ID, chosen suggestion, acceptance/rejection, update timestamp
Telemetry	provider identity, latency, safe error category; no photos/secrets

Appendix E — Verified team contributions and development evidence

This appendix documents the work described in the team repository, initial project presentation, weekly reports and screenshots available at the time of preparation (27 October 2026, updated 29 October 2026). It is an evidence-based snapshot, not a claim that all planned product requirements have passed user acceptance. Contributions are attributed by assigned responsibility and team reports; repository evidence alone does not prove individual authorship of every commit.

E.1 Repository and project provenance

Team B — The Outliers maintains its project under https://github.com/bhsei/26B (main branch). The repository includes a FastAPI app, database migrations, automated tests, documentation, AI-provider scaffolding, GitHub Actions configuration and weekly reports. The project is a standalone browser-based AAC application; Cboard is a design inspiration only, not a copied or modified codebase. The original nine-slide proposal described an extension of Cboard; this was explicitly superseded by SRS version 0.2 and Week 6 reporting. The SRS therefore specifies the standalone implementation.

E.2 Group contributions and evidence

Table 65. E.2 Group contributions and evidence

Team member	Documented responsibility / work	Current evidence / boundary
Veronika	Backend API, data models, SQL persistence, Alembic migrations, integration and tests; coordinate database and interface connections.	FastAPI app with seven documented endpoints (reuse endpoint merged 28 Oct 2026), 15 error codes, request validation, persistence and migrations; 77 backend tests. PostgreSQL deployment verification remains open.
Jiahui	SentenceProvider interface, model research and comparison, prompt design, free-tier limit measurements and evaluation strategy.	AI model plan; Gemini scripts and a rate-limit survey of 20 models; backup chain, provider adapters and reuse prototype in `src/ai/` with 31 offline tests. Not yet connected to the backend; evaluation targets and validated AI results are pending.
Thibaut	Frontend design, symbol board, photo input and context/suggestions transitions; user-facing choose, reject and confirm/speak flow.	Screenshots show sign-in, symbol selection and suggestion pages; screenshots are UI evidence, not independent proof of complete authentication
Abid Ali	Containerization, environment configuration, hosting, security planning	Assigned deployment work in Week 6; Docker Compose/public hosting, authentication and isolated PostgreSQL
All members	Requirements, reviews, integration, café scenario testing, documentation and course progress reporting.	SRS v0.2, weekly presentations, cross-team discussions and documented milestone planning.

E.3 Implemented backend behavior (API v0.1)

The current backend implements request validation for symbols, intent text and scene hint; optional photo validation with resize/metadata handling; fixed café-related suggestion templates; accept/reject feedback; non-repeating regeneration; and metadata persistence using SQLAlchemy/Alembic with SQLite in the reported local test environment. It exposes health and readiness checks and automated checks. The reusable-suggestions Swagger screenshot shows

POST /api/suggestions/reuse returning HTTP 200 with a previously accepted water-request sentence. This verifies one demonstrated local endpoint response, not general model accuracy or a production-grade service.

Table 66. E.3 Implemented backend behavior (API v0.1)

API route	Documented purpose	Status wording
GET /health	Liveness check	Reported implemented
GET /ready	Readiness check	Reported implemented
POST /api/suggestions	Generate up to three mock candidate sentences	Reported implemented (mock provider)
POST /api/suggestions/image	Accept validated optional photo input	Reported implemented; no confirmed real scene understanding
PUT /api/requests/{request_id}/feedback	Record acceptance or rejection	Reported implemented
POST /api/suggestions/reuse	Retrieve eligible previously accepted text/symbol suggestions	Implemented and merged 28 Oct 2026; 40 tests; not yet in docs/API.md

E.4 Verification evidence, limitations and reporting consistency

In the Week 6 report, the backend starter had 26 automated test cases passing, and the 45 requirements were summarized as 19 passed (including 5 partly supported), 8 in progress, 6 awaiting manual checks and 12 not started. On 29 October 2026, `main` passes CI with 108 automated tests, also on Windows; Chapter 4 gives the re-checked status of each requirement. Actual voice audio and browser click-through, a live PostgreSQL connection, AI integration in the backend, authentication, full deployment and hosting are still not verified. A screenshot of a sign-in page does not alter the backend authentication requirement status unless end-to-end access-control tests are supplied.

Screenshot evidence:

- login interface with email, password and recovery links
- café context page with symbols (water, coffee, sugar, milk, hot/cold, take-away/eat-in), free-text intention and optional photo controls
- candidate-suggestion view with user selection, confirm/speak, reject/try again and stop-speaking controls
- GitHub repository overview and README
- Swagger/OpenAPI endpoint and successful reuse response. The screen itself states that templates are mocked and photos are not analyzed; this disclosure must remain prominent in demonstrations.

E.5 Near-term work and ownership

Increment 1 must complete a real web-to-API café workflow with accessible symbol mapping, validated speech playback, the evaluated sentence-generation provider and safe output handling. Before an external trial, the team should implement authentication, ownership checks, secret handling, rate/cost limits and controlled hosting. Before involving real AAC users, it must settle consent, privacy, retention and licensing, and obtain accessible usability feedback. Increment 2 may expand to additional everyday locations after the café scenario meets agreed acceptance criteria. These are milestones and dependencies, not completed features.

Appendix F — Scholarly literature and technical reference list

[1] Pereira, J. A., Pereira, J. A., Zanchettin, C., & Fidalgo, R. N. (2024). PrAACT: Predictive Augmentative and Alternative Communication with Transformers.
Expert Systems with Applications
, 240, Article 122417.

[2] Valencia, S., Cave, R., Kallarackal, K., Seaver, K., Terry, M., & Kane, S. (2023). "The less I type, the better": How AI language models can enhance or impede communication for AAC users.
Proceedings of the 2023 CHI Conference on Human Factors in Computing Systems
.

[3] Pak, N. S., Bailey, K. M., Ledford, J. R., & Kaiser, A. P. (2023). Comparing interventions with speech-generating devices and other augmentative and alternative communication modes: A meta-analysis.
American Journal of Speech-Language Pathology
, 32(2), 786–802.

[4] White, E. N., Ayres, K. M., Snyder, S. K., Cagliani, R. R., & Ledford, J. R. (2021). Augmentative and alternative communication and speech production for individuals with ASD: A systematic review.
Journal of Autism and Developmental Disorders
, 51, 4199–4212.

[5] B — The Outliers. (2026). 26B software engineering project repository (source code, README, tests, docs and weekly reports). GitHub. https://github.com/bhsei/26B

[6] B — The Outliers. (2026, October 13). Software requirements specification, version 0.2. https://github.com/bhsei/26B/blob/main/docs/requirements/SRS.md

[7] ovikrai. (n.d.). SRS-Template-IEEE: Software requirements specification template. GitHub. https://github.com/ovikrai/SRS-Template-IEEE

Application of research to SRS: Pereira et al. motivates symbolic/predictive assistance and candidate relevance tests; Valencia et al. supports preserving the user's own intention and control over final wording; Pak et al. and White et al. provide context for evaluating communication outcomes without assuming all AAC methods are interchangeable. See requirements REQ-ML-003 through REQ-ML-005, REQ-FUNC-005 through REQ-FUNC-007, and UI accessibility requirements.

Appendix G — Sources and limitations

Primary evidence: uploaded bare SRS template, project presentation script and weekly progress slides; current screenshots. Cross-check: publicly visible team SRS v0.2 at github.com/bhsei/26B. Since v0.5 the evidence fields and Chapter 4 are based on the repository itself: CI results on `main`, the named automated tests, and dated measurements of the AI prototype in `src/ai/README.md`. Real AI inference has been run only in the standalone prototype with synthetic inputs; it is not yet part of the backend. The screenshots show a login interface but do not prove functioning security. Before the final export, each requirement owner should confirm the status of their requirements.